

FCC Part 15C
Measurement and Test Report
For
Netatmo

892, rue yves kermen - 92100 Boulogne Billancourt - FRANCE

FCC ID: N3A-TPG01

FCC Rule(s):	<u>FCC Part 15C</u>
Product Description:	<u>Netatmo Gateway</u>
Tested Model:	<u>TPG01</u>
Report No.:	<u>STR15038275I-1</u>
Tested Date:	<u>2015-03-27 to 2015-04-03</u>
Issued Date:	<u>2015-04-14</u>
Tested By:	<u>Jason Su/ Engineer</u>
Reviewed By:	<u>Lahm Peng / EMC Manager</u>
Approved & Authorized By:	<u>Jandy so / PSQ Manager</u>
Prepared By:	

Jason Su
Lahm peng
Jandyso

Shenzhen SEM.Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
2. SUMMARY OF TEST RESULTS	6
3. RF EXPOSURE	7
3.1 STANDARD APPLICABLE.....	7
3.2 TEST RESULT.....	7
4. ANTENNA REQUIREMENT	8
4.1 STANDARD APPLICABLE.....	8
4.2 EVALUATION INFORMATION	8
5. POWER SPECTRAL DENSITY	9
5.1 STANDARD APPLICABLE.....	9
5.2 TEST EQUIPMENT LIST AND DETAILS	9
5.3 TEST PROCEDURE.....	9
5.4 ENVIRONMENTAL CONDITIONS	9
5.5 SUMMARY OF TEST RESULTS/PLOTS	10
6. 6DB BANDWIDTH	16
6.1 STANDARD APPLICABLE.....	16
6.2 TEST EQUIPMENT LIST AND DETAILS	16
6.3 TEST PROCEDURE.....	16
6.4 ENVIRONMENTAL CONDITIONS	16
6.5 SUMMARY OF TEST RESULTS/PLOTS	17
7. RF OUTPUT POWER.....	23
7.1 STANDARD APPLICABLE.....	23
7.2 TEST EQUIPMENT LIST AND DETAILS	23
7.3 TEST PROCEDURE.....	23
7.4 ENVIRONMENTAL CONDITIONS	23
7.5 SUMMARY OF TEST RESULTS/PLOTS	24
8. FIELD STRENGTH OF SPURIOUS EMISSIONS	30
8.1 MEASUREMENT UNCERTAINTY	30
8.2 STANDARD APPLICABLE.....	30
8.3 TEST EQUIPMENT LIST AND DETAILS	30
8.4 TEST PROCEDURE.....	31
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	32
8.6 ENVIRONMENTAL CONDITIONS	32
8.7 SUMMARY OF TEST RESULTS/PLOTS	32
9. OUT OF BAND EMISSIONS.....	54
9.1 STANDARD APPLICABLE.....	54
9.2 TEST EQUIPMENT LIST AND DETAILS	54
9.3 TEST PROCEDURE.....	54
9.4 ENVIRONMENTAL CONDITIONS	55
9.5 SUMMARY OF TEST RESULTS/PLOTS	55
10. CONDUCTED EMISSIONS	62
10.1 MEASUREMENT UNCERTAINTY	62
10.2 TEST EQUIPMENT LIST AND DETAILS	62
10.3 TEST PROCEDURE.....	62
10.4 BASIC TEST SETUP BLOCK DIAGRAM.....	62
10.5 ENVIRONMENTAL CONDITIONS	63
10.6 TEST RECEIVER SETUP	63
10.7 SUMMARY OF TEST RESULTS/PLOTS	63
10.8 CONDUCTED EMISSIONS TEST DATA.....	63

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Netatmo
Address of applicant: 892, rue yves kermen - 92100 Boulogne Billancourt - FRANCE
Manufacturer: Netatmo
Address of manufacturer: 892, rue yves kermen - 92100 Boulogne Billancourt - FRANCE

General Description of EUT	
Product Name:	Netatmo Gateway
Trade Name:	Netatmo
Model No.:	TPG01
Adding Model(s):	/
Rated Voltage:	100-240VAC or 5VDC(USB)
Power Adapter Model:	/
Note: The test data is gathered from a production sample provided by the manufacturer.	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n/HT20
Frequency Range:	2412-2462MHz
RF Output Power:	12.52dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11
Channel Separation:	5MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	0dBi
Lowest Internal Frequency	32.768KHz

1.2 Test Standards

The following report is prepared on behalf of the Netatmo in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 V03r02 for digital transmission systems shall be performed also.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	0.5	Unshielded	Without Ferrite
AC Cable	1.2	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an integral antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2014-05-28	2015-05-27
Attenuator	ATTEN	ATS100-4-20	/	2014-05-28	2015-05-27

5.3 Test Procedure

According to the KDB 558074 D01 V03r02, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.4 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.5 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b	2412	-14.68	8
	2437	-14.23	8
	2462	-13.26	8
802.11g	2412	-20.29	8
	2437	-16.87	8
	2462	-17.93	8
802.11n HT20	2412	-20.63	8
	2437	-17.34	8
	2462	-17.93	8

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel



802.11n-HT20-Middle Channel



802.11n-HT20-High Channel



6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2014-05-28	2015-05-27
Attenuator	ATTEN	ATS100-4-20	/	2014-05-28	2015-05-27

6.3 Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Environmental Conditions


Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.5 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz
802.11b	2412	7571	12068.5	500
	2437	7135	12077.1	500
	2462	8059	12061.2	500
802.11g	2412	15045	16312.2	500
	2437	14257	16303.0	500
	2462	15028	16309.0	500
802.11n-HT20	2412	17010	17490.9	500
	2437	15181	17497.3	500
	2462	14964	17443.4	500

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel



802.11n-HT20-Middle Channel



802.11n-HT20-High Channel



7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2014-05-28	2015-05-27
Attenuator	ATTEN	ATS100-4-20	/	2014-05-28	2015-05-27

7.3 Test Procedure

According to section 15.247(b)-power output of the KDB-558074 D01 V03r02, 9.2.2.2 (channel integration method) When this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.4 Environmental Conditions


Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

7.5 Summary of Test Results/Plots


Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b _ 1Mbps	2412	12.52	17.865	1000
	2437	12.05	16.032	1000
	2462	11.78	15.066	1000
802.11g_6Mbps	2412	10.77	11.940	1000
	2437	10.10	10.233	1000
	2462	10.80	12.023	1000
802.11n HT20_MCS7	2412	11.14	13.002	1000
	2437	11.25	13.335	1000
	2462	10.65	11.615	1000

Please refer to the following test plots:


802.11b-1Mbps-Low Channel




802.11b -1Mbps-Middle Channel




802.11b -1Mbps-High Channel




802.11g-6Mbps-Low Channel




802.11g-6Mbps-Middle Channel




802.11g-6Mbps-High Channel




802.11n-HT20-MCS7-Low Channel



802.11n-HT20-MCS7-Middle Channel



802.11n-HT20-MCS7-High Channel



8. Field Strength of Spurious Emissions

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.10 dB.

8.2 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.3 Test Equipment List and Details



Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Horn Antenna	ETS	3116B	00088203	2014-05-24	2015-05-23
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2014-05-24	2015-05-23

8.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.6 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.7 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: Netatmo Gateway

Tested Model: TPG01

Operating Condition: 802.11b Transmitting Low Channel-2412MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	95.7622	16.57	5.06	21.63	43.50	-21.87	95	100	peak
2	375.9385	17.00	9.20	26.20	46.00	-19.80	232	100	peak
3	742.2587	17.34	13.67	31.01	46.00	-14.99	195	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	35.0048	16.63	8.39	25.02	40.00	-14.98	136	100	peak
2	96.0986	21.86	5.14	27.00	43.50	-16.50	235	100	peak
3	302.4812	15.15	9.19	24.34	46.00	-21.66	316	100	peak

Operating Condition: 802.11b Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	96.0986	19.12	5.14	24.26	43.50	-19.24	168	100	peak
2	599.3213	17.63	13.30	30.93	46.00	-15.07	36	100	peak
3	747.4826	16.81	13.95	30.76	46.00	-15.24	198	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	41.4215	15.66	8.82	24.48	40.00	-15.52	98	100	peak
2	96.0986	20.43	5.14	25.57	43.50	-17.93	236	100	peak
3	593.0497	20.77	13.06	33.83	46.00	-12.17	165	100	peak

Operating Condition: 802.11b Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	96.0986	18.06	5.14	23.20	43.50	-20.30	78	100	peak
2	234.9909	16.80	6.02	22.82	46.00	-23.18	164	100	peak
3	599.3213	18.47	13.30	31.77	46.00	-14.23	234	100	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	95.7622	18.13	5.06	23.19	43.50	-20.31	98	100	peak
2	597.2234	19.93	13.21	33.14	46.00	-12.86	125	100	peak
3	750.1083	16.40	15.09	31.49	46.00	-14.51	136	100	peak

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: Netatmo Gateway

Tested Model: TPG01

Operating Condition: 802.11g Transmitting Low Channel-2412MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	99.5281	15.08	6.01	21.09	43.50	-22.41	174	100	peak
2	603.5392	16.35	13.06	29.41	46.00	-16.59	160	100	peak
3	744.8661	17.43	13.82	31.25	46.00	-14.75	320	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	96.0986	18.98	5.14	24.12	43.50	-19.38	177	100	peak
2	325.5958	16.14	9.14	25.28	46.00	-20.72	90	100	peak
3	750.1083	16.06	15.09	31.15	46.00	-14.85	336	100	peak

Operating Condition: 802.11g Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	96.0986	18.35	5.14	23.49	43.50	-20.01	214	100	peak
2	322.1886	15.96	9.23	25.19	46.00	-20.81	98	100	peak
3	599.3213	16.77	13.30	30.07	46.00	-15.93	128	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	96.0986	19.00	5.14	24.14	43.50	-19.36	165	100	peak
2	501.1790	18.23	10.88	29.11	46.00	-16.89	198	100	peak
3	739.6605	15.97	15.53	31.50	46.00	-14.50	321	100	peak

Operating Condition: 802.11g Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	96.0986	18.14	5.14	23.28	43.50	-20.22	89	100	peak
2	239.1473	15.97	6.28	22.25	46.00	-23.75	135	200	peak
3	599.3213	18.22	13.30	31.52	46.00	-14.48	215	200	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	96.0986	18.34	5.14	23.48	43.50	-20.02	85	100	peak
2	501.1790	21.59	10.88	32.47	46.00	-13.53	214	100	peak
3	609.9217	22.03	12.63	34.66	46.00	-11.34	45	100	peak

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: Netatmo Gateway

Tested Model: TPG01

Operating Condition: 802.11n-HT20 Transmitting Low Channel-2412MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	36.6375	18.21	6.34	24.55	40.00	-15.45	89	100	peak
2	96.0986	18.78	5.14	23.92	43.50	-19.58	136	100	peak
3	750.1083	17.37	14.10	31.47	46.00	-14.53	26	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	96.0986	18.10	5.14	23.24	43.50	-20.26	265	100	peak
2	499.4247	23.42	10.83	34.25	46.00	-11.75	19	100	peak
3	597.2234	22.75	13.21	35.96	46.00	-10.04	336	100	peak

Operating Condition: 802.11n-HT20 Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	40.4172	16.25	7.21	23.46	40.00	-16.54	89	100	peak
2	96.0986	17.63	5.14	22.77	43.50	-20.73	65	100	peak
3	597.2234	17.18	13.21	30.39	46.00	-15.61	169	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	96.0986	19.39	5.14	24.53	43.50	-18.97	89	100	peak
2	501.1790	25.73	10.88	36.61	46.00	-9.39	135	100	peak
3	590.9737	19.78	12.97	32.75	46.00	-13.25	235	100	peak

Operating Condition: 802.11n-HT20 Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	96.0986	18.48	5.14	23.62	43.50	-19.88	89	100	peak
2	599.3213	16.16	13.30	29.46	46.00	-16.54	236	100	peak
3	734.4913	17.46	13.22	30.68	46.00	-15.32	165	200	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	96.0986	17.90	5.14	23.04	43.50	-20.46	89	100	peak
2	501.1790	22.91	10.88	33.79	46.00	-12.21	236	100	peak
3	599.3213	21.64	13.30	34.94	46.00	-11.06	16	100	peak

*Spurious Emissions Above 1GHz**Test Mode: 802.11b*

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	39.44	0.57	40.01	74.00	-33.99	H	PK
4824.000	28.98	0.56	29.54	54.00	-24.46	H	AV
7236.000	28.73	3.69	32.42	74.00	-41.58	H	PK
7236.000	18.35	3.69	22.04	54.00	-31.96	H	AV
4824.000	59.07	0.56	59.63	74.00	-14.37	V	PK
4824.000	44.81	0.56	45.37	54.00	-8.63	V	AV
7236.000	29.06	3.69	32.75	74.00	-41.25	V	PK
7236.000	18.16	3.68	21.84	54.00	-32.16	V	AV
Middle Channel-2437MHz							
4874.000	41.76	0.64	42.40	74.00	-31.60	H	PK
4874.000	28.93	0.66	29.59	54.00	-24.41	H	AV
7311.000	30.86	3.75	34.61	74.00	-39.39	H	PK
7311.000	18.85	3.73	22.58	54.00	-31.42	H	AV
4874.000	57.02	0.64	57.66	74.00	-16.34	V	PK
4874.000	42.02	0.64	42.66	54.00	-11.34	V	AV
7311.000	29.68	3.76	33.44	74.00	-40.56	V	PK
7311.000	19.91	3.76	23.67	54.00	-30.33	V	AV
High Channel-2462MHz							
4924.000	41.15	0.72	41.87	74.00	-32.13	H	PK
4924.000	29.60	0.72	30.32	54.00	-23.68	H	AV
7386.000	31.72	3.81	35.53	74.00	-38.47	H	PK
7386.000	20.31	3.83	24.14	54.00	-29.86	H	AV
4924.000	50.11	0.72	50.83	74.00	-23.17	V	PK
4924.000	37.53	0.72	38.25	54.00	-15.75	V	AV
7386.000	31.81	3.81	35.62	74.00	-38.38	V	PK
7386.000	20.70	3.82	24.52	54.00	-29.48	V	AV

Test Mode: 802.11g

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	40.83	0.57	41.40	74.00	-32.60	H	PK
4824.000	29.22	0.51	29.73	54.00	-24.27	H	AV
7236.000	40.83	0.57	41.40	74.00	-32.60	H	PK
7236.000	18.28	3.68	21.96	54.00	-32.04	H	AV
4824.000	56.99	0.56	57.55	74.00	-16.45	V	PK
4824.000	41.66	0.56	42.22	54.00	-11.78	V	AV
7236.000	29.61	3.69	33.30	74.00	-40.70	V	PK
7236.000	19.17	3.69	22.86	54.00	-31.14	V	AV
Middle Channel-2437MHz							
4874.000	40.29	0.64	40.93	74.00	-33.07	H	PK
4874.000	28.78	0.66	29.44	54.00	-24.56	H	AV
7311.000	30.68	3.75	34.43	74.00	-39.57	H	PK
7311.000	19.66	3.76	23.42	54.00	-30.58	H	AV
4874.000	47.51	0.64	48.15	74.00	-25.85	V	PK
4874.000	33.69	0.64	34.33	54.00	-19.67	V	AV
7311.000	31.16	3.75	34.91	74.00	-39.09	V	PK
7311.000	19.67	3.75	23.42	54.00	-30.58	V	AV
High Channel-2462MHz							
4924.000	39.56	0.72	40.28	74.00	-33.72	H	PK
4924.000	29.44	0.72	30.16	54.00	-23.84	H	AV
7386.000	32.06	3.81	35.87	74.00	-38.13	H	PK
7386.000	20.50	3.84	24.34	54.00	-29.66	H	AV
4924.000	56.02	0.56	56.58	74.00	-17.42	V	PK
4924.000	40.94	0.56	41.50	54.00	-12.50	V	AV
7386.000	32.79	3.81	36.60	74.00	-37.40	V	PK
7386.000	20.75	3.81	24.56	54.00	-29.44	V	AV

Test Mode: 802.11n-HT20

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	40.11	0.57	40.68	74.00	-33.32	H	PK
4824.000	28.88	0.53	29.41	54.00	-24.59	H	AV
7236.000	29.74	3.69	33.43	74.00	-40.57	H	PK
7236.000	18.22	3.67	21.89	54.00	-32.11	H	AV
4824.000	40.11	0.57	40.68	74.00	-33.32	V	PK
4824.000	28.88	0.53	29.41	54.00	-24.59	V	AV
7236.000	29.74	3.69	33.43	74.00	-40.57	V	PK
7236.000	18.22	3.67	21.89	54.00	-32.11	V	AV
Middle Channel-2437MHz							
4874.000	40.66	0.64	41.30	74.00	-32.70	H	PK
4874.000	29.47	0.64	30.11	54.00	-23.89	H	AV
7311.000	31.85	3.75	35.60	74.00	-38.40	H	PK
7311.000	20.82	3.79	24.61	54.00	-29.39	H	AV
4874.000	38.98	0.61	39.59	74.00	-34.41	V	PK
4874.000	28.83	0.57	29.40	54.00	-24.60	V	AV
7311.000	30.90	3.75	34.65	74.00	-39.35	V	PK
7311.000	20.05	3.76	23.81	54.00	-30.19	V	AV
High Channel-2462MHz							
4924.000	41.58	0.72	42.30	74.00	-31.70	H	PK
4924.000	29.86	0.70	30.56	54.00	-23.44	H	AV
7386.000	33.14	3.81	36.95	74.00	-37.05	H	PK
7386.000	21.54	3.81	25.35	54.00	-28.65	H	AV
4924.000	57.18	0.72	57.90	74.00	-16.10	V	PK
4924.000	40.84	0.72	41.56	54.00	-12.44	V	AV
7386.000	35.22	3.81	39.03	74.00	-34.97	V	PK
7386.000	22.44	3.81	26.25	54.00	-27.75	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23

9.3 Test Procedure

According to the KDB 558074D01 v03r02, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 V03r02, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW $\geq$ 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.


9.4 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.5 Summary of Test Results/Plots

Please refer to the test plots as below.


802.11b-Lowest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	30.27	-3.71	26.56	54.00	-27.44	Average Detector
	2310.000	42.60	-3.71	38.89	74.00	-35.11	Peak Detector
2	2390.000	38.00	-3.54	34.46	54.00	-19.54	Average Detector
	2390.000	51.53	-3.54	47.99	74.00	-26.01	Peak Detector
3	2400.000	41.75	-3.51	38.24	Delta=52.01dBc		Average Detector
4	2412.720	93.73	-3.48	90.25			Average Detector

802.11b-Highest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.850	93.05	-3.37	89.68	/	/	Average Detector
	2462.950	97.98	-3.37	94.61	/	/	Peak Detector
2	2483.500	Delta = 57.36dBc		32.32	54.00	-21.68	Average Detector
	2483.500			37.25	74.00	-36.75	Peak Detector
3	2500.000	34.98	-3.28	31.70	54.00	-22.30	Average Detector
	2500.000	46.83	-3.28	43.55	74.00	-30.45	Peak Detector

802.11g-Lowest Bandedge


Vertical (Worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	30.69	-3.71	26.98	54.00	-27.02	Average Detector
	2310.000	42.09	-3.71	38.38	74.00	-35.62	Peak Detector
2	2390.000	38.23	-3.54	34.69	54.00	-19.31	Average Detector
	2390.000	52.50	-3.54	48.96	74.00	-25.04	Peak Detector
3	2400.000	42.30	-3.51	38.79	Delta=34.65dBc		Average Detector
4	2412.720	76.92	-3.48	73.44			Peak Detector

802.11g-Highest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2	2462.500	76.44	-3.37	73.07	/	/	Average Detector
	2461.100	99.51	-3.37	96.14	/	/	Peak Detector
1	2483.500	Delta = 50.42dBc		22.65	54.00	-31.35	Average Detector
	2483.500			45.72	74.00	-28.28	Peak Detector
3	2500.000	33.40	-3.28	30.12	54.00	-23.88	Average Detector
	2500.000	46.31	-3.28	43.03	74.00	-30.97	Peak Detector

802.11n-HT20-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	32.27	-3.71	28.56	54.00	-25.44	Average Detector
	2310.000	42.57	-3.71	38.86	74.00	-35.14	Peak Detector
2	2390.000	41.44	-3.54	37.90	54.00	-16.10	Average Detector
	2390.000	55.33	-3.54	51.79	74.00	-22.21	Peak Detector
3	2400.000	49.00	-3.51	45.49	Delta = 39.73dBc		Average Detector
4	2412.840	88.70	-3.48	85.22			Peak Detector

802.11n-HT20-Highest Bandedge

Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.000	88.83	-3.37	85.46	/	/	Average Detector
	2463.400	98.70	-3.36	95.34	/	/	Peak Detector
2	2483.500	Delta = 51.26dBc		34.20	54.00	-19.80	Average Detector
	2483.500			44.08	74.00	-29.92	Peak Detector
3	2500.000	36.59	-3.28	33.31	54.00	-20.69	Average Detector
	2500.000	46.52	-3.28	43.24	74.00	-30.76	Peak Detector

10. Conducted Emissions

10.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

10.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2014-05-28	2015-05-27
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2014-05-28	2015-05-27
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2014-05-28	2015-05-27


10.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

10.4 Basic Test Setup Block Diagram



10.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

10.7 Summary of Test Results/Plots

According to the data in section 9.8, the EUT complied with the FCC Part 15.207 Conducted margin for a Class B device, with the *worst* margin reading of:


-9.36 dB at 0.1540 MHz in the Neutral mode, Peak detector, 0.15-30MHz

10.8 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Netatmo Gateway
 Tested Model: TPG01
 Operating Condition: Transmitting(Wi-Fi)
 Comment: AC 120V/60Hz

Test Specification: Neutral



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1	0.1540	46.92	9.50	56.42	65.78	-9.36	peak
2	0.1540	26.46	9.50	35.96	55.78	-19.82	AVG
3	3.7220	18.05	10.00	28.05	46.00	-17.95	AVG
4	4.2180	29.84	10.00	39.84	56.00	-16.16	peak
5	18.1820	16.94	11.64	28.58	50.00	-21.42	AVG
6	18.3340	27.00	11.67	38.67	60.00	-21.33	peak

Test Specification: Live



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1	0.1740	44.35	9.50	53.85	64.77	-10.92	peak
2	0.1740	27.43	9.50	36.93	54.77	-17.84	AVG
3	4.1820	17.75	10.00	27.75	46.00	-18.25	AVG
4	4.2580	29.70	10.00	39.70	56.00	-16.30	peak
5	18.1940	27.05	11.64	38.69	60.00	-21.31	peak
6	18.1940	17.35	11.64	28.99	50.00	-21.01	AVG

***** END OF REPORT *****