

TEST REPORT

FCC MPE Test for ADXV-HPR-43BTF
Certification

APPLICANT
ADRF KOREA, Inc.

REPORT NO.
HCT-RF-2108-FC002

DATE OF ISSUE
August 5, 2021

Tested by
Kyung Soo Kang



Technical Manager
Jong Seok Lee



HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO

HCT CO., LTD.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si,
Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

F-TP22-03(Rev.04)

1 / 6

The report shall not be reproduced except in full(only partly) without approval of the laboratory.



HCT Co., Ltd.

74, Seocheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

TEST REPORT FCC MPE Test for ADXV-HPR-43BTF	REPORT NO. HCT-RF-2108-FC002
	DATE OF ISSUE August 05, 2021
	Additional Model -

Applicant	ADRF KOREA, Inc. 5-5, Mojeon-Ri, Backsa-Myun, Icheon-Citi, Kyunggi-Do, Korea
Eut Type Model Name	DAS ADXV-HPR-43BTF
FCC ID	N52-ADXV-HPR-BTF

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	August 05, 2021	Initial Release

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

If this report is required to confirmation of authenticity, please contact to www.hct.co.kr

RF Exposure Statement**1. Limit**

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magneticfield Strength (A/m)	Powerdensity (mW/cm ²)	Averagingtime (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. RESULTS

3.1 MPE calculation for standalone operations

- BRS/EBS – LTE 20 MHz (Downlink)

Max Peak output Power at antenna input terminal	43.50	dBm
Max Peak output Power at antenna input terminal	22387.21	mW
Prediction distance	80.00	cm
Prediction frequency	2591.91	MHz
Antenna Gain(typical)	3.00	dBi
Antenna Gain(numeric)	2.00	-
Power density at prediction frequency(S)	0.5554	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- BRS/EBS – 5G NR 100 MHz (Downlink)

Max Peak output Power at antenna input terminal	43.50	dBm
Max Peak output Power at antenna input terminal	22387.21	mW
Prediction distance	80.00	cm
Prediction frequency	2591.91	MHz
Antenna Gain(typical)	3.00	dBi
Antenna Gain(numeric)	2.00	-
Power density at prediction frequency(S)	0.5554	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

3.2 Simultaneous band emission conditions

- BRS/EBS – LTE 20 MHz (Downlink)

Max Peak output Power at antenna input terminal	40.50	dBm
Max Peak output Power at antenna input terminal	11220.18	mW
Prediction distance	80.00	cm
Prediction frequency	2591.91	MHz
Antenna Gain(typical)	3.00	dBi
Antenna Gain(numeric)	2.00	-
Power density at prediction frequency(S)	0.2784	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- BRS/EBS – 5G NR 100 MHz (Downlink)

Max Peak output Power at antenna input terminal	40.50	dBm
Max Peak output Power at antenna input terminal	11220.18	mW
Prediction distance	80.00	cm
Prediction frequency	2591.91	MHz
Antenna Gain(typical)	3.00	dBi
Antenna Gain(numeric)	2.00	-
Power density at prediction frequency(S)	0.2784	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

[Downlink]

Band	Signal	MPE Ratio (Power density / Limit)	Sum of MPE Ratio
BRS/EBS	LTE	0.2784	0.5567
	5G NR	0.2784	

*Note

1. The result of each band was applied to the worst value.
2. MPE ratios are calculated as

$$[(\text{Power density1} / \text{MPE Limit}) + (\text{Power density2} / \text{MPE Limit}) + \dots] \leq 1$$