

TEST REPORT

FCC MPE Test for ADVX-R-25VU-U2B
Certification

APPLICANT
ADRF KOREA, Inc.

REPORT NO.
HCT-RF-2412-FC040

DATE OF ISSUE
December 5, 2024

Tested by
Kyung Soo Kang



Technical Manager
Jong Seok Lee



HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea

Tel. +82 31 645 6300 Fax. +82 31 645 6401

**TEST
REPORT****REPORT NO.**

HCT-RF-2412-FC040

DATE OF ISSUE

December 5, 2024

Applicant**ADRF KOREA, Inc.**

196-16 IYEO-RO BAEKSA-MYEON ICHEON-SI, GYEONGGI-DO, 17316, KOREA

Product Name

DAS

Model Name

ADXV-R-25VU-U2B

FCC ID

N52-ADXVR3378PU2B

Date of Test

October 25, 2024 ~ December 02, 2024

Location of Test☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

Test Standard Used

CFR 47 Part 2.1091

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	December 5, 2024	Initial Release

Notice

Content

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

RF Exposure Statement

1. LIMITS

According to § 1.1310 and § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	#)(100)	30
1.34 - 30.....	824/f	2.19/f	#)(180/f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

= Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. RESULTS

- VHF – Downlink, 1 Carrier

Max Peak output Power at antenna input terminal	25.50	dBm
Max Peak output Power at antenna input terminal	354.81	mW
Prediction distance	30.00	cm
Prediction frequency	150.05	MHz
Antenna Gain(typical)	2.00	dBi
Antenna Gain(numeric)	1.58	-
Power density at prediction frequency(S)	0.0497	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.1000	mW/cm ²

- UHF – Downlink, 1 Carrier

Max Peak output Power at antenna input terminal	25.50	dBm
Max Peak output Power at antenna input terminal	354.81	mW
Prediction distance	30.00	cm
Prediction frequency	406.10	MHz
Antenna Gain(typical)	1.80	dBi
Antenna Gain(numeric)	1.51	-
Power density at prediction frequency(S)	0.0475	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.2707	mW/cm ²

Simultaneous band emission conditions

Band	MPE Ratio (Power density / Limit)	Sum of MPE Ratio	
VHF	0.4971	0.6724	≤ 1
UHF	0.1754		

#Note

1. The result of each band was applied to the worst value.
2. MPE ratios are calculated as

$$[(\text{Power density1} / \text{MPE Limit}) + [(\text{Power density2} / \text{MPE Limit}) + \dots] \leq 1$$