

TABLE OF CONTENTS

APPLICANT: WINATION TECHNOLOGY MFG.LTD.

FCC ID: N57RY-1350

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST & TEST PROCEDURE
PAGE 2.....TEST PROCEDURE CONTINUED
PAGE 3.....CIRCUIT DESCRIPTION
PAGE 4.....49.86MHz Tx RADIATION INTERFERENCE TEST DATA
PAGE 5.....49.405MHz Tx RADIATION INTERFERENCE TEST DATA
PAGE 6.....OCCUPIED BANDWIDTH TEST DATA

EXHIBITS ATTACHMENTS:

EXHIBIT 1.....BLOCK DIAGRAM
EXHIBIT 2.....SCHEMATIC
EXHIBIT 3A-3B....INSTRUCTION MANUAL
EXHIBIT 4.....FCC ID LABEL SAMPLE
EXHIBIT 5.....FCC ID LABEL LOCATION
EXHIBIT 6.....EXTERNAL PHOTO FRONT VIEW
EXHIBIT 7.....EXTERNAL PHOTO REAR VIEW
EXHIBIT 8.....INTERNAL PHOTO COMPONENT SIDE
EXHIBIT 9.....INTERNAL PHOTO COPPER SIDE
EXHIBIT 10A.....OCCUPIED BANDWIDTH PLOT - 49.405 MHz TX
EXHIBIT 10B.....OCCUPIED BANDWIDTH PLOT - 49.86 MHz TX

APPLICANT: WINATION TECHNOLOGY MFG.LTD.

FCC ID: N57RY-1350

REPORT #: T:\CUS\W\WINATION\196AH0\196AH.RPT

TABLE OF CONTENTS

APPLICANT: WINATION TECHNOLOGY MFG.LTD.
FCC ID: N57RY-1350

TEST EQUIPMENT LIST

1. Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/ preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02, S/N 3008A00372 Cal. 10/17/99
2. Biconnical Antenna: Eaton Model 94455-1, S/N 1057
3. Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
4. Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180, 1-18 GHz, S/N 2319 Cal. 4/27/99
5. Horn 40-60GHz: ATM Part #19-443-6R
6. Line Impedance Stabilization Network: Electro-Metrics Model ANS-25/2, S/N 2604 Cal. 2/9/00
7. Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
8. Frequency Counter: HP Model 5385A, S/N 3242A07460 Cal 10/6/99
9. Peak Power Meter: HP Model 8900C, S/N 2131A00545 Cal 7/19/99
10. Open Area Test Site #1-3meters Cal. 12/22/99
11. Signal Generator: HP 8640B, S/N 2308A21464 Cal. 9/23/99
12. Signal Generator: HP 8614A, S/N 2015A07428 Cal. 5/29/99
13. Passive Loop Antenna: EMCO Model 6512, 9KHz to 30MHz, S/N 9706-1211 Cal. 6/23/97
14. Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153 Cal. 11/24/99
15. AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 9/21/99
16. Digital Multimeter: Fluke Model 8012A, S/N 4810047 Cal 9/21/99
17. Digital Multimeter: Fluke Model 77, S/N 43850817 Cal 9/21/99
18. Oscilloscope: Tektronix Model 2230, S/N 300572 Cal 9/23/99

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 78°F with a humidity of 30%.

APPLICANT: WINATION TECHNOLOGY MFG.LTD.
FCC ID: N57RY-1350
REPORT #: T:\CUS\W\WINATION\196AH0\196AH.RPT
PAGE #: 1

TEST PROCEDURES CONTINUED

APPLICANT: WINATION TECHNOLOGY MFG.LTD.
FCC ID: N57RY-1350

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-1992 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The ambient temperature of the UUT was 78°F with a humidity of 40%.

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

APPLICANT: WINATION TECHNOLOGY MFG.LTD.
FCC ID: N57RY-1350
REPORT #: T:\CUS\W\WINATION\196AH0\196AH.RPT
PAGE #: 2

APPLICANT: WINATION TECHNOLOGY MFG.LTD.
FCCID: N57RY-1350

CIRCUIT DESCRIPTION:

When Unit A is turned on, it transmits on 49.86MHz. this is the frequency generated by crystal oscillator formed by the components around Q3. 49.86 MHz serves as a receiver local oscillator signal which hetrodynes an incoming 49.405 MHz signal to a 455 kHz IF frequency. The IF amplifier, detector, are all in IC2. Q1 is the RF amplifier for the receiver. IC1 is a CMOS hex inverter IC that is being used as an audio amp for the receiver audio. T2 is used to couple the microphone audio with the RF. The antenna is a spring wound wire which acts as a electrically short monopole. It is inductively coupled to the RF output through L1 and T1.

When Unit B is turned on it transmits on 49.405MHz. This frequency again serves as both the transmitter carrier and the receiver Local Oscillator. This signal provides low side injection to produce a 455 kHz IF from an incoming 49.86 MHz. signal.

ANTENNA AND GROUND CIRCUITRY

Energy is supplied by a 9 volt battery.

No external ground connection is provided. The unit relies on the ground track of the printed circuit board.

APPLICANT: WINATION TECHNOLOGY MFG.LTD.
FCC ID: N57RY-1350
REPORT #: T:\CUS\W\WINATION\196AH0\196AH.RPT
PAGE #: 3

APPLICANT: WINATION TECHNOLOGY MFG.LTD.

FCC ID: N57RY-1350

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.235

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

| | | |
|---------------|-------------|----------------------|
| 30 - 88 MHz | 40.0 dBuV/M | MEASURED AT 3 METERS |
| 88 - 216 MHz | 43.5 dBuV/M | |
| 216 - 960 MHz | 46.0 dBuV/M | |
| ABOVE 960 MHz | 54.0 dBuV/M | |

* Harmonics must be less than the fundamental.

TEST DATA:

| EMISSION FREQUENCY MHz | METER READING AT 3 METERS dBuV | COAX LOSS dB | ANTENNA CORRECTION FACTOR | FIELD STRENGTH dBuV/m@3m | MARGIN dB | ANT. POL. |
|------------------------------|--------------------------------------|--------------------|---------------------------------|--------------------------------|--------------|--------------|
| 49.86 | 48.20 | 0.25 | 10.99 | 59.44 | 20.56 | V |
| 99.70 | 12.50 | 0.80 | 8.39 | 21.69 | 21.81 | V |
| 149.60 | 6.70 | 0.80 | 16.90 | 24.40 | 19.10 | V |
| 199.40 | 23.00 | 0.90 | 12.66 | 36.56 | 6.94 | V |
| 249.30 | 19.80 | 1.20 | 13.35 | 34.35 | 11.65 | V |
| 299.20 | 14.10 | 1.40 | 15.65 | 31.15 | 14.85 | V |
| 349.00 | 15.30 | 1.40 | 15.52 | 32.22 | 13.78 | V |
| 398.90 | 10.30 | 1.40 | 16.97 | 28.67 | 17.33 | V |
| 448.70 | 11.00 | 1.60 | 18.12 | 30.72 | 15.28 | V |
| 498.60 | 11.50 | 1.60 | 19.27 | 32.37 | 13.63 | V |

SAMPLE CALCULATION: $FSdBuV/m = MR(dBuV) + ACFdB$.

WITH THE TRANSMITTER SECTIONS OF THIS UNIT DISABLED BY REMOVING R11, THE SPECTRUM WAS SCANNED FROM 30 TO 1000 MHz. NO SIGNIFICANT EMISSIONS WERE NOTED.

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

TEST RESULTS: THE UNIT does MEET THE FCC REQUIREMENTS.

PERFORMED BY: Mario R. de Aranzeta DATE: JUNE 15, 2000

APPLICANT: WINATION TECHNOLOGY MFG.LTD.
FCC ID: N57RY-1350
REPORT #: T:\CUS\W\WINATION\196AH0\196AH.RPT
PAGE #: 4

APPLICANT : WINATION TECHNOLOGY MFG. LTD.

FCC ID: N57RY-1350

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.209

REQUIREMENTS: 1.705 to 30 MHz: 49.54 dBuV/m @ 3 METERS
 30 to 88 MHz: 40.00 dBuV/M @ 3 METERS
 88 to 216 MHz: 43.52 dBuV/M
 216 to 960 MHz: 46.02 dBuV/M
 ABOVE 960 MHz: 54.00 dBuV/M

* Harmonics must be less than the fundamental

TEST RESULTS: A search was made of the spectrum from 25 to 1000 MHz and the measurements indicate that the unit DOES meet the FCC requirements.

TEST DATA:

| EMISSION FREQUENCY MHz | METER READING AT 3 METERS dBuV | COAX LOSS dB | ANTENNA CORRECTION FACTOR | FIELD STRENGTH dBuV/m@3m | MARGIN dB | ANT. POL. |
|------------------------------|---|--------------------|---------------------------------|--------------------------------|--------------|--------------|
| 49.40 | 27.40 | 0.25 | 10.98 | 38.63 | 1.37 | V |
| 98.80 | 7.60 | 0.80 | 8.81 | 17.21 | 26.29 | V |

SAMPLE CALCULATION: $FSdBuV/m = MR(dBuV) + ACFdB.$

TEST PROCEDURE: ANSI STANDARD C63.4-1992 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Preselector, a Hewlett Packard Model 85650A Quasi-Peak adapter, Electro-Metric Dipole kits, models TDA, TDS-25-1, TDS-25-2, and an Eaton Model 94455-1 Biconical Antenna. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

PERFORMED BY: Mario R. de Aranzeta

DATE: JUNE 15, 2000

APPLICANT: WINATION TECHNOLOGY MFG. LTD.

FCC ID: N57RY-1350

REPORT #: T:\CUS\W\WINATION\196AH0\196AH.RPT

PAGE #: 5

APPLICANT: WINATION TECHNOLOGY MFG.LTD.

FCC ID: N57RY-1350

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.235

REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPHS IN EXHIBITS 10A-10B REPRESENT THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the above photo was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: Mario R. de Aranzeta JUNE 15, 2000

APPLICANT: WINATION TECHNOLOGY MFG.LTD.
FCC ID: N57RY-1350
REPORT #: T:\CUS\W\WINATION\196AH0\196AH.RPT
PAGE #: 6