

Test report No:
NIE: 63024RRF.002A1

Test report

USA FCC Part 15.247, 15.209

CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz.

Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio Apparatus.

(*) Identification of item tested	BLx Hub (BRT, VRR)
(*) Trademark	Valeo
(*) Model and /or type reference	BLXH1A
Other identification of the product	SW version: V3.25 HW version: B156717_0x_a FCC ID: N5F-BLXH1 IC: 3248A-BLXH1
(*) Features	Valeo proprietary protocol, Bluetooth Low Energy
Applicant	VALEO COMFORT & DRIVING ASSISTANCE SYSTEMS, SAS 76 rue Auguste Perret, 94046 Créteil CEDEX, FRANCE
Test method requested, standard	USA FCC Part 15.247 (10-1-19 Edition): Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 (10-1-19 Edition): Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 (Marh 2019). Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Rafael López EMC Consumer & RF Lab. Manager
Date of issue	2021-05-17
Report template No	FDT08_23 (*) "Data provided by the client"

Index

Competences and guarantees3

General conditions3

Uncertainty3

Data provided by the client.....3

Usage of samples4

Test sample description5

Identification of the client.....6

Testing period and place.....6

Document history6

Environmental conditions6

Remarks and comments7

Testing verdicts.....8

Summary8

Appendix A: Test results. Bluetooth Low Energy.....9

Competences and guarantees

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC -Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample consists of an Automotive Smart Connectivity device (Bluetooth Low Energy Hub).

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of result.

Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Reception
63024E/024	The device shall enable the remote management of Vehicle functions via a Smart Phone.	BLXH1A	--	2020/01/15

- Sample S/01 is composed of the following auxiliary elements:

Control N°	Description	Model	Serial N°	Reception
63024E/017	Test box McLaren VRR	--	--	2020/01/15
63024E/018	Connecting cable	--	--	2020/01/15
63024E/019	RS232 cable	--	--	2020/01/15
63024E/023	Sensor	--	--	2020/01/15

Sample S/01 has undergone the following test(s): All RADIATED tests indicated in Appendix A.

- Sample S/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Reception
63024E/024	The device shall enable the remote management of Vehicle functions via a Smart Phone.	BLXH1A	--	2020/01/15

- Sample S/02 is composed of the following auxiliary elements:

Control N°	Description	Model	Serial N°	Reception
63024E/017	Test box McLaren VRR	--	--	2020/01/15
63024E/018	Connecting cable	--	--	2020/01/15
63024E/019	RS232 cable	--	--	2020/01/15

Sample S/02 has undergone the following test(s): All CONDUCTED tests indicated in Appendix A.

Test sample description

Ports..... :	Port name and description	Cable					
		Specified max length [m]	Attached during test	Shielded	Coupled to patient ⁽³⁾		
			☐	☐	☐		
Supplementary information to the ports..... :							
Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☐	AC:	☐	☐	☐	☐	☐
	☐	DC:					
Rated Power							
Clock frequencies							
Other parameters..... :							
Software version	V3.25						
Hardware version..... :	B156717_0x_a						
Dimensions in cm (W x H x D).... :							
Mounting position..... :	☐	Table top equipment					
	☐	Wall/Ceiling mounted equipment					
	☐	Floor standing equipment					
	☐	Hand-held equipment					
	☐	Other:					
Modules/parts	Module/parts of test item	Type			Manufacturer		
Accessories (not part of the test item)	Description	Type			Manufacturer		
Documents as provided by the applicant..... :	Description	File name			Issue date		

⁽³⁾ Only applicable to medical equipments.

Identification of the client

VALEO COMFORT & DRIVING ASSISTANCE SYSTEMS, SAS
76 rue Auguste Perret, 94046 Créteil CEDEX, FRANCE

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2020-01-16
Date (finish)	2020-01-17

Document history

Report number	Date	Description
63024RRF.002	2020-04-03	First release
63024RRF.002A1	2021-05-17	Second release: First modification due to changes in model name, antenna gain and FCC ID, IC. This modification test report cancels and replaces the test report 63024RRF.002

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 35 %

Remarks and comments

The tests have been performed by the technical personnel: Nicolás Salguero, Cristina Calle and Ignacio Cabra.

Used instrumentation:

Conducted Measurements:

		Last Calibration	Due Calibration
1.	Signal and Spectrum Analyzer ROHDE AND SCHWARZ FSV40	2019/09	2021/09
2.	DC power supply R&S NGPE 40/40	2018/02	2021/02

Radiated Measurements:

		Last Calibration	Due Calibration
1.	Semianechoic Absorber Lined Chamber ETS LINDGREN FACT 3 200 STP	N.A.	N.A.
2.	EMI Test Receiver ROHDE AND SCHWARZ ESR7	2019/10	2021/10
3.	RF pre-amplifier 30 MHz-6 GHz Bonn Elektronik BLNA 0160-01N	2019/09	2020/09
4.	Biconical/Log Antenna ETS LINDGREN 3142E	2017/04	2020/04
5.	Signal and Spectrum Analyzer ROHDE AND SCHWARZ FSW50	2018/02	2020/02
6.	RF pre-amplifier 1-18 GHz Bonn Elektronik BLMA 0118-1M	2019/04	2020/04
7.	RF Pre-amplifier 30 dB, 18 GHz-40 GHz BONN ELEKTRONIK BLMA 1840-1M	2019/02	2021/02
8.	Broadband Horn antenna 1-18 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9120 D	2019/11	2022/11
9.	Broadband Horn antenna 18-40 GHz SCHWARZBECK BBHA 9170	2018/07	2021/07
10.	DC Power supply GPS-3030D GW INSTTEK	--	--
11.	Digital multimeter FLUKE 175	2019/10	2020/10

Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

Summary

1. Bluetooth Low Energy.

FCC PART 15 PARAGRAPH/ RSS-247			
Requirement – Test case		Verdict	Remark
Section 15.247 Subclause (a) (2) / RSS-247 5.2. (a)	6 dB Bandwidth	P	
Section 15.247 Subclause (b) / RSS-247 5.4. (d)	Maximum output power and antenna gain	P	
Section 15.247 Subclause (d) / RSS-247 5.5.	Band-edge emissions compliance (Transmitter)	P	
Section 15.247 Subclause (e) / RSS-247 5.2. (b)	Power spectral density	P	
Section 15.247 Subclause (d) / RSS-247 5.5.	Emission limitations radiated (Transmitter)	P	
<u>Supplementary information and remarks:</u>			
None.			

Appendix A: Test results. Bluetooth Low Energy.

TEST CONDITIONS	11
Occupied Bandwidth	13
FCC Section 15.247 Subclause (a) (2) / RSS-247 Clause 5.2 (a) 6 dB Bandwidth.....	15
FCC Section 15.247 Subclause (b) / RSS-247 Clause 5.4 (d) Maximum output power and antenna gain	17
FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Band-edge emissions compliance (Transmitter) ..	20
FCC Section 15.247 Subclause (e) / RSS-247 5.2. (b) Power spectral density	24
FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Emission limitations radiated (Transmitter)	26

TEST CONDITIONS

POWER SUPPLY (V):

Vn:	12 Vdc
Type of Power Supply:	Battery
Type of Antenna:	Dedicated Antenna (equipment with antenna connector)
Maximum Declared Antenna Gain:	2.3 dBi

TEST FREQUENCIES:

Low Channel:	2402 MHz
Middle Channel:	2440 MHz
High Channel:	2480 MHz

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to the spectrum analyser using a low loss RF cable. The reading of the spectrum analyser is corrected taking into account the cable loss.



RADIATED MEASUREMENTS


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna (Bilog antenna for the range between 30 MHz to 1000 MHz) is situated at a distance of 3 m and at a distance of 1m for the frequency range 1 GHz-26 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height (Bilog antenna and Double ridge horn antenna) was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup from 30 MHz to 1 GHz:



Radiated measurements setup $f > 1$ GHz:




Occupied Bandwidth


RESULTS:

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
99% bandwidth (MHz)	1.035	1.035	1.035
-26 dBc bandwith (MHz)	1.265	1.265	1.26
Measurement uncertainty (kHz)	<± 5.00		


- Low Channel:



- Middle Channel:



- High Channel:



FCC Section 15.247 Subclause (a) (2) / RSS-247 Clause 5.2 (a) 6 dB Bandwidth.

SPECIFICATION:


The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS:


	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
6 dB Spectrum bandwidth (kHz)	705.0	705.0	705.0
Measurement uncertainty (kHz)	<±17.0		

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:



FCC Section 15.247 Subclause (b) / RSS-247 Clause 5.4 (d) Maximum output power and antenna gain

SPECIFICATION:

For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).

The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

RESULTS:

The maximum peak conducted output power level in the fundamental emission was measured using the method according to point 11.9.1.1 "RBW $\geq$ DTS bandwidth" of ANSI C.63.10-2013.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.


Maximum Declared Antenna Gain: 2.3 dBi

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Maximum Conducted Power (dBm)	6.60	5.97	6.20
Maximum EIRP Power (dBm)	8.90	8.27	8.50
Measurement uncertainty (dB)	< $\pm$ 0.78		


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:




FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Band-edge emissions compliance (Transmitter)

SPECIFICATION:

In any 100 kHz bandwidths outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.


RESULTS:

- Low Channel:



Verdict: PASS

- High Channel:



Verdict: PASS


Measurement uncertainty (dB)	<±2.03
------------------------------	--------

Band-edge compliance of radiated emissions.


Maximum peak and average field strength of fundamental emission at 3 m distance

CHANNEL (2480 MHz).


Maximum field strength at 3 m. Peak value:



Maximum field strength at 3 m. Average value:



BAND-EDGE COMPLIANCE. RADIATED. Marker-Delta Method.



Band edge compliance of radiated emissions

Fundamental max. average value 3 m	Delta value	Calculated value 3 m	Limit
74.58 dBμV/m	42.88 dB	31.7 dBμV/m	54 dBμV/m

Fundamental max. Peak value 3 m	Delta value	Calculated value 3 m	Limit
99.69 dBμV/m	42.88 dB	56.81 dBμV/m	74 dBμV/m

Verdict: PASS

FCC Section 15.247 Subclause (e) / RSS-247 5.2. (b) Power spectral density

SPECIFICATION:

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


RESULTS:

The maximum power spectral density level in the fundamental emission was measured using the method according to point 11.10.2.” Method PKPSD (peak PSD)” of ANSI C.63.10-2013.


	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Power Spectral Density (dBm)	6.05	5.39	5.63
Measurement uncertainty (dB)	<±0.78		

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:



FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Emission limitations radiated (Transmitter)

SPECIFICATION:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)/RSS-Gen):

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 10000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247: Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz - 1 GHz:

The spurious frequencies detected do not depend neither on the operating channel nor the modulation mode.

-Spurious frequencies detected at less than 20 dB below the limit:

Spurious frequency (MHz)	Detector	Emission Level (dBμV/m)	Polarization	Measurement Uncertainty (dB)
30.534	Peak	24.69	V	<± 3.86
	Quasipeak	20.10		
63.999	Peak	25.10	V	
	Quasipeak	24.40		
96.009	Peak	38.50	V	
	Quasipeak	38.20		
128.019	Peak	27.97	V	
	Quasipeak	27.60		
160.029	Peak	30.13	H	
	Quasipeak	28.40		
192.006	Peak	24.22	V	
	Quasipeak	22.10		
320.014	Peak	31.00	V	
	Quasipeak	30.10		
351.992	Peak	27.7	V	
	Quasipeak	26.3		
416.012	Peak	29.46	V	
	Quasipeak	25.80		

Verdict: PASS

Frequency range 1 - 26 GHz:

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz.

Spurious frequencies with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with average detector for checking compliance with the average limit.

- LOW CHANNEL. Spurious frequencies detected at less than 20 dB below the limit:

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.3899	Peak	62.50	V	< $\pm$ 4.72
	AVG	37.45		
4.8043	Peak	40.51	V	
7.2063	Peak	46.02	V	
9.6072	Peak	46.27	V	

- MIDDLE CHANNEL. Spurious frequencies detected at less than 20 dB below the limit:

Spurious frequency (GHz)	Detector	Emission Level (dBμV/m)	Polarization	Measurement Uncertainty (dB)
2.3914	Peak	52.25	V	<± 4.72
2.4875	Peak	53.61	V	
2.4879	Peak	52.57	V	
4.8795	Peak	40.69	H	
7.3192	Peak	46.79	V	


- HIGH CHANNEL. Spurious frequencies detected at less than 20 dB below the limit:

Spurious frequency (GHz)	Detector	Emission Level (dBμV/m)	Polarization	Measurement Uncertainty (dB)
2.4399	Peak	50.56	V	<± 4.72
2.4856	Peak	70.07	V	
	AVG	41.16		
2.49575	Peak	59.09	V	
	AVG	38.86		
4.9602	Peak	41.03	V	
7.4391	Peak	47.92	V	

Verdict: PASS

FREQUENCY RANGE 30 MHz - 1 GHz:


The spurious frequencies detected do not depend neither on the operating channel nor the modulation mode.



This plot is valid for the Low, Middle and High Channels.


FREQUENCY RANGE 1 - 3 GHz:

- Low Channel:




The peak above the limit is the carrier frequency.

- Middle Channel:



The peak above the limit is the carrier frequency.


- High Channel:




The peak above the limit is the carrier frequency.

FREQUENCY RANGE 3 - 17 GHz:


- Low Channel:



- Middle Channel:




- High Channel:



FREQUENCY RANGE 17 - 26 GHz:


The spurious frequencies detected do not depend on the operating channel.




This plot is valid for the Low, Middle and High Channels.

FREQUENCY RANGE 2.31-2.39 GHz:


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 2.4835-2.5 GHz:

- Low Channel:



- Middle Channel:



- High Channel:

