



## **SAR Test exclusion documentation according to FCC KDB 447498, RSS-102**

**Report identification number: 1-4505/17-01-08 Exclusion (FCC\_IC)**

### **Product: Activity Key**

**contains the module with the following certification numbers**

FCC ID	N5F-FK1A
IC number	3248A-FK1A
HVIN (Hardware Version Identification Number)	FK1A
PMN (Product Marketing Name)	Activity Key
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### **Document authorised:**

Alexander Hnatovskiy  
Lab Manager  
Radio Communications & EMC

Marco Scigliano  
Testing Manager  
Radio Communications & EMC

**EUT technologies:**

Technologies:	Max. power: (AVG)	Max. EIRP (AVG):
434 MHz radio module	---	Fieldstrength: 75.8 dB $\mu$ V/m @ 3 m = - 19.4 dBm = 0.007 mW

Applied worst case averaged field strength see CTC advanced GmbH test report 1-4505/17-01-02 section 10.4.

**SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)**

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

(1) Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances  $\leq$  50mm

$$(\text{Threshold}_{1\text{-g};10\text{-g}}) \times d_{\text{seperation}} / f^{0.5}$$

where

$\text{Threshold}_{1\text{-g};10\text{-g}}$  is 3 for 1-g; 7.5 for 10-g

$d_{\text{seperation}}$  is the min. test separation distance; 5mm is used if the distance is less

$f$  is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	d <sub>seperation</sub> [mm]	Threshold <sub>1-g</sub>	Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
				[dBm]	[mW]	
434.00	5	3	22.77	-19.40	0.01	yes

**SAR test exclusion according to RSS-102 Issue 5 Section 2.5.1/Table 1**

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	d <sub>seperation</sub> [mm]	tissue volume	Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
				[dBm]	[mW]	
434.00	5	1 g	56.00	-19.40	0.01	yes