



BUREAU
VERITAS Test Report No.: FS120331N026

RF EXPOSURE REPORT

Applicant	Terraboost Media LLC
Address	3109 Grand Avenue #300Miami, Florida, U.S.A. 33133

Manufacturer or Supplier	Terraboost Media LLC	
Address	3109 Grand Avenue #300Miami, Florida, U.S.A. 33133	
Product:	LED Hand Sanitizing Billboard	
Brand Name:	Terraboost Media®	
Model:	LCDFSAMC04-WF	
Date of tests:	April 02 ~ May 25 , 2012	

the tests have been carried out according to the requirements of the following standards:

- FCC Part 2 (Section 2.1091)**
- FCC OET Bulletin 65, Supplement C (01-01)**
- IEEE C95.1**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Reviewed by Glyn He Supervisor / EMC Department	Approved by Sam Tung Manager / EMC Department

Date: May 25, 2012

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF Exposure Limit	5
3. MPE calculation Formula.....	5
4. Classification.....	5
5. calculation result of maximum conducted power	6



**BUREAU
VERITAS** Test Report No.: FS120331N026

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	N/A	May 25, 2012

**Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch**

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



**BUREAU
VERITAS** Test Report No.: FS120331N026

1. CERTIFICATION

PRODUCT: LED Hand Sanitizing Billboard

MODEL: LCDFSAMC04-WF

APPLICANT: Terraboost Media LLC

TESTED: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1



2. RF Exposure Limit

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
802.11b max 2412MHz	19.48	3.8	20	0.042	1.00
802.11g Max 2437MHz	24.32	3.8	20	0.129	1.00
802.11n 20MHz Max 2462MHz	24.37	3.8	20	0.131	1.00
802.11n 40MHz Max 2452MHz	23.89	3.8	20	0.117	1.00