

# TEST REPORT

<b>Eurofins KCTL Co.,Ltd.</b> 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <a href="http://www.kctl.co.kr">www.kctl.co.kr</a>	Report No.: KR23-SRF0061 Page (1) of (7)	 <b>KCTL</b>
--	--	--

**1. Client**

- Name : Golfzon. CO., LTD
- Address : GOLFZON TOWER SEOUL 10-11F, 13F-17F, 19F, 735, Yeongdong-daero, Gangnam, Seoul, Republic of Korea
- Date of Receipt : 2022-07-21

**2. Use of Report** : Certification

**3. Name of Product / Model** : Portable Golfsensor\_IR / GZ-GWPS-22

**4. Manufacturer / Country of Origin** : Teravalue Inc., / Korea

**5. FCC ID** : N5Y-GZ-GWPS-22

**6. Date of Test** : 2022-08-09 to 2022-08-16

**7. Location of Test** :  Permanent Testing Lab  On Site Testing  
 (Address: 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)

**8. Test method used** : Part 1.1310

**9. Test Result** : Refer to the test result in the test report

Affirmation	Tested by  Name : Hyesom Shin 	Technical Manager  Name : Harim Lee 
-------------	---	---

2023-02-15

**Eurofins KCTL Co.,Ltd.**

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

## REPORT REVISION HISTORY

Date	Revision	Page No
2023-02-15	Originally issued	-

*This report shall not be reproduced except in full, without the written approval of Eurofins KCTL Co.,Ltd. This document may be altered or revised by Eurofins KCTL Co.,Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by Eurofins KCTL Co.,Ltd. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.*

### General remarks for test reports

#### Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

**Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:**

#### Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

**Statement not required by the standard or client used for type testing**

## CONTENTS

1. General information .....	4
2. Device information .....	4
2.1. Frequency/channel operations.....	5
3. Antenna requirement .....	5
4. RF Exposure.....	6
4.1. Test results.....	7



## 1. General information

Client : Golfzon. CO., LTD  
Address : GOLFZON TOWER SEOUL 10-11F, 13F-17F, 19F, 735,  
Yeongdong-daero, Gangnam, Seoul, Republic of Korea  
Manufacturer : Teravalue Inc.,  
Address : 70, Gasan digital 2-ro, Geumcheon-gu, Seoul, Republic of Korea  
Laboratory : Eurofins KCTL Co.,Ltd.  
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132  
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056  
CAB Identifier: KR0040  
ISED Number: 8035A  
KOLAS No.: KT231

## 2. Device information

Equipment under test : Portable Golfsensor\_IR  
Model : GZ-GWPS-22  
Modulation technique : Bluetooth(BLE)\_GFSK  
Number of channels : 40 ch  
Power source : DC 5 V  
Antenna specification : Chip Antenna  
Antenna gain : -7.08 dBi  
Frequency range : 2 402 MHz ~ 2 480 MHz  
Software version : Wave-P1-221128  
Hardware version : IR-PUTT V0.9  
Test device serial No. : N/A  
Operation temperature : -10 °C ~ 50 °C

## 2.1. Frequency/channel operations

This device contains the following capabilities:

Bluetooth Low Energy

Ch.	Frequency (MHz)
00	2 402
:	:
19	2 440
:	:
39	2 480

Table 2.1.1. Bluetooth Low Energy

## 3. Antenna requirement

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty ( $\pm$ )
Conducted RF power	0.9 dB

<b>Eurofins KCTL Co.,Ltd.</b> 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <a href="http://www.kctl.co.kr">www.kctl.co.kr</a>	Report No.: KR23-SRF0061 Page (6) of (7)	 <b>eurofins</b> <b>KCTL</b>
--	--	--

## 4. RF Exposure

### Regulation

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Table 1 – Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm <sup>2</sup> ]	Averaging Time [minute]
(A) Limits for Occupational / Controlled Exposure				
0.3 ~ 3.0	614	1.63	*100	6
3.0 ~ 30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30 ~ 300	61.4	0.163	1.0	6
300 ~ 1 500	/	/	f/300	6
1 500 ~ 15 000	/	/	5	6
(B) Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19/f	*180/f <sup>2</sup>	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, \* = plane-wave equivalent power density

Per the guidance of KDB 680106, the E-field and H-field limits shown in the table above are extended down to 100 kHz

### MPE (Maximum Permissive Exposure) Prediction

Prediction of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm<sup>2</sup>]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

## 4.1. Test results

### Calculation Result of RF exposure (FCC)

Maximum tune-up tolerance

Mode	Frequency [MHz]	Max Tune-up Power [dBm]	Max Tune-up Power [mW]	Ant Gain [dBi]	Ant Gain [mW]	Power density at 20 cm [mW/cm <sup>2</sup> ]	Limit [mW/cm <sup>2</sup> ]
BLE_1M Bits/s	2 402	1.00	1.26	-7.08	0.20	0.000 05	1.000 00

**Note.**

1. The power density  $P_d$  at a distance of 20 cm calculated from the friis transmission Formula is far below the limit of 1  $\text{mW/cm}^2$ .

**End of test report**