

RF Exposure Evaluation

1. Maximum Permissible Exposure

1.1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

1.3. Calculated Result and Limit

Antenna Type : PIFA Antenna
Max Conducted Power for 5GHz

Mobile
For Single Chain:
IEEE 802.11a

Operating Frequency (GHz)	Min. User Distance (cm)	Gain (dBi)	Numeric Gain	Output Power (dBm)	Conducted Power (mW)	Power Density (mW/cm ²)
5.745	20	2	1.584893	15.68	36.9828	0.0117

For Two Chain:
Configuration of IEEE 802.11n (20MHz)

Operating Frequency (GHz)	Min. User Distance (cm)	Gain (dBi)	Numeric Gain	Output Power (dBm)	Conducted Power (mW)	Power Density (mW/cm ²)
5.745	20	2	1.584893	17.13	51.6416	0.0163

Configuration of IEEE 802.11n (40MHz)

Operating Frequency (GHz)	Min. User Distance (cm)	Gain (dBi)	Numeric Gain	Output Power (dBm)	Conducted Power (mW)	Power Density (mW/cm ²)
5.755	20	2	1.584893	18.23	66.5273	0.0210