

FCC PART 15.249

TEST REPORT

For

HANGZHOU CENTURY CO., LTD

1418-48# Moganshan Road, Hangzhou Zhejiang, P.R.China

FCC ID: N6K-LA132S

Report Type: Original Report	Product Type: Electronic Shelf Label
Test Engineer: Hope Zhang	<i>Hope Zhang</i>
Report Number: RSHA180711014-00B	
Report Date: 2018-08-28	
Reviewed By: Oscar Ye RF Leader	<i>Oscar Ye</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
FCC§15.203 - ANTENNA REQUIREMENT.....	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION.....	10
APPLICABLE STANDARD	10
EUT SETUP	10
TEST EQUIPMENT SETUP	11
TEST PROCEDURE	11
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST RESULTS SUMMARY	12
TEST DATA	12
FCC §15.215(C) - 20 DB BANDWIDTH TESTING.....	19
APPLICABLE STANDARD	19
TEST PROCEDURE	19
TEST DATA	19

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	HANGZHOU CENTURY CO., LTD
Tested Model:	LA132S
Product Type:	Electronic Shelf Label
Dimension:	75.6mm(L)*34.3mm(W)*16.2mm(H)
Power Supply:	DC 3.0V from CR2032 Lithium Battery

All measurement and test data in this report was gathered from production sample serial number: 20180711014. (Assigned by BACL, Kunshan). The EUT was received on 2018-07-11.

Objective

This type approval report is prepared on behalf of HANGZHOU CENTURY CO., LTD in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

Grant with FCC Part 15.249 DXT under FCC ID: N6K-WB-DB308

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Justification

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2404.21	21	2424.21	41	2444.21	61	2464.21
2	2405.21	22	2425.21	42	2445.21	62	2465.21
3	2406.21	23	2426.21	43	2446.21	63	2466.21
4	2407.21	24	2427.21	44	2447.21	64	2467.21
5	2408.21	25	2428.21	45	2448.21	65	2468.21
6	2409.21	26	2429.21	46	2449.21	66	2469.21
7	2410.21	27	2430.21	47	2450.21	67	2470.21
8	2411.21	28	2431.21	48	2451.21	68	2471.21
9	2412.21	29	2432.21	49	2452.21	69	2472.21
10	2413.21	30	2433.21	50	2453.21	70	2473.21
11	2414.21	31	2434.21	51	2454.21	71	2474.21
12	2415.21	32	2435.21	52	2455.21	72	2475.21
13	2416.21	33	2436.21	53	2456.21	73	2476.21
14	2417.21	34	2437.21	54	2457.21	74	2477.21
15	2418.21	35	2438.21	55	2458.21	75	2478.21
16	2419.21	36	2439.21	56	2459.21	76	2479.21
17	2420.21	37	2440.21	57	2460.21	77	2480.21
18	2421.21	38	2441.21	58	2461.21		
19	2422.21	39	2442.21	59	2462.21		
20	2423.21	40	2443.21	60	2463.21		

EUT was tested with channel 1, 37 and 77.

EUT Exercise Software

No software was used during the test; the applicant provided three fixed frequencies samples for test.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	Conduction Emissions	Not Applicant
15.205, §15.209, §15.249	Radiated Emissions& Out of Band Emission	Compliant
§15.215 (c)	20 dB Bandwidth	Compliant

Note 1: The EUT is battery operated equipment.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2018-08-15	2019-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2018-08-27	2019-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
MICRO-TRONICS	Notch filter	BRM50702	/	2018-08-05	2019-08-04
Mini-Circuits	Amplifier	ZVA-183W-S+	220701818	2018-05-20	2019-05-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2018-03-22	2019-03-21
Narda	Attenuator/10dB	10dB	/	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2018-08-15	2019-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2017-09-21	2018-09-20
Narda	Attenuator/2dB	10dB	/	2018-08-15	2019-08-14
CENTURY	RF Cable	/	/	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has a PCB antenna and antenna gain is 0 dBi, which was permanently attached ,fulfill the requirement of this section, please refer to the EUT photos.

Result: Compliant.

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:


Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Test Equipment Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz - 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode from 30MHz to 1GHz, Peak and average detection mode above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 &15.205 & 15.249.

Test Data

Environmental Conditions


Temperature:	24.6°C
Relative Humidity:	52%
ATM Pressure:	101.2 kPa

The testing was performed by Hope Zhang on 2018-08-27~2018-08-28

Test Mode: Transmitting (Scan with X-Axis, Y-Axis and Z-Axis position, the worst case X-Axis was recorded)

Spurious Emission Test:**30MHz-1GHz**

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low channel of operation in X-axis of orientation** was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	Quasi-peak (dB μ V/m)	Height (cm)	Polar (H/V)				
31.447258	28.62	200.0	H	262.0	-4.3	40.00	11.38
77.661900	15.48	200.0	V	352.0	-17.6	40.00	24.52
120.816350	20.66	100.0	H	214.0	-11.2	43.50	22.84
256.038500	25.92	100.0	H	246.0	-11.9	46.00	20.08
639.998250	36.60	100.0	H	272.0	-4.4	46.00	9.40
799.990650	38.25	100.0	H	3.0	-1.7	46.00	7.75

1GHz-18GHz


(Pre-scan in the X, Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded.)

Note:

1. This test was performed with the 2.4-2.4835GHz notch filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit – Corrected. Amplitude

Low Channel: 2404.21MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1646.000000	40.22	---	150.0	V	174.0	-0.2	74.00	33.78
1646.000000	---	29.72	150.0	V	174.0	-0.2	54.00	24.28
3573.800000	46.46	---	150.0	H	80.0	7.5	74.00	27.54
3573.800000	---	37.17	200.0	H	80.0	7.5	54.00	16.83
4808.420000	55.27	---	100.0	V	26.0	10.7	74.00	18.73
4808.420000	---	45.10	100.0	V	26.0	10.7	54.00	8.90
7212.630000	52.45	---	150.0	H	174.0	15.2	74.00	21.55
7212.630000	---	42.84	100.0	H	174.0	15.2	54.00	11.16
10302.400000	55.88	---	200.0	V	0.0	17.9	74.00	18.12
10302.400000	---	44.96	200.0	V	0.0	17.9	54.00	9.04
14814.200000	56.87	---	100.0	V	68.0	18.8	74.00	17.13
14814.200000	---	45.62	100.0	V	68.0	18.8	54.00	8.38

Middle Channel: 2440.21MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1455.600000	39.13	---	200.0	H	0.0	-1.5	74.00	34.87
1455.600000	---	28.72	100.0	H	0.0	-1.5	54.00	25.28
3573.800000	47.72	---	150.0	V	35.0	7.5	74.00	26.28
3573.800000	---	37.27	150.0	V	35.0	7.5	54.00	16.73
4880.420000	54.28	---	150.0	H	227.0	11.1	74.00	19.72
4880.420000	---	45.97	150.0	H	227.0	11.1	54.00	8.03
7320.630000	53.09	---	200.0	H	8.0	15.6	74.00	20.91
7320.630000	---	42.69	200.0	H	8.0	15.6	54.00	11.31
11019.800000	56.39	---	150.0	H	100.0	19.0	74.00	17.61
11019.800000	---	45.76	200.0	H	100.0	19.0	54.00	8.24
15290.200000	57.58	---	100.0	V	218.0	18.4	74.00	16.42
15290.200000	---	46.50	100.0	V	218.0	18.4	54.00	7.50

High Channel: 2480.21MHz



Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1414.800000	38.37	---	100.0	V	67.0	-1.7	74.00	35.63
1414.800000	---	28.58	100.0	V	67.0	-1.7	54.00	25.42
2625.200000	44.38	---	200.0	V	280.0	3.9	74.00	29.62
2625.200000	---	33.92	200.0	V	280.0	3.9	54.00	20.08
4960.420000	54.99	---	100.0	H	14.0	11.5	74.00	19.01
4960.420000	---	43.43	100.0	H	14.0	11.5	54.00	10.57
7440.630000	52.49	---	150.0	V	31.0	15.5	74.00	21.51
7440.630000	---	43.19	150.0	V	31.0	15.5	54.00	10.81
10224.200000	55.42	---	100.0	V	355.0	18.0	74.00	18.58
10224.200000	---	45.56	100.0	V	355.0	18.0	54.00	8.44
14338.200000	56.18	---	150.0	V	314.0	18.7	74.00	17.82
14338.200000	---	45.41	150.0	V	314.0	18.7	54.00	8.59

18GHz-25GHz

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low channel of operation in X-axis of orientation** was recorded)

Horizontal**Vertical**

Fundamental Test & Restricted Bands Emissions Test:

(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)

Note:

1. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2404.21MHz								
2400.00	---	37.62	200	V	132	2.8	54.00	16.38
2400.00	50.65	---	200	V	132	2.8	74.00	23.35
2404.21	---	89.14	200	V	230	2.8	94.00	4.86
2404.21	90.27	---	200	V	230	2.8	114.00	23.73
2404.21	---	85.7	150	H	322	2.8	94.00	8.30
2404.21	87.03	---	150	H	322	2.8	114.00	26.97
Middle Channel: 2440.21MHz								
2440.21	---	89.14	250	V	62	2.9	94.00	4.86
2440.21	90.54	---	250	V	62	2.9	114.00	23.46
2440.21	---	87.99	200	H	159	2.9	94.00	6.01
2440.21	88.35	---	200	H	159	2.9	114.00	25.65
High Channel: 2480.21MHz								
2480.21	---	89.93	250	V	55	3.1	94.00	4.07
2480.21	91.19	---	250	V	55	3.1	114.00	22.81
2480.21	---	89.05	150	H	161	3.1	94.00	4.95
2480.21	91.48	---	150	H	161	3.1	114.00	22.52
2483.50	---	31.55	200	V	324	3.1	54.00	22.45
2483.50	42.37	---	200	V	324	3.1	74.00	31.63

FCC §15.215(c) - 20 dB BANDWIDTH TESTING

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through § 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	24.2°C
Relative Humidity:	50 %
ATM Pressure:	101.3kPa


The testing was performed by Hope Zhang on 2018-08-27.

Test Result: Compliant.


Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2404.21	1.551
Middle	2440.21	1.299
High	2480.21	1.311

Low Channel



Middle Channel



High Channel



***** END OF REPORT *****