



# FCC RF Test Report

**APPLICANT** : Sierra Wireless, Inc.  
**EQUIPMENT** : Wireless Module  
**BRAND NAME** : AirPrime  
**MODEL NAME** : EM9190  
**FCC ID** : N7NEM91  
**STANDARD** : 47 CFR Part 2, 90(R)  
**CLASSIFICATION** : PCS Licensed Transmitter (PCB)

The product was received on Feb. 15, 2020 and completely tested on May 10, 2020. We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Reviewed by: Derreck Chen / Supervisor

Approved by: Eric Shih / Manager



**Sportun International (ShenZhen) Inc.**  
1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055  
People's Republic of China



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1 Applicant .....	5
1.2 Manufacturer.....	5
1.3 Feature of Equipment Under Test .....	5
1.4 Maximum Conducted Power, Frequency Tolerance, and Emission Designator.....	6
1.5 Testing Site.....	6
1.6 Test Software.....	7
1.7 Applied Standards .....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1 Test Mode .....	8
2.2 Connection Diagram of Test System.....	9
2.3 Support Unit used in test configuration and system .....	9
2.4 Measurement Results Explanation Example.....	9
<b>3 CONDUCTED TEST ITEMS .....</b>	<b>10</b>
3.1 Measuring Instruments .....	10
3.2 Conducted Output Power and ERP .....	11
3.3 Peak-to-Average Ratio .....	12
3.4 Occupied Bandwidth.....	13
3.5 Conducted Band Edge Measurement .....	14
3.6 Emission Mask.....	15
3.7 Conducted Spurious Emission Measurement .....	16
3.8 Frequency Stability Measurement .....	17
<b>4 RADIATED TEST ITEMS .....</b>	<b>18</b>
4.1 Measuring Instruments .....	18
4.2 Test Setup .....	18
4.3 Test Result of Radiated Test .....	18
4.4 Radiated Spurious Emission Measurement .....	19
<b>5 LIST OF MEASURING EQUIPMENT .....</b>	<b>20</b>
<b>6 UNCERTAINTY OF EVALUATION.....</b>	<b>21</b>
<b>APPENDIX A. TEST RESULTS OF CONDUCTED TEST</b>	
<b>APPENDIX B. TEST RESULTS OF RADIATED TEST</b>	
<b>APPENDIX C. TEST SETUP PHOTOGRAPHS</b>	



# REVISION HISTORY



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	PASS	-
	§90.542 (a)(7)	Effective Radiated Power	ERP < 3Watt	PASS	-
3.3	-	Peak-to-Average Ratio	Reporting only	-	-
3.4	§2.1049	Occupied Bandwidth	Reporting only	PASS	-
3.5	§2.1053 §90.543 (e)(2)(3)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.6	§2.1051 §90.210(n)	Emission Mask	Mask B	PASS	-
3.7	§2.1053 §90.543 (e)(3)	Conducted Spurious Emission	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.8	§2.1055 §90.539 (e)	Frequency Stability Temperature & Voltage	< ±1.25 ppm	PASS	-
4.4	§2.1053 §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 28.75 dB at 1581.50 MHz

### Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

### Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



## 1 General Description

### 1.1 Applicant

**Sierra Wireless, Inc.**

13811 Wireless Way, Richmond, BC, Canada V6A 3A4

### 1.2 Manufacturer

**Sierra Wireless, Inc.**

13811 Wireless Way, Richmond, BC, Canada V6A 3A4

### 1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Wireless Module
Brand Name	AirPrime
Model Name	EM9190
FCC ID	N7NEM91
Tx Frequency	LTE Band 14: 790.5 MHz ~ 795.5 MHz
Rx Frequency	LTE Band 14: 760.5 MHz ~ 765.5 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	23.22 dBm
Antenna Gain	2.0 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM
IMEI Code	Conducted/ Radiation: 351735110001290
HW Version	1.0
SW Version	00.15.01.00
EUT Stage	Identical Prototype

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. For modulation of QPSK / 16QAM / 64QAM / 256QAM supports uplink and measurement output power, according to the maximum power of 256QAM is lower than other modulation, therefore, 256QAM measurement is unnecessary. We always chose higher power (QPSK / 16QAM / 64QAM) to perform all tests.



## 1.4 Maximum Conducted Power, Frequency Tolerance, and Emission Designator

LTE Band 14		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum Conducted power (W)
5	790.5~795.5	4M50G7D	-	0.2065	4M49W7D	-	0.1774
10	793	9M05G7D	0.0080	0.2099	9M05W7D	-	0.1795
LTE Band 14		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)		Maximum Conducted power (W)		
5	790.5~795.5	4M51W7D	-		0.1387		
10	793	9M05W7D	-		0.1387		

## 1.5 Testing Site

Sportun International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

<b>Test Firm</b>	Sportun International (Shenzhen) Inc.		
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
<b>Test Site No.</b>	<b>Sportun Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	TH01-SZ	CN1256	421272
<b>Test Firm</b>	Sportun International (Shenzhen) Inc.		
<b>Test Site Location</b>	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan Shenzhen, 518055 People's Republic of China TEL: +86-755-33202398		
<b>Test Site No.</b>	<b>Sportun Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	03CH02-SZ	CN1256	421272



## 1.6 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a

## 1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, Part 90(R)
- ♦ ANSI C63.26
- ♦ KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ KDB 412172 D01 Determining ERP and EIRP v01r01

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test


### 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	14	-	-	V	-	-	-	V	V	V	V	V	V	V	V	V
	14	-	-		V	-	-	V	V	V	V	V	V		V	
Peak-to-Average Ratio	14	-	-		V	-	-	V	V	V	V		V		V	
26dB and 99% Bandwidth	14	-	-	V		-	-	V	V	V			V	V	V	V
	14	-	-		V	-	-	V	V	V			V		V	
Conducted Band Edge	14	-	-	V		-	-	V	V	V	V		V	V		V
	14	-	-		V	-	-	V	V	V	V		V		V	
Emission Mask	14	-	-	V		-	-	V	V	V	V		V	V	V	V
	14	-	-		V	-	-	V	V	V	V		V		V	
Conducted Spurious Emission	14	-	-	V		-	-	V	V	V	V		V	V	V	V
	14	-	-		V	-	-	V	V	V	V				V	
Frequency Stability	14	-	-		V	-	-	V					V		V	
E.R.P	14	-	-	V		-	-	V	V	V	V		V	V	V	V
	14	-	-		V	-	-	V	V	V	V				V	
Radiated Spurious Emission	14	-	-	V		-	-	V			V		V	V	V	V
		-	-		V			V			V			V		V
Note	<ol style="list-style-type: none"> <li>1. The mark "v" means that this configuration is chosen for testing</li> <li>2. The mark "-" means that this bandwidth is not supported.</li> <li>3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.</li> </ol>															

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	DC Power Supply	Topward	3303DR	N/A	N/A	Unshielded, 1.8m
3.	WWAN Antenna	PANORAMA	PWB-6-60-RSMAP	N/A	N/A	N/A

## 2.4 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.0 + 10 = 14.0 \text{ (dB)} \end{aligned}$$

### 3 Conducted Test Items

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

##### 3.1.1 Test Setup


##### 3.1.2 Conducted Output Power



##### 3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission



##### 3.1.4 Frequency Stability



##### 3.1.5 Test Result of Conducted Test

Please refer to Appendix A.



## 3.2 Conducted Output Power and ERP

### 3.2.1 Description of the Conducted Output Power Measurement and ERP

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

### 3.2.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



### 3.3 Peak-to-Average Ratio

#### 3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

#### 3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.



## 3.4 Occupied Bandwidth

### 3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

### 3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.  
The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.  
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



## 3.5 Conducted Band Edge Measurement

### 3.5.1 Description of Conducted Band Edge Measurement

For operations in the 758-768 MHz and the 788-798 MHz bands

- (1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $76 + 10 \log (P)$  dB in a 6.25 kHz band segment, for base and fixed stations.
- (2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $65 + 10 \log (P)$  dB in a 6.25 kHz band segment, for mobile and portable stations.
- (3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least  $43 + 10 \log (P)$  dB.

Compliance with the provisions of paragraph (3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.

### 3.5.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power  $P$  (Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB) = -13 dBm.



## 3.6 Emission Mask

### 3.6.1 Test Procedures

For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
- (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
- (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least  $43 + 10 \log(P)$  dB.

### 3.6.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.  
The path loss was compensated to the results for each measurement.
4. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
5. Set spectrum analyzer with RMS detector.
6. Taking the record of maximum spurious emission.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13 \text{ dBm.}$$



## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10<sup>th</sup> harmonic.

### 3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and base station via power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's, for under 1GHz RBW = 100kHz, VBW = 300kHz and for above 1GHz RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.



## 3.8 Frequency Stability Measurement

### 3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 1.25$  ppm of the center frequency.

### 3.8.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.8.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at  $20\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup

#### 4.2.1 For radiated test from 30MHz to 1GHz



#### 4.2.2 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

Please refer to Appendix B.



## 4.4 Radiated Spurious Emission Measurement

### 4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

### 4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10.  $EIRP (dBm) = S.G. Power - Tx Cable Loss + Tx Antenna Gain$
11.  $ERP (dBm) = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 18, 2019	Mar. 20, 2020~ May 10, 2020	Apr. 17, 2020	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 16, 2020		Apr. 15, 2021	Conducted (TH01-SZ)
DC Power Supply	GWINSTEK	AnritsuGPS-3030D	EM882636	Max 30V	Apr. 18, 2019	Mar. 20, 2020~ May 10, 2020	Apr. 17, 2020	Conducted (TH01-SZ)
DC Power Supply	GWINSTEK	AnritsuGPS-3030D	EM882636	Max 30V	Apr. 16, 2020		Apr. 15, 2021	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Dec. 26, 2019	Mar. 20, 2020~ May 10, 2020	Dec. 25, 2020	Conducted (TH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Apr. 19, 2019	Mar. 25, 2020	Apr. 18, 2020	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Jul. 19, 2019	Mar. 25, 2020	Jul. 18, 2020	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Aug. 27, 2019	Mar. 25, 2020	Aug. 26, 2020	Radiation (03CH02-SZ)
LF Amplifier	Burgeon	BPA-530	102211	0.01~3000Mhz	Oct. 18, 2019	Mar. 25, 2020	Oct. 17, 2020	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 18, 2019	Mar. 25, 2020	Oct. 17, 2020	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010002470	N/A	NCR	Mar. 25, 2020	NCR	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Mar. 25, 2020	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Mar. 25, 2020	NCR	Radiation (03CH02-SZ)

NCR: No Calibration Required



## 6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2U <sub>c</sub> (y))	2.5dB
--	-------

### Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2U <sub>c</sub> (y))	3.3dB
--	-------



## Appendix A. Test Results of Conducted Test

### Conducted Output Power(Average power)

LTE Band 14 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	-	23.22	-
10	1	25			23.05	
10	1	49			22.78	
10	25	0			22.86	
10	25	12			22.98	
10	25	25			22.17	
10	50	0			22.13	
10	1	0			22.54	
10	1	25			22.49	
10	1	49			22.41	
10	25	0			21.16	
10	25	12			21.19	
10	25	25			21.20	
10	50	0			21.13	
10	1	0	16-QAM	-	21.35	-
10	1	25			21.38	
10	1	49			21.42	
10	25	0			20.15	
10	25	12			20.18	
10	25	25			20.20	
10	50	0			20.15	



LTE Band 14 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.06	23.01	23.08
	1	12		23.15	23.14	23.05
	1	24		23.10	23.07	23.00
	12	0		22.17	22.15	22.07
	12	7		22.24	22.17	22.14
	12	13		22.19	22.15	22.09
	25	0		22.20	22.13	22.10
	1	0		22.41	22.36	22.31
5	1	12	16-QAM	22.49	22.49	22.39
	1	24		22.49	22.42	22.39
	12	0		21.22	21.10	21.12
	12	7		21.25	21.17	21.15
	12	13		21.20	21.15	21.10
	25	0		21.19	21.12	21.09
	1	0		21.33	21.29	21.23
	1	12		21.38	21.42	21.28
5	1	24	64QAM	21.39	21.35	21.29
	12	0		20.27	20.01	20.17
	12	7		20.29	20.23	20.19
	12	13		20.24	20.21	20.14
	25	0		20.24	20.17	20.14



## ERP

LTE Band 14 ( $G_T - L_C = 2.0 \text{ dBi}$ ) QPSK						
Bandwidth	5M			10M		
Channel	23305 (Low)	23330 (Mid)	23355 (High)	-	23330 (Mid)	-
	790.5	793	795.5	-	793	-
Frequency (MHz)	23.15	23.14	23.05	-	23.22	-
	0.2065	0.2061	0.2018	-	0.2099	-
Conducted Power (dBm)	23.00	22.99	22.90	-	23.07	-
Conducted Power (Watts)	0.1995	0.1991	0.1950	-	0.2028	-
ERP(dBm)						
ERP(Watts)						

LTE Band 14 ( $G_T - L_C = 2.0 \text{ dBi}$ ) 16QAM						
Bandwidth	5M			10M		
Channel	23305 (Low)	23330 (Mid)	23355 (High)	-	23330 (Mid)	-
	790.5	793	795.5	-	793	-
Frequency (MHz)	22.49	22.49	22.39	-	22.54	-
	0.1774	0.1774	0.1734	-	0.1795	-
Conducted Power (dBm)	22.34	22.34	22.24	-	22.39	-
Conducted Power (Watts)	0.1714	0.1714	0.1675	-	0.1734	-
ERP(dBm)						
ERP(Watts)						




LTE Band 14 ( $G_T - L_C = 2.0 \text{ dBi}$ ) 64QAM						
Bandwidth	5M			10M		
Channel	23305 (Low)	23330 (Mid)	23355 (High)	-	23330 (Mid)	-
	790.5	793	795.5	-	793	-
Frequency (MHz)	21.38	21.42	21.28	-	21.42	-
Conducted Power (dBm)	0.1374	0.1387	0.1343	-	0.1387	-
ERP(dBm)	21.23	21.27	21.13	-	21.27	-
ERP(Watts)	0.1327	0.1340	0.1297	-	0.1340	-

**Peak-to-Average Ratio**

Mode	LTE Band 14 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	PASS
Middle CH	3.68	5.01	5.36	5.83	
Highest CH	-	-	-	-	

Mode	LTE Band 14 / 10MHz		
Mod.	64QAM		Limit: 13dB
RB Size	1RB	Full RB	Result
Lowest CH	-	-	PASS
Middle CH	5.33	5.88	
Highest CH	-	-	




**26dB Bandwidth**

Mode	LTE Band 14 : 26dB BW(MHz)					
	5MHz		10MHz		5MHz	10MHz
Mod.	QPSK	16QAM	QPSK	16QAM	64QAM	64QAM
Lowest CH	4.94	4.81	-	-	4.92	-
Middle CH	4.80	4.87	9.87	9.95	4.84	9.73
Highest CH	4.93	4.92	-	-	4.89	-




## LTE Band 14

## Lowest Channel / 5MHz / QPSK




Date: 20-MAR-2020 12:19:29

## Lowest Channel / 5MHz / 16QAM




Date: 20-MAR-2020 12:19:33

## Middle Channel / 5MHz / QPSK




Date: 20-MAR-2020 11:46:06

## Middle Channel / 5MHz / 16QAM




Date: 20-MAR-2020 11:47:06

## Highest Channel / 5MHz / QPSK




Date: 20-MAR-2020 12:24:11

## Highest Channel / 5MHz / 16QAM




Date: 20-MAR-2020 12:26:07






## LTE Band 14


## Lowest Channel / 5MHz / 64QAM




## Middle Channel / 5MHz / 64QAM



## Middle Channel / 10MHz / 64QAM





## Highest Channel / 5MHz / 64QAM



**Occupied Bandwidth**

Mode	LTE Band 14 : 99%OBW(MHz)					
	5MHz		10MHz		5MHz	10MHz
Mod.	QPSK	16QAM	QPSK	16QAM	64QAM	64QAM
Lowest CH	4.50	4.48	-	-	4.47	-
Middle CH	4.48	4.49	9.05	9.05	4.49	9.05
Highest CH	4.49	4.49	-	-	4.51	-









## LTE Band 14


## Lowest Channel / 5MHz / 64QAM




## Middle Channel / 5MHz / 64QAM



## Middle Channel / 10MHz / 64QAM




## Highest Channel / 5MHz / 64QAM





## Conducted Band Edge







## LTE Band 14 / 5MHz / 16QAM

## Lowest Band Edge / 1 RB

## Highest Band Edge / 1 RB





Date: 10.MAY.2020 16:27:10

Date: 29.APR.2020 20:00:33

## Lowest Band Edge / Full RB

## Highest Band Edge / Full RB



Date: 29.APR.2020 19:24:38



Date: 29.APR.2020 20:06:32



## LTE Band 14 / 5MHz / 64QAM

## Lowest Band Edge / 1 RB

## Highest Band Edge / 1 RB




Date: 10.MAY.2020 18:29:14

Date: 29.APR.2020 19:58:50


## Lowest Band Edge / Full RB

## Highest Band Edge / Full RB



Date: 29.APR.2020 19:26:46

Date: 29.APR.2020 20:09:29








## LTE Band 14 / 10MHz / QPSK

## Lowest Band Edge / 1 RB

## Highest Band Edge / 1 RB



## Band Edge / Full RB








## LTE Band 14 / 10MHz / 16QAM

## Lowest Band Edge / 1 RB

## Highest Band Edge / 1 RB



## Band Edge / Full RB








## LTE Band 14 / 10MHz / 64QAM

## Lowest Band Edge / 1 RB

## Highest Band Edge / 1 RB



## Band Edge / Full RB



Date: 29.APR.2020 20:11:26





## Conducted Spurious Emission

### LTE Band 14 / 5MHz



#### Lowest Channel / QPSK

#### Lowest Channel / 16QAM



#### Middle Channel / QPSK

#### Middle Channel / 16QAM







## LTE Band 14 / 5MHz

## Highest Channel / QPSK


## Highest Channel / 16QAM



## LTE Band 14 / 10MHz

## Middle Channel / QPSK

## Middle Channel / 16QAM








## LTE Band 14 / 5MHz

## Lowest Channel / 64QAM

## Middle Channel / 64QAM




## Highest Channel / 64QAM






## LTE Band 14 / 10MHz


## Middle Channel / 64QAM








## Mask


































## Frequency Stability

Test Conditions		LTE Band 14 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0018	PASS
40	Normal Voltage	0.0080	
30	Normal Voltage	0.0037	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0042	
0	Normal Voltage	0.0012	
-10	Normal Voltage	0.0017	
-20	Normal Voltage	0.0050	
-30	Normal Voltage	0.0007	
20	Maximum Voltage	0.0027	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0057	

**Note:**

1. Normal Voltage =3.3 V. ; Battery End Point (BEP) =3.135 V. ; Maximum Voltage =4.4 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.



## Appendix B. Test Results of Radiated Test

### Field Strength of Spurious Radiated

LTE Band 14 / QPSK / RB Size 1 Offset 0									
Bandwidth	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
5MHz (Lowest)	1576.5	-69.03	-40	-29.03	-78.47	-72.26	3.98	9.36	H
	2364.75	-66.79	-13	-53.79	-80.46	-70.34	4.85	10.55	H
	3153	-65.34	-13	-52.34	-81.12	-70.27	5.50	12.58	H
	1576.5	-69.45	-40	-29.45	-78.33	-72.68	3.98	9.36	V
	2364.75	-66.52	-13	-53.52	-80.26	-70.07	4.85	10.55	V
	3153	-65.59	-13	-52.59	-81.44	-70.52	5.50	12.58	V
5MHz (Middle)	1581.5	-68.75	-40	-28.75	-78.19	-72.00	4.00	9.40	H
	2372.25	-66.69	-13	-53.69	-80.28	-70.26	4.88	10.60	H
	3163	-65.06	-13	-52.06	-80.84	-69.99	5.52	12.60	H
	1581.5	-69.22	-40	-29.22	-78.10	-72.47	4.00	9.40	V
	2372.25	-66.90	-13	-53.90	-80.59	-70.47	4.88	10.60	V
	3163	-65.03	-13	-52.03	-80.88	-69.96	5.52	12.60	V
5MHz (Highest)	1586.5	-69.20	-40	-29.20	-78.64	-72.37	4.10	9.42	H
	2379.75	-66.53	-13	-53.53	-80.12	-70.11	4.90	10.63	H
	3173	-65.29	-13	-52.29	-81.08	-70.21	5.55	12.62	H
	1586.5	-69.67	-40	-29.67	-78.55	-72.84	4.10	9.42	V
	2379.75	-66.74	-13	-53.74	-80.43	-70.32	4.90	10.63	V
	3173	-64.89	-13	-51.89	-80.83	-69.81	5.55	12.62	V
10MHz	1577	-69.05	-40	-29.05	-78.49	-72.30	4.00	9.40	H
	2365.5	-66.52	-13	-53.52	-80.19	-70.09	4.88	10.60	H
	3154	-65.28	-13	-52.28	-81.06	-70.21	5.52	12.60	H
	1577	-69.55	-40	-29.55	-78.43	-72.80	4.00	9.40	V
	2365.5	-66.66	-13	-53.66	-80.40	-70.23	4.88	10.60	V
	3154	-65.34	-13	-52.34	-81.19	-70.27	5.52	12.60	V
Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.									
Test Result					PASS				