



MC7750-L Label Drawing

Label Format:



Label Placement:



NO.	DESCRIPTION	DATE	BY
1.0	PRODUCTION RELEASE	17-MAR-11	AL
2.0	NEW BOX (2200145) AND TRAYS (2201288, 2201289)	12-MAY-11	AL
3.0	ADDED LOOSE LABEL (IF REQUIRED IN THE SKU BOM)	22-DEC-11	AL

GENERAL REQUIREMENTS

- USE CURRENT APPROVED SWI BOM AS THE MASTER CONTROL DOCUMENT FOR MATERIAL, DOCUMENTS AND SOFTWARE. THIS BOM LISTS THE CORRECT REVISION OF EACH ITEM THAT IS TO BE PACKED.
- PRIOR TO SHIPMENT, ALL LABELS MUST HAVE THE PROPER NUMBERS FOR SKU, ESN, IMEI, ETC. AS SPECIFIED IN THE LABEL DRAWING SPECS FOR THIS SKU.
- SHIPPED PRODUCT MUST CONFORM TO THE STANDARD DESCRIBED IN SWI DOC# 2140122 - GENERAL COSMETIC SPEC FOR SWI.
- DIMENSIONS ARE SHOWN IN MILLIMETERS AND INCHES. DIMENSIONS IN INCHES ARE SHOWN IN [BRACKETS].
- RECOMMENDED PACKOUT SEQUENCE IS DESCRIBED BELOW.
 - APPLY MINICARD LABEL
 - FOLD MANUFACTURING BOX
 - INSERT MINICARDS AND LOOSE LABELS, IF REQUIRED INTO TRAY AND COVER THE TRAY
 - INSERT TRAY INTO MANUFACTURING BOX
 - CLOSE, SEAL AND LABEL MANUFACTURING BOX
 - REFER TO SWI LOGISTICS DEPARTMENT FOR SHIPPING AND PACK LIST INSTRUCTIONS.

APPLY MINICARD LABEL

- FOR DISPLAY PURPOSES, MC7750 MINICARD AND LABEL IS SHOWN. ACTUAL MINICARD AND LABEL MAY NOT BE EXACTLY AS SHOWN. NONETHELESS, OPERATOR IS TO FOLLOW BELOW INSTRUCTIONS.
 - IF APPLICABLE, REMOVE TEMPORARY LABEL FROM MINICARD (M1) AND APPLY MINICARD LABEL (L1) TO THE SHIELD LID OF THE MINICARD (M1). PLACE AS SHOWN, CENTERED ON THE TOP FACE OF THE SHIELD LID. THE TOP EDGE SHOULD BE LOCATED 0.5 MM $\pm$ 0.5MM FROM THE SHIELD TOP EDGE. MAX. HORIZONTAL SKEW FROM TOP EDGE 0.25MM.
 - LABEL SHOULD BE ORIENTED IN SUCH A WAY THAT THE ARTWORKED TRIANGLES POINT TOWARDS THE ANTENNA CONNECTORS ON THE MODem.



DATE THIS DOCUMENT WAS REVISED: 22-DEC-11

DO NOT SCALE PRINT

SIERRA WIRELESS

22002292

3.0