



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com>



## RF EXPOSURE EVALUATION (MAXIMUM PERMISSIBLE EXPOSURE)

**Applicant Name:**

Sierra Wireless  
13811 Wireless Way  
Richmond, Canada

**Date of Testing:**

November 5, 2010

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Test Report Serial No.:**

0Y1010261761.N7N-R5

**FCC ID:** **N7NMC7750****APPLICANT:** **Sierra Wireless****EUT Type:** Cellular/PCS GSM/EDGE/WCDMA/CDMA/EvDO and 700 MHz LTE Wireless Module**FCC Rule Part(s):** FCC Part 1 (§1.1310) and Part 2 (§2.1091)**FCC Classification:** PCS Licensed Transmitter (PCB)**Test Procedure:** OET Bulletin 65

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in FCC OET Bulletin 65 (See Test Report). These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

**\*This revised Test Report (S/N: 0Y1010261761.N7N-R5) supersedes and replaces the previously issued test report on the same subject EUT for the same type of testing as indicated. Please discard and destroy the previously issued test report (S/N: 0Y1010261761.N7N-R4) and dispose of it accordingly.**

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

*PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862*

  
\_\_\_\_\_  
Randy Ortanez  
President

FCC ID: N7NMC7750	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		
Test Report S/N: 0Y1010261761.N7N-R5	Test Dates: November 5, 2010	EUT Type: Cellular/PCS GSM/EDGE/WCDMA/CDMA/EvDO and 700 MHz LTE Wireless Module	Reviewed by: Quality Manager Page 1 of 7

## T A B L E   O F   C O N T E N T S

---

1.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	3
1.1	INTRODUCTION .....	3
1.2	EUT DESCRIPTION.....	3
1.3	MPE REQUIREMENTS OVERVIEW.....	4
1.4	PROCEDURE.....	5
1.5	SUMMARY OF RESULTS.....	6
2.0	CONCLUSION.....	7

FCC ID: N7NMC7750	 <b>MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT</b>			 <b>Reviewed by:</b> Quality Manager
Test Report S/N: 0Y1010261761.N7N-R5	Test Dates: November 5, 2010	EUT Type: Cellular/PCS GSM/EDGE/WCDMA/CDMA/EvDO and 700 MHz LTE Wireless Module		Page 2 of 7

## 1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### 1.1 Introduction

This document is prepared on behalf of Sierra Wireless to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations and RSS-102 of Industry Canada.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310 and RSS-102: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

**Table 1-1. Limits for Maximum Permissible Exposure (MPE)**

### 1.2 EUT Description

The Sierra Wireless Model: MC7750 is a GSM/EDGE/WCDMA/CDMA/EvDO and LTE Band 13 Module. For this MPE evaluation the device is set to transmit from the antenna of each transmitter and the RF exposure of each transmitter is evaluated individually.

#### EUT:

Model: MC7750  
 Grantee: Sierra Wireless  
 FCC ID: N7NMC7750

FCC ID: N7NMC7750		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	Reviewed by: Quality Manager
Test Report S/N: 0Y1010261761.N7N-R5	Test Dates: November 5, 2010	EUT Type: Cellular/PCS GSM/EDGE/WCDMA/CDMA/EvDO and 700 MHz LTE Wireless Module	Page 3 of 7

### 1.3 MPE Requirements Overview

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows:

- **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The **Sierra Wireless Cellular/PCS GSM/EDGE/WCDMA/CDMA/EvDO and 700 MHz LTE Wireless Module** FCC ID: **N7NMC7750** is evaluated to the Mobile Device requirements and is considered a device to be used by the General Population/Uncontrolled Exposure.

FCC ID: N7NMC7750		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1010261761.N7N-R5	Test Dates: November 5, 2010	EUT Type: Cellular/PCS GSM/EDGE/WCDMA/CDMA/EvDO and 700 MHz LTE Wireless Module		Page 4 of 7

## 1.4 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each transmitter used in this product was initially measured by a power meter and the powers were recorded. Through use of the Friis transmission formula and the maximum antenna gain specified by the manufacturer, the power density level is calculated at a distance of 20cm.

The antenna gains of each antenna to be used with the different available transmitters were used to calculate the MPE in all relevant bands of operation.

### Friis Transmission Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

$P_d$  = Power Density (mW/cm<sup>2</sup>)

$\pi = 3.1416$

$P_{out}$  = output power to antenna (mW)

$r$  = distance between observation point and center of the radiator (cm)

$G$  = gain of antenna in linear scale

### Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1.

There is no co-location between the electric fields of any two transmitters therefore following power densities are calculated for each individual transmitter by frequency at 20cm spacing.

Calculations for RF Exposure compliance in the cellular and PCS bands are based on the maximum source-based time-averaged powers obtained from 2-Slot GPRS operation. The resulting duty-cycle factor is 2/8, or 6.02dB.

Frequency	848.8 MHz	
Limit	0.566 mW/cm <sup>2</sup>	
Distance (cm), R =	20 cm	
Power (dBm), P =	32.60 dBm	1819.70 mW
S-B T-A Power (dBm), Psb =	26.58 dBm	454.93 mW
TX Ant Gain (dBi), G =	7.30 dBi	
Power Density (S) =	0.275 mW/cm <sup>2</sup> (at 20cm)	
Minimum Distance =	2.7 cm	

Table 1-2. Calculated MPE Data for Cellular Band

FCC ID: N7NMC7750	 <b>PCTEST</b> Engineering Laboratory, Inc.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1010261761.N7N-R5	Test Dates: November 5, 2010	EUT Type: Cellular/PCS GSM/EDGE/WCDMA/CDMA/EvDO and 700 MHz LTE Wireless Module		Page 5 of 7

Frequency:	1880 MHz	
Limit:	1.000 mW/cm <sup>2</sup>	
Distance (cm), R =	20 cm	
Power (dBm), P =	29.54 dBm	899.50 mW
S-B T-A Power (dBm), Psb =	23.52 dBm	224.87 mW
TX Ant Gain (dBi), G =	3.00 dBi	
Power Density (S) =	0.065 mW/cm <sup>2</sup> (at 20cm)	
Minimum Distance =	6.0 cm	

Table 1-3. Calculated MPE Data for PCS Band

Frequency	782 MHz	
Limit	0.521 mW/cm <sup>2</sup>	
Distance (cm), R =	20 cm	
Power (dBm), P =	23.56 dBm	226.99 mW
TX Ant Gain (dB), G =	9.00 dBi	
Power Density (S) =	0.359 mW/cm <sup>2</sup> (at 20cm)	
Minimum Distance =	16.6 cm	

Table 1-4. Calculated MPE Data for LTE Band

## 1.5 Summary of Results

Frequency Band [MHz]	Maximum Antenna Gain [dBi]	MPE @ 20cm (mW/cm <sup>2</sup> )	Test Result
824.2 – 848.8	7.30	0.275	PASS
1850.2 – 1909.8	3.00	0.065	PASS
779.5 – 784.5	9.00	0.359	PASS

Table 1-5. Maximum Permissible Exposure Summary Table

FCC ID: N7NMC7750	 <b>PCTEST</b> Engineering Laboratory, Inc.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	 <b>SIERRA WIRELESS</b> WEAR OF THE WIRELESS MACHINE	Reviewed by: Quality Manager
Test Report S/N: 0Y1010261761.N7N-R5	Test Dates: November 5, 2010	EUT Type: Cellular/PCS GSM/EDGE/WCDMA/CDMA/EvDO and 700 MHz LTE Wireless Module		Page 6 of 7

## 2.0 CONCLUSION

The device meets the mobile RF exposure limit at a 20cm separation distance as specified in §2.1091 of the FCC Rules and Regulations and Health Canada Safety Code 6. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: N7NMC7750	 PCTEST <sup>®</sup> Engineering Laboratory, Inc.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		 SIERRA WIRELESS WEAR OF THE WIRELESS MACHINE	Reviewed by: Quality Manager
Test Report S/N: 0Y1010261761.N7N-R5	Test Dates: November 5, 2010	EUT Type: Cellular/PCS GSM/EDGE/WCDMA/CDMA/EvDO and 700 MHz LTE Wireless Module			Page 7 of 7