



**FCC OET BULLETIN 65 SUPPLEMENT C 01-01  
IEEE STD 1528:2003**

**SAR EVALUATION REPORT**

*For*  
**MC7750 PCI Express Mini Card**  
**(Tested inside of Panasonic Laptop PC CF-C1)**

**MODEL NUMBER: MC7750**  
**FCC ID: N7NMC7750**

**REPORT NUMBER: 11J14091-1C**  
**ISSUE DATE: 4/9/2012**

*Prepared for*  
**Sierra Wireless Inc.**  
**13811 Wireless Way**  
**Richmond, BC, V6V 3A4**  
**Canada**

*Prepared by*  
**COMPLIANCE CERTIFICATION SERVICES (UL CCS)**  
**47173 BENICIA STREET**  
**FREMONT, CA 94538, U.S.A.**  
**TEL: (510) 771-1000**  
**FAX: (510) 661-0888**

**NVLAP**<sup>®</sup>  
NVLAP LAB CODE 200065-0

Revision History

| Rev. | Issue Date | Revisions   | Revised By   |
|------|------------|---|--------------|
| --   | 10/26/2011 | Initial Issue   | --           |
| A    | 1/4/2012   | <ol style="list-style-type: none"><li>1. Sec. 2: Added KDB 616217</li><li>2. Sec. 5.1: Updated Table</li><li>3. Sec. 11: Removed 1xRTT power table as voice mode is not supported</li><li>4. Sec. 11.2: Added Measured MPR on LTE Output Power Table</li><li>5. Sec. 11.2.1: Updated Spectrum Plots</li><li>6. Sec. 12: Additional Testing for LTE Band 13. Removed unnecessary 5MHz Bandwidth SAR Test Results and Test Plots.</li><li>7. Sec. 13: Added Table</li><li>8. Sec. 16: Updated Antenna Diagram</li></ol> | Bobby Bayani |
| B    | 1/11/2012  | <ol style="list-style-type: none"><li>1. Sec. 5: Corrected typo for item #7</li><li>2. Sec. 12.1: Added Note explain why low and high channels were not tested (CDMA modes)</li><li>3. Sec. 12.2: Removed unnecessary SAR Data</li><li>4. Added missing System Validation Dipole for D750V3 – S/N 1024</li></ol>  | Bobby Bayani |
| B1   | 2/17/2012  | <ol style="list-style-type: none"><li>1. Sec. 12.2: Additional Testing for LTE Band 13 performed. Removed unnecessary SAR Data.</li></ol>   | Bobby Bayani |
| C    | 4/9/2012   | <ol style="list-style-type: none"><li>1. Sec. 5 &amp; 5.1: Updated Table.</li><li>2. Sec. 11.2.1: Removed 5MHz Bandwidth LTE Spectrum Plots.</li><li>3. Sec. 12, 15, &amp;16: Revised Configuration Labels.</li><li>4. Sec. 12.2: Added Measured MPR and LTE Test Reduction Note.</li></ol>   | Bobby Bayani |


## Table of Contents

|  |           |
|--|-----------|
| <b>1. Attestation of Test Results.....</b>                                     | <b>5</b>  |
| <b>2. Test Methodology .....</b>   | <b>6</b>  |
| <b>3. Facilities and Accreditation .....</b>                                   | <b>6</b>  |
| <b>4. Calibration and Uncertainty .....</b>                                    | <b>7</b>  |
| 4.1. <i>Measuring Instrument Calibration .....</i>                             | 7         |
| 4.2. <i>Measurement Uncertainty.....</i>                                       | 8         |
| <b>5. Equipment Under Test.....</b>  | <b>9</b>  |
| 5.1. <i>KDB 941225 D05 "SAR for LTE Devices v01".....</i>                      | 10        |
| <b>6. System Specification .....</b>   | <b>12</b> |
| <b>7. Composition of Ingredients for Tissue Simulating Liquids .....</b>       | <b>13</b> |
| <b>8. Liquid Parameters.....</b>   | <b>14</b> |
| 8.1. <i>Simulating Liquid Check Results.....</i>                               | 15        |
| <b>9. System Verification.....</b>   | <b>16</b> |
| 9.1. <i>System Check Results.....</i>  | 17        |
| <b>10. SAR Measurement Procedures .....</b>                                    | <b>18</b> |
| <b>11. RF Output Power Verification.....</b>                                   | <b>19</b> |
| 11.1. <i>CDMA2000 Cell and PCS Band .....</i>                                  | 19        |
| 11.2. <i>LTE Band 13 .....</i>   | 21        |
| 11.2.1. <i>Spectrum Plots for the Test RB allocations .....</i>                | 22        |
| <b>12. Summary of Test Results .....</b>                                       | <b>26</b> |
| 12.1. <i>CDMA2000 Cell &amp; PCS Band.....</i>                                 | 26        |
| 12.2. <i>LTE BAND 13.....</i>  | 27        |
| <b>13. Simultaneous Transmission SAR Analysis .....</b>                        | <b>29</b> |
| <b>14. Appendixes.....</b>   | <b>30</b> |
| 14.1. <i>Appendix A: System Check Plots .....</i>                              | 30        |
| 14.2. <i>Appendix B: SAR Test Plots for CDMA2000 Cell &amp; PCS band .....</i> | 30        |
| 14.3. <i>Appendix C: SAR Test Plots for LTE Band 13.....</i>                   | 30        |
| 14.4. <i>Appendix D: Calibration Certificate for EX3DV4 SN 3686.....</i>       | 30        |
| 14.5. <i>Appendix E: Calibration Certificate for EX3DV4 SN 3772.....</i>       | 30        |
| 14.6. <i>Appendix F: Calibration Certificate for EX3DV4 SN 3773.....</i>       | 30        |
| 14.7. <i>Appendix G: Calibration Certificate for D750V3 SN1019 .....</i>       | 30        |

---

|  |           |
|--|-----------|
| 14.8. <i>Appendix H: Calibration Certificate for D750V3 SN1024 .....</i>     | 30        |
| 14.9. <i>Appendix I: Calibration Certificate for D835V2 SN 4d117.....</i>    | 30        |
| 14.10. <i>Appendix J: Calibration Certificate for D1900V2 SN 5d140 .....</i> | 30        |
| <b>15. Summary of Test configurations.....</b>                               | <b>31</b> |
| <b>16. Antenna Locations &amp; Separation Distances.....</b>                 | <b>32</b> |
| <b>17. Host Device Photos.....</b>   | <b>36</b> |

## 1. Attestation of Test Results

| Applicant name:  | Sierra Wireless Inc.   |  |              |
|--|--|--|--------------|
| EUT description:   | The EUT is the Sierra Wireless MC7750<br>Cell and PCS band for CDMA/EvDO and Band 13 for LTE Module<br>(Tested inside of Panasonic Laptop PC, Model CF-C1)<br>(GPRS/EDGE and UMTS are disabled.) |  |              |
| Model number:  | MC7750   |  |              |
| Device category:   | Portable   |  |              |
| Exposure category:   | General Population/Uncontrolled Exposure   |  |              |
| Date tested:   | October 17-20, 2011<br>February 10, 2012 (Additional Testing)  |  |              |
| FCC Rule Parts   | Freq. Range [MHz]  | Highest 1g SAR (mW/g)  | Limit (mW/g) |
| 27 (LTE Band 13)   | 779.5 – 784.5  | 0.116<br>(Tablet mode Edge 1)  | 1.6          |
| 22H  | 824 – 849  | 0.135<br>(Tablet mode Edge 1)  |              |
| 24E  | 1850 – 1910  | 0.504<br>(Tablet mode Edge 1)  |              |
| Applicable Standards   |  |  | Test Results |
| OET Bulletin 65 Supplement C 01-01, IEEE STD 1528: 2003  |  |  | Pass         |
| Compliance Certification Services, Inc. (UL CCS) tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.   |  |  |              |
| <p><b>Note:</b> The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government (NIST Handbook 150, Annex A). This report is written to support regulatory compliance of the applicable standards stated above.</p> |  |  |              |
| Approved & Released For CCS By:  |  | Tested By:   |              |
|   |  |  |              |
| Sunny Shih<br>Engineering Team Leader<br>Compliance Certification Services (UL CCS)  |  | Bobby Bayani<br>SAR Engineer<br>Compliance Certification Services (UL CCS)           |              |

## 2. Test Methodology

The tests documented in this report were performed in accordance with FCC OET Bulletin 65 Supplement C Edition 01-01, IEEE STD 1528:2003 and the following KDBs Procedures.

- 447498 D01 Mobile Portable RF Exposure v04
- 616217 D03 SAR Supp Note and Netbook Laptop V01
- 941225 D01 SAR test for 3G devices v02
- 941225 D05 SAR for LTE Devices v01

## 3. Facilities and Accreditation

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>

## 4. Calibration and Uncertainty

### 4.1. Measuring Instrument Calibration

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

| Name of Equipment            | Manufacturer  | Type/Model  | Serial No. | Cal. Due date               |    |      |
|------------------------------|---------------|-------------|------------|-----------------------------|----|------|
|                              |               |             |            | MM                          | DD | Year |
| Dielectric Probe Kit         | HP            | 85070C      | N/A        | N/A                         |    |      |
| Network Analyzer             | Agilent       | E5071B      | MY42100131 | 2                           | 11 | 2013 |
| Synthesized Signal Generator | HP            | 83732B      | US34490599 | 7                           | 14 | 2012 |
| E-Field Probe                | SPEAG         | EX3DV4      | 3686       | 1                           | 24 | 2012 |
| E-Field Probe                | SPEAG         | EX3DV4      | 3772       | 5                           | 3  | 2012 |
| E-Field Probe                | SPEAG         | EX3DV4      | 3773       | 5                           | 3  | 2012 |
| Thermometer                  | EXTECH        | Thermometer | SCL29766   | 5                           | 17 | 2012 |
| Data Acquisition Electronics | SPEAG         | DAE3        | 500        | 7                           | 14 | 2012 |
| System Validation Dipole     | SPEAG         | D750V3      | 1019       | 12                          | 10 | 2011 |
| System Validation Dipole     | SPEAG         | D750V3      | 1024       | 4                           | 20 | 2012 |
| System Validation Dipole     | SPEAG         | D835V2      | 4d117      | 4                           | 15 | 2012 |
| System Validation Dipole     | SPEAG         | D1900V2     | 5d140      | 4                           | 18 | 2012 |
| Power Meter                  | HP            | 437B        | 3125U16345 | 5                           | 13 | 2012 |
| Power Sensor                 | HP            | 8481A       | 1834588    | 5                           | 13 | 2012 |
| Directional Coupler          | Warlatone     | C8060-102   | 2141       | N/A                         |    |      |
| Radio Communication Analyzer | R&S           | CMU200      | 838114/032 | 3                           | 1  | 2012 |
| Radio Communication Analyzer | Anritsu       | MT8820C     | 6200985430 | 6                           | 17 | 2012 |
| Amplifier                    | Mini-Circuits | ZVE-8G      | 90606      | N/A                         |    |      |
| Amplifier                    | Mini-Circuits | ZHL-42W     | D072701-5  | N/A                         |    |      |
| Simulating Liquid            | SPEAG         | MSL750      | N/A        | Within 24 hrs of first test |    |      |
| Simulating Liquid            | SPEAG         | MSL900      | N/A        | Within 24 hrs of first test |    |      |
| Simulating Liquid            | SPEAG         | MSL1900     | N/A        | Within 24 hrs of first test |    |      |

## 4.2. Measurement Uncertainty

| Specific Absorption Rate (SAR) uncertainty calculation            |          |                    |         |             |           |
|---|----------|--------------------|---------|-------------|-----------|
| Measurement uncertainty for 300 MHz to 3 GHz averaged over 1 gram |          |                    |         |             |           |
| Component   | error, % | Probe Distribution | Divisor | Sensitivity | U (Xi), % |
| <b>Measurement System</b>   |          |                    |         |             |           |
| Probe Calibration (k=1)   | 5.50     | Normal             | 1       | 1           | 5.50      |
| Axial Isotropy  | 1.15     | Rectangular        | 1.732   | 0.7071      | 0.47      |
| Hemispherical Isotropy  | 2.30     | Rectangular        | 1.732   | 0.7071      | 0.94      |
| Boundary Effect   | 0.90     | Rectangular        | 1.732   | 1           | 0.52      |
| Probe Linearity   | 3.45     | Rectangular        | 1.732   | 1           | 1.99      |
| System Detection Limits   | 1.00     | Rectangular        | 1.732   | 1           | 0.58      |
| Readout Electronics   | 0.30     | Normal             | 1       | 1           | 0.30      |
| Response Time   | 0.80     | Rectangular        | 1.732   | 1           | 0.46      |
| Integration Time  | 2.60     | Rectangular        | 1.732   | 1           | 1.50      |
| RF Ambient Conditions - Noise                                     | 3.00     | Rectangular        | 1.732   | 1           | 1.73      |
| RF Ambient Conditions - Reflections                               | 3.00     | Rectangular        | 1.732   | 1           | 1.73      |
| Probe Positioner Mechanical Tolerance                             | 0.40     | Rectangular        | 1.732   | 1           | 0.23      |
| Probe Positioning with respect to Phantom                         | 2.90     | Rectangular        | 1.732   | 1           | 1.67      |
| Extrapolation, Interpolation and Integration                      | 1.00     | Rectangular        | 1.732   | 1           | 0.58      |
| <b>Test Sample Related</b>  |          |                    |         |             |           |
| Test Sample Positioning   | 2.90     | Normal             | 1       | 1           | 2.90      |
| Device Holder Uncertainty   | 3.60     | Normal             | 1       | 1           | 3.60      |
| Output Power Variation - SAR Drift                                | 5.00     | Rectangular        | 1.732   | 1           | 2.89      |
| <b>Phantom and Tissue Parameters</b>                              |          |                    |         |             |           |
| Phantom Uncertainty (shape and thickness)                         | 4.00     | Rectangular        | 1.732   | 1           | 2.31      |
| Liquid Conductivity - deviation from target                       | 5.00     | Rectangular        | 1.732   | 0.64        | 1.85      |
| Liquid Conductivity - measurement                                 | 3.10     | Normal             | 1       | 0.64        | 1.98      |
| Liquid Permittivity - deviation from target                       | 5.00     | Rectangular        | 1.732   | 0.6         | 1.73      |
| Liquid Permittivity - measurement                                 | -2.59    | Normal             | 1       | 0.6         | -1.55     |
| Combined Standard Uncertainty Uc(y) =                             |          |                    |         |             | 9.77      |
| Expanded Uncertainty U, Coverage Factor = 2, > 95 % Confidence =  |          |                    |         |             | 19.54 %   |
| Expanded Uncertainty U, Coverage Factor = 2, > 95 % Confidence =  |          |                    |         |             | 1.55 dB   |

## 5. Equipment Under Test

|  |   |  |
|--|---|--|
| <p>The EUT is the Sierra Wireless MC7750 Cell and PCS band for CDMA/EvDO and Band 13 for LTE Module. Tested inside Panasonic Laptop PC, CF-C1 (GPRS/EDGE and UMTS are disabled.)</p> |   |  |
| Normal operation:  | <ul style="list-style-type: none"><li>• Laptop mode (notebook)</li><li>• Tablet with Multiple display orientations supporting all Edge configurations.</li></ul>  |  |
| Antenna tested:  | <u>Manufactured:</u><br>Panasonic   | <u>Part Number:</u><br>Main: DFUP1887ZA(1)<br>Aux: Rx only |
| Antenna-to-antenna/user separation distances:  | See Section 16 for details of antenna locations and separation distances.   |  |
| Simultaneous transmission:   | <ul style="list-style-type: none"><li>• WWAN can transmit simultaneously with WiFi</li><li>• WWAN can transmit simultaneously with Bluetooth</li><li>• WiFi can transmit simultaneously with Bluetooth</li></ul>  |  |
| Assessment for SAR evaluation for Simultaneous transmission:   | <p><b>WiFi and BT</b><br/>Due to Bluetooth's maximum output is <math>&lt; 60/f(\text{GHz})</math> mW and standalone SAR is not required, that WiFi and Bluetooth are not considered as co-located transmitters each other.<br/>(Bluetooth – FCC ID: ACJ9TGBT11B, IC: 216A-CFBT11B)</p> <p><b>WWAN and BT</b><br/>Same as WiFi and BT</p> <p><b>WWAN and WiFi</b><br/>SAR is not required due to <math>\sum (\text{SAR}_{1g}) &lt; \text{SAR limit}</math>.<br/>(Refer to Sec. 13 Simultaneous Transmission SAR Analyses.)</p> |  |


## 5.1. KDB 941225 D05 “SAR for LTE Devices v01”

| #  | Description   | Parameter  |
|----|---|--|
| 1  | Identify the operating frequency range of each LTE transmission band used by the device   | Band 13: 779.5 - 784.5 MHz (5 MHz BW)<br>782 MHz (10MHz BW)  |
| 2  | Identify the channel bandwidths used in each frequency band; 1.4, 3, 5, 10, 15, 20 MHz etc  | 5MHz, 10MHz  |
| 3  | Identify the high, middle and low (H, M, L) channel numbers and frequencies in each LTE frequency band  | Please refer to section 11.2   |
| 4  | Specify the UE category and uplink modulations used   | The UE Category is 3<br>Uplink modulations: QPSK, 16QAM  |
| 5  | Descriptions of the LTE transmitter and antenna implementation & identify whether it is a standalone transmitter operating independently of other wireless transmitters in the device or sharing hardware components and/or antenna(s) with other transmitters etc.   | Please refer Sec. 16 Antenna locations and distance  |
| 6  | Identify the LTE voice/data requirements in each operating mode and exposure condition with respect to head and body test configurations, antenna locations, handset flip-cover or slide positions, antenna diversity conditions, etc.  | Please refer to Tables in section 12   |
| 7  | Identify if Maximum Power Reduction (MPR) is optional or mandatory, i.e. built-in by design: a) only mandatory MPR may be considered during SAR testing, when the maximum output power is permanently limited by the MPR implemented within the UE; and only for the applicable RB (resource block) configurations specified in LTE standards b) A-MPR (additional MPR) must be disabled.   | <ul style="list-style-type: none"> <li>• Built-in by design</li> <li>• A-MPR was disabled.</li> </ul> Please refer to Tables in section 12 |
| 8  | Include the maximum average conducted output power measured on the required test channels for each channel bandwidth and UL modulation used in each frequency band: <ul style="list-style-type: none"> <li>a) with 1 RB allocated at the upper edge of a channel</li> <li>b) with 1 RB allocated at the lower edge of a channel</li> <li>c) using 50% RB allocation centered within a channel</li> <li>d) using 100% RB allocation</li> </ul> | Refer to section 11.2 RF output power table  |
| 9  | Identify all other U.S. wireless operating modes (3G, Wi-Fi, WiMax, Bluetooth etc), device/exposure configurations (head and body, antenna and handset flip-cover or slide positions, antenna diversity conditions etc.) and frequency bands used for these modes   | CDMA2000 (Cell and PCS) and LTE functions are contained within the module. Only one band/mode can be operational at a time                 |
| 10 | Include the maximum average conducted output power measured for the other wireless mode and frequency bands   | See section 11 RF output power measurements in SAR report.   |
| 11 | Identify the simultaneous transmission conditions for the voice and data configurations supported by all wireless modes, device configurations and frequency bands, for the head and body exposure conditions and device operating configurations (handset flip or cover positions, antenna diversity conditions etc.)  | Please refer to the table in section 5   |

**KDB 941225 D05 "SAR for LTE Devices v01" (continued)**

|    |  |                |
|----|--|----------------|
| 12 | When power reduction is applied to certain wireless modes to satisfy SAR compliance for simultaneous transmission conditions, other equipment certification or operating requirements, include the maximum average conducted output power measured in each power reduction mode applicable to the simultaneous voice/data transmission configurations for such wireless configurations and frequency bands; and also include details of the power reduction implementation and measurement setup | Not Applicable |
| 13 | Include descriptions of the test equipment, test software, built-in test firmware etc. required to support testing the device when power reduction is applied to one or more transmitters/antennas for simultaneous voice/data transmission  | Not Applicable |
| 14 | When appropriate, include a SAR test plan proposal with respect to the above   | Not Applicable |
| 15 | If applicable, include preliminary SAR test data and/or supporting information in laboratory testing inquiries to address specific issues and concerns or for requesting further test reduction considerations appropriate for the device; for example, simultaneous transmission configurations   | Not applicable |

## 6. System Specification



**The DASY system for performing compliance tests consists of the following items:**

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DASY software.
- Remote controls with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.

## 7. Composition of Ingredients for Tissue Simulating Liquids

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

| Ingredients<br>(% by weight) | Frequency (MHz) |       |       |      |       |       |       |      |      |      |
|------------------------------|-----------------|-------|-------|------|-------|-------|-------|------|------|------|
|                              | 450             |       | 835   |      | 915   |       | 1900  |      | 2450 |      |
| Tissue Type                  | Head            | Body  | Head  | Body | Head  | Body  | Head  | Body | Head | Body |
| Water                        | 38.56           | 51.16 | 41.45 | 52.4 | 41.05 | 56.0  | 54.9  | 40.4 | 62.7 | 73.2 |
| Salt (NaCl)                  | 3.95            | 1.49  | 1.45  | 1.4  | 1.35  | 0.76  | 0.18  | 0.5  | 0.5  | 0.04 |
| Sugar                        | 56.32           | 46.78 | 56.0  | 45.0 | 56.5  | 41.76 | 0.0   | 58.0 | 0.0  | 0.0  |
| HEC                          | 0.98            | 0.52  | 1.0   | 1.0  | 1.0   | 1.21  | 0.0   | 1.0  | 0.0  | 0.0  |
| Bactericide                  | 0.19            | 0.05  | 0.1   | 0.1  | 0.1   | 0.27  | 0.0   | 0.1  | 0.0  | 0.0  |
| Triton X-100                 | 0.0             | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 0.0   | 0.0  | 36.8 | 0.0  |
| DGBE                         | 0.0             | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 44.92 | 0.0  | 0.0  | 26.7 |
| Dielectric Constant          | 43.42           | 58.0  | 42.54 | 56.1 | 42.0  | 56.8  | 39.9  | 54.0 | 39.8 | 52.5 |
| Conductivity (S/m)           | 0.85            | 0.83  | 0.91  | 0.95 | 1.0   | 1.07  | 1.42  | 1.45 | 1.88 | 1.78 |

Salt: 99+% Pure Sodium Chloride

Sugar: 98+% Pure Sucrose

Water: De-ionized, 16 MΩ+ resistivity

HEC: Hydroxyethyl Cellulose

DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1, 3, 3-tetramethylbutyl)phenyl]ether

### MSL/HSL750 (Body and Head liquids for 700 – 800 MHz)

|  |   |
|--|---|
| Item   | Head Tissue Simulation Liquids HSL750<br>Muscle (body) Tissue Simulation Liquids MSL750   |
| Type No  | SL AAH 075  |
| Manufacturer                                       | SPEAG   |
| The item is composed of the following ingredients: |   |
| H <sup>2</sup> O                                   | Water, 35 – 58%   |
| Sucrose  | Sugar, white, refined, 40-60%   |
| NaCl   | Sodium Chloride, 0-6%   |
| Hydroxyethyl-cellulsoe                             | Medium Viscosity (CAS# 9004-62-0), <0.3%  |
| Preventol-D7                                       | Preservative: aqueous preparation, (CAS# 55965-84-9), containing 5-chloro-2-methyl-3(2H)-isothiazolone and 2-methyl-3(2H)-isothiazolone, 0.1-0.7% |

### MSL/HSL1750 (Body and Head liquids for 1700 – 1800 MHz)

|  |   |
|--|---|
| Item   | Head Tissue Simulation Liquids HSL1750<br>Muscle (body) Tissue Simulation Liquids MSL1750 |
| Type No  | SL AAM 175  |
| Manufacturer                                       | SPEAG   |
| The item is composed of the following ingredients: |   |
| H <sup>2</sup> O                                   | Water, 52 – 75%   |
| C8H18O3  | Diethylene glycol monobutyl ether (DGBE), 25-48%  |
| NaCl   | Sodium Chloride, <1.0%  |

## 8. Liquid Parameters

The simulating liquids are checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. For frequencies in 300 MHz to just under 2 GHz, the measured conductivity and relative permittivity were within  $\pm 5\%$  of the target values. For frequencies above 2 GHz the measured conductivity was within  $\pm 5\%$  of the target values. The measured relative permittivity tolerance was within  $\pm 10\%$  of the target value.

### Reference Values of Tissue Dielectric Parameters for Head & Body Phantom

The body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in IEEE Standard 1528.

| Target Frequency (MHz) | Head         |                | Body         |                |
|------------------------|--------------|----------------|--------------|----------------|
|                        | $\epsilon_r$ | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) |
| 150                    | 52.3         | 0.76           | 61.9         | 0.8            |
| 300                    | 45.3         | 0.87           | 58.2         | 0.92           |
| 450                    | 43.5         | 0.87           | 56.7         | 0.94           |
| 750                    | 41.96        | 0.89           | 55.6         | 0.96           |
| 835                    | 41.5         | 0.9            | 55.2         | 0.97           |
| 900                    | 41.5         | 0.97           | 55           | 1.05           |
| 915                    | 41.5         | 0.98           | 55           | 1.06           |
| 1450                   | 40.5         | 1.2            | 54           | 1.3            |
| 1610                   | 40.3         | 1.29           | 53.8         | 1.4            |
| 1750                   | 40.08        | 1.37           | 53.44        | 1.49           |
| 1800 – 2000            | 40           | 1.4            | 53.3         | 1.52           |
| 2450                   | 39.2         | 1.8            | 52.7         | 1.95           |
| 3000                   | 38.5         | 2.4            | 52           | 2.73           |

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000$  kg/m<sup>3</sup>)

## 8.1. Simulating Liquid Check Results

| Date       | Freq. (MHz) | Liquid Parameters |         | Measured                                | Target | Delta (%) | Limit ±(%) |   |
|------------|-------------|-------------------|---------|---|--------|-----------|------------|---|
| 10/17/2011 | Body 835    | e'                | 53.8385 | Relative Permittivity ( $\epsilon_r$ ): | 53.84  | 55.20     | -2.47      | 5 |
|            |             | e''               | 21.2134 | Conductivity ( $\sigma$ ):              | 0.98   | 0.97      | 1.54       | 5 |
| 10/18/2011 | Body 1900   | e'                | 51.9189 | Relative Permittivity ( $\epsilon_r$ ): | 51.92  | 53.30     | -2.59      | 5 |
|            |             | e''               | 14.0796 | Conductivity ( $\sigma$ ):              | 1.49   | 1.52      | -2.14      | 5 |
| 10/18/2011 | Body 750    | e'                | 54.5980 | Relative Permittivity ( $\epsilon_r$ ): | 54.60  | 55.55     | -1.71      | 5 |
|            |             | e''               | 23.5839 | Conductivity ( $\sigma$ ):              | 0.98   | 0.96      | 2.12       | 5 |
| 10/19/2011 | Body 750    | e'                | 54.8742 | Relative Permittivity ( $\epsilon_r$ ): | 54.87  | 55.55     | -1.21      | 5 |
|            |             | e''               | 23.6116 | Conductivity ( $\sigma$ ):              | 0.98   | 0.96      | 2.24       | 5 |
| 10/20/2011 | Body 750    | e'                | 54.5819 | Relative Permittivity ( $\epsilon_r$ ): | 54.58  | 55.55     | -1.74      | 5 |
|            |             | e''               | 23.5233 | Conductivity ( $\sigma$ ):              | 0.98   | 0.96      | 1.86       | 5 |
| 12/30/2011 | Body 750    | e'                | 55.6750 | Relative Permittivity ( $\epsilon_r$ ): | 55.68  | 55.55     | 0.23       | 5 |
|            |             | e''               | 22.8304 | Conductivity ( $\sigma$ ):              | 0.95   | 0.96      | -1.14      | 5 |
|            | Body 775    | e'                | 55.4296 | Relative Permittivity ( $\epsilon_r$ ): | 55.43  | 55.45     | -0.04      | 5 |
|            |             | e''               | 22.6199 | Conductivity ( $\sigma$ ):              | 0.97   | 0.97      | 1.01       | 5 |
|            | Body 790    | e'                | 55.2885 | Relative Permittivity ( $\epsilon_r$ ): | 55.29  | 55.39     | -0.19      | 5 |
|            |             | e''               | 22.5508 | Conductivity ( $\sigma$ ):              | 0.99   | 0.97      | 2.53       | 5 |
| 02/10/2012 | Body 750    | e'                | 55.0280 | Relative Permittivity ( $\epsilon_r$ ): | 55.03  | 55.55     | -0.93      | 5 |
|            |             | e''               | 23.0432 | Conductivity ( $\sigma$ ):              | 0.96   | 0.96      | -0.22      | 5 |
|            | Body 775    | e'                | 54.6960 | Relative Permittivity ( $\epsilon_r$ ): | 54.70  | 55.45     | -1.36      | 5 |
|            |             | e''               | 22.9016 | Conductivity ( $\sigma$ ):              | 0.99   | 0.97      | 2.27       | 5 |
|            | Body 790    | e'                | 54.3517 | Relative Permittivity ( $\epsilon_r$ ): | 54.35  | 55.39     | -1.88      | 5 |
|            |             | e''               | 22.6759 | Conductivity ( $\sigma$ ):              | 1.00   | 0.97      | 3.10       | 5 |

## 9. System Verification

The system performance check is performed prior to any usage of the system in order to verify SAR system accuracy. The system performance check verifies that the system operates within its specifications of  $\pm 10\%$ .

### System Performance Check Measurement Conditions

The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness:  $2.0 \pm 0.2$  mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.

The DASY5 system with an Isotropic E-Field Probe EX3DV4 was used for the measurements.

The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.

The coarse grid with a grid spacing of 15 mm was aligned with the dipole.

For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.

Special 7x7x7 (2.4 GHz) fine cube was chosen for cube integration and Special 8x8x10 (5 GHz) fine cube was chosen for cube integration

Distance between probe sensors and phantom surface was set to 2.5 mm.

For 5 GHz band - Distance between probe sensors and phantom surface was set to 2.5 mm

The dipole input powers (forward power) were 100 mW.

The results are normalized to 1 W input power.

### Reference SAR Values for HEAD & BODY-tissue from calibration certificate of SPEAG.

| System validation dipole | Cal. certificate #  | Cal. date | SAR Avg (mW/g) |       |      |      |
|--------------------------|---------------------|-----------|----------------|-------|------|------|
|                          |                     |           | Tissue:        | Freq. | Head | Body |
| D750V3<br>SN: 1019       | D750V3-1019_Dec10   | 12/10/10  | 1g SAR:        | 750   | 8.16 | 8.64 |
|                          |                     |           | 10g SAR:       | MHz   | 5.32 | 5.72 |
| D835V2<br>SN: 4d117      | D835V2-4d117_Apr11  | 4/15/11   | 1g SAR:        | 835   | 9.64 | 10.1 |
|                          |                     |           | 10g SAR:       | MHz   | 6.28 | 6.6  |
| D1900V2<br>SN: 5d140     | D1900V2-5d140_Apr11 | 4/18/11   | 1g SAR:        | 1.9   | 41.6 | 41.2 |
|                          |                     |           | 10g SAR:       | GHz   | 21.5 | 21.6 |
| D750V3<br>SN: 1024       | D750V3-1024_Apr11   | 4/20/11   | 1g SAR:        | 750   | 8.52 | 8.8  |
|                          |                     |           | 10g SAR:       | MHz   | 5.56 | 5.84 |

## 9.1. System Check Results

| System validation dipole | Date Tested | Measured (Normalized to 1 W) |       | Target | Delta (%) | Tolerance (%) |
|--------------------------|-------------|------------------------------|-------|--------|-----------|---------------|
|                          |             | Tissue:                      | Body  |        |           |               |
| D835V2<br>SN: 4d117      | 10/17/11    | 1g SAR:                      | 10.40 | 10.1   | 2.97      | ±10           |
|                          |             | 10g SAR:                     | 6.82  | 6.6    | 3.33      |               |
| D1900V2<br>SN: 5d140     | 10/18/11    | 1g SAR:                      | 42.0  | 41.2   | 1.94      | ±10           |
|                          |             | 10g SAR:                     | 22.1  | 21.6   | 2.31      |               |
| D750V3<br>SN: 1019       | 10/18/11    | 1g SAR:                      | 9.35  | 8.64   | 8.22      | ±10           |
|                          |             | 10g SAR:                     | 6.18  | 5.72   | 8.04      |               |
| D750V3<br>SN: 1019       | 10/19/11    | 1g SAR:                      | 9.25  | 8.64   | 7.06      | ±10           |
|                          |             | 10g SAR:                     | 6.16  | 5.72   | 7.69      |               |
| D750V3<br>SN: 1019       | 10/20/11    | 1g SAR:                      | 9.30  | 8.64   | 7.64      | ±10           |
|                          |             | 10g SAR:                     | 6.18  | 5.72   | 8.04      |               |
| D750V3<br>SN: 1024       | 01/03/12    | 1g SAR:                      | 8.61  | 8.80   | -2.16     | ±10           |
|                          |             | 10g SAR:                     | 5.71  | 5.84   | -2.23     |               |
| D750V3<br>SN: 1024       | 02/10/12    | 1g SAR:                      | 8.81  | 8.80   | 0.11      | ±10           |
|                          |             | 10g SAR:                     | 5.84  | 5.84   | 0.00      |               |

## 10. SAR Measurement Procedures

### Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The Minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the Distance of sensor calibration points to probe tip as defined in the probe properties.

### Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY5 software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

### Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures  $\geq 7 \times 7 \times 9$  (above 4.5 GHz) or  $5 \times 5 \times 7$  (below 3 GHz) points within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

### Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

### Step 5: Z-Scan

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation, the extrapolated distance should not be larger than the step size in Z-direction.

## 11. RF Output Power Verification

### 11.1. CDMA2000 Cell and PCS Band

#### 1xEv-Do - Release 0 (Rel. 0)

This procedure assumes the Agilent 8960 Test Set has the following applications installed and with valid license.

##### EVDO Release 0 - RTAP

- Call Setup > Shift & Preset
- Call Control:
  - Access Network Info > Cell Parameters > Sector ID > 00000000 : 00000000 : 00000000 : 00000000 > Subnet Mask > 0
- Generator Info > Termination Parameters > Max Forward Packet Duration > 16 Slots
- CallParms:
  - Cell Power > -105.5 dBm/1.23 MHz
- System ID: 2004; NID: 65535, Reg. Ch. #: 610 for Cell and 600 for PCS
- Channel > (Enter channel number)
- Application Config > Enhanced Test Application Protocol > RTAP
- RTAP Rate > 153.6 kbps
- Rvs Power Ctrl > Active bits
- Protocol Rel > 0 (1xEV-DO)
- Press "Start Data Connection" when "Session Open" appear in "Active Cell"
- Rvs Power Ctrl > All Up bits (Maximum TxPout)

##### EVDO Release 0 - FTAP

- Call Setup > Shift & Preset
- Call Control:
  - Access Network Info > Cell Parameters > Sector ID > 00000000 : 00000000 : 00000000 : 00000000 > Subnet Mask > 0
- Generator Info > Termination Parameters > Max Forward Packet Duration > 16 Slots
- CallParms:
  - Cell Power > -105.5 dBm/1.23 MHz
  - Cell Band > (Select US Cellular or US PCS)
  - Channel > (Enter channel number)
- Application Config > Enhanced Test Application Protocol > FTAP (default)
- FTAP Rate > 307.2 kbps (2 Slot, QPSK)
- Rvs Power Ctrl > Active bits
- Protocol Rel > 0 (1xEV-DO)
- Press "Start Data Connection" when "Session Open" appear in "Active Cell"
- Rvs Power Ctrl > All Up bits (Maximum TxPout)

| Band | FTAP Rate                    | RTAP Rate  | Channel | f (MHz) | Conducted power (dBm) |      |
|------|------------------------------|------------|---------|---------|-----------------------|------|
|      |                              |            |         |         | Average               | Peak |
| Cell | 307.2 kbps<br>(2 slot, QPSK) | 153.6 kbps | 1013    | 824.70  | 25.32                 |      |
|      |                              |            | 384     | 836.52  | 25.30                 |      |
|      |                              |            | 777     | 848.31  | 25.30                 |      |
| PCS  | 307.2 kbps<br>(2 slot, QPSK) | 153.6 kbps | 25      | 1851.25 | 25.30                 |      |
|      |                              |            | 600     | 1880.00 | 24.74                 |      |
|      |                              |            | 1175    | 1908.75 | 25.29                 |      |

## 1xEv-DO - Revision A (Rev. A)

This procedure assumes the Agilent 8960 Test Set has the following applications installed and with valid license.

| <u>Application</u>    | <u>Rev, License</u> |
|-----------------------|---------------------|
| 1xEV-DO Terminal Test | A.09.13             |

### EVDO Rev. A – RETAP

- Call Setup > Shift & Preset
- Cell Power > -60 dBm/1.23 MHz
- Protocol Rev > A (1xEV-DO-A)
- Application Config > Enhanced Test Application Protocol > RETAP
- R-Data Pkt Size > 4096
- Protocol Subtype Config > Release A Physical Layer Subtype > Subtype 2
- > PL Subtype 2 Access Channel MAC Subtype > Default (Subtype 0)
- Access Network Info > Cell Parameters > Sector ID > 00000000: 00000000: 00000000: 00000000 > Subnet Mask > 0
- Generator Info > Termination Parameters > Max Forward Packet Duration >16 Slots
- > ACK R-Data After > Subpacket 0 (All ACK)
- Rvs Power Ctrl > All Up bits (to get the maximum power)

### EVDO Rev. A - FETAP

- Call Setup > Shift & Preset
- Cell Power > -60 dBm/1.23 MHz
- Protocol Rev > A (1xEV-DO-A)
- Application Config > Enhanced Test Application Protocol > FETAP
- F-Traffic Format > 4 (1024, 2,128) Canonical (307.2k, QPSK)
- Protocol Subtype Config > Release A Physical Layer Subtype > Subtype 2
- > PL Subtype 2 Access Channel MAC Subtype > Default (Subtype 0)
- Access Network Info > Cell Parameters > Sector ID > 00000000: 00000000: 00000000: 00000000 > Subnet Mask > 0
- Generator Info > Termination Parameters > Max Forward Packet Duration >16 Slots
- > ACK R-Data After > Subpacket 0 (All ACK)
- Rvs Power Ctrl > All Up bits (to get the maximum power)

| Band | FETAP Traffic Format                                      | RETAP Data Payload Size | Channel | f (MHz) | Conducted power (dBm) |      |
|------|---|-------------------------|---------|---------|-----------------------|------|
|      |   |                         |         |         | Average               | Peak |
| Cell | 307.2k, QPSK/ ACK channel is transmitted at all the slots | 4096                    | 1013    | 824.70  | 25.31                 |      |
|      |   |                         | 384     | 836.52  | 25.28                 |      |
|      |   |                         | 777     | 848.31  | 25.25                 |      |
| PCS  | 307.2k, QPSK/ ACK channel is transmitted at all the slots | 4096                    | 25      | 1851.25 | 25.29                 |      |
|      |   |                         | 600     | 1880.00 | 24.63                 |      |
|      |   |                         | 1175    | 1908.75 | 25.27                 |      |

## 11.2. LTE Band 13


### Output power for LTE Band 13

| BW | Ch    | Freq.<br>(MHz) | Mode  | UL RB<br>Allocation | UL RB<br>Start | Target<br>MPR | Measured<br>MPR | Max. Avg.<br>Power (dBm) |
|----|-------|----------------|-------|---------------------|----------------|---------------|-----------------|--------------------------|
| 5  | 23205 | 779.5          | QPSK  | 1                   | 0              | 0             | 0               | 23.4                     |
|    |       |                |       | 1                   | 24             | 0             | 0               | 23.8                     |
|    |       |                |       | 12                  | 6              | 1             | 1               | 22.8                     |
|    |       |                |       | 25                  | 0              | 1             | 1               | 22.6                     |
|    |       |                | 16QAM | 1                   | 0              | 1             | 1               | 22.6                     |
|    |       |                |       | 1                   | 24             | 1             | 1               | 22.8                     |
|    |       |                |       | 12                  | 6              | 2             | 2               | 21.9                     |
|    |       |                |       | 25                  | 0              | 2             | 2               | 21.9                     |
| 10 | 23230 | 782.0          | QPSK  | 1                   | 0              | 0             | 0               | 23.5                     |
|    |       |                |       | 1                   | 49             | 0             | 0               | 23.4                     |
|    |       |                |       | 25                  | 12             | 1             | 1               | 22.6                     |
|    |       |                |       | 50                  | 0              | 1             | 1               | 22.6                     |
|    |       |                | 16QAM | 1                   | 0              | 1             | 1               | 22.6                     |
|    |       |                |       | 1                   | 49             | 1             | 1               | 22.8                     |
|    |       |                |       | 25                  | 12             | 2             | 2               | 21.7                     |
|    |       |                |       | 50                  | 0              | 2             | 2               | 21.8                     |
| 5  | 23255 | 784.5          | QPSK  | 1                   | 0              | 0             | 0               | 23.4                     |
|    |       |                |       | 1                   | 24             | 0             | 0               | 23.5                     |
|    |       |                |       | 12                  | 6              | 1             | 1               | 22.7                     |
|    |       |                |       | 25                  | 0              | 1             | 1               | 22.7                     |
|    |       |                | 16QAM | 1                   | 0              | 1             | 1               | 22.7                     |
|    |       |                |       | 1                   | 24             | 1             | 1               | 22.7                     |
|    |       |                |       | 12                  | 6              | 2             | 2               | 21.9                     |
|    |       |                |       | 25                  | 0              | 2             | 2               | 22.0                     |


### 11.2.1. Spectrum Plots for the Test RB allocations

The following plots are to demonstrate the tested RB allocations have been established correctly at the maximum output power conditions.


#### 10MHz Band Width: RB Size = 1; RB Offset = 0




10MHz Band Width: RB Size = 1; RB Offset = 49



10MHz Band Width 50% RB: RB Size = 25; RB Offset = 12



10MHz Band Width 100% RB: RB Size = 50; RB Offset = 0



## 12. Summary of Test Results

### 12.1. CDMA2000 Cell & PCS Band

The following SAR is measured using Subtype 0/1 Physical Layer configurations for Rel. 0.

SAR for Subtype 2 Physical layer configurations is not required for Rev. A since the maximum average output of each RF channel is less than that measured in Subtype 0/1 Physical layer configurations as per KDB 941225 D01 SAR test for 3G devices v02.

#### Laptop Mode - LapHeld

| Band     | Mode            | Ch No. | f (MHz) | Average Power | SAR (mW/g) |       |
|----------|-----------------|--------|---------|---------------|------------|-------|
|          |                 |        |         |               | 1-g        | 10-g  |
| Cellular | 1xEVDO (Rel. 0) | 1013   | 824.70  | 25.32         |            |       |
|          |                 | 384    | 836.52  | 25.30         | 0.011      | 0.009 |
|          |                 | 777    | 848.31  | 25.30         |            |       |
| PCS      | 1xEVDO (Rel. 0) | 25     | 1851.25 | 25.30         |            |       |
|          |                 | 600    | 1880.00 | 24.74         | 0.014      | 0.011 |
|          |                 | 1175   | 1908.75 | 25.29         |            |       |

#### Tablet Mode – Bottom Face

| Band     | Mode            | Ch No. | f (MHz) | Average Power | SAR (mW/g) |       |
|----------|-----------------|--------|---------|---------------|------------|-------|
|          |                 |        |         |               | 1-g        | 10-g  |
| Cellular | 1xEVDO (Rel. 0) | 1013   | 824.70  | 25.32         |            |       |
|          |                 | 384    | 836.52  | 25.30         | 0.100      | 0.070 |
|          |                 | 777    | 848.31  | 25.30         |            |       |
| PCS      | 1xEVDO (Rel. 0) | 25     | 1851.25 | 25.30         |            |       |
|          |                 | 600    | 1880.00 | 24.74         | 0.062      | 0.039 |
|          |                 | 1175   | 1908.75 | 25.29         |            |       |

#### Tablet Mode – Edge 1

| Band     | Mode            | Ch No. | f (MHz) | Average Power | SAR (mW/g) |       |
|----------|-----------------|--------|---------|---------------|------------|-------|
|          |                 |        |         |               | 1-g        | 10-g  |
| Cellular | 1xEVDO (Rel. 0) | 1013   | 824.70  | 25.32         |            |       |
|          |                 | 384    | 836.52  | 25.30         | 0.135      | 0.086 |
|          |                 | 777    | 848.31  | 25.30         |            |       |
| PCS      | 1xEVDO (Rel. 0) | 25     | 1851.25 | 25.30         |            |       |
|          |                 | 600    | 1880.00 | 24.74         | 0.504      | 0.245 |
|          |                 | 1175   | 1908.75 | 25.29         |            |       |

#### Note(s):

1. SAR test was performed in the middle channel only as the measured level was < 50% of the SAR limit as stated in FCC "Public Notice DA 02-1438" by the SCC-34/SC-2. Testing in the low and high channel is optional.

## 12.2. LTE BAND 13

The test reduction for LTE SAR is based on KDB 941225 D05 SAR for LTE Devices v01.

## Tablet Mode – Edge 1

## BAND 13, 10 MHz BW - Middle Channel

| Mode  | UL Ch #. | Freq. (MHz) | RB Size | RB Offset | Avg Pwr (dBm) | MPR | Measured MPR | Separation Distance (mm) | SAR (mW/g) |       |
|-------|----------|-------------|---------|-----------|---------------|-----|--------------|--------------------------|------------|-------|
|       |          |             |         |           |               |     |              |                          | 1-g        | 10-g  |
| QPSK  | 23230    | 782         | 1       | 0         | 23.5          | 0   | 0            | 0                        | 0.116      | 0.072 |
|       | 23230    | 782         | 1       | 49        | 23.4          | 0   | 0            | 0                        | 0.113      | 0.070 |
|       | 23230    | 782         | 25      | 12        | 22.6          | 1   | 1            | 0                        | 0.100      | 0.062 |
|       | 23230    | 782         | 50      | 0         | 22.6          | 1   | 1            | 0                        |            |       |
| 16QAM | 23230    | 782         | 1       | 0         | 22.6          | 1   | 1            | 0                        | 0.058      | 0.036 |
|       | 23230    | 782         | 1       | 49        | 22.8          | 1   | 1            | 0                        | 0.080      | 0.050 |
|       | 23230    | 782         | 25      | 12        | 21.7          | 2   | 2            | 0                        | 0.081      | 0.051 |
|       | 23230    | 782         | 50      | 0         | 21.8          | 2   | 2            | 0                        |            |       |

**Note(s):**

Testing for 100% RB allocation is not required because the SAR value for 50% RB allocation is  $\leq 1.45\text{W/Kg}$ .

Testing was only performed on the middle channel because the output power variance over low/middle/high channels is  $\leq 1/2$  dB and the measured SAR for the middle channel is  $\leq 0.8\text{W/Kg}$ .

Testing for 5MHz Bandwidth is not required as the SAR for the Largest Channel Bandwidth (10MHz) measured is < 1.45 W/kg and the output power for the 5MHz channel bandwidth is within +/- 1/2dB of the output power for the widest (10MHz) bandwidth.

## Tablet Mode – Bottom Face

### BAND 13, 10 MHz BW - Middle Channel

| Mode  | UL Ch #. | Freq. (MHz) | RB Size | RB Offset | Avg Pwr (dBm) | MPR | Measured MPR | Separation Distance (mm) | SAR (mW/g) |       |
|-------|----------|-------------|---------|-----------|---------------|-----|--------------|--------------------------|------------|-------|
|       |          |             |         |           |               |     |              |                          | 1-g        | 10-g  |
| QPSK  | 23230    | 782         | 1       | 0         | 23.5          | 0   | 0            | 0                        | 0.087      | 0.060 |
| QPSK  | 23230    | 782         | 1       | 49        | 23.4          | 0   | 0            | 0                        | 0.098      | 0.065 |
| QPSK  | 23230    | 782         | 25      | 12        | 22.6          | 1   | 1            | 0                        | 0.076      | 0.050 |
| QPSK  | 23230    | 782         | 50      | 0         | 22.6          | 1   | 1            | 0                        |            |       |
| 16QAM | 23230    | 782         | 1       | 0         | 22.6          | 1   | 1            | 0                        | 0.073      | 0.049 |
| 16QAM | 23230    | 782         | 1       | 49        | 22.8          | 1   | 1            | 0                        | 0.060      | 0.041 |
| 16QAM | 23230    | 782         | 25      | 12        | 21.7          | 2   | 2            | 0                        | 0.056      | 0.039 |
| 16QAM | 23230    | 782         | 50      | 0         | 21.8          | 2   | 2            | 0                        |            |       |

**Note(s):**

Testing for 100% RB allocation is not required because the SAR value for 50% RB allocation is  $\leq 1.45\text{W/Kg}$ .

Testing was only performed on the middle channel because the output power variance over low/middle/high channels is  $\leq 1/2$  dB and the measured SAR for the middle channel is  $\leq 0.8\text{W/Kg}$ .

Testing for 5MHz Bandwidth is not required as the SAR for the Largest Channel Bandwidth (10MHz) measured is < 1.45 W/kg and the measured SAR for the middle channel is < 0.5 W/kg.

**Laptop Mode – LapHeld**

BAND 13, 10 MHz BW - Middle Channel

| Mode  | UL Ch #. | Freq. (MHz) | RB Slze | RB Offset | Avg Pwr (dBm) | MPR | Measured MPR | Separation Distance (mm) | SAR (mW/g) |         |
|-------|----------|-------------|---------|-----------|---------------|-----|--------------|--------------------------|------------|---------|
|       |          |             |         |           |               |     |              |                          | 1-g        | 10-g    |
| QPSK  | 23230    | 782         | 1       | 0         | 23.5          | 0   | 0            | 0                        | 0.015      | 0.012   |
| QPSK  | 23230    | 782         | 1       | 49        | 23.4          | 0   | 0            | 0                        | 0.00940    | 0.00679 |
| QPSK  | 23230    | 782         | 25      | 12        | 22.6          | 1   | 1            | 0                        | 0.0086     | 0.00424 |
| QPSK  | 23230    | 782         | 50      | 0         | 22.6          | 1   | 1            | 0                        | / \        |         |
| 16QAM | 23230    | 782         | 1       | 0         | 22.6          | 1   | 1            | 0                        | 0.015      | 0.011   |
| 16QAM | 23230    | 782         | 1       | 49        | 22.8          | 1   | 1            | 0                        | 0.013      | 0.00937 |
| 16QAM | 23230    | 782         | 25      | 12        | 21.7          | 2   | 2            | 0                        | 0.011      | 0.00911 |
| 16QAM | 23230    | 782         | 50      | 0         | 21.8          | 2   | 2            | 0                        | / \        |         |

**Note(s):**

Testing for 100% RB allocation is not required because the SAR value for 50% RB allocation is  $\leq 1.45\text{W/Kg}$ .

Testing was only performed on the middle channel because the output power variance over low/middle/high channels is  $\leq \frac{1}{2}\text{ dB}$  and the measured SAR for the middle channel is  $\leq 0.8\text{W/Kg}$ .

Testing for 5MHz Bandwidth is not required as the SAR for the Largest Channel Bandwidth (10MHz) measured is  $< 1.45\text{ W/kg}$  and the output power for the 5MHz channel bandwidth is within  $+\text{- } \frac{1}{2}\text{dB}$  of the output power for the widest (10MHz) bandwidth.

### 13. Simultaneous Transmission SAR Analysis

#### WWAN + WiFi 2.4 GHz

| Test configuration            | (1) CDMA Cell | (2) CDMA PCS | (3) LTE Band 13 | (4)* WiFi Main | (5)* WiFi Aux | Sum of 1g SAR (mW/g) |
|-------------------------------|---------------|--------------|-----------------|----------------|---------------|----------------------|
| Laptop Mode<br>Lapheld        | 0.011         |              |                 |                | 0.02          | 0.03                 |
|                               |               | 0.014        |                 |                | 0.02          | 0.03                 |
|                               |               |              | 0.015           |                | 0.02          | 0.04                 |
| Tablet Mode<br>Bottom<br>Face | 0.100         |              |                 | 0.024          | 0.031         | 0.16                 |
|                               |               | 0.062        |                 | 0.024          | 0.031         | 0.12                 |
|                               |               |              | 0.098           | 0.024          | 0.031         | 0.15                 |

#### WWAN + WiFi 5.2 GHz

| Test configuration            | (1) CDMA Cell | (2) CDMA PCS | (3) LTE Band 13 | (4)* WiFi Main | (5)* WiFi Aux | Sum of 1g SAR (mW/g) |
|-------------------------------|---------------|--------------|-----------------|----------------|---------------|----------------------|
| Laptop Mode<br>Lapheld        | 0.011         |              |                 |                | 0.052         | 0.06                 |
|                               |               | 0.014        |                 |                | 0.052         | 0.07                 |
|                               |               |              | 0.015           |                | 0.052         | 0.07                 |
| Tablet Mode<br>Bottom<br>Face | 0.100         |              |                 | 0.024          | 0.024         | 0.15                 |
|                               |               | 0.062        |                 | 0.024          | 0.024         | 0.11                 |
|                               |               |              | 0.098           | 0.024          | 0.024         | 0.15                 |

#### WWAN + WiFi 5.3 GHz

| Test configuration            | (1) CDMA Cell | (2) CDMA PCS | (3) LTE Band 13 | (4)* WiFi Main | (5)* WiFi Aux | Sum of 1g SAR (mW/g) |
|-------------------------------|---------------|--------------|-----------------|----------------|---------------|----------------------|
| Laptop Mode<br>Lapheld        | 0.011         |              |                 |                | 0.017         | 0.03                 |
|                               |               | 0.014        |                 |                | 0.017         | 0.03                 |
|                               |               |              | 0.015           |                | 0.017         | 0.03                 |
| Tablet Mode<br>Bottom<br>Face | 0.100         |              |                 | 0.033          | 0.043         | 0.18                 |
|                               |               | 0.062        |                 | 0.033          | 0.043         | 0.14                 |
|                               |               |              | 0.098           | 0.033          | 0.043         | 0.17                 |

#### WWAN + WiFi 5.5 GHz

| Test configuration            | (1) CDMA Cell | (2) CDMA PCS | (3) LTE Band 13 | (4)* WiFi Main | (5)* WiFi Aux | Sum of 1g SAR (mW/g) |
|-------------------------------|---------------|--------------|-----------------|----------------|---------------|----------------------|
| Laptop Mode<br>Lapheld        | 0.011         |              |                 |                | 0.011         | 0.02                 |
|                               |               | 0.014        |                 |                | 0.011         | 0.03                 |
|                               |               |              | 0.015           |                | 0.011         | 0.03                 |
| Tablet Mode<br>Bottom<br>Face | 0.100         |              |                 | 0.038          | 0.037         | 0.18                 |
|                               |               | 0.062        |                 | 0.038          | 0.037         | 0.14                 |
|                               |               |              | 0.098           | 0.038          | 0.037         | 0.17                 |

#### WWAN + WiFi 5.8 GHz

| Test configuration            | (1) CDMA Cell | (2) CDMA PCS | (3) LTE Band 13 | (4)* WiFi Main | (5)* WiFi Aux | Sum of 1g SAR (mW/g) |
|-------------------------------|---------------|--------------|-----------------|----------------|---------------|----------------------|
| Laptop Mode<br>Lapheld        | 0.011         |              |                 |                | 0.029         | 0.04                 |
|                               |               | 0.014        |                 |                | 0.029         | 0.04                 |
|                               |               |              | 0.015           |                | 0.029         | 0.04                 |
| Tablet Mode<br>Bottom<br>Face | 0.100         |              |                 | 0.00112        | 0.029         | 0.13                 |
|                               |               | 0.062        |                 | 0.00112        | 0.029         | 0.09                 |
|                               |               |              | 0.098           | 0.00112        | 0.029         | 0.13                 |

#### Note(s)

- \*: WiFi max. 1g SAR from SAR report "11J13739-3 SAR report" submitted under FCC ID: ACJ9TGWL11A (Panasonic Corporation of North America)

This WiFi module supports MIMO operation in all bands in 802.11n modes and the simultaneous evaluation has included an evaluation with both WLAN antennas operational with the WWAN antenna based on the worst case SAR in each band for each individual WLAN antenna.

#### Conclusions:

Simultaneous transmission SAR is not required because the sum of the 1-g SAR is < 1.6 W/kg

## 14. Appendixes

Refer to separated files for the following appendixes

- 14.1. **Appendix A: System Check Plots**
- 14.2. **Appendix B: SAR Test Plots for CDMA2000 Cell & PCS band**
- 14.3. **Appendix C: SAR Test Plots for LTE Band 13**
- 14.4. **Appendix D: Calibration Certificate for EX3DV4 SN 3686**
- 14.5. **Appendix E: Calibration Certificate for EX3DV4 SN 3772**
- 14.6. **Appendix F: Calibration Certificate for EX3DV4 SN 3773**
- 14.7. **Appendix G: Calibration Certificate for D750V3 SN1019**
- 14.8. **Appendix H: Calibration Certificate for D750V3 SN1024**
- 14.9. **Appendix I: Calibration Certificate for D835V2 SN 4d117**
- 14.10. **Appendix J: Calibration Certificate for D1900V2 SN 5d140**

## 15. Summary of Test configurations

| Configuration                            | Antenna-to-User distance       | SAR Require | Comments   |
|--|--------------------------------|-------------|--|
| <b>(1) Bottom/Base<br/>(Tablet mode)</b> | 28 mm from WWAN Main to user.  | Yes         |  |
|  | 28 mm from WWAN Aux to user.   | No          | WWAN Aux is Rx only.   |
| <b>(2) Bottom/Base<br/>(Laptop held)</b> | 155 mm from WWAN Main to user. | Yes         |  |
|  | 155 mm from WWAN Aux to user.  | No          | WWAN Aux is Rx only.   |
| Edge 3                                   | 135 mm from WWAN Main to user. | No          |  |
|  | 135 mm from WWAN Aux to user.  | No          |  |
| <b>(3) Edge 1</b>                        | 20 mm from WWAN Main to user.  | Yes         |  |
|  | 20 mm from WWAN Aux to user.   | No          | WWAN Aux is Rx only.   |
| Edge 2                                   | 1 mm from WWAN Main to user.   | No          | Tx is disabled by software when screen turn to this orientation. |
|  | 296 mm from WWAN Aux to user.  | No          |  |
| Edge 4                                   | 296 mm from WWAN Main to user. | No          |  |
|  | 1 mm from WWAN Aux to user.    | No          | WWAN Aux is Rx only.   |