



Smart Grid Node Model: X-3200-xxx
RF exposure calculations for Embedded Modules with collocated antennas
according FCC 47 CFR 1.307(b)(1).

Modules type:

- Cellular/PCS GSM/EDGE/WCDMA/SDMA/700 MHz LTE modem, Sierra Wireless Inc., Mod: MC7750 (FCC ID: N7NMC7750) and
- 802.11 a/b/g/n: Compex Systems Pte Ltd, Mod: WLE200NX (FCC ID: TK4-10-WLE200NX)

The following calculations was made for RF exposure evaluation of the smart grid node Model: X-3200-xxx, which equipped with embedded Cellular/PCS GSM/EDGE/WCDMA/SDMA/700 MHz LTE module Model: MC7750 (Sierra Wireless Inc.) and 802.11 b/g/n module Model: WLE200NX (Compex Systems Pte Ltd). Both modules has been evaluated and comply with FCC RF exposure requirements separately, however in case of X- 3200, these antennas are collocated less then 20 cm from each other and therefore X-3200 is subject to cumulative RF exposure evaluation.

The EUT will be only used with a separation of 20 cm or greater between the antennas and the user or nearby person and therefore can be consider a mobile transmitter per 47 CFR 2.1091(b). Due to deployment conditions, device has to comply with Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled Exposure.

EUT contains:

- a) Cellular/PCS GSM/EDGE/WCDMA/SDMA/700 MHz LTE transmitter (FCC ID: N7NMC7750) operates under Parts 22E, 22H, 24E, 24H and Part 27 of the FCC Rules. Device transmitting characteristics has been showing in the Table1.

Table1

| FCC Part No. | Frequency Range (MHz) | Maximum output power (mW) | Duty Cycle | Peak Antenna Gain (cable loss included) for calculation MPE (dBi) | Numeric Peak Antenna Gain (cable loss included) for calculation MPE |
|--------------|-----------------------|---------------------------|------------|---|---|
| 24E | 1850.2 - 1908.8 | 0.899 | 0.25 | 2.6 | 1.82 |
| 24E | 1851.2 – 1908.8 | 0.34 | 1 | 2.6 | 1.82 |
| 24E | 1852.4 – 1907.6 | 0.182 | 1 | 2.6 | 1.82 |
| 24E | 1851.25 – 1908.75 | 0.337 | 1 | 2.6 | 1.82 |
| 22H | 824.2 – 848.8 | 1.82 | 0.25 | 1.5 | 1.42 |
| 22H | 824.2 – 848.8 | 0.419 | 1 | 1.5 | 1.42 |
| 22H | 826.4 – 846.6 | 0.22 | 1 | 1.5 | 1.42 |
| 22H | 824.7 – 848.31 | 0.34 | 1 | 1.5 | 1.42 |
| 27 | 779.5 – 784.5 | 0.224 | 1 | 0.8 | 1.21 |
| 27 | 779.5 – 784.5 | 0.221 | 1 | 0.8 | 1.21 |



| | | | | | |
|----|---------------|-------|---|-----|------|
| 27 | 782.0 – 782.0 | 0.227 | 1 | 0.8 | 1.21 |
| 27 | 782.0 – 782.0 | 0.226 | 1 | 0.8 | 1.21 |

b) 802.11 a/b/g/n transmitter (FCC ID: TK4-10-WLE200NX) operates under Part 15C of FCC Rules in ISM band and has transmitting characteristics that are showing in Table2

Table2

| FCC Part No. | Modulation | Frequency Range (MHz) | Maximum output power (mW) | Duty Cycle | Peak Antenna Gain (cable loss included) for calculation MPE (dBi) | Numeric Peak Antenna Gain (cable loss included) for calculation MPE |
|--------------|--------------|-----------------------|---------------------------|------------|---|---|
| 15C | 802.11b/g/n | 2412.0 - 2462.0 | 410 | 1 | 2.6 | 1.82 |
| 15C | 802.11 b/g/n | 2422.0 - 2452.0 | 240 | 1 | 2.6 | 1.82 |
| 15C | 802.11a/n | 5745.0 - 5825.0 | 410 | 1 | 2.3 | 1.7 |
| 15C | 802.11a/n | 5755.0 - 5795.0 | 300 | 1 | 2.3 | 1.7 |

According 47 CFR 1.1310 FCC MPE limits for General population/Uncontrolled Exposure are showing in the Table3

Table3

| Frequency Range (MHz) | Electric Field Strength [E] (V/m) | Magnetic Field Strength [H](A/m) | Power density [S] (mW/cm ²) | Averaging time (min) |
|-----------------------|-----------------------------------|----------------------------------|---|----------------------|
| 0.3 - 1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34 - 30 | 824/f | 2.19/f | (180/f ²)* | 30 |
| 30 - 300 | 27.5 | 0.073 | 0.2 | 30 |
| 300 - 1500 | ----- | ----- | f/1500 | 30 |
| 1500 -100,000 | ----- | ----- | 1 | 30 |

f = frequency in MHz

* = Plane-wave equivalent Power Density

Based on FCC Bulletin OET 65, the MPE calculations in case of multiple transmitters have been performed on the following and assumptions and equations:

1. For transmitters which operate in the frequency band with a same MPE limit the Power Densities are summed. The Total Power Density shall not exceed the Limit for this band
2. For transmitters which operate in frequency bands with a different MPE the Power Densities are calculated separately for each band, and then divided by Limit for each band. The sum of these ratios shall not exceed 1.
3. The calculation of the Power Density based on equation given in OET 65:

$$E = \sqrt{(30 \times P \times DC \times G) / d} \quad (\text{Eq.1})$$

and

$$S = E^2 / 3770 \quad (\text{Eq.2})$$

Where:

E = field strength in volts/meter

P = power in watts

DC = numeric duty cycle

G = numeric antenna gain

d = distance in meters

S = power density in milliwatts / square centimeter

Combining (Eq.1) and (Eq.2), S may be calculated as:

$$S = (30 \times P \times DC \times G) / (3770 \times d^2) \quad (\text{Eq.3})$$

By changing units for P to mW and distance to cm, (Eq.3) can be written as:

$$S = [30 \times (0.001 \times P) \times DC \times G] / [3770 \times (0.01 \times d)^2] \quad (\text{Eq.4})$$

Or:

$$S = (0.0795756 \times P \times DC \times G) / d^2 \quad (\text{Eq.4})$$

Where:

P = power in mW

DC = numeric duty cycle

G = numeric antenna gain

d = distance in cm

S = power density in mW/cm²

4. According Table3, limit for the transmitter in 824.2 – 848.8 MHz band shall be calculated at the lowest frequency (worst case) as:

$$824.2 / 1500 = 0.55 \text{ mW/cm}^2$$

Correspondingly, the worst case limit for the transmitter in 779.5 – 784.5 MHz band shall be calculated as:

:

$$779.5 / 1500 = 0.519 \text{ mW/cm}^2$$

- For the all frequency bands the worst case combination of conducted power, duty cycle and antennas gain was used for calculation. The results of calculations for these cases are showing in Table 4.

Table 4

| Device (transmitter) | Transmitting frequency bands (MHz) | Transmitting conductive power (mW) | Transmitter duty cycle | Peak antenna gain (cable loss included) (dBi) | Numeric peak antenna gain (cable loss included) | Power density at 20 cm from antennas (mW/cm ²) | Ratio the of power density to the limit |
|-------------------------|--|---|---------------------------|---|--|--|--|
| GRPS | 824.2-848.8 | 1820 | 0.25 | 1.5 | 1.42 | 0.129 | 0.234 |
| EV-DO | 824.2-848.8 | 419 | 1 | 1.5 | 1.42 | 0.119 | 0.216 |
| GRPS | 1850.2- 1909.8 | 899 | 0.25 | 2.6 | 1.82 | 0.082 | 0.082 |
| EV-DO | 1850.2- 1900.8 | 340 | 1 | 2.6 | 1.82 | 0.124 | 0.124 |
| LTE | 782.0-782.0 | 227 | 1 | 0.8 | 1.21 | 0.055 | 0.106 |
| 802.11 b/g/n | 2412.0- 2462.0 | 410 | 1 | 2.6 | 1.82 | 0.149 | 0.149 |
| 802.11 b/g/n | 2422.0- 2452.0 | 240 | 1 | 2.6 | 1.82 | 0.087 | 0.087 |
| 802.11 a/n | 5745.0- 5825.0 | 410 | 1 | 2.3 | 1.7 | 0.139 | 0.139 |
| 802.11 a/n | 5755.0- 5795.0 | 300 | 1 | 2.3 | 1.7 | 0.102 | 0.102 |

- Finally, the MPE calculations (worst cases) for collocated Cellular/PCS GSM/EDGE/WCDMA/SDMA/700 MHz LTE and 802.11 a/b/g/n transmitters are shown in the Table5

Table5

| Power density worst cases (fraction of the limit) | Active transmitters in frequency bands (MHz): | | | | | MPE Total (numerical) | Limit (numerical) | Margin (numerical) | Pass/ Fail |
|---|---|---------------------------------|---------------------|---------------------------------|----------------------------|-----------------------|-------------------|--------------------|-------------|
| | 824.2-848.8 (EV-DO or GPRS) | 1850.2 - 1909.8 (EV-DO or GPRS) | 782.0 - 782.0 (LTE) | 2.412.0 - 2462.0 (802.11 b/g/n) | 5745.0-5825.0 (802.11 a/n) | | | | |
| GPRS (fraction of the limit) | 0.234 | | | 0.149 | | 0.383 | 1 | -0.617 | Pass |
| GPRS (fraction of the limit) | 0.234 | | | | 0.139 | 0.373 | 1 | -0.627 | Pass |
| GPRS (fraction of the limit) | | 0.082 | | 0.149 | | 0.231 | 1 | -0.769 | Pass |
| GPRS (fraction of the limit) | | 0.082 | | | 0.139 | 0.221 | 1 | -0.779 | Pass |
| EV-DO: (fraction of the limit) | 0.216 | | | 0.149 | | 0.365 | 1 | -0.635 | Pass |
| EV-DO: (fraction of the limit) | 0.216 | | | | 0.139 | 0.355 | 1 | -0.645 | Pass |
| EV-DO: (fraction of the limit) | | 0.124 | | 0.149 | | 0.273 | 1 | -0.727 | Pass |
| EV-DO: (fraction of the limit) | | 0.124 | | | 0.139 | 0.263 | 1 | -0.737 | Pass |
| LTE (fraction of the limit) | | | 0.106 | 0.149 | | 0.255 | 1 | -0.745 | Pass |
| LTE (fraction of the limit) | | | 0.106 | | 0.139 | 0.245 | 1 | -0.755 | Pass |

7. Conclusion.

Calculated worst case MPE numbers are complying with FCC limits for General population/Uncontrolled Exposure as a mobile device.