

RF Exposure Evaluation Report

Product : Receiver assembly
Trade mark : Kohler
Model/Type reference : 1371930
Serial Number : N/A
Report Number : EED32L00366302
FCC ID : N82-KOHLER041
Date of Issue : Jan. 09, 2020
Test Standards : 47 CFR Part 1.1307(2015)
47 CFR Part 1.1310(2015)
KDB447498D01v06
Test result : PASS

Prepared for:

Kohler Co.

444 Highland Drive, Kohler, WI 53044 USA

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Tested By:

mark.chen.

Mark chen

Compiled by:

Sunlight Sun

Sunlight Sun

Reviewed by:

Ware Xin

Ware Xin

Approved by:

Sam Chuang

Sam Chuang

Date:

Jan. 09, 2020

Check No.:3096368193



2 Version

Version No.	Date	Description
00	Jan. 09, 2020	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 RF EXPOSURE EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

4 General Information

4.1 Client Information

Applicant:	Kohler Co.
Address of Applicant:	444 Highland Drive, Kohler, WI 53044 USA
Manufacturer:	Kohler Co.
Address of Manufacturer:	444 Highland Drive, Kohler, WI 53044 USA
Factory:	VTech (Dongguan) Communications Ltd.
Address of Factory:	Xia Ling Bei Management Zone, Liaobu Town, Dongguan City , Guangdong province, China.

4.2 General Description of EUT

Product Name:	Receiver assembly
Model No.(EUT):	1371930
Trade Mark:	Kohler
EUT Supports Radios application	BT 4.2 Single mode, 2402MHz to 2480MHz

4.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz			
Modulation Type:	GFSK			
Number of Channels:	40			
Test Power Grade:	Tx Power:5			
Test Software of EUT:	BlueNRG GUI			
Antenna Type:	Chip Antenna			
Antenna Specification	Bluetooth :	Antenna Gain :	2.00 dBi	(Numeric gain: 1.58)
Maximum tune up power	Bluetooth:		-2.00 dBm	(0.631 mW)
Power Supply:	Battery	DC 1.5V*4 SIZE +AA		
Sample Received Date:	Dec. 03, 2019			
Sample tested Date:	Dec. 03, 2019 to Dec. 09, 2019			
The tested sample(s) and the sample information are provided by the client.				

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Bluetooth:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
0	2402	0.666	1.58	20	0.0002	1

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32L00366301 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.