



FCC Radio Test Report

FCC ID: N89-BU067HS

This report concerns (check one): Original Grant Class II Change

Issued Date : Nov. 12, 2013
Project No. : 1310C045
Equipment : BT Module
Model Name : M26H004.01
Applicant : CyberTAN Technology, Inc.
Address : 99 Park Avenue III, Science park, Hsinchu
308 Taiwan, R.O.C

Tested by: Neutron Engineering Inc. EMC Laboratory

Date of Receipt: Oct. 21, 2013

Date of Test: Oct. 21, 2013 ~ Nov 11, 2013

Testing Engineer : David Mao
(David Mao)

Technical Manager : Leo Hung
(Leo Hung)

Authorized Signatory : Steven Lu
(Steven Lu)

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia,
Dalang Town, Dong Guan, China.

TEL: 0769-8318-3000

FAX: 0769-8319-6000



Neutron Engineering Inc.

Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C**, or National Institute of Standards and Technology (**NIST**) of **U.S.A**.

Neutron's reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



Table of Contents

	Page
REPORT ISSUED HISTORY	5
1 . CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3 . GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	11
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
3.5 DESCRIPTION OF SUPPORT UNITS	13
4 . EMC EMISSION TEST	14
4.1 CONDUCTED EMISSION MEASUREMENT	14
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING	14
4.1.3 TEST PROCEDURE	15
4.1.4 DEVIATION FROM TEST STANDARD	15
4.1.5 TEST SETUP	15
4.1.6 EUT OPERATING CONDITIONS	15
4.1.7 TEST RESULTS	16
4.2 RADIATED EMISSION MEASUREMENT	19
4.2.1 RADIATED EMISSION LIMITS	19
4.2.2 MEASUREMENT INSTRUMENTS LIST AND SETTING	20
4.2.3 TEST PROCEDURE	21
4.2.4 DEVIATION FROM TEST STANDARD	21
4.2.5 TEST SETUP	22
4.2.6 EUT OPERATING CONDITIONS	23
4.2.7 TEST RESULTS-BETWEEN 30MHZ AND 1000MHZ	24
4.2.8 TEST RESULTS-BETWEEN 30MHZ AND 1000MHZ	26
4.2.8 TEST RESULTS (ABOVE 1000 MHZ)	33
5 . BANDWIDTH TEST	45
5.1 APPLIED PROCEDURES / LIMIT	45
5.1.1 MEASUREMENT INSTRUMENTS LIST	45
5.1.2 TEST PROCEDURE	45
5.1.3 DEVIATION FROM STANDARD	45
5.1.4 TEST SETUP	45
5.1.5 EUT OPERATION CONDITIONS	45
5.1.6 TEST RESULTS	46



Table of Contents

	Page
5.2 APPLIED PROCEDURES / LIMIT	48
5.2.1 MEASUREMENT INSTRUMENTS LIST	48
5.2.2 TEST PROCEDURE	48
5.2.3 DEVIATION FROM STANDARD	48
5.2.4 TEST SETUP	48
5.2.5 EUT OPERATION CONDITIONS	48
5.2.6 TEST RESULTS	49
6 . ANTENNA CONDUCTED SPURIOUS EMISSION	50
6.1 APPLIED PROCEDURES / LIMIT	50
6.1.1 MEASUREMENT INSTRUMENTS LIST	50
6.1.2 TEST PROCEDURE	50
6.1.3 DEVIATION FROM STANDARD	50
6.1.4 TEST SETUP	50
6.1.5 EUT OPERATION CONDITIONS	50
6.1.6 TEST RESULTS	51
7 . POWER SPECTRAL DENSITY TEST	56
7.1 APPLIED PROCEDURES / LIMIT	56
7.1.1 MEASUREMENT INSTRUMENTS LIST	56
7.1.2 TEST PROCEDURE	56
7.1.3 DEVIATION FROM STANDARD	56
7.1.4 TEST SETUP	56
7.1.5 EUT OPERATION CONDITIONS	56
7.1.6 TEST RESULTS	57
8 . EUT TEST PHOTO	59



REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
NEI-FCCP-2-1310C045	Original Issue.	Nov. 12, 2013



1. CERTIFICATION

Equipment : BT Module
Brand Name : CyberTAN Technology
Model Name : M26H004.01
Applicant : CyberTAN Technology, Inc.
Manufacturer : CyberTAN Technology, Inc.
Address : 99 Park Avenue III, Science park, Hsinchu 308 Taiwan ,R.O.C
Factory : CyberTAN Technology, Inc.
Address : 99 Park Avenue III, Science park, Hsinchu 308 Taiwan ,R.O.C
Date of Test : Oct. 21, 2013 ~ Nov 11, 2013
Test Item : ENGINEERING SAMPLE
Standard(s) : FCC Part15, Subpart C(15.247) / ANSI C63.4-2009

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-2-1310C045) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15 (15.247) , Subpart C:2012				
Standard(s)	Section	Test Item	Judgment	Remark
	15.207	Conducted Emission	PASS	
	15.247(d)	Antenna conducted Spurious Emission	PASS	
	15.247(a)(2)	6dB Bandwidth	PASS	
	15.247(b)(3)	Peak Output Power	PASS	
	15.247(e)	Power Spectral Density	PASS	
	15.203	Antenna Requirement	PASS	
	15.209/15.205	Transmitter Radiated Emissions	PASS	

NOTE:

- (1)" N/A" denotes test is not applicable in this test report.
- (2) The test follows FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r01
(Measurement Guidelines of DTS)



2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792
Neutron's test firm number for FCC 319330

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 % .

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)	NOTE
DG-CB03	CISPR	9KHz~30MHz	V	3.79	
		9KHz~30MHz	H	3.57	
		30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	H	4.14	



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	BT Module	
Brand Name	CyberTAN Technology	
Model Name for FCC	M26H004.01	
Model Difference	N/A	
Product Description	Operation Frequency	2402~2480 MHz
	Modulation Technology	GFSK(1Mbps)
	Bit Rate of Transmitter	
	Number of Channel	40CH
	Antenna Designation	Please see note 3.(Page 9)
	Antenna Gain(Peak)	
	Peak Output Power	4.02 dBm (1Mbps)
More details of EUT technical specification, please refer to the User's Manual.		
Power Source	Supplied from PC USB port.	
Power Rating	I/P AC 120V/60Hz	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

Channel List			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	YAGEO	CAN4311781042453 K	Chip	N/A	2.13



3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode NOTE (1)
Mode 2	Bluetooth

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Mode 2	Bluetooth

For Radiated Test	
Final Test Mode	Description
Mode 1	TX Mode NOTE (1)

Note:

- (1) The measurements are performed at the high, middle, low available channels.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

Test software version	CSR		
Frequency	2402MHz	2440 MHz	2480MHz
GFSK-1Mbps	40	10	10



3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted



Control Room
C-1: USB Cable
C-2: USB Cable
C-3: D-Sub Cable
C-4: USB Cable
C-5: Parallel Cable
C-6: RS232 Cable



C-4: USB Cable



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	BT Module	CyberTAN Technology	M26H004.01	N89-BU067HS	N/A	EUT
E-2	PC	Dell	745	DOC	G7K832X	
E-3	LCD monitor	Dell	E177FPc	DOC	CNOFJ179-6418 0-6AG-1WNS	
E-4	Modem	ACEEX	DM-1414V	IFAXDM1414	0603002131	
E-5	Printer	SII	DPU-414	DOC	3018507 B	
E-6	USB Keyboard	Dell	L100	DOC	CNORH6596589 071T08NE	
E-7	USB Mouse	Dell	M056UOA	DOC	FQJ000BS	
E-8	Phone	NOKIA	NOKIA 603	DOC	N/A	
E-9	Notebook	DELL	Inspiron 14-N4030	DOC	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	YES	NO	1.5m	
C-2	YES	YES	1.5m	
C-3	YES	YES	1.5m	
C-4	YES	NO	0.1m	
C-5	YES	NO	1.5m	
C-6	YES	NO	1.5m	

Note:

- (1) For detachable type I/O cable should be specified the length in m in『Length』 column.



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Until
1	LISN	EMCO	3816/2	00052765	Apr. 25, 2014
2	LISN	R&S	ENV216	100087	Nov.16, 2013
3	Test Cable	N/A	C_17	N/A	Mar.15.2014
4	EMI TEST RECEIVER	R&S	ESCS30	826547/022	Apr. 25, 2014
5	50Ω Terminator	SHX	TF2-3G-A	08122902	Apr. 25, 2014

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it). The EUT was programmed to be in continuously transmitting mode.




4.1.7 TEST RESULTS

Remark

- (1) All readings are QP Mode value unless otherwise stated AVG in column of『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a “*” marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.
- (3) “N/A” denotes test is not applicable in this test report.




EUT:	BT Module	Model Name :	M26H004.01
Temperature:	25 °C	Relative Humidity:	50 %
Test Power:	AC 120V/60Hz	Phase:	Line
Test Mode:	TX Mode		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		0.1685	32.15	9.63	41.78	65.03	-23.25	QP	
2		0.1685	20.47	9.63	30.10	55.03	-24.93	AVG	
3		0.4273	23.66	9.69	33.35	57.31	-23.96	QP	
4		0.4273	12.69	9.69	22.38	47.31	-24.93	AVG	
5		0.6343	23.56	9.72	33.28	56.00	-22.72	QP	
6		0.6343	14.39	9.72	24.11	46.00	-21.89	AVG	
7		4.8437	26.19	9.92	36.11	56.00	-19.89	QP	
8		4.8437	14.32	9.92	24.24	46.00	-21.76	AVG	
9 *		10.6914	33.24	10.11	43.35	60.00	-16.65	QP	
10		10.6914	22.55	10.11	32.66	50.00	-17.34	AVG	
11		18.1015	22.82	10.28	33.10	60.00	-26.90	QP	
12		18.1015	10.99	10.28	21.27	50.00	-28.73	AVG	



EUT:	BT Module	Model Name :	M26H004.01
Temperature:	25 °C	Relative Humidity:	50 %
Test Power:	AC 120V/60Hz	Phase:	Neutral
Test Mode:	TX Mode		



No.	Mk.	Freq.	Reading	Correct	Meaure	Limit	Over	Detector	Comment:
			Level	Factor	ment				
1		0.1734	36.35	9.70	46.05	44.80	-18.75	QP	
2		0.1734	24.26	9.70	33.96	54.80	-20.84	AVG	
3		0.2515	29.79	9.72	39.51	61.71	-22.20	QP	
4		0.2515	17.86	9.72	27.58	51.71	-24.13	AVG	
5		0.5093	26.80	9.74	36.54	56.00	-19.46	QP	
6		0.5093	14.57	9.74	24.31	46.00	-21.69	AVG	
7		1.2320	26.07	9.79	35.66	56.00	-20.14	QP	
8		1.2320	13.85	9.79	23.64	46.00	-22.36	AVG	
9	*	10.6875	33.08	10.22	43.30	60.00	16.70	QP	
10		10.6875	22.63	10.22	32.65	50.00	-17.15	AVG	
11		24.1367	21.37	10.56	31.93	60.00	-28.07	QP	
12		24.1367	10.09	10.56	20.65	50.00	-29.35	AVG	



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

**4.2.2 MEASUREMENT INSTRUMENTS LIST AND SETTING**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Apr. 25, 2014
2	Amplifier	HP	8447D	2944A09673	Apr. 25, 2014
3	Test Receiver	R&S	ESCI	100382	Apr. 25, 2014
4	Test Cable	N/A	C-01_CB03	N/A	Jul. 02, 2014
5	Antenna	ETS	3115	00075789	Apr. 25, 2014
6	Amplifier	Agilent	8449B	3008A02274	Apr. 25, 2014
7	Spectrum	Agilent	E4408B	US39240143	Nov. 16, 2013
8	Test Cable	HUBER+SUHNE R	C-45	N/A	Apr. 30, 2014
9	Controller	CT	SC100	N/A	N/A
10	Horn Antenna	EMCO	3115	9605-4803	Apr. 25, 2014
11	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Apr. 25, 2014
12	Broad-Band Horn Antenna	Schwarbeck	BBHA 9170	9170319	Oct.23, 2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz for PK/AVG detector
Start ~ Stop Frequency	90kHz~110kHz for QP detector
Start ~ Stop Frequency	110kHz~490kHz for PK/AVG detector
Start ~ Stop Frequency	490kHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector



4.2.3 TEST PROCEDURE


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation

4.2.5 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz




(B) Radiated Emission Test Set-Up Frequency Above 1 GHz





(C) For radiated emissions below 30MHz



4.2.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



4.2.7 TEST RESULTS-BETWEEN 30MHZ AND 1000MHZ

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.



EUT:	BT Module	Model Name:	M26H004.01
Temperature:	25 °C	Relative Humidity:	46 %
Test Voltage:	AC 120V/60Hz		
Test Mode:	TX 2402MHz -CH00-1Mbps		

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0089	0°	26.32	24.30	50.62	128.62	-78.00	AVG
0.0089	0°	30.19	24.30	54.49	148.62	-94.13	PEAK
0.02562	0°	22.85	23.94	46.79	119.43	-72.64	AVG
0.02562	0°	25.37	23.94	49.31	139.43	-90.12	PEAK
0.03823	0°	20.92	23.15	44.07	115.96	-71.89	AVG
0.03823	0°	23.65	23.15	46.80	135.96	-89.16	PEAK
0.0652	0°	19.82	22.10	41.92	111.32	-69.40	AVG
0.0652	0°	24.27	22.10	46.37	131.32	-84.95	PEAK
0.2639	0°	20.38	20.37	40.75	99.18	-58.43	AVG
0.2639	0°	23.72	20.37	44.09	119.18	-75.09	PEAK
1.4864	0°	27.68	19.55	47.23	64.16	-16.93	QP

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.00993	90°	18.45	24.30	42.75	127.67	-84.92	AVG
0.00993	90°	21.35	24.30	45.65	147.67	-102.02	PEAK
0.02243	90°	14.26	24.15	38.41	120.59	-82.18	AVG
0.02243	90°	16.69	24.15	40.84	140.59	-99.75	PEAK
0.04627	90°	19.71	22.64	42.35	114.30	-71.95	AVG
0.04627	90°	22.38	22.64	45.02	134.30	-89.28	PEAK
0.07738	90°	20.60	21.85	42.45	109.83	-67.38	AVG
0.07738	90°	23.52	21.85	45.37	129.83	-84.46	PEAK
0.37561	90°	20.30	20.10	40.40	96.11	-55.71	AVG
0.37561	90°	23.71	20.10	43.81	116.11	-72.30	PEAK
1.6719	90°	24.99	19.53	44.52	63.14	-18.62	QP

Remark :

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.




4.2.8 TEST RESULTS-BETWEEN 30MHZ AND 1000MHZ

Remark :

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.




EUT:	BT Module	Model Name:	M26H004.01
Temperature:	28 °C	Relative Humidity:	56 %
Test Power:	AC 120V/60Hz	Phase:	Vertical
Test Mode:	TX 2402MHz -CH00-1Mbps		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	57.1600	45.23	-15.03	30.20	40.00	-9.80	peak	
2		167.7400	38.46	-12.93	25.53	43.50	-17.97	peak	
3		239.5200	38.64	-14.80	23.84	46.00	-22.16	peak	
4		398.6000	33.26	-9.92	23.34	46.00	-22.66	peak	
5		500.4500	35.01	-10.31	24.70	46.00	-21.30	peak	
6		951.5000	31.14	-0.50	30.64	46.00	-15.36	peak	




EUT:	BT Module	Model Name:	M26H004.01
Temperature:	28 °C	Relative Humidity:	56 %
Test Power:	AC 120V/60Hz	Phase:	Horizontal
Test Mode:	TX 2402MHz -CH00-1Mbps		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1		33.8800	38.11	-15.54	22.57	40.00	-17.43	peak
2		114.3900	45.75	-14.37	31.38	43.50	-12.12	peak
3	*	212.3600	49.58	-15.20	34.38	43.50	-9.12	peak
4		254.0700	48.88	-14.89	33.99	46.00	-12.01	peak
5		884.5700	33.33	-2.01	31.32	46.00	-14.68	peak
6		1000.0000	32.14	0.26	32.40	54.00	-21.60	peak




EUT:	BT Module	Model Name:	M26H004.01
Temperature:	28 °C	Relative Humidity:	56 %
Test Power:	AC 120V/60Hz	Phase:	Vertical
Test Mode:	TX 2440MHz -CH19-1Mbps		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1	*	32.9100	49.80	-15.75	34.05	40.00	-5.95	peak
2		55.2200	48.47	-14.85	33.62	40.00	-6.38	peak
3		75.5900	48.71	-16.85	31.86	40.00	-8.14	peak
4		264.7400	43.85	-14.34	29.51	46.00	-16.49	peak
5		500.4500	36.53	-10.31	26.22	46.00	-19.78	peak
6		1000.000	31.39	0.26	31.65	54.00	-22.35	peak




EUT:	BT Module	Model Name:	M26H004.01
Temperature:	28 °C	Relative Humidity:	56 %
Test Power:	AC 120V/60Hz	Phase:	Horizontal
Test Mode:	TX 2440MHz -CH19-1Mbps		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		116.3300	45.21	-14.20	31.01	43.50	-12.49		peak
2	*	212.3600	50.10	-15.20	34.90	43.50	-8.60		peak
3		265.7100	51.06	-14.25	36.81	46.00	-9.19		peak
4		449.0400	36.97	-8.93	28.04	46.00	-17.96		peak
5		743.9200	35.22	-4.89	30.33	46.00	-15.67		peak
6		877.7800	34.06	-2.34	31.72	46.00	-14.28		peak




EUT:	BT Module	Model Name:	M26H004.01
Temperature:	28 °C	Relative Humidity:	56 %
Test Power:	AC 120V/60Hz	Phase:	Vertical
Test Mode:	TX 2480MHz -CH39-1Mbps		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		32.9100 MHz	48.94 dBuV	-15.75 dB	33.19 dBuV/m	40.00 dBuV/m	-6.81	peak	
2	*	71.7100 MHz	49.72 dBuV	-16.46 dB	33.26 dBuV/m	40.00 dBuV/m	-6.74	peak	
3		167.7400 MHz	39.36 dBuV	-12.93 dB	26.43 dBuV/m	43.50 dBuV/m	-17.07	peak	
4		268.6200 MHz	43.86 dBuV	-14.01 dB	29.85 dBuV/m	46.00 dBuV/m	-16.15	peak	
5		530.5200 MHz	36.10 dBuV	-8.69 dB	27.41 dBuV/m	46.00 dBuV/m	-18.59	peak	
6		971.8700 MHz	29.91 dBuV	-0.18 dB	29.73 dBuV/m	54.00 dBuV/m	-24.27	peak	



EUT:	BT Module	Model Name:	M26H004.01
Temperature:	28 °C	Relative Humidity:	56 %
Test Power:	AC 120V/60Hz	Phase:	Horizontal
Test Mode:	TX 2480MHz –CH39-1Mbps		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		83.3500	40.61	-17.75	22.86	40.00	-17.14	peak	
2		116.3300	44.15	-14.20	29.95	43.50	-13.55	peak	
3		160.9500	43.12	-13.56	29.56	43.50	-13.94	peak	
4		216.2400	49.13	-15.12	34.01	46.00	-11.99	peak	
5 *		271.5300	50.02	-13.68	36.34	46.00	-9.66	peak	
6		1000.000	33.16	0.26	33.42	54.00	-20.58	peak	

**4.2.8 TEST RESULTS (ABOVE 1000 MHZ)**

EUT :	BT Module	Model Name :	M26H004.01
Temperature :	23 °C	Relative Humidity :	51 %
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 2402MHz – CH 00-1Mbps		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	V	24.59	13.42	34.09	58.68	47.51	74.00	54.00	X/E
2402.00	V	61.25	54.60	34.12	95.37	88.72			X/F
4803.93	V	44.25	36.49	6.38	50.63	42.87	74.00	54.00	X/H

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission.
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



TX CH00 (Above 1000 MHz, Vertical)






EUT :	BT Module	Model Name :	M26H004.01
Temperature :	23 °C	Relative Humidity :	51 %
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 2402MHz – CH 00-1Mbps		

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	H	22.42	13.41	34.09	56.51	47.50	74.00	54.00	X/E
2402.00	H	56.72	51.00	34.12	90.84	85.12			X/F
4803.84	H	41.23	33.05	6.38	47.61	39.43	74.00	54.00	X/H

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna





EUT :	BT Module	Model Name :	M26H004.01
Temperature :	23 °C	Relative Humidity :	51 %
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 2440MHz -CH19-1Mbps		

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2440.00	V	62.13	56.48	34.24	96.37	90.72			X/F
4879.79	V	44.24	35.16	6.61	50.85	41.77	74.00	54.00	X/H

Remark :


- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission.
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna




Neutron Engineering Inc.

TX CH19 (Above 1000 MHz, Vertical)

110.0 dBuV/m



80.0 dBuV/m





EUT :	BT Module	Model Name :	M26H004.01
Temperature :	23 °C	Relative Humidity :	51 %
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 2440MHz -CH19-1Mbps		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2440.00	H	60.14	52.28	34.24	94.38	86.52			X/F
4879.83	H	39.95	28.46	6.61	46.56	35.07	74.00	54.00	X/H

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission.
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



TX CH19 (Above 1000 MHz, Horizontal)





EUT :	BT Module	Model Name :	M26H004.01
Temperature :	23 °C	Relative Humidity :	51 %
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 2480MHz -CH39-1Mbps		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	X/F
2480.00	V	60.82	52.83	34.36	95.18	87.19			X/E
2483.50	V	25.36	13.51	34.37	59.73	47.88	74.00	54.00	X/H
4959.96	V	45.18	36.97	6.83	52.01	43.80	74.00	54.00	

Remark :


- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna




Neutron Engineering Inc.

TX CH39 (Above 1000 MHz, Vertical)

110.0 dBuV/m



80.0 dBuV/m





EUT :	BT Module	Model Name :	M26H004.01
Temperature :	23 °C	Relative Humidity :	51 %
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 2480MHz -CH39-1Mbps		



Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		Note
		Peak	AV		Peak	AV	Peak	AV	
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2480.00	H	56.48	48.90	34.36	90.84	83.26			X/F
2483.50	H	23.46	13.41	34.37	57.83	47.78	74.00	54.00	X/E
4959.84	H	45.17	36.98	6.83	52.00	43.81	74.00	54.00	X/H

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



TX CH39 (Above 1000 MHz, Horizontal)





5. BANDWIDTH TEST

5.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

5.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Until
1	Spectrum Analyzer	R&S	FSP_40	100185	Nov.16, 2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

5.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

5.1.3 DEVIATION FROM STANDARD

No deviation.

5.1.4 TEST SETUP



5.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.





5.1.6 TEST RESULTS

EUT :	BT Module	Model Name. :	M26H004.01
Temperature :	28 °C	Relative Humidity :	60 %
Pressure :	1016 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00, CH19, CH39 - 1Mbps		

Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	LIMIT (MHz)
2402	0.539	1.0778	>=500KHz
2440	0.519	1.0778	>=500KHz
2480	0.509	1.0878	>=500KHz





**5.1.7. MAXIMUM OUTPUT POWER TEST****5.2 Applied procedures / limit**

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Maximum Output Power	1 watt or 30dBm	2400-2483.5	PASS

5.2.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	P-series Power meter	Agilent	N1911A	MY45100473	Apr. 25, 2014
2	Wireband Power sensor	Agilent	N1921A	MY51100041	Apr. 25, 2014

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

5.2.2 TEST PROCEDURE

- The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- The maximum peak conducted output power was performed in accordance with method 9.1.3 of FCC KDB 558074 D01 DTS Meas Guidance v03r01.

5.2.3 DEVIATION FROM STANDARD

No deviation.

5.2.4 TEST SETUP**5.2.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Transmit output power was measured while the host equipment supply voltage was varied from 85 % to 115 % of the nominal rated supply voltage. No change in transmit output power was observed.



5.2.6 TEST RESULTS

EUT :	BT Module	Model Name :	M26H004.01
Temperature :	28 °C	Relative Humidity :	60 %
Pressure :	1016 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00, CH19, CH39 - 1Mbps		

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH00	2402	3.45	30	1
CH19	2440	4.02	30	1
CH39	2480	4.01	30	1



6. ANTENNA CONDUCTED SPURIOUS EMISSION

6.1 Applied procedures / limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

6.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Until
1	Spectrum Analyzer	R&S	FSP_40	100185	Nov.16, 2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

6.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = 10 ms.

6.1.3 DEVIATION FROM STANDARD

No deviation.

6.1.4 TEST SETUP



6.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



**6.1.6 TEST RESULTS**



EUT :	BT Module	Model Name :	M26H004.01
Temperature :	28 °C	Relative Humidity :	60 %
Pressure :	1016 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00, CH19 , CH39 - 1Mbps		



Channel of Worst Data: CH39



The max. radio frequency power in any 100kHz bandwidth outside the frequency band	The max. radio frequency power in any 100 kHz bandwidth within the frequency band.		
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2381.80	-56.07	2500.00	-55.45
Result			

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.











7. POWER SPECTRAL DENSITY TEST

7.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

7.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Until
1	Spectrum Analyzer	R&S	FSP_40	100185	Nov.16, 2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

7.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW=3KHz, VBW=10 KHz, Sweep time = auto.

7.1.3 DEVIATION FROM STANDARD

No deviation.

7.1.4 TEST SETUP



7.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.





7.1.6 TEST RESULTS

EUT :	BT Module	Model Name :	M26H004.01
Temperature :	28 °C	Relative Humidity :	60 %
Pressure :	1016 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00, CH19, CH39 -1Mbps		

Test Channel	Frequency (MHz)	Power Density (dBm)	LIMIT (dBm)
CH00	2402	-14.96	8
CH19	2440	-14.68	8
CH39	2480	-14.49	8








8. EUT TEST PHOTO

Conducted Measurement Photos







Radiated Measurement Photos
9K~30MHz





Radiated Measurement Photos
30M~1000MHz





**Radiated Measurement Photos
Above 1000MHz**

