



FCC TEST REPORT

REPORT NO.: RF920421R01

MODEL NO.: MW302-P

RECEIVED: Apr. 21, 2003

TESTED: Apr. 25 ~ Apr. 30, 2003

APPLICANT: CYBERTAN TECHNOLOGY INC.

ADDRESS: No. 99, Park Avenue III, Science-based Industrial
Park, Hsinchu, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 54 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Lab Code: 200102-0



Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS.....	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS.....	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	9
4.1.2	TEST INSTRUMENTS	9
4.1.3	TEST PROCEDURES.....	10
4.1.4	TEST SETUP	10
4.1.5	EUT OPERATING CONDITIONS.....	11
4.1.6	TEST RESULTS.....	12
4.2	RADIATED EMISSION MEASUREMENT	18
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	18
4.2.2	TEST INSTRUMENTS	19
4.2.3	TEST PROCEDURES.....	20
4.2.4	TEST SETUP	21
4.2.5	EUT OPERATING CONDITIONS.....	21
4.2.6	TEST RESULTS(A).....	22
4.2.7	TEST RESULTS(B).....	27
4.3	6dB BANDWIDTH MEASUREMENT	32
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	32
4.3.2	TEST INSTRUMENTS	32
4.3.3	TEST PROCEDURE	33
4.3.4	TEST SETUP	33
4.3.5	EUT OPERATING CONDITIONS.....	33
4.3.6	TEST RESULTS.....	34
4.4	MAXIMUM PEAK OUTPUT POWER	38
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	38
4.4.2	TEST INSTRUMENTS	38
4.4.3	TEST PROCEDURES.....	39
4.4.4	TEST SETUP	39



4.4.5	EUT OPERATING CONDITIONS.....	39
4.4.6	TEST RESULTS.....	40
4.5	POWER SPECTRAL DENSITY MEASUREMENT	41
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	41
4.5.2	TEST INSTRUMENTS	41
4.5.3	TEST PROCEDURE	42
4.5.4	TEST SETUP	42
4.5.5	EUT OPERATING CONDITIONS.....	42
4.5.6	TEST RESULTS.....	43
4.6	BAND EDGES MEASUREMENT	47
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	47
4.6.2	TEST INSTRUMENTS	47
4.6.3	TEST PROCEDURE	47
4.6.4	EUT OPERATING CONDITION	47
4.6.5	TEST RESULTS.....	48
4.7	ANTENNA REQUIREMENT.....	51
4.7.1	STANDARD APPLICABLE	51
4.7.2	ANTENNA CONNECTED CONSTRUCTION.....	51
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	52
6	INFORMATION ON THE TESTING LABORATORIES	54



1 CERTIFICATION

PRODUCT : 11M WLAN PCI Adapter
BRAND NAME : CyberTAN
MODEL NO. : MW302-P
APPLICANT : CYBERTAN TECHNOLOGY INC.
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Apr. 25 ~ Apr. 30, 2003, The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

CHECKED BY: Demi Chen, DATE: May 8, 2003
Demi Chen

APPROVED BY: Dr. Alan Lane, DATE: May 8, 2003
Dr. Alan Lane
Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -21.84dBuV at 0.716MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -4.90dBuV at 9648.00MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	11M WLAN PCI Adapter
MODEL NO.	MW302-P
POWER SUPPLY	5VDC from host equipment
MODULATION TYPE	BPSK, QPSK, CCK
RADIO TECHNOLOGY	DSSS
TRANSFER RATE	1/2/5.5/11Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	19.94dBm
ANTENNA TYPE	Dipole antenna
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

1. Two sets of antenna were provided to this EUT. Please refer to the following:

Antenna	Antenna Gain (dBi)
Dipole	2
Dipole	5

2. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. Two test results were provided to this EUT. The test result A was for antenna gain with 2dBi, and the test result B was for antenna gain with 5dBi.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a 11M WLAN PCI Adapter. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 15, Subpart C. (15.247)

ANSI C63.4 : 1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PERSONAL COMPUTER	HP	DTPC 27	SG21103587	FCC DoC Approve
2	MONITOR	ADI	CM100	020058T10200176	FCC DoC Approved
3	PS/2 KEYBOARD	BTC	5121W	A00801379	E5XKB5121WTH0110
4	PS/2 MOUSE	LOGITECH	M-S61	HCA10801957	JNZ211403
5	PRINTER	EPSON	LQ-300+	DCGY017067	FCC DoC Approved
6	MODEM	ACEEX	1414	980020508	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.8 m braid shielded wire, terminated with VGA connector via metallic frame, w/o core
3	1.6 m foil shielded wire, terminated with PS/2 connector via metallic frame, w/o core.
4	1.8 m Non shielded wire, terminated with PS/2 connector via drain wire, w/o core.
5	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
6	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

NOTE: All power cords of the above support units are non shielded (1.8m).

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS


DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	834115/016	Mar. 02, 2004
ROHDE & SCHWARZ Artificial Mains Network (For EUT)	ESH2-Z5	892107/003	July 10, 2003
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Nov. 29, 2003
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Nov. 29, 2003
EMCO L.I.S.N. (For peripherals)	3825/2	9504-2359	July 10, 2003
Software	Cond-V2M1	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C03.01	July 11, 2003
Terminator (For EMCO LISN)	NA	E1-01-300	Feb. 23, 2004
Terminator (For EMCO LISN)	NA	E1-01-301	Feb. 23, 2004

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. "*": These equipment are used for conducted telecom port test only (if tested).
 3. The test was performed in ADT Shielded Room No. 3.
 4. The VCCI Site Registration No. is C-274.

4.1.3 TEST PROCEDURES

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.4 TEST SETUP



- Note:**
- Support units were connected to second LISN.
 - Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.5 EUT OPERATING CONDITIONS

- a. Connected the EUT to a computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer, and the printer prints them on paper.


4.1.6 TEST RESULTS

EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Steven Lu	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.185	0.10	39.23	-	39.33	-	64.25	54.25	-24.92	-
2	0.357	0.10	33.92	-	34.02	-	58.80	48.80	-24.78	-
3	0.716	0.15	34.01	-	34.16	-	56.00	46.00	-21.84	-
4	1.836	0.28	28.25	-	28.53	-	56.00	46.00	-27.47	-
5	6.238	0.40	31.93	-	32.33	-	60.00	50.00	-27.67	-
6	8.172	0.40	31.01	-	31.41	-	60.00	50.00	-28.59	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Steven Lu	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.184	0.10	41.03	-	41.13	-	64.31	54.31	-23.18	-
2	0.361	0.10	29.78	-	29.88	-	58.71	48.71	-28.83	-
3	0.714	0.15	33.67	-	33.82	-	56.00	46.00	-22.18	-
4	0.917	0.19	30.78	-	30.97	-	56.00	46.00	-25.03	-
5	6.237	0.50	31.30	-	31.80	-	60.00	50.00	-28.20	-
6	8.074	0.50	32.28	-	32.78	-	60.00	50.00	-27.22	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Steven Lu	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.185	0.10	37.37	-	37.47	-	64.25	54.25	-26.78	-
2	0.357	0.10	32.49	-	32.59	-	58.80	48.80	-26.21	-
3	0.714	0.15	33.27	-	33.42	-	56.00	46.00	-22.58	-
4	1.285	0.23	27.14	-	27.37	-	56.00	46.00	-28.63	-
5	6.238	0.40	30.24	-	30.64	-	60.00	50.00	-29.36	-
6	8.074	0.40	30.52	-	30.92	-	60.00	50.00	-29.08	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Steven Lu	

No	Freq.	Corr. Factor	Reading Value [dB (Uv)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.185	0.10	40.48	-	40.58	-	64.25	54.25	-23.67	-
2	0.365	0.10	31.67	-	31.77	-	58.62	48.62	-26.85	-
3	0.714	0.15	33.94	-	34.09	-	56.00	46.00	-21.91	-
4	1.012	0.20	30.10	-	30.30	-	56.00	46.00	-25.70	-
5	6.145	0.50	29.46	-	29.96	-	60.00	50.00	-30.04	-
6	8.074	0.50	32.26	-	32.76	-	60.00	50.00	-27.24	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Steven Lu	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.183	0.10	37.57	-	37.67	-	64.36	54.36	-26.69	-
2	0.357	0.10	32.07	-	32.17	-	58.80	48.80	-26.63	-
3	0.716	0.15	31.95	-	32.10	-	56.00	46.00	-23.90	-
4	1.836	0.28	25.76	-	26.04	-	56.00	46.00	-29.96	-
5	3.578	0.38	27.45	-	27.83	-	56.00	46.00	-28.17	-
6	7.156	0.40	28.98	-	29.38	-	60.00	50.00	-30.62	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Netural (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Steven Lu	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.185	0.10	39.85	-	39.95	-	64.25	54.25	-24.30	-
2	0.367	0.10	32.02	-	32.12	-	58.57	48.57	-26.45	-
3	0.713	0.15	32.74	-	32.89	-	56.00	46.00	-23.11	-
4	1.012	0.20	29.44	-	29.64	-	56.00	46.00	-26.36	-
5	5.043	0.50	24.51	-	25.01	-	60.00	50.00	-34.99	-
6	8.074	0.50	30.16	-	30.66	-	60.00	50.00	-29.34	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01042	May 1, 2004
* HP Preamplifier	8447D	2944A08313	Mar. 6, 2004
* HP Preamplifier	8449B	3008A01201	Dec. 01, 2003
* HP Preamplifier	8449B	3008A01292	Aug. 07, 2003
* ROHDE & SCHWARZ TEST RECEIVER	ESVS 10	844594/010	Sep. 29, 2003
SCHAFFNER Tunable Dipole Antenna	VHBA 9123	459	Nov. 22, 2003
SCHWARZBECK Tunable Dipole Antenna	UHA 9105	977	
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Feb. 13, 2004
* CHASE BILOG Antenna	CBL6111A	1647	Mar. 21, 2004
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	July 3, 2003
* EMCO Horn Antenna	3115	9312-4192	Mar. 23, 2004
* EMCO Turn Table	1016	1722	NA
* EMCO Tower	1051	1825	NA
* Software	ADT_Radiated_V5.09	NA	NA
* ANRITSU RF Switches	MP59B	M28342	Sep. 25, 2003
* TIMES RF cable	LMR-600	CABLE-ST4-01	Sep. 25, 2003

- NOTE:** 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. "*" = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. 4.
5. The VCCI Site Registration No. is R-1038.




4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.5 EUT OPERATING CONDITIONS

Same as 4.1.5

4.2.6 TEST RESULTS(A)

EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	27 deg. C, 60 % RH, 991 hPa	TESTED BY: Steven Lu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	240.03	21.4 QP	46.00	-24.60	1.61 H	108	9.00	12.40
2	320.04	16.4 QP	46.00	-29.60	1.85 H	31	1.90	14.60
3	398.79	20.7 QP	46.00	-25.30	1.49 H	96	3.30	17.40
4	453.32	24.7 QP	46.00	-21.30	1.59 H	299	6.30	18.40
5	525.05	25.3 QP	46.00	-20.70	2.73 H	299	4.40	20.80
6	633.26	28.7 QP	46.00	-17.30	1.28 H	99	6.10	22.50
7	687.28	29.1 QP	46.00	-16.90	1.30 H	156	6.10	23.00
8	750.05	27.0 QP	46.00	-19.00	1.29 H	154	2.70	24.30
9	864.16	31.1 QP	46.00	-14.90	1.30 H	219	4.80	26.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 991 hPa	TESTED BY: Steven Lu	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	240.06	19.7 QP	46.00	-26.30	1.70 V	340	7.30	12.40
2	320.02	19.7 QP	46.00	-26.30	1.70 V	97	5.20	14.60
3	398.81	27.2 QP	46.00	-18.80	1.90 V	285	9.80	17.40
4	453.31	30.6 QP	46.00	-15.40	1.48 V	92	12.20	18.40
5	525.06	25.7 QP	46.00	-20.30	1.73 V	301	4.80	20.80
6	597.26	39.3 QP	46.00	-6.70	1.61 V	89	17.60	21.70
7	625.11	28.2 QP	46.00	-17.80	1.61 V	125	5.90	22.30
8	750.05	26.0 QP	46.00	-20.00	2.22 V	8	1.70	24.30
9	864.20	32.6 QP	46.00	-13.40	1.65 V	243	6.20	26.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 991 hPa	TESTED BY: Steven Lu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	41.7 PK	74.00	-32.30	1.10 H	265	13.10	28.60
2	*2411.20	103.2 PK			1.21 H	140	72.20	31.00
2	*2411.20	100.1 AV			1.21 H	140	69.10	28.60
3	3216.00	59.7 PK	83.20	-23.50	1.10 H	135	26.00	33.80
3	3216.00	57.0 AV	80.10	-23.10	1.10 H	135	23.20	31.00
4	4823.60	42.0 PK	74.00	-32.00	1.52 H	211	5.10	36.90
5	7235.68	48.6 PK	74.00	-25.40	1.22 H	354	7.10	41.50
6	9648.00	54.9 PK	74.00	-19.10	1.10 H	11	11.00	43.90
6	9648.00	48.2 AV	54.00	-5.80	1.10 H	11	4.30	33.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	44.0 PK	74.00	-30.00	1.36 V	211	15.40	28.60
2	*2412.00	111.0 PK			1.08 V	120	80.00	31.00
2	*2412.00	108.0 AV			1.08 V	120	77.00	28.60
3	3216.16	69.5 PK	91.00	-21.50	1.50 V	200	35.70	33.80
3	3216.16	66.4 AV	88.00	-21.60	1.50 V	200	32.60	31.00
4	4824.50	45.2 PK	74.00	-28.80	1.66 V	200	8.30	36.90
5	7236.00	49.9 PK	74.00	-24.10	1.33 V	299	8.40	41.50
6	9648.00	53.6 PK	74.00	-20.40	1.12 V	198	9.70	43.90
6	9648.00	44.0 AV	54.00	-10.00	1.12 V	198	0.00	33.80

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 991 hPa	TESTED BY: Steven Lu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.76	42.1 PK	74.00	-31.90	1.25 H	198	13.40	28.70
2	*2437.00	102.0 PK			1.10 H	202	70.90	31.10
2	*2437.00	99.3 AV			1.10 H	202	68.20	28.70
3	3249.52	58.8 PK	82.00	-23.20	1.29 H	185	25.00	33.80
3	3249.52	55.4 AV	79.30	-23.90	1.29 H	185	21.60	31.10
4	4874.20	42.4 PK	74.00	-31.60	1.28 H	125	5.30	37.00
5	7311.20	47.7 PK	74.00	-26.30	1.56 H	247	5.90	41.80
6	9748.00	51.3 PK	74.00	-22.70	1.68 H	155	7.30	44.00
6	9748.00	42.4 AV	54.00	-11.60	1.68 H	155	-1.60	33.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.84	46.7 PK	74.00	-27.30	1.60 V	180	18.00	28.70
2	*2437.00	112.3 PK			1.06 V	144	81.30	31.10
2	*2437.00	109.1 AV			1.06 V	144	78.00	28.70
3	3249.52	70.0 PK	92.30	-22.30	1.12 V	165	36.20	33.80
3	3249.52	68.0 AV	89.10	-21.10	1.12 V	165	34.10	31.10
4	4873.95	44.0 PK	74.00	-30.00	1.28 V	192	7.00	37.00
5	7310.92	50.0 PK	74.00	-24.00	1.12 V	240	8.20	41.80
5	7310.92	-	54.00	-	1.12 V	240	-999.00	33.80
6	9747.20	49.3 PK	74.00	-24.70	1.19 V	22	5.30	44.00

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 991 hPa	TESTED BY: Steven Lu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	40.3 PK	74.00	-33.70	1.44 H	350	11.50	28.80
2	*2462.00	102.6 PK			1.00 H	123	71.50	31.10
2	*2462.00	99.8 AV			1.00 H	123	68.70	28.80
3	3282.30	44.2 PK	82.60	-38.40	1.54 H	352	10.30	33.90
4	4923.98	45.2 PK	79.80	-38.50	1.54 H	177	8.00	37.20
5	7385.98	50.3 PK	74.00	-23.70	1.20 H	57	8.30	42.00
5	7385.98	-	54.00	-	1.20 H	57	-999.00	31.10
6	9848.00	51.3 PK	74.00	-22.70	1.12 H	20	7.20	44.10
6	9848.00	42.3 AV	54.00	-11.70	1.12 H	20	-1.80	33.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.50	48.2 PK	74.00	-25.80	1.13 V	265	19.40	28.80
2	*2462.00	113.4 PK			1.03 V	145	82.30	31.10
2	*2462.00	110.1 AV			1.03 V	145	79.00	28.80
3	3282.67	69.2 PK	93.40	-24.20	1.56 V	222	35.30	33.90
3	3282.67	67.2 AV	90.10	-22.90	1.56 V	222	33.30	31.10
4	4923.98	42.3 PK	74.00	-31.70	1.18 V	59	5.20	37.20
5	7385.98	52.4 PK	74.00	-21.60	1.22 V	240	10.30	42.00
5	7385.98	45.5 AV	54.00	-8.50	1.22 V	240	3.50	33.90
6	9847.20	53.2 PK	74.00	-20.80	1.32 V	210	9.10	44.10
6	9847.20	43.2 AV	54.00	-10.80	1.32 V	210	-0.90	37.20

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

4.2.7 TEST RESULTS(B)

EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	27 deg. C, 60 % RH, 991 hPa	TESTED BY: Steven Lu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	240.06	24.7 QP	46.00	-21.30	1.03 H	111	12.30	12.40
2	320.01	24.3 QP	46.00	-21.70	1.00 H	0	9.70	14.60
3	398.78	30.1 QP	46.00	-15.90	1.64 H	289	12.70	17.40
4	425.05	24.9 QP	46.00	-21.10	2.38 H	117	7.00	17.90
5	448.01	20.3 QP	46.00	-25.70	1.37 H	248	2.00	18.30
6	480.07	21.6 QP	46.00	-24.40	1.79 H	294	2.40	19.20
7	550.06	25.9 QP	46.00	-20.10	2.38 H	328	4.00	21.90
8	750.13	29.1 QP	46.00	-16.90	1.00 H	126	4.80	24.30
9	821.30	36.0 QP	46.00	-10.00	1.00 H	336	10.70	25.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 991 hPa	TESTED BY: Steven	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	240.06	21.4 QP	46.00	-24.60	1.00 V	266	9.00	12.40
2	320.00	24.5 QP	46.00	-21.50	1.17 V	196	10.00	14.60
3	398.81	21.9 QP	46.00	-24.10	1.19 V	59	4.50	17.40
4	425.99	21.9 QP	46.00	-24.10	1.00 V	0	3.90	17.90
5	447.39	22.9 QP	46.00	-23.10	1.49 V	277	4.60	18.30
6	480.10	22.3 QP	46.00	-23.70	2.01 V	54	3.10	19.20
7	550.05	25.6 QP	46.00	-20.40	2.44 V	0	3.70	21.90
8	750.15	30.9 QP	46.00	-15.10	1.38 V	197	6.60	24.30
9	821.40	35.7 QP	46.00	-10.30	1.20 V	29	10.40	25.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 991 hPa	TESTED BY: Steven Lu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	42.2 PK	74.00	-31.80	1.06 H	219	13.60	28.60
2	*2411.20	106.0 PK			1.00 H	139	75.00	31.00
2	*2411.20	103.0 AV			1.00 H	139	72.00	28.60
3	3216.12	60.2 PK	86.00	-28.80	1.00 H	130	26.40	33.80
3	3216.12	57.5 AV	83.00	-25.50	1.00 H	130	23.70	31.00
4	4823.60	42.8 PK	74.00	-31.20	1.43 H	233	5.90	36.90
5	7235.68	49.8 PK	74.00	-24.20	1.17 H	7	8.20	41.50
6	9648.00	55.2 PK	74.00	-18.80	1.05 H	9	11.30	43.90
6	9648.00	49.1 AV	54.00	-4.90	1.05 H	9	5.20	33.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	45.0 PK	74.00	-29.00	1.30 V	198	16.40	28.60
2	*2412.00	115.0 PK			1.08 V	130	84.00	31.00
2	*2412.00	111.9 AV			1.08 V	130	80.90	28.60
3	3216.16	70.5 PK	95.00	-24.50	1.49 V	189	36.70	33.80
3	3216.16	67.5 AV	91.90	-24.40	1.49 V	189	33.70	31.00
4	4824.50	46.1 PK	74.00	-27.90	1.52 V	202	9.20	36.90
5	7236.00	51.1 PK	74.00	-22.90	1.45 V	269	9.60	41.50
5	7236.00	-	54.00	-	1.45 V	269	-999.00	33.80
6	9648.00	52.6 PK	74.00	-21.40	1.21 V	220	8.70	43.90
6	9648.00	42.6 AV	54.00	-11.40	1.21 V	220	-1.40	36.90

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 991 hPa	TESTED BY: Steven Lu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.76	43.0 PK	74.00	-31.00	1.19 H	166	14.30	28.70
2	*2437.00	105.0 PK			1.05 H	145	74.00	31.10
2	*2437.00	101.4 AV			1.05 H	145	70.40	28.70
3	3249.52	59.3 PK	85.00	-25.70	1.27 H	168	25.40	33.80
3	3249.52	56.7 AV	81.40	-24.70	1.27 H	168	22.80	31.10
4	4874.00	43.3 PK	74.00	-30.70	1.28 H	71	6.20	37.00
5	7311.20	48.7 PK	74.00	-25.30	1.40 H	200	6.90	41.80
6	9748.00	52.7 PK	74.00	-21.30	1.02 H	175	8.70	44.00
6	9748.00	43.7 AV	54.00	-10.30	1.02 H	175	-0.30	33.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.84	47.8 PK	74.00	-26.20	1.60 V	175	19.10	28.70
2	*2437.00	115.4 PK			1.04 V	138	84.30	31.10
2	*2437.00	112.6 AV			1.04 V	138	81.50	28.70
3	3249.52	71.5 PK	95.40	-23.90	1.06 V	185	37.70	33.80
3	3249.52	69.9 AV	92.60	-22.70	1.06 V	185	36.10	31.10
4	4873.67	44.3 PK	74.00	-29.70	1.28 V	180	7.20	37.00
5	7310.92	50.2 PK	74.00	-23.80	1.10 V	245	8.40	41.80
5	7310.92	-	54.00	-	1.10 V	245	-999.00	33.80
6	9747.92	50.7 PK	74.00	-23.30	1.28 V	328	6.70	44.00
6	9747.92	44.0 AV	54.00	-10.00	1.28 V	328	0.00	37.00

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency



EUT	11M WLAN PCI Adapter	MODEL	MW302-P
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 991 hPa	TESTED BY: Steven Lu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.50	41.3 PK	74.00	-32.70	1.32 H	354	12.50	28.80
2	*2461.40	105.2 PK			1.01 H	157	74.10	31.10
2	*2461.40	102.2 AV			1.01 H	157	71.10	28.80
3	3100.04	45.4 PK	85.20	-39.80	1.48 H	288	11.90	33.50
4	4923.88	44.4 PK	74.00	-29.60	1.19 H	177	7.30	37.20
5	7385.80	51.1 PK	74.00	-22.90	1.19 H	79	9.00	42.00
5	7385.80	-999.0 AV	54.00	-999.00	1.19 H	79	-999.00	31.10
6	9848.00	52.3 PK	74.00	-21.70	1.00 H	70	8.20	44.10
6	9848.00	42.4 AV	54.00	-11.60	1.00 H	70	-1.70	33.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.50	49.6 PK	74.00	-24.40	1.32 V	162	20.80	28.80
2	*2462.60	115.5 PK			1.03 V	137	84.40	31.10
2	*2462.60	112.6 AV			1.03 V	137	81.50	28.80
3	3282.67	71.6 PK	95.50	-23.90	1.41 V	189	37.60	33.90
3	3282.67	69.8 AV	92.60	-22.80	1.41 V	189	35.90	31.10
4	4923.98	44.8 PK	74.00	-29.20	1.18 V	227	7.60	37.20
5	7385.98	53.9 PK	74.00	-20.10	1.18 V	240	11.80	42.00
5	7385.98	46.8 AV	54.00	-7.20	1.18 V	240	4.80	33.90
6	9847.92	53.1 PK	74.00	-20.90	1.00 V	347	9.00	44.10
6	9847.92	43.9 AV	54.00	-10.10	1.00 V	347	-0.10	37.20

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003


NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




4.3.6 TEST RESULTS


EUT	11M WLAN PCI Adapter	MODEL	MW302-P
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 60%RH, 991 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	10.060	0.5	PASS
6	2437	9.980	0.5	PASS
11	2462	9.980	0.5	PASS


CH1



CH6



CH11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
POWER METER	E4416A	GB41291118	Jul. 30, 2003
PEAK POWER SENSOR	E9327A	US40440722	Jul. 30, 2003


NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

The transmitter output was connected to the peak power meter.

4.4.4 TEST SETUP



4.4.5 EUT OPERATING CONDITIONS

Same as Item 4.3.5

4.4.6 TEST RESULTS

EUT	11M WLAN PCI Adapter	MODEL	MW302-P
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 60%RH, 991 hPa
TESTED BY: Steven			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	19.85	30	PASS
6	2437	19.94	30	PASS
11	2462	19.85	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003


NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

4.5.4 TEST SETUP



4.5.5 EUT OPERATING CONDITIONS


Same as 4.3.5

4.5.6 TEST RESULTS


EUT	11M WLAN PCI Adapter	MODEL	MW302-P
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 60%RH, 991 hPa
TESTED BY: Steven Lu			

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-7.17	8	PASS
6	2437	-7.43	8	PASS
11	2462	-7.03	8	PASS


CH1



CH6



CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges were measured and recorded.

4.6.4 EUT OPERATING CONDITION


Same as Item 4.3.5




4.6.5 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE: The band edge emission plot on the following 2 pages shows 58.75dB / 58.85dB delta between carrier maximum power and local maximum emission in restrict band (2.3853GHz / 2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 (Page 31) is 112.6dBuV/m, so the maximum field strength in restrict band is $112.6 - 58.85 = 53.75$ dBuV/m which is under 54 dBuV/m limit.







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION


The antenna used in this product is Dipole Antenna with Reversed SMA antenna connector. And the maximum Gain of this antenna is 5dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.