



A D T

RF EXPOSURE REPORT

REPORT NO.: SA110401E06A

MODEL NO.: VTAB1008-NA, VTAB1008

FCC ID: N89-T77N250

ACCORDING: FCC Guidelines for Human Exposure

IEEE C95.1

APPLICANT: CyberTAN Technology, Inc.

ADDRESS: No.99, Park Avenue III, Science-based Industrial Park, Hsinchu, Taiwan 308,R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA991022E10A	Original release	June 03, 2011



A D T

CERTIFICATION

PRODUCT : Vizio Tablet
BRAND NAME : VIZIO
MODEL NO. : VTAB1008-NA, VTAB1008
TEST SAMPLE : ENGINEERING SAMPLE(DVT1.0)
APPLICANT : CyberTAN Technology, Inc.
STANDARDS : IEEE C95.1

The above equipment (Model: VTAB1008-NA) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : , **DATE:** June 03, 2011
(Claire Kuan, Specialist)

APPROVED BY : , **DATE:** June 03, 2011
(May Chen, Deputy Manager)



A D T

For Bluetooth Function:

No SAR Evaluation Required if power is below the following threshold:

Tunable Range		60/f SAR Limitation (mW)
F(GHz) Low	F(GHz) High	
2.402	2.480	24.19

Maximum measured transmitter power:

Pout Conducted (dBm)	Pout Conducted (mW)	Maximum Antenna Gain (dBi)	Pout EIRP (mW)
5	3.2	2.35	5.4325

Threshold for no SAR evaluation is 24.19 mW

Maximum TX Power is 3.2 mW Conducted and 5.4325 mW EIRP

Conclusion: No SAR evaluation required since maximum Transmitter Pout (both conducted and EIRP) is below FCC threshold

--- END ---