



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 1 of 57



TEST REPORT

Product Name : Wireless Broadband Router

Model Number : WG-414

Applicant : CyberTAN Technology Inc.

Address : No. 99, PARK AVE. III, Science Industrial Park, Hsinchu, Taiwan
308, R.O.C.

Date Received : MAY. 15, 2003

Date Tested : MAY. 15~JUN20, 2003

Notes :

1. This report will be invalid if duplicated or photocopied in part.
2. This report refers only to the specimen(s) submitted to testing, and be invalid as separately used.
3. This report is invalid without examination stamp and signature of this institute.
4. The tested specimen(s) will be preserved for thirty days from the data issued.
5. The report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.





Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 2 of 57

Test Report Certification

Product Name : Wireless Broadband Router
Model Number : WG-414
Applicant : CyberTAN Technology Inc.


Measurement Standard :

47 CFR Part 15, Subpart B and Subpart C (Section 15.247),
ANSI C63.4-2001

Tested By : K. P. Pang , **Date** : Jul 11, 2003
(K. P. Pang)

Reviewed By : Roger Sheng , **Date** : Jul 11, 2003
(Roger Sheng)

Approved By : Chieh-De Tsai , **Date** : Jul 11, 2003
(Chieh-De Tsai , Manager)



WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.



TABLE OF CONTENTS

TITLE	PAGE NO.
1. GENERAL INFORMATION	5
1.1 General Statement.....	5
1.2 General Description of EUT & Power.....	5
1.3 Description of Peripherals	6-7
1.4 EUT & Peripherals Setup Diagram	8
1.5 EUT Operating Condition	8
1.6 Description of Test Site	9
1.7 Summary of Test Results.....	9
2. CONDUCTED POWERLINE TEST	10
2.1 Test Equipments	10
2.2 Test Setup	10
2.3 Conducted Power Line Emission Limit.....	11
2.4 Test Procedure	11
2.5 Uncertainty of Conducted Emission.....	11
2.6 Conducted Power Line Emission Measurement.....	12-13
2.7 Photos of Conduction Test	14
3. RADIATED EMISSION TEST	15
3.1 Test Equipments	15
3.2 Test Setup	15
3.3 Radiation Limit.....	16
3.4 Test Procedures.....	17
3.5 Uncertainty of Radiated Emission.....	17
3.6 Radiated RF Noise Measurement	18-37
3.7 Photos of Open Site	38-39
4. 6dB BANDWIDTH MEASUREMENT	40
4.1 Test Equipments	40
4.2 Test Setup	40
4.3 Limits of 6dB Bandwidth Measurement.....	40
4.4 Test Procedure	40
4.5 Uncertainty of Conducted Emission.....	41
4.6 Test Results.....	41
4.7 Photo of 6dB Bandwidth Measurement.....	42-43
5. MAXIMUM PEAK OUTPUT POWER.....	44
5.1 Test Equipments	44
5.2 Test Setup	44
5.3 Limits of Maximum Peak Output Power.....	44
5.4 Test Procedure	45
5.5 Uncertainty of Conducted Emission.....	45
5.6 Test Results.....	45
6. POWER SPECTRAL DENSITY MEASUREMENT	46
6.1 Test Equipments	46
6.2 Test Setup	46
6.3 Limits of Power Spectral Density Measurement	46
6.4 Test Procedure	47
6.5 Uncertainty of Conducted Emission.....	47
6.7 Photo of Power Spectral Density Measurement.....	48-49



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 4 of 57

TABLE OF CONTENTS

TITLE	PAGE NO.
7. OUT OF BAND MEASUREMENT	50
7.1 Test Equipments	50
7.2 Test Setup	50
7.3 Limits of Out of Band Emissions Measurement.....	50
7.4 Test Procedure	51
7.5 Uncertainty of Conducted Emission.....	51
7.6 Test Results.....	51-52
7.7 Photo of Out of Band Measurement	53-54
8. ANTENNA REQUIREMENT.....	55
8.1 Standard Applicable	55
8.2 Antenna Connected Construction	55
9. RF EXPOSURE EVALUATION	56
9.1 Friis Formula	56
9.2 EUT Operating Condition	56
9.3 Test Result of Rf Exposure Evaluation	57
9.3.1 Antenna Gain	57
9.3.2 Output Power into Antenna & RF Exposure Evaluation Distance	57



1. GENERAL INFORMATION

1.1 General Statement

MEASUREMENT DEVIATION : Comply with standard in full

TRACEABILITY : This test result is traceable to national or international std.

1.2 General Description of EUT & Power

MANUFACTURER : CyberTAN Technology Inc.

SAMPLE NAME : Wireless Broadband Router

MODEL NO : WG-414

FREQUENCY RANGE : 2412 MHz TO 2462MHz

CHANNEL NUMBER : 11

AIR DATA RATE : 54Mbps (802.11g Mode), 11Mbps(802.11b Mode)

TYPE OF MODULATION : Orthogonal Frequency Division Multiplex or Direct Sequence
Spread Spectrum

FREQUENCY SELECTION : BY SOFTWARE

EUT Description : 2.4GHz (Orthogonal Frequency Division Multiplex or Direct
Sequence Spread Spectrum) Data Transceiver for Wireless
Broadband Router

ANTENNA TYPE : DIPOLE ANTENNA

POWER SOURCE : 5VDC(From Adaptor)

Power Adapter(1) :

MANUFACTURER : Bothhand Enterprise Inc.

MODEL NUMBER : M1-10S05

INPUT POWER : 100-120VAC, 0.5A, 47-63Hz

OUTPUT POWER : 5VDC, 2A

Power Adapter(2) :

MANUFACTURER : Bothhand Enterprise Inc.

MODEL NUMBER : SA0705-D-7

INPUT POWER : 100-240VAC, 0.5A, 47-63Hz

OUTPUT POWER : 5VDC, 2A



1.3 Description of Peripherals

(1) PC

MANUFACTURER : HP CORP.
MODEL NUMBER : VECTRA VEI8DT
SERIAL NUMBER : SG1202412
FCC : DOC

(2) PC

MANUFACTURER : HP CORP.
MODEL NUMBER : VECTRA VEI8DT
SERIAL NUMBER : SG1202415
FCC : DOC

(3) Notebook PC

MANUFACTURER : DELL CORP.
MODEL NUMBER : PP01L
SERIAL NUMBER : CN-09C748-48155-1AP-6081
FCC : DOC
POWER CORD : Unshielded, Detachable, 1.8m

(4) Notebook PC

MANUFACTURER : DELL CORP.
MODEL NUMBER : PP01L
SERIAL NUMBER : CN-09C748-48155-1AP-6630
FCC : DOC
POWER CORD : Unshielded, Detachable, 1.8m

(5) MONITOR

MODEL NUMBER : D8894A
SERIAL NUMBER : CN00905269
MANUFACTURER : HP CORP.
FCC ID : ARSCM356N
POWER CORD : Unshielded , Detachable , 1.8m

(6) KEYBOARD

MODEL NUMBER : K288
SERIAL NUMBER : 206628619
MANUFACTURER : Genuine Company INC.
FCC ID : FKD46AK288
SIGNAL CABLE : Shielded , Undetachable , 1.8m
POWER SOURCE : 5VDC (from PC)

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 7 of 57**(7) MOUSE**

MODEL NUMBER : M-S34
SERIAL NUMBER : LZE95050431
MANUFACTURER : HP CORP.
FCC ID : DZL211029
SIGNAL CABLE : Shielded , Undetachable , 1.8m
POWER SOURCE : 5VDC (from PC)

(8) MONITOR

MODEL NUMBER : D8894A
SERIAL NUMBER : CN00905251
MANUFACTURER : HP CORP.
FCC ID : ARSCM356N
POWER CORD : Unshielded , Detachable , 1.8m

(9) KEYBOARD

MODEL NUMBER : K288
SERIAL NUMBER : 206628620
MANUFACTURER : Genuine Company INC.
FCC ID : FKD46AK288
SIGNAL CABLE : Shielded , Undetachable , 1.8m
POWER SOURCE : 5VDC (from PC)


(10) MOUSE

MODEL NUMBER : M-S34
SERIAL NUMBER : LZE95050437
MANUFACTURER : HP CORP.
FCC ID : DZL211029
SIGNAL CABLE : Shielded , Undetachable , 1.8m
POWER SOURCE : 5VDC (from PC)

(11) CABLE

	Type	Connector	shielded	Length
(A)	Cat5 twisted-pair	RJ-45, Plastic	NO	15m

1.4 EUT & Peripherals Setup Diagram



1.5 EUT Operating Condition

1. Set up all computers like the setup diagram.
2. NB(4) ping 192.168.1.1 -t -l 5000 to EUT
3. PC(1) ping 192.168.1.80 -t -l 5000 to PC(2)
4. NB(3) ping 192.168.1.70 -t -l 5000 to PC(1)
5. All of the function are under run.
6. Start test.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 9 of 57

1.6 Description of Test Site

SITE DESCRIPTION : FCC certificate NO. : 90585

BSMI certificate NO. : SL2-IN-E-0002

NVLAP Lab code : 200118-0

CNLA certificate NO. : CNLA-ZL97018

VCCI certificate NO. : R-1229, C-1250

NAME OF SITE : Ecom Sertech Corp. Hsinchu
(Spin-off from ITRI / ERSO on April. 01, 2003)SITE LOCATION : Rm.258, Bldg.17, NO.195 , Sec. 4, Chung Hsing Rd.,
Chu-Tung Chen. Hsin-Chu, Taiwan 310 R.O.C.

1.7 Summary of Test Results

The EUT has been tested according to the following specifications :

Applied Standard : 47 CFR Part 15, Subpart B and Subpart C

Standard Section	Test Type and Limit	Result	REMARK
15.107 15.207	AC Power Conducted Emission Limit : Table 15.209	PASS	Meet the requirement of limit
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit : 6dB bandwidth > 500KHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit : max. 30dBm	PASS	Meet the requirement of limit
15.109 15.205 15.209	Transmitter Radiated Emissions Limit : Table 15.209	PASS	Meet the requirement of limit
15.247(d)	Power Spectral Density Limit : max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Out of Band Emission and Restricted Band Radiation Limit:20dB less than peak value of fundamental frequency Restricted band Limit:Table 15.209	PASS	Meet the requirement of limit


2. CONDUCTED POWERLINE TEST

2.1 Test Equipments

The following test equipments are used during the conducted power line tests :

Manufacturer or Type	Model No	Serial No.	Date of Calibration	Calibration Period	Remark
SPECTRUM ANALYZER & DISPLAY	HP 8568A	2235A02320	APR. 01, 2003	1 Year	PRETEST
QUASI-PEAK ADAPTER	HP 85650 A	2341A00672	APR. 01, 2003	1 Year	PRETEST
ISOLATION TRANSFORMER	SOLAR 7032-1	N/A	N/A	N/A	FINAL
L.I.S.N.	EMCO 3850/2	9311-1025 9401-1028	JAN. 08, 2003 For Characteristic impedance	1 Year	FINAL
			MAY 18, 2003 For Insertion loss		
TEST RECEIVER	R/S ESHS30	838550/003	JAN. 22, 2003	1 Year	FINAL
SHIELDED ROOM	KEENE 5983	NO.1	N/A	N/A	FINAL
PULSE LIMIT	R/S EHS3Z2	357.8810.52	JUL. 10, 2002	1 Year	FINAL
N TYPE COAXIAL CABLE	-----	-----	JUL. 10, 2002	1 Year	FINAL
50Ω TERMINATOR	-----	-----	JUL. 10, 2002	1 Year	FINAL

2.2 Test Setup





2.3 Conducted Power Line Emission Limit

All emanation from a class B computing device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified below :

Frequency (MHz)	Maximum Rf Line Voltage (dB μ V)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56	56-46
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

For intentional device, according to § 15.207(a) Line Conducted Emission Limit is same as above table.

2.4 Test Procedure

The test procedure is performed in a 12ft×12ft×8ft(L×W×H) shielded room. the EUT along with its peripherals were placed on a 1.0m(W)× 1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chasis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chasis ground also bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

2.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 1.36 dB.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 12 of 57

2.6 Conducted Power Line Emission Measurement

The frequency spectrum from 0.45 MHz to 30 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

Temperature : 26 °C

Humidity : 65 % RH

Frequency (MHz)	Loss(dB)		Measurement				L1 Emission (dB μ V)		L2 Emission (dB μ V)		Limits (dB μ V)	
			L1(dB μ V)		L2(dB μ V)							
	L1	L2	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.
0.150	0.1	0.2	*	*	*	*	*	*	*	*	66.00	56.00
0.204	0.10	0.20	46.70	*	48.50	*	46.80	*	48.70	*	63.45	53.45
0.306	0.10	0.20	39.30	*	40.80	*	39.40	*	41.00	*	60.08	50.08
1.047	0.10	0.20	24.80	*	23.20	*	24.90	*	23.40	*	56.00	46.00
1.587	0.10	0.20	30.00	*	*	*	30.10	*	*	*	56.00	46.00
1.629	0.10	0.20	29.00	*	31.00	*	29.10	*	31.20	*	56.00	46.00
2.340	0.13	0.20	28.10	*	*	*	28.23	*	*	*	56.00	46.00
4.083	0.20	0.20	27.60	*	29.30	*	27.80	*	29.50	*	56.00	46.00
4.389	0.20	0.20	*	*	28.40	*	*	*	28.60	*	56.00	46.00
7.638	0.36	0.30	*	*	*	*	*	*	*	*	60.00	50.00
15.288	0.63	0.63	33.50	*	*	*	34.13	*	*	*	60.00	50.00
15.312	0.63	0.63	31.50	*	35.00	*	32.13	*	35.63	*	60.00	50.00
15.312	0.63	0.63	*	*	*	*	*	*	*	*	60.00	50.00
15.492	0.65	0.65	29.90	*	31.20	*	30.55	*	31.85	*	60.00	50.00
18.072	0.90	0.99	*	*	*	*	*	*	*	*	60.00	50.00
30.000	1.4	1.8	*	*	*	*	*	*	*	*	60.00	50.00

REMARKS : 1. * Undetectable or the Q.P.values is lower than the limits of Ave.

2. Adapter (1).

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 13 of 57

The frequency spectrum from 0.45 MHz to 30 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

Temperature : 26 °C

Humidity : 65 % RH

Frequency (MHz)	Loss(dB)		Measurement				L1 Emission (dB μ V)		L2 Emission (dB μ V)		Limits (dB μ V)	
			L1(dB μ V)		L2(dB μ V)							
	L1	L2	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.
0.150	0.10	0.20	*	*	*	*	*	*	*	*	66.00	56.00
0.185	0.10	0.20	*	*	57.00	42.10	*	*	57.20	42.30	64.26	54.26
0.187	0.10	0.20	55.80	41.20	*	*	55.90	41.30	*	*	64.17	54.17
0.278	0.10	0.20	*	*	52.60	35.40	*	*	52.80	35.60	60.88	50.88
0.281	0.10	0.20	51.30	30.40	*	*	51.40	30.50	*	*	60.79	50.79
0.326	0.10	0.20	*	*	47.50	30.20	*	*	47.70	30.40	59.55	49.55
0.371	0.10	0.20	*	*	49.20	30.10	*	*	49.40	30.30	58.48	48.48
0.420	0.10	0.20	42.90	*	46.30	29.20	43.00	*	46.50	29.40	57.45	47.45
0.513	0.10	0.20	*	*	44.70	27.30	*	*	44.90	27.50	56.00	46.00
0.609	0.10	0.20	*	*	41.10	*	*	*	41.30	*	56.00	46.00
0.708	0.10	0.20	38.30	*	*	*	38.40	*	*	*	56.00	46.00
1.164	0.10	0.20	*	*	35.30	*	*	*	35.50	*	56.00	46.00
1.695	0.10	0.20	28.30	*	*	*	28.40	*	*	*	56.00	46.00
2.676	0.17	0.20	20.30	*	*	*	20.47	*	*	*	60.00	50.00
2.841	0.18	0.20	*	*	21.30	*	*	*	21.50	*	56.00	46.00
6.708	0.30	0.30	*	*	15.80	*	*	*	16.10	*	60.00	50.00
7.299	0.33	0.30	26.20	*	*	*	26.53	*	*	*	60.00	50.00
12.777	0.50	0.50	23.20	*	*	*	23.70	*	*	*	60.00	50.00
14.574	0.56	0.60	*	*	18.20	*	*	*	18.80	*	60.00	50.00
15.492	0.65	0.65	21.40	*	17.70	*	22.05	*	18.35	*	60.00	50.00
30.000	1.40	1.80	*	*	*	*	*	*	*	*	60.00	50.00

REMARKS : 1. * Undetectable or the Q.P.values is lower than the limits of Ave.
2. Adapter (2).

2.7 Photos of Conduction Test



3. RADIATED EMISSION TEST


3.1 Test Equipments

The following test equipments are utilized in making the measurements contained in this report.

MANUFACTURER OR TYPE	MODEL NO	SERIAL NO	DATE OF CALIBRATION	CALIBRATION PERIOD	REMARK
CHASE BI-LOG ANTENNA	CBL6112B	2421	MAY 07, 2003	1 Year	FINAL
R/S TEST RECEIVER	ESMI	842088/005 841978/008	SEPT. 03, 2002	1 Year	FINAL
OPEN SITE	-----	No.2	JUL. 10~12, 2002	1 Year	FINAL
N TYPE COAXIAL CABLE	CHA9525	4	JUL. 13, 2002	1 Year	FINAL
Horn Antenna	AH-118	10089	FEB. 25, 2003	1 Year	FINAL
HP Pre-amplifier	8449B	3008A01471	OCT. 11, 2002	1 Year	FINAL
HP High pass filter	84300/80038	011	cal. on use	1 Year	FINAL
Horn Antenna	AH-840	03077	FEB. 25, 2003	1 Year	FINAL

3.2 Test Setup

The diagram below shows the test setup which is utilized to make these measurements.



Antenna Elevation Variable

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 16 of 57

3.3 Radiation Limit

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (METERS)	Radiated (dB μ V/M)	Radiated (μ V/M)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

3.4 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

3.5 Uncertainty of Radiated Emission

The uncertainty of radiated emission is $\pm 2.72\text{dB}$.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 18 of 57

3.6 Radiated RF Noise Measurement

Test Requirement: 15.109, 15.209

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are quasi-peak values.

Temperature : 31 °C

Humidity : 53 % RH

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Meter Reading at 3m(dB μ V/M)		Limits (dB μ V/M)	Emission Level at 3m(dB μ V/M)	
			Horizontal	Vertical		Horizontal	Vertical
30.00	21.39	0.90	*	*	40.00	*	*
124.79	13.33	2.10	23.16	10.62	43.50	38.58	26.04
200.03	10.39	2.80	24.16	11.62	43.50	37.35	24.81
125.01	13.33	2.10	13.26	12.03	43.50	28.69	27.46
250.03	13.09	3.20	12.30	10.15	46.00	28.59	26.44
319.03	14.21	3.71	8.16	8.54	46.00	26.09	26.47
500.07	18.32	4.90	8.32	9.87	46.00	31.54	33.09
559.99	19.05	5.20	6.59	7.59	46.00	30.84	31.84
639.99	19.50	5.60	6.74	6.84	46.00	31.84	31.94
719.98	19.65	6.00	6.12	6.54	46.00	31.77	32.19
799.98	20.53	6.40	6.10	7.26	46.00	33.03	34.19
1000.00	21.58	7.00	*	*	54.00	*	*

REMARKS : 1. * Undetectable

2. Emission level (dB μ V/M) = Antenna Factor (dB/m) + Cable loss (dB)
+ Meter Reading (dB μ V).

3. According to technical experiences, all spurious emission at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representation for the test.

4. FOR 11Mbps(802.11b Mode)

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 19 of 57

Test Requirement: 15.109, 15.209

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are quasi-peak values.

Temperature : 31 °C

Humidity : 53 % RH

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Meter Reading at 3m(dB μ V/M)		Limits (dB μ V/M)	Emission Level at 3m(dB μ V/M)	
			Horizontal	Vertical		Horizontal	Vertical
30.00	21.39	0.90	*	*	40.00	*	*
124.79	13.33	2.10	24.20	11.70	43.50	39.62	27.12
200.03	10.39	2.80	25.40	13.60	43.50	38.59	26.79
125.01	13.33	2.10	12.10	12.80	43.50	27.53	28.23
250.03	13.09	3.20	13.10	11.30	46.00	29.39	27.59
319.03	14.21	3.71	8.30	7.60	46.00	26.23	25.53
500.07	18.32	4.90	9.40	10.90	46.00	32.62	34.12
559.99	19.05	5.20	7.70	8.70	46.00	31.95	32.95
639.99	19.50	5.60	7.01	7.20	46.00	32.11	32.30
719.98	19.65	6.00	6.30	7.10	46.00	31.95	32.75
799.98	20.53	6.40	6.40	8.30	46.00	33.33	35.23
1000.00	21.58	7.00	*	*	54.00	*	*

REMARKS : 1. * Undetectable

2. Emission level (dB μ V/M) = Antenna Factor (dB/m) + Cable loss (dB)
+ Meter Reading (dB μ V).

3. According to technical experiences, all spurious emission at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representation for the test.

4. FOR 54Mbps(802.11g Mode)



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 20 of 57

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Receiving	Test Date :	2003/6/28
Fundamental Frequency:	2412MHz (CH 1)	Test By:	K.P. Pang
Temperature :	27 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
4823.87	39.43	34.44	2.77	35.38	9.5	0	31.76	74	-42.24	P	H	1.0
4823.87	27.98	34.44	2.77	35.38	9.5	0	20.31	54	-33.69	A	H	1.0
7236.59	39.48	39.81	3.94	35.56	9.5	0	38.17	74	-35.83	P	H	1.0
7236.59	28.11	39.81	3.94	35.56	9.5	0	26.80	54	-27.20	A	H	1.0
9647.62	40.13	38.54	4.10	35.67	9.5	0	37.59	74	-36.41	P	H	1.0
9647.62	28.57	38.54	4.10	35.67	9.5	0	26.03	54	-27.97	A	H	1.0
4823.83	39.81	34.44	2.77	35.38	9.5	0	32.14	74	-41.86	P	V	1.0
4823.83	28.36	34.44	2.77	35.38	9.5	0	20.69	54	-33.31	A	V	1.0
7236.26	40.23	39.81	3.94	35.56	9.5	0	38.92	74	-35.08	P	V	1.0
7236.26	28.34	39.81	3.94	35.56	9.5	0	27.03	54	-26.97	A	V	1.0
9647.62	41.39	38.54	4.10	35.67	9.5	0	38.85	74	-35.15	P	V	1.0
9647.62	31.28	38.54	4.10	35.67	9.5	0	28.74	54	-25.26	A	V	1.0

Note :

1. Measurement was up to 18GHz harmonic, “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss,
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. for wireless 802.11b mode
7. Test Distance : at 3M

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 21 of 57

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Receiving	Test Date :	2003/6/28
Fundamental Frequency:	2437MHz (CH 6)	Test By:	K.P. Pang
Temperature :	27 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
4873.82	40.83	34.77	2.80	35.40	9.5	0	33.50	74	-40.50	P	H	1.0
4873.82	29.52	34.77	2.80	35.40	9.5	0	22.19	54	-31.81	A	H	1.0
7310.91	41.02	39.78	4.00	35.57	9.5	0	39.73	74	-34.27	P	H	1.0
7310.91	28.67	39.78	4.00	35.57	9.5	0	27.38	54	-26.62	A	H	1.0
9747.81	39.89	38.53	4.02	35.72	9.5	0	37.21	74	-36.79	P	H	1.0
9747.81	28.34	38.53	4.02	35.72	9.5	0	25.66	54	-28.34	A	H	1.0
4873.82	41.67	34.77	2.80	35.40	9.5	0	34.34	74	-39.66	P	V	1.0
4873.82	28.94	34.77	2.80	35.40	9.5	0	21.61	54	-32.39	A	V	1.0
7310.81	40.22	39.78	4.00	35.57	9.5	0	38.93	74	-35.07	P	V	1.0
7310.81	28.17	39.78	4.00	35.57	9.5	0	26.88	54	-27.12	A	V	1.0
9747.79	41.88	38.53	4.02	35.72	9.5	0	39.20	74	-34.80	P	V	1.0
9747.79	29.18	38.53	4.02	35.72	9.5	0	26.50	54	-27.50	A	V	1.0

Note :

1. Measurement was up to 18GHz harmonic, “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss,
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. for wireless 802.11b mode
7. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 22 of 57

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Receiving	Test Date :	2003/6/28
Fundamental Frequency:	2462MHz (CH 11)	Test By:	K.P. Pang
Temperature :	27 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
4923.81	40.53	35.10	2.83	35.41	9.5	0	33.55	74	-40.45	P	H	1.0
4923.81	28.84	35.10	2.83	35.41	9.5	0	21.86	54	-32.14	A	H	1.0
7385.33	39.95	39.75	4.06	35.57	9.5	0	38.68	74	-35.32	P	H	1.0
7385.33	28.06	39.75	4.06	35.57	9.5	0	26.79	54	-27.21	A	H	1.0
9847.81	41.76	38.52	3.93	35.77	9.5	0	38.94	74	-35.06	P	H	1.0
9847.81	29.56	38.52	3.93	35.77	9.5	0	26.74	54	-27.26	A	H	1.0
4924.06	42.76	35.10	2.83	35.41	9.5	0	35.78	74	-38.22	P	V	1.0
4924.06	29.73	35.10	2.83	35.41	9.5	0	22.75	54	-31.25	A	V	1.0
7386.61	39.98	39.75	4.06	35.57	9.5	0	38.71	74	-35.29	P	V	1.0
7386.61	27.73	39.75	4.06	35.57	9.5	0	26.46	54	-27.54	A	V	1.0
9848.31	40.53	38.52	3.93	35.77	9.5	0	37.71	74	-36.29	P	V	1.0
9848.31	41.03	38.52	3.93	35.77	9.5	0	38.21	54	-15.79	A	V	1.0

Note :

1. Measurement was up to 18GHz harmonic, "----" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss,
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
5. The result basic equation calculation as follow :
$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. for wireless 802.11b mode
7. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 23 of 57

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Receiving	Test Date :	2003/6/28
Fundamental Frequency:	2412MHz (CH 1)	Test By:	K.P. Pang
Temperature :	27 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
4823.87	39.26	34.44	2.77	35.38	9.5	0	31.59	74	-42.41	P	H	1.0
4823.87	28.18	34.44	2.77	35.38	9.5	0	20.51	54	-33.49	A	H	1.0
7236.59	40.10	39.81	3.94	35.56	9.5	0	38.79	74	-35.21	P	H	1.0
7236.59	28.13	39.81	3.94	35.56	9.5	0	26.82	54	-27.18	A	H	1.0
9647.62	40.42	38.54	4.10	35.67	9.5	0	37.88	74	-36.12	P	H	1.0
9647.62	28.72	38.54	4.10	35.67	9.5	0	26.18	54	-27.82	A	H	1.0
4823.83	40.24	34.44	2.77	35.38	9.5	0	32.57	74	-41.43	P	V	1.0
4823.83	28.59	34.44	2.77	35.38	9.5	0	20.92	54	-33.08	A	V	1.0
7236.26	38.24	39.81	3.94	35.56	9.5	0	36.93	74	-37.07	P	V	1.0
7236.26	27.17	39.81	3.94	35.56	9.5	0	25.86	54	-28.14	A	V	1.0
9647.62	40.88	38.54	4.10	35.67	9.5	0	38.34	74	-35.66	P	V	1.0
9647.62	28.77	38.54	4.10	35.67	9.5	0	26.23	54	-27.77	A	V	1.0

Note :

1. Measurement was up to 18GHz harmonic, "----" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss,
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. for wireless 802.1g mode
7. Test Distance : at 3M

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 24 of 57

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Receiving	Test Date :	2003/6/28
Fundamental Frequency:	2437MHz (CH 6)	Test By:	K.P. Pang
Temperature :	27 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
4873.82	41.93	34.77	2.80	35.40	9.5	0	34.60	74	-39.40	P	H	1.0
4873.82	29.45	34.77	2.80	35.40	9.5	0	22.12	54	-31.88	A	H	1.0
7310.91	40.17	39.78	4.00	35.57	9.5	0	38.88	74	-35.12	P	H	1.0
7310.91	28.34	39.78	4.00	35.57	9.5	0	27.05	54	-26.95	A	H	1.0
9747.81	41.44	38.53	4.02	35.72	9.5	0	38.76	74	-35.24	P	H	1.0
9747.81	28.74	38.53	4.02	35.72	9.5	0	26.06	54	-27.94	A	H	1.0
4873.82	41.24	34.77	2.80	35.40	9.5	0	33.91	74	-40.09	P	V	1.0
4873.82	29.28	34.77	2.80	35.40	9.5	0	21.95	54	-32.05	A	V	1.0
7310.81	40.53	39.78	4.00	35.57	9.5	0	39.24	74	-34.76	P	V	1.0
7310.81	28.94	39.78	4.00	35.57	9.5	0	27.65	54	-26.35	A	V	1.0
9747.79	40.13	38.53	4.02	35.72	9.5	0	37.45	74	-36.55	P	V	1.0
9747.79	28.77	38.53	4.02	35.72	9.5	0	26.09	54	-27.91	A	V	1.0

Note :

1. Measurement was up to 18GHz harmonic, “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss,
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. for wireless 802.11g mode
7. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 25 of 57

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Receiving	Test Date :	2003/6/28
Fundamental Frequency:	2462MHz (CH 11)	Test By:	K.P. Pang
Temperature :	27 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
4923.81	41.73	35.10	2.83	35.41	9.5	0	34.75	74	-39.25	P	H	1.0
4923.81	29.66	35.10	2.83	35.41	9.5	0	22.68	54	-31.32	A	H	1.0
7385.33	38.85	39.75	4.06	35.57	9.5	0	37.58	74	-36.42	P	H	1.0
7385.33	27.83	39.75	4.06	35.57	9.5	0	26.56	54	-27.44	A	H	1.0
9847.81	41.56	38.52	3.93	35.77	9.5	0	38.74	74	-35.26	P	H	1.0
9847.81	29.15	38.52	3.93	35.77	9.5	0	26.33	54	-27.67	A	H	1.0
4924.06	41.73	35.10	2.83	35.41	9.5	0	34.75	74	-39.25	P	V	1.0
4924.06	29.71	35.10	2.83	35.41	9.5	0	22.73	54	-31.27	A	V	1.0
7386.61	39.61	39.75	4.06	35.57	9.5	0	38.34	74	-35.66	P	V	1.0
7386.61	27.96	39.75	4.06	35.57	9.5	0	26.69	54	-27.31	A	V	1.0
9848.31	41.03	38.52	3.93	35.77	9.5	0	38.21	74	-35.79	P	V	1.0
9848.31	29.97	38.52	3.93	35.77	9.5	0	27.15	54	-26.85	A	V	1.0

Note :

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss,
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
5. The result basic equation calculation as follow :
$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. for wireless 802.11g mode
7. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 26 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2412MHz (CH 1)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	(dB)	(P/Q/A)	(H/V)	(Meter)
2411.88	108.11	31.79	2.36	35.31	9.5	0	97.44	Fundamental frequency		P	H	1.0
2411.88	106.18	31.79	2.36	35.31	9.5	0	95.51			A	H	1.0
4823.05	42.81	34.43	2.77	35.38	9.5	1	36.13	74	-37.87	P	H	1.0
4823.05	32.73	34.43	2.77	35.38	9.5	1	26.05	54	-27.95	A	H	1.0
7235.29	40.73	39.81	3.94	35.56	9.5	1	40.42	74	-33.58	P	H	1.0
7235.29	29.01	39.81	3.94	35.56	9.5	1	28.70	54	-25.30	A	H	1.0
9647.81	41.57	38.54	4.10	35.67	9.5	1	40.03	74	-33.97	P	H	1.0
9647.81	29.63	38.54	4.10	35.67	9.5	1	28.09	54	-25.91	A	H	1.0
12059.93*	---	42.60	15.20	35.30	9.5	1	---	---	---	---	H	1.0
14471.97*	---	43.40	16.80	34.00	9.5	1	---	---	---	---	H	1.0
16884.01	---	45.20	17.60	34.30	9.5	1	---	---	---	---	H	1.0
19296.05*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	H	1.0
21708.09	---	36.20	19.20	34.60	9.5	1	---	---	---	---	H	1.0
24120.13	---	36.80	21.00	34.20	9.5	1	---	---	---	---	H	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11b mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 27 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2412MHz (CH 1)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2411.55	114.82	31.79	2.36	35.31	9.5	0	104.15	Fundamental frequency		P	V	1.0
2411.55	113.21	31.79	2.36	35.31	9.5	0	102.54			A	V	1.0
4823.11	45.73	34.43	2.77	35.38	9.5	1	39.05	74	-34.95	P	V	1.0
4823.11	38.24	34.43	2.77	35.38	9.5	1	31.56	54	-22.44	A	V	1.0
7235.38	44.16	39.81	3.94	35.56	9.5	1	43.85	74	-30.15	P	V	1.0
7235.38	32.63	39.81	3.94	35.56	9.5	1	32.32	54	-21.68	A	V	1.0
9647.73	40.96	38.54	4.10	35.67	9.5	1	39.42	74	-34.58	P	V	1.0
9647.73	29.66	38.54	4.10	35.67	9.5	1	28.12	54	-25.88	A	V	1.0
12059.93*	---	42.60	15.20	35.30	9.5	1	---	---	---	---	V	1.0
14471.97*	---	43.40	16.80	34.00	9.5	1	---	---	---	---	V	1.0
16884.01	---	45.20	17.60	34.30	9.5	1	---	---	---	---	V	1.0
19296.05*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	V	1.0
21708.09	---	36.20	19.20	34.60	9.5	1	---	---	---	---	V	1.0
24120.13	---	36.80	21.00	34.20	9.5	1	---	---	---	---	V	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark "----" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extrea plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11b mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 28 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2437MHz (CH 6)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2435.77	106.25	31.76	2.42	35.32	9.5	0	95.62	Fundamental frequency		P	H	1.0
2435.77	103.58	31.76	2.42	35.32	9.5	0	92.95			A	H	1.0
4873.81	42.36	34.77	2.80	35.40	9.5	1	36.03	74	-37.97	P	H	1.0
4873.81	30.89	34.77	2.80	35.40	9.5	1	24.56	54	-29.44	A	H	1.0
7311.62	40.26	39.78	4.00	35.57	9.5	1	39.97	74	-34.03	P	H	1.0
7311.62	29.46	39.78	4.00	35.57	9.5	1	29.17	54	-24.83	A	H	1.0
9747.83	41.37	38.53	4.02	35.72	9.5	1	39.69	74	-34.31	P	H	1.0
9747.83	29.73	38.53	4.02	35.72	9.5	1	28.05	54	-25.95	A	H	1.0
12185.10*	---	32.14	4.53	35.24	9.5	1	---	---	---	---	H	1.0
14622.12	---	43.40	16.80	34.00	9.5	1	---	---	---	---	H	1.0
17059.14	---	45.20	17.60	34.30	9.5	1	---	---	---	---	H	1.0
19496.16*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	H	1.0
21933.18	---	36.20	19.20	34.60	9.5	1	---	---	---	---	H	1.0
24370.2	---	36.80	21.00	34.20	9.5	1	---	---	---	---	H	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extera plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11b mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 29 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2437MHz (CH 6)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2435.77	107.09	31.76	2.42	35.32	9.5	0	96.46	Fundamental frequency		P	V	1.0
2435.77	105.37	31.76	2.42	35.32	9.5	0	94.74			A	V	1.0
4873.82	41.57	34.77	2.80	35.40	9.5	1	35.24	74	-38.76	P	V	1.0
4873.82	28.98	34.77	2.80	35.40	9.5	1	22.65	54	-31.35	A	V	1.0
7311.24	40.26	39.78	4.00	35.57	9.5	1	39.97	74	-34.03	P	V	1.0
7311.24	27.93	39.78	4.00	35.57	9.5	1	27.64	54	-26.36	A	V	1.0
9747.82	42.11	38.53	4.02	35.72	9.5	1	40.43	74	-33.57	P	V	1.0
9747.82	29.51	38.53	4.02	35.72	9.5	1	27.83	54	-26.17	A	V	1.0
12185.10*	---	32.14	4.53	35.24	9.5	1	---	---	---	---	V	1.0
14622.12	---	43.40	16.80	34.00	9.5	1	---	---	---	---	V	1.0
17059.14	---	45.20	17.60	34.30	9.5	1	---	---	---	---	V	1.0
19496.16*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	V	1.0
21933.18	---	36.20	19.20	34.60	9.5	1	---	---	---	---	V	1.0
24370.20	---	36.80	21.00	34.20	9.5	1	---	---	---	---	V	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extrea plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs+Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11b mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 30 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2462MHz (CH 11)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2461.72	105.39	31.74	2.49	35.32	9.5	0	94.79	Fundamental frequency		P	H	1.0
2461.72	102.57	31.74	2.49	35.32	9.5	0	91.97			A	H	1.0
4923.84	43.16	35.10	2.83	35.41	9.5	1	37.18	74	-36.82	P	H	1.0
4923.84	33.06	35.10	2.83	35.41	9.5	1	27.08	54	-26.92	A	H	1.0
7385.71	43.67	39.75	4.06	35.57	9.5	1	43.40	74	-30.60	P	H	1.0
7385.71	32.30	39.75	4.06	35.57	9.5	1	32.03	54	-21.97	A	H	1.0
9847.99	41.16	38.52	3.93	35.77	9.5	1	39.34	74	-34.66	P	H	1.0
9847.99	30.06	38.52	3.93	35.77	9.5	1	28.24	54	-25.76	A	H	1.0
14772.06	---	43.40	16.80	34.00	9.5	1	---	---	---	---	H	1.0
17234.08	---	45.20	17.60	34.30	9.5	1	---	---	---	---	H	1.0
19696.1*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	H	1.0
22158.12*	---	36.20	19.20	34.60	9.5	1	---	---	---	---	H	1.0
24620.14	---	36.80	21.00	34.20	9.5	1	---	---	---	---	H	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs+Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11b mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 31 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2462MHz (CH 11)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2461.44	114.25	31.74	2.49	35.32	9.5	0	103.65	Fundamental frequency		P	V	1.0
2461.44	113.52	31.74	2.49	35.32	9.5	0	102.92			A	V	1.0
4923.81	47.13	35.10	2.83	35.41	9.5	1	41.15	74	-32.85	P	V	1.0
4923.81	39.41	35.10	2.83	35.41	9.5	1	33.43	54	-20.57	A	V	1.0
7385.62	47.48	39.75	4.06	35.57	9.5	1	47.21	74	-26.79	P	V	1.0
7385.62	36.89	39.75	4.06	35.57	9.5	1	36.62	54	-17.38	A	V	1.0
9847.64	42.02	38.52	3.93	35.77	9.5	1	40.20	74	-33.80	P	V	1.0
9847.64	30.82	38.52	3.93	35.77	9.5	1	29.00	54	-25.00	A	V	1.0
12310.04*	---	32.14	4.53	35.24	9.5	1	---	---	---	---	V	1.0
14772.06	---	43.40	16.80	34.00	9.5	1	---	---	---	---	V	1.0
17234.08	---	45.20	17.60	34.30	9.5	1	---	---	---	---	V	1.0
19696.1*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	V	1.0
22158.12*	---	36.20	19.20	34.60	9.5	1	---	---	---	---	V	1.0
24620.14	---	36.80	21.00	34.20	9.5	1	---	---	---	---	V	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11b mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 32 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2412MHz (CH 1)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	(dB)	(P/Q/A)	(H/V)	(Meter)
2411.61	102.18	31.79	2.36	35.31	9.5	0	91.51	Fundamental frequency		P	H	1.0
2411.61	100.45	31.79	2.36	35.31	9.5	0	89.78			A	H	1.0
4823.05	40.45	34.43	2.77	35.38	9.5	1	33.77	74	-40.23	P	H	1.0
4823.05	28.49	34.43	2.77	35.38	9.5	1	21.81	54	-32.19	A	H	1.0
7235.29	39.10	39.81	3.94	35.56	9.5	1	38.79	74	-35.21	P	H	1.0
7235.29	27.42	39.81	3.94	35.56	9.5	1	27.11	54	-26.89	A	H	1.0
9647.81	41.01	38.54	4.10	35.67	9.5	1	39.47	74	-34.53	P	H	1.0
9647.81	28.84	38.54	4.10	35.67	9.5	1	27.30	54	-26.70	A	H	1.0
12059.93*	---	42.60	15.20	35.30	9.5	1	---	---	---	---	H	1.0
14471.97*	---	43.40	16.80	34.00	9.5	1	---	---	---	---	H	1.0
16884.01	---	45.20	17.60	34.30	9.5	1	---	---	---	---	H	1.0
19296.05*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	H	1.0
21708.09	---	36.20	19.20	34.60	9.5	1	---	---	---	---	H	1.0
24120.13	---	36.80	21.00	34.20	9.5	1	---	---	---	---	H	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11g mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 33 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2412MHz (CH 1)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2411.55	114.28	31.79	2.36	35.31	9.5	0	103.61	Fundamental frequency		P	V	1.0
2411.55	112.56	31.79	2.36	35.31	9.5	0	101.89			A	V	1.0
4823.11	43.74	34.43	2.77	35.38	9.5	1	37.06	74	-36.94	P	V	1.0
4823.11	29.25	34.43	2.77	35.38	9.5	1	22.57	54	-31.43	A	V	1.0
7235.38	40.12	39.81	3.94	35.56	9.5	1	39.81	74	-34.19	P	V	1.0
7235.38	29.54	39.81	3.94	35.56	9.5	1	29.23	54	-24.77	A	V	1.0
9647.73	41.96	38.54	4.10	35.67	9.5	1	40.42	74	-33.58	P	V	1.0
9647.73	29.07	38.54	4.10	35.67	9.5	1	27.53	54	-26.47	A	V	1.0
12059.93*	---	42.60	15.20	35.30	9.5	1	---	---	---	---	V	1.0
14471.97*	---	43.40	16.80	34.00	9.5	1	---	---	---	---	V	1.0
16884.01	---	45.20	17.60	34.30	9.5	1	---	---	---	---	V	1.0
19296.05*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	V	1.0
21708.09	---	36.20	19.20	34.60	9.5	1	---	---	---	---	V	1.0
24120.13	---	36.80	21.00	34.20	9.5	1	---	---	---	---	V	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extrea plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11g mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 34 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2437MHz (CH 6)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2435.77	100.75	31.76	2.42	35.32	9.5	0	90.12	Fundamental frequency		P	H	1.0
2435.77	96.67	31.76	2.42	35.32	9.5	0	86.04			A	H	1.0
4873.81	41.55	34.77	2.80	35.40	9.5	1	35.22	74	-38.78	P	H	1.0
4873.81	29.28	34.77	2.80	35.40	9.5	1	22.95	54	-31.05	A	H	1.0
7311.62	40.01	39.78	4.00	35.57	9.5	1	39.72	74	-34.28	P	H	1.0
7311.62	28.85	39.78	4.00	35.57	9.5	1	28.56	54	-25.44	A	H	1.0
9747.83	40.65	38.53	4.02	35.72	9.5	1	38.97	74	-35.03	P	H	1.0
9747.83	28.95	38.53	4.02	35.72	9.5	1	27.27	54	-26.73	A	H	1.0
12185.10*	---	32.14	4.53	35.24	9.5	1	---	---	---	---	H	1.0
14622.12	---	43.40	16.80	34.00	9.5	1	---	---	---	---	H	1.0
17059.14	---	45.20	17.60	34.30	9.5	1	---	---	---	---	H	1.0
19496.16*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	H	1.0
21933.18	---	36.20	19.20	34.60	9.5	1	---	---	---	---	H	1.0
24370.20	---	36.80	21.00	34.20	9.5	1	---	---	---	---	H	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11g mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 35 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2437MHz (CH 6)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2435.77	113.50	31.76	2.42	35.32	9.5	0	102.87	Fundamental frequency		P	V	1.0
2435.77	100.13	31.76	2.42	35.32	9.5	0	89.50			A	V	1.0
4873.82	44.63	34.77	2.80	35.40	9.5	1	38.30	74	-35.70	P	V	1.0
4873.82	31.74	34.77	2.80	35.40	9.5	1	25.41	54	-28.59	A	V	1.0
7311.24	39.45	39.78	4.00	35.57	9.5	1	39.16	74	-34.84	P	V	1.0
7311.24	28.37	39.78	4.00	35.57	9.5	1	28.08	54	-25.92	A	V	1.0
9747.82	41.52	38.53	4.02	35.72	9.5	1	39.84	74	-34.16	P	V	1.0
9747.82	28.84	38.53	4.02	35.72	9.5	1	27.16	54	-26.84	A	V	1.0
12185.10*	---	32.14	4.53	35.24	9.5	1	---	---	---	---	V	1.0
14622.12	---	43.40	16.80	34.00	9.5	1	---	---	---	---	V	1.0
17059.14	---	45.20	17.60	34.30	9.5	1	---	---	---	---	V	1.0
19496.16*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	V	1.0
21933.18	---	36.20	19.20	34.60	9.5	1	---	---	---	---	V	1.0
24370.20	---	36.80	21.00	34.20	9.5	1	---	---	---	---	V	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11g mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 36 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2462MHz (CH 11)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2461.72	100.08	31.74	2.49	35.32	9.5	0	89.48	Fundamental frequency		P	H	1.0
2461.72	98.52	31.74	2.49	35.32	9.5	0	87.92			A	H	1.0
4923.84	44.35	35.10	2.83	35.41	9.5	1	38.37	74	-35.63	P	H	1.0
4923.84	31.49	35.10	2.83	35.41	9.5	1	25.51	54	-28.49	A	H	1.0
7385.71	45.91	39.75	4.06	35.57	9.5	1	45.64	74	-28.36	P	H	1.0
7385.71	30.19	39.75	4.06	35.57	9.5	1	29.92	54	-24.08	A	H	1.0
9847.99	45.93	38.52	3.93	35.77	9.5	1	44.11	74	-29.89	P	H	1.0
9847.99	30.42	38.52	3.93	35.77	9.5	1	28.60	54	-25.40	A	H	1.0
14772.06	---	43.40	16.80	34.00	9.5	1	---	---	---	---	H	1.0
17234.08	---	45.20	17.60	34.30	9.5	1	---	---	---	---	H	1.0
19696.1*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	H	1.0
22158.12*	---	36.20	19.20	34.60	9.5	1	---	---	---	---	H	1.0
24620.14	---	36.80	21.00	34.20	9.5	1	---	---	---	---	H	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11g mode
9. Test Distance : at 3M



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 37 of 57

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/28
Fundamental Frequency:	2462MHz (CH 11)	Test By:	K.P. Pang
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2461.44	111.52	31.74	2.49	35.32	9.5	0	100.92	Fundamental frequency		P	V	1.0
2461.44	108.42	31.74	2.49	35.32	9.5	0	97.82			A	V	1.0
4923.81	42.63	35.10	2.83	35.41	9.5	1	36.65	74	-37.35	P	V	1.0
4923.81	30.37	35.10	2.83	35.41	9.5	1	24.39	54	-29.61	A	V	1.0
7385.62	39.64	39.75	4.06	35.57	9.5	1	39.37	74	-34.63	P	V	1.0
7385.62	27.96	39.75	4.06	35.57	9.5	1	27.69	54	-26.31	A	V	1.0
9847.64	42.02	38.52	3.93	35.77	9.5	1	40.20	74	-33.80	P	V	1.0
9847.64	30.82	38.52	3.93	35.77	9.5	1	29.00	54	-25.00	A	V	1.0
12310.04*	---	32.14	4.53	35.24	9.5	1	---	---	---	---	V	1.0
14772.06	---	43.40	16.80	34.00	9.5	1	---	---	---	---	V	1.0
17234.08	---	45.20	17.60	34.30	9.5	1	---	---	---	---	V	1.0
19696.1*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	V	1.0
22158.12*	---	36.20	19.20	34.60	9.5	1	---	---	---	---	V	1.0
24620.14	---	36.80	21.00	34.20	9.5	1	---	---	---	---	V	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extrea plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. for wireless 802.11g mode
9. Test Distance : at 3M

3.7 Photos of Open Site





Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 39 of 57

3.7 Photos of Open Site





4. 6dB BANDWIDTH MEASUREMENT


4.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	DATE OF CALIBRATION
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	SEPT. 3, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.2 Test Setup



4.3 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is $>500\text{KHz}$

4.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 100 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 41 of 57

4.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 200\text{KHz}$.

4.6 Test Results

Input Power (System)	5VDC (From Adaptor)	Environmental Conditions	27°C, 70%RH,
Tested By	K. P. Pang		

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	7.86	0.5	PASS
6	2437	8.17	0.5	PASS
11	2462	8.11	0.5	PASS

NOTE: FOR 11Mbps(802.11b Mode)

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	8.13	0.5	PASS
6	2437	8.17	0.5	PASS
11	2462	12.82	0.5	PASS

NOTE: FOR 54Mbps(802.11g Mode)



Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414


Report No. : ER03-05-033FRF

Page 42 of 57


4.7 Photo of 6dB Bandwidth Measurement



Channel 1



Channel 6



Channel 11

NOTE: FOR 11Mbps(802.11b Mode)




Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720


FCC ID : N89-WG414

Report No. : ER03-05-033FRF


Page 43 of 57



Channel 1



Channel 6



Channel 11

NOTE: FOR 54Mbps(802.11g Mode)

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 44 of 57

5. MAXIMUM PEAK OUTPUT POWER


5.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	SEPT. 3, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A
GIGA-TRONICS Powre meter	8542	1828329	Sept.21,2002

NOTE :

1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.2 Test Setup



5.3 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 45 of 57

5.4 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency.

5.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 1.82\text{dB}$.

5.6 Test Results

Input Power (System)	5VDC (From Adaptor)	Environmental Conditions	27°C, 70%RH,
Tested By	K. P. Pang		

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
1	2412	20.52	30	PASS
6	2437	19.92	30	PASS
11	2462	19.28	30	PASS

NOTE: FOR 11Mbps(802.11b Mode)

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
1	2412	20.11	30	PASS
6	2437	19.62	30	PASS
11	2462	19.13	30	PASS

NOTE: FOR 54Mbps(802.11g Mode)



6. POWER SPECTRAL DENSITY MEASUREMENT


6.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	SEPT. 3, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

6.2 Test Setup



6.3 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

6.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3KHz RBW and 30KHz VBW, set sweep time=span / 3KHz.

The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.

6.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 1.82\text{dB}$.

Input Power (System)	5VDC (From Adaptor)	Environmental Conditions	27°C, 70%RH,
Tested By	K. P. Pang		

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
1	2412	3.78	8	PASS
6	2437	2.94	8	PASS
11	2462	2.46	8	PASS

NOTE: 1.FOR 11Mbps(802.11b Mode)

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
1	2412	0.33	8	PASS
6	2437	0.38	8	PASS
11	2462	-0.43	8	PASS

NOTE: 1.FOR 54Mbps(802.11g Mode)

2.The measurement value of RF Power Level + 10dB attenuator=Final RF Power Level



Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414


Report No. : ER03-05-033FRF

Page 48 of 57


6.7 Photo of Power Spectral Density Measurement



Channel 1



Channel 6



Channel 11

NOTE: FOR 11Mbps(802.11b Mode)




Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720


FCC ID : N89-WG414

Report No. : ER03-05-033FRF


Page 49 of 57



Channel 1



Channel 6



Channel 11

NOTE: FOR 54Mbps(802.11g Mode)



7. OUT OF BAND MEASUREMENT


7.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	SEPT. 3, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

3. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
4. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

7.2 Test Setup



7.3 Limits of Out of Band Emissions Measurement

1. Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 51 of 57

7.4 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100KHz with suitable frequency span including 100KHz bandwidth from band edge. The band edges were measured and recorded.

7.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 1.82 dB.

7.6 Test Results

A. Conducted

Refer to 7.7 photo of out band Emission measurement

B. Radiated

NOTE1: FOR 11Mbps(802.11b Mode)

NOTE2: The band edge emission plot on the following first figure shows 53.19 dBuV/m delta between carrier maximum power and local maximum emission in restrict band (2.3201GHz). The emission of carrier strength list in the test result of channel 1 at the item 3.6 is 102.54 dBuV/m, so the maximum field strength in restrict band is $102.54 - 53.19 = 49.35$ dBuV/m which is under 54 dBuV/m limit.

NOTE3: The band edge emission plot on the following second figure shows 57.09 dBuV/m delta between carrier maximum power and local maximum emission in restrict band (2.4839GHz). The emission of carrier strength list in the test result of channel 11 at the item 3.6 is 102.92 dBuV/m, so the maximum field strength in restrict band is $102.92 - 57.09 = 45.83$ dBuV/m which is under 54 dBuV/m limit.

Input Power (System)	5VDC (From Adaptor)	Environmental Conditions	27°C, 70%RH,
Tested By	K. P. Pang		

Channel Frequency (MHz)	Required Limit (dBc)	Pass / Fail
<2400	>20	PASS
>2483.5	>20	PASS

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414

Report No. : ER03-05-033FRF

Page 52 of 57**B. Radiated**

NOTE1: FOR 54Mbps(802.11gMode)

NOTE1: The band edge emission plot on the following first figure shows 50.18 dBuV/m delta between carrier maximum power and local maximum emission in restrict band (2.3206GHz) The emission of carrier strength list in the test result of channel 1 at the item 3.6 is 101.89 dBuV/m, so the maximum field strength in restrict band is $101.89 - 50.18 = 51.71$ dBuV/m which is under 54 dBuV/m limit.

NOTE2: The band edge emission plot on the following second figure shows 49.19 dBuV/m delta between carrier maximum power and local maximum emission in restrict band (2.4887GHz) The emission of carrier strength list in the test result of channel 11 at the item 3.6 is 97.82 dBuV/m, so the maximum field strength in restrict band is $97.82 - 49.19 = 48.63$ dBuV/m which is under 54 dBuV/m limit.

Input Power (System)	5VDC (From Adaptor)	Environmental Conditions	27°C, 70%RH,
Tested By	K. P. Pang		

Channel Frequency (MHz)	Required Limit (dBc)	Pass / Fail
<2400	>20	PASS
>2483.5	>20	PASS



Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414


Report No. : ER03-05-033FRF

Page 53 of 57

7.7 Photo of Out of Band Measurement



FRONT



BACK

NOTE: FOR 11Mbps(802.11b Mode)



Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : N89-WG414


Report No. : ER03-05-033FRF

Page 54 of 57

7.7 Photo of Out of Band Measurement



FRONT



BACK

NOTE: FOR 54Mbps(802.11g Mode)



8. ANTENNA REQUIREMENT

8.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.2 Antenna Connected Construction

The antenna used in this product is dipole antenna. The dipole antenna connector is MMCX And the maximum Gain of this antenna is only 2dBi.



9. RF EXPOSURE EVALUATION

According to FCC 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational / Control Exposures				
300-1,500	--	--	F/300	6
1,500-100,000	--	--	5	6
(B) Limits for General Population / Uncontrol Exposures				
300-1,500	--	--	F/1500	6
1,500-100,000	--	--	1	30

9.1 Friis Formula

Friis transmission formula : $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

9.2 EUT Operating Condition

A software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



9.3 Test Result of Rf Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

9.3.1 Antenna Gain

Antenna Gain : The maximum Gain measured in fully anechoic chamber is 2dBi linear scale.

9.3.2 Output Power into Antenna & RF Exposure Evaluation Distance

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power density in mW/cm ² at Friis formula when r=20cm(mW/cm ²)	LIMITS
CH1	2412.00	18.52	0.022425	1
CH6	2437.00	17.92	0.019531	1
CH11	2462.00	17.28	0.016855	1

NOTE1: FOR 11Mbps(802.11b Mode)

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power density in mW/cm ² at Friis formula when r=20cm(mW/cm ²)	LIMITS
CH1	2412.00	18.11	0.020405	1
CH6	2437.00	17.62	0.018228	1
CH11	2462.00	17.13	0.016283	1

NOTE1: FOR 54 Mbps (802.11g Mode)

The power density Pd (4th column) at a distance of 20cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm². So, RF exposure limit warning or SAR test are not required.