

FCC TEST REPORT

REPORT NO.: RF981211H04

MODEL NO.: WM141

RECEIVED: Dec. 11, 2009

TESTED: Dec. 11 to 31, 2009

ISSUED: Jan. 07, 2010

APPLICANT: CyberTAN Technology, Inc.

ADDRESS: No.99, Park Avenue III, Science-based
Industrial Park, Hsinchu, Taiwan 308,R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch Hsin Chu Laboratory

ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 77 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.



Table of Contents

1.	CERTIFICATION	4
2.	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	6
3.	GENERAL INFORMATION.....	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	DESCRIPTION OF TEST MODES	9
3.2.1	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	10
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	13
3.4	DESCRIPTION OF SUPPORT UNITS.....	14
3.5	CONFIGURATION OF SYSTEM UNDER TEST	14
4.	TEST TYPES AND RESULTS	15
4.1	CONDUCTED EMISSION MEASUREMENT	15
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	15
4.1.2	TEST INSTRUMENTS	15
4.1.3	TEST PROCEDURES.....	16
4.1.4	DEVIATION FROM TEST STANDARD	16
4.1.5	TEST SETUP	17
4.1.6	EUT OPERATING CONDITIONS.....	17
4.1.7	TEST RESULTS	18
4.2	RADIATED EMISSION MEASUREMENT	20
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	20
4.2.2	TEST INSTRUMENTS	21
4.2.3	TEST PROCEDURES.....	22
4.2.4	DEVIATION FROM TEST STANDARD	22
4.2.5	TEST SETUP	23
4.2.6	EUT OPERATING CONDITIONS.....	23
4.2.7	TEST RESULTS.....	24
4.3	6dB BANDWIDTH MEASUREMENT	53
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	53
4.3.2	TEST INSTRUMENTS	53
4.3.3	TEST PROCEDURE	54
4.3.4	DEVIATION FROM TEST STANDARD	54
4.3.5	TEST SETUP	54
4.3.6	EUT OPERATING CONDITIONS.....	54
4.3.7	TEST RESULTS.....	55
4.4	MAXIMUM PEAK OUTPUT POWER.....	59
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	59
4.4.2	INSTRUMENTS	59



A D T

4.4.3	TEST PROCEDURES.....	59
4.4.4	DEVIATION FROM TEST STANDARD	59
4.4.5	TEST SETUP	59
4.4.6	EUT OPERATING CONDITIONS.....	59
4.4.7	TEST RESULTS	60
4.5	POWER SPECTRAL DENSITY MEASUREMENT.....	62
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	62
4.5.2	TEST INSTRUMENTS	62
4.5.3	TEST PROCEDURE	62
4.5.4	DEVIATION FROM TEST STANDARD	62
4.5.5	TEST SETUP	62
4.5.6	EUT OPERATING CONDITION	62
4.5.7	TEST RESULTS.....	63
4.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT	67
4.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT	67
4.6.2	TEST INSTRUMENTS	67
4.6.3	TEST PROCEDURE	67
4.6.4	DEVIATION FROM TEST STANDARD	67
4.6.5	EUT OPERATING CONDITION	67
4.6.6	TEST RESULTS.....	67
5.	INFORMATION ON THE TESTING LABORATORIES.....	76
6.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	77

1. CERTIFICATION

PRODUCT: 2.4GHz Draft 802.11n 2*2 miniCard Module
BRAND NAME: Cisco
MODEL NO.: WM141
TEST SAMPLE: ENGINEERING SAMPLE
TESTED: Dec. 11 to 31, 2009
APPLICANT: CyberTAN Technology, Inc.
STANDARDS: FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment (Model: WM141) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** Jan. 07, 2010
(Claire Kuan, Specialist)

TECHNICAL ACCEPTANCE :  , **DATE:** Jan. 07, 2010
(Hank Chung, Deputy Manager)

APPROVED BY :  , **DATE:** Jan. 07, 2010
(May Chen, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.247)			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -9.63dB at 3.897MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -3.0dB at 2390.00MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Conducted Out-Band Emission Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.44 dB
Radiated emissions (30MHz-1GHz)	3.94 dB
Radiated emissions (1GHz -18GHz)	2.49 dB
Radiated emissions (18GHz -40GHz)	2.70 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	2.4GHz Draft 802.11n 2*2 miniCard Module
MODEL NO.	WM141
FCC ID	N89- WM141
POWER SUPPLY	DC 3.3V from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11 / 5.5 / 2 / 1Mbps 802.11g: 54 / 48 / 36 / 24 / 18 / 12 / 9 / 6Mbps 802.11n HT20 (800ns GI): 130 / 117 / 104 / 78 / 52 / 39 / 26 / 13 / 65 / 58.5 / 52 / 39 / 26 / 19.5 / 13 / 6.5Mbps 802.11n HT40 (800ns GI): 270 / 243 / 216 / 162 / 108 / 81 / 54 / 27 / 135 / 121.5 / 108 / 81 / 54 / 40.5 / 27 / 13.5Mbps
FREQUENCY RANGE	2412 ~ 2462MHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz)
MAXIMUM OUTPUT POWER	802.11b: 75.9mW 802.11g: 120.2mW 802.11n (20MHz): 239.0mW 802.11n (40MHz): 137.5mW
ANTENNA TYPE	Please see note 1
ANTENNA CONNECTOR	Please see note 1
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

1. There are two antennas provided to this EUT, please refer to the following table:

Chain	Gain (dBi)	Antenna Type	Connector
Chain (0)	1.8	Dipole	I-PEX MHF
Chain (1)	1.8	Dipole	I-PEX MHF

2. The EUT incorporates a MIMO function with 802.11n. Physically, the EUT provides two completed transmitters and two completed receivers.
3. The EUT is 2 * 2 spatial MIMO (2Tx & 2Rx) without beam forming function. The antenna configurations are two transmitter antennas and two receiver antennas, as there are 2 Dipole antennas. Spatial multiplexing modes for simultaneous transmission using 2 antennas, and for simultaneous receiver using 2 antennas.
4. The EUT complies with 802.11n standards and backwards compatible with 802.11b, 802.11g products.
5. The above EUT information was declared by manufacturer and for more detailed feature descriptions, please refer to the manufacturer's specifications or user's manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

Eleven channels are provided for 802.11b, 802.11g, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

Seven channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2422MHz	5	2442MHz
2	2427MHz	6	2447MHz
3	2432MHz	7	2452MHz
4	2437MHz		

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	APCM	
-	√	√	√	√	-

Where **PLC**: Power Line Conducted Emission

RE < 1G: Radiated Emission below 1GHz

RE ≥ 1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

ANTENNA COMBINATION MODE:

COMBINATION MODE	OPERATION MODE	TX CHAIN(0)	TX CHAIN(1)
A	802.11 b	√	
B	802.11 g	√	
C	802.11n(20MHz) for MCS0~15	√	√
D	802.11n(40MHz) for MCS0~15	√	√

Note:

- The above information was declared by manufacturer and for more detailed feature descriptions, please refer to the manufacturer's specifications or user's manual.

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX COMBINATION
802.11n (20MHz)	1 to 11	6	OFDM	BPSK	6.5	C

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX COMBINATION
802.11n (20MHz)	1 to 11	6	OFDM	BPSK	6.5	C

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX COMBINATION
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	B
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	C
802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	13	D

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX COMBINATION
802.11b	1 to 11	1, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 11	OFDM	BPSK	6	B
802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5	C
802.11n (40MHz)	1 to 7	1, 7	OFDM	BPSK	13	D

✧ After verification, conducted out band emission as show worst chain in report by investigations.

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX COMBINATION
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	B
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	C
802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	13	D

※ After verification, bandwidth as show worst chain in report by investigations.

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE ³ 1G	16deg. C, 63%RH, 1024 hPa	120Vac, 60Hz	Phoenix Huang
RE<1G	29deg. C, 66%RH, 1024 hPa	120Vac, 60Hz	Kent Liu
PLC	25deg. C, 60%RH, 1024 hPa	120Vac, 60Hz	Phoenix Huang
APCM	22deg. C, 62%RH, 1024 hPa	120Vac, 60Hz	Leo Peng

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a 2.4GHz Draft 802.11n 2*2 miniCard Module. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)
ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP19L	CN-OHC416-70166-5CA-0448	PIW632500516610
2	TEST TOOL	Cisco	NA	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA

NOTE: All power cords of the above support units are non shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST



4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	100287	Mar. 05, 2009	Mar. 04, 2010
Line-Impedance Stabilization Network (for EUT)	NSLK 8127	8127-523	Sep. 23, 2009	Sep. 22, 2010
Line-Impedance Stabilization Network (for Peripheral)	KNW-407	8-1395-12	May 04, 2009	May 03, 2010
RF Cable (JYEBAO)	5DFB	COACAB-001	Dec. 14, 2009	Dec. 13, 2010
50 ohms Terminator	50	3	Oct. 28, 2009	Oct. 27, 2010
Software	BV ADT_Cond_V7.3.7	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. A.
3. The VCCI Con A Registration No. is C-817.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- Connect the EUT with the support unit 1 (Notebook Computer) which placed on a testing table.
- The communication partner run test program “V0_9_b7_ar928x(art.exe)” to enable EUT under transmission/receiving condition continuously at specific channel frequency.


4.1.7 TEST RESULTS

DRAFT 802.11n (20MHz) OFDM MODULATION:

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.04	51.93	-	51.97	-	64.79	54.79	-12.82	-
2	0.228	0.04	46.54	-	46.58	-	62.52	52.52	-15.94	-
3	0.287	0.05	42.01	-	42.06	-	60.62	50.62	-18.56	-
4	1.776	0.11	40.03	-	40.14	-	56.00	46.00	-15.86	-
5	2.005	0.12	40.83	-	40.95	-	56.00	46.00	-15.05	-
6	3.897	0.20	46.17	32.72	46.37	32.92	56.00	46.00	-9.63	-13.08


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.172	0.05	51.89	-	51.94	-	64.87	54.87	-12.93	-
2	0.287	0.06	40.39	-	40.45	-	60.62	50.62	-20.17	-
3	0.744	0.09	33.25	-	33.34	-	56.00	46.00	-22.66	-
4	1.258	0.11	34.56	-	34.67	-	56.00	46.00	-21.33	-
5	2.063	0.13	39.33	-	39.46	-	56.00	46.00	-16.54	-
6	3.836	0.21	45.96	33.88	46.17	34.09	56.00	46.00	-9.83	-11.91

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ Spectrum Analyzer	FSP40	100036	Dec. 18, 2009	Dec. 17, 2010
Agilent PSA Spectrum Analyzer	E4446A	MY46180622	Apr. 24 , 2009	Apr. 23 , 2010
HP Pre_Amplifier	8449B	300801923	Nov. 02, 2009	Nov. 01, 2010
ROHDE & SCHWARZ Test Receiver	ESCS30	847124/029	Aug. 28, 2009	Aug. 27, 2010
SCHWARZBECK TRILOG Broadband Antenna	VULB 9168	138	April 29, 2009	April 28, 2010
Schwarzbeck Horn_Antenna	BBHA9120	D124	Dec. 18, 2009	Dec. 17, 2010
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 22, 2009	Jan. 21, 2010
R&S Loop Antenna	HFH2-Z2	100070	Jan. 14, 2008	Jan. 13, 2010
RF Switches	EMH-011	1001	NA	NA
RF CABLE (Chaintek)	Sucoflex 106	28077	Aug. 14, 2009	Aug. 13, 2010
RF Cable	8DFB	STCCAB-30M-1GHz	NA	NA
Software	ADT_Radiated_V7.6.15.9.2	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, HP preamplifier (model: 8449B) and Spectrum Analyzer (model: FSP40) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 7450G-3.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as the 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA : DRAFT 802.11n (20MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	29deg. C, 66%RH 1024 hPa	TESTED BY	Kent Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	120.00	24.9 QP	43.50	-18.6	1.54 H	19	12.97	11.95
2	144.00	30.0 QP	43.50	-13.5	1.90 H	237	15.47	14.55
3	199.37	35.2 QP	43.50	-8.3	1.33 H	21	23.32	11.90
4	299.99	34.7 QP	46.00	-11.3	1.00 H	157	18.69	16.01
5	383.99	26.9 QP	46.00	-19.1	1.07 H	122	8.79	18.13
6	719.98	32.8 QP	46.00	-13.2	1.00 H	252	7.57	25.22
7	863.98	34.2 QP	46.00	-11.9	1.18 H	111	6.56	27.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	120.17	17.7 QP	43.50	-25.8	1.05 V	142	5.72	11.97
2	199.95	24.9 QP	43.50	-18.6	1.00 V	95	13.01	11.86
3	299.99	29.3 QP	46.00	-16.7	1.00 V	315	13.28	16.01
4	374.99	28.7 QP	46.00	-17.4	1.47 V	220	10.75	17.90
5	449.99	29.8 QP	46.00	-16.2	1.00 V	241	9.87	19.89
6	863.98	36.3 QP	46.00	-9.7	1.00 V	200	8.75	27.59
7	911.97	36.7 QP	46.00	-9.3	1.07 V	189	8.44	28.29

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

ABOVE 1GHz WORST-CASE DATA

802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2389.87	57.6 PK	74.00	-16.4	1.47 H	239	27.55	30.06
2	2389.87	43.6 AV	54.00	-10.4	1.47 H	239	13.51	30.06
3	*2412.00	97.3 PK			1.48 H	240	67.12	30.15
4	*2412.00	93.7 AV			1.48 H	240	63.56	30.15
5	4824.00	53.7 PK	74.00	-20.3	1.42 H	98	18.26	35.46
6	4824.00	49.8 AV	54.00	-4.2	1.42 H	98	14.34	35.46
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	58.3 PK	74.00	-15.7	1.44 V	91	28.64	29.66
2	2288.00	46.9 AV	54.00	-7.1	1.44 V	91	17.28	29.66
3	2390.00	59.8 PK	74.00	-14.2	1.36 V	72	29.78	30.06
4	2390.00	48.2 AV	54.00	-5.8	1.36 V	72	18.17	30.06
5	*2412.00	106.4 PK			1.33 V	72	76.20	30.15
6	*2412.00	103.9 AV			1.33 V	72	73.71	30.15
7	4824.00	53.9 PK	74.00	-20.1	1.42 V	60	18.44	35.46
8	4824.00	50.6 AV	54.00	-3.4	1.42 V	60	15.14	35.46

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	97.1 PK			1.44 H	245	66.86	30.24
2	*2437.00	93.4 AV			1.44 H	245	63.16	30.24
3	4874.00	52.9 PK	74.00	-21.1	1.48 H	92	17.35	35.55
4	4874.00	49.8 AV	54.00	-4.3	1.48 H	92	14.20	35.55
5	7311.00	51.1 PK	74.00	-22.9	1.30 H	67	9.04	42.04
6	7311.00	38.2 AV	54.00	-15.8	1.30 H	67	-3.80	42.04
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	60.1 PK	74.00	-13.9	1.39 V	92	30.44	29.66
2	2288.00	50.2 AV	54.00	-3.8	1.39 V	92	20.54	29.66
3	*2437.00	107.3 PK			1.30 V	72	77.06	30.24
4	*2437.00	104.7 AV			1.30 V	72	74.46	30.24
5	4874.00	51.0 PK	74.00	-23.0	1.15 V	315	15.42	35.55
6	4874.00	47.3 AV	54.00	-6.7	1.15 V	315	11.75	35.55
7	7311.00	50.6 PK	74.00	-23.4	1.30 V	130	8.60	42.04
8	7311.00	38.2 AV	54.00	-15.8	1.30 V	130	-3.82	42.04

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	96.4 PK			1.29 H	123	66.06	30.34
2	*2462.00	92.8 AV			1.29 H	123	62.46	30.34
3	2483.50	57.7 PK	74.00	-16.3	1.26 H	126	27.23	30.43
4	2483.50	43.7 AV	54.00	-10.3	1.26 H	126	13.27	30.43
5	4924.00	50.3 PK	74.00	-23.7	1.70 H	89	14.66	35.63
6	4924.00	45.9 AV	54.00	-8.1	1.70 H	89	10.24	35.63
7	7386.00	50.6 PK	74.00	-23.4	1.31 H	69	8.37	42.23
8	7386.00	38.4 AV	54.00	-15.6	1.31 H	69	-3.83	42.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	58.9 PK	74.00	-15.1	1.38 V	92	29.24	29.66
2	2288.00	49.9 AV	54.00	-4.1	1.38 V	92	20.24	29.66
3	*2462.00	107.2 PK			1.45 V	233	76.88	30.34
4	*2462.00	104.8 AV			1.45 V	233	74.48	30.34
5	2483.50	59.9 PK	74.00	-14.2	1.14 V	230	29.42	30.43
6	2483.50	50.0 AV	54.00	-4.0	1.14 V	230	19.59	30.43
7	4924.00	50.3 PK	74.00	-23.7	1.21 V	97	14.67	35.63
8	4924.00	46.0 AV	54.00	-8.0	1.21 V	97	10.37	35.63
9	7386.00	50.1 PK	74.00	-23.9	1.25 V	103	7.87	42.23
10	7386.00	39.0 AV	54.00	-15.0	1.25 V	103	-3.23	42.23

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



RESTRICTED BANDEDGE (802.11b MODE,CH1, HORIZONTAL)





RESTRICTED BANDEDGE (802.11b MODE,CH1, VERTICAL)



RESTRICTED BANDEDGE (802.11b MODE,CH11, HORIZONTAL)



RESTRICTED BANDEDGE (802.11b MODE,CH11, VERTICAL)



802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.9 PK	74.00	-9.1	1.08 H	64	34.82	30.06
2	2390.00	47.7 AV	54.00	-6.3	1.08 H	64	17.60	30.06
3	*2412.00	95.3 PK			1.07 H	69	65.15	30.15
4	*2412.00	84.2 AV			1.07 H	69	54.05	30.15
5	4824.00	47.9 PK	74.00	-26.1	1.32 H	64	12.44	35.46
6	4824.00	35.3 AV	54.00	-18.7	1.32 H	64	-0.16	35.46
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	58.2 PK	74.00	-15.8	1.44 V	91	28.54	29.66
2	2288.00	45.9 AV	54.00	-8.1	1.44 V	91	16.24	29.66
3	2390.00	67.4 PK	74.00	-6.6	1.30 V	94	37.36	30.06
4	2390.00	51.0 AV	54.00	-3.1	1.30 V	94	20.89	30.06
5	*2412.00	106.8 PK			1.29 V	95	76.68	30.15
6	*2412.00	96.5 AV			1.29 V	95	66.39	30.15
7	4824.00	47.6 PK	74.00	-26.4	1.37 V	56	12.14	35.46
8	4824.00	35.2 AV	54.00	-18.8	1.37 V	56	-0.26	35.46

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	98.2 PK			1.04 H	72	67.96	30.24
2	*2437.00	88.4 AV			1.04 H	72	58.16	30.24
3	4874.00	47.8 PK	74.00	-26.2	1.23 H	94	12.26	35.55
4	4874.00	34.5 AV	54.00	-19.5	1.23 H	94	-1.09	35.55
5	7311.00	50.6 PK	74.00	-23.4	1.23 H	245	8.53	42.04
6	7311.00	38.1 AV	54.00	-15.9	1.23 H	245	-3.96	42.04
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	60.2 PK	74.00	-13.8	1.38 V	105	30.54	29.66
2	2288.00	49.6 AV	54.00	-4.4	1.38 V	105	19.94	29.66
3	2390.00	55.7 PK	74.00	-18.3	1.66 V	0	25.61	30.06
4	2390.00	45.4 AV	54.00	-8.6	1.66 V	0	15.35	30.06
5	*2437.00	106.4 PK			1.52 V	205	76.15	30.24
6	*2437.00	96.6 AV			1.52 V	205	66.32	30.24
7	2483.50	54.5 PK	74.00	-19.5	1.66 V	241	24.04	30.43
8	2483.50	43.5 AV	54.00	-10.5	1.66 V	241	13.05	30.43
9	4874.00	48.2 PK	74.00	-25.8	1.47 V	54	12.65	35.55
10	4874.00	35.7 AV	54.00	-18.3	1.47 V	54	0.15	35.55
11	7311.00	50.7 PK	74.00	-23.3	1.32 V	69	8.70	42.04
12	7311.00	38.3 AV	54.00	-15.7	1.32 V	69	-3.74	42.04

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	95.1 PK			1.02 H	66	64.76	30.34
2	*2462.00	83.7 AV			1.02 H	66	53.36	30.34
3	2483.50	60.0 PK	74.00	-14.0	1.03 H	72	29.59	30.43
4	2483.50	44.3 AV	54.00	-9.7	1.03 H	72	13.90	30.43
5	4924.00	47.1 PK	74.00	-26.9	1.26 H	83	11.47	35.63
6	4924.00	34.2 AV	54.00	-19.8	1.26 H	83	-1.43	35.63
7	7386.00	50.6 PK	74.00	-23.4	1.29 H	249	8.37	42.23
8	7386.00	38.1 AV	54.00	-15.9	1.29 H	249	-4.13	42.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	59.2 PK	74.00	-14.8	1.41 V	92	29.54	29.66
2	2288.00	49.7 AV	54.00	-4.3	1.41 V	92	20.04	29.66
3	*2462.00	104.9 PK			1.29 V	83	74.58	30.34
4	*2462.00	95.5 AV			1.29 V	83	65.13	30.34
5	2483.50	69.2 PK	74.00	-4.8	1.22 V	70	38.78	30.43
6	2483.50	50.1 AV	54.00	-3.9	1.22 V	70	19.71	30.43
7	4924.00	47.3 PK	74.00	-26.7	1.35 V	117	11.67	35.63
8	4924.00	34.6 AV	54.00	-19.4	1.35 V	117	-1.03	35.63
9	7386.00	50.4 PK	74.00	-23.6	1.29 V	126	8.17	42.23
10	7386.00	38.1 AV	54.00	-15.9	1.29 V	126	-4.13	42.23

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.


RESTRICTED BANDEDGE (802.11g MODE,CH1, HORIZONTAL)





RESTRICTED BANDEDGE (802.11g MODE,CH1, VERTICAL)



Report No.: RF981211H04



RESTRICTED BANDEDGE (802.11g MODE,CH11, VERTICAL)



DRAFT 802.11n (20MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.4 PK	74.00	-14.6	1.04 H	69	29.38	30.06
2	2390.00	45.4 AV	54.00	-8.6	1.04 H	69	15.38	30.06
3	*2412.00	95.6 PK			1.08 H	72	65.45	30.15
4	*2412.00	84.5 AV			1.08 H	72	54.35	30.15
5	4824.00	47.3 PK	74.00	-26.7	1.36 H	59	11.84	35.46
6	4824.00	34.5 AV	54.00	-19.5	1.36 H	59	-0.96	35.46
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	57.6 PK	74.00	-16.4	1.45 V	93	27.98	29.66
2	2288.00	45.3 AV	54.00	-8.7	1.45 V	93	15.66	29.66
3	2390.00	69.9 PK	74.00	-4.1	1.32 V	334	39.86	30.06
4	2390.00	50.7 AV	54.00	-3.3	1.32 V	334	20.64	30.06
5	*2412.00	107.6 PK			1.34 V	267	77.47	30.15
6	*2412.00	96.6 AV			1.34 V	267	66.45	30.15
7	4824.00	47.1 PK	74.00	-26.9	1.32 V	64	11.64	35.46
8	4824.00	34.6 AV	54.00	-19.4	1.32 V	64	-0.86	35.46

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	99.3 PK			1.04 H	68	69.06	30.24
2	*2437.00	89.2 AV			1.04 H	68	58.96	30.24
3	4874.00	58.7 PK	74.00	-15.3	1.34 H	76	23.13	35.55
4	4874.00	45.1 AV	54.00	-8.9	1.34 H	76	9.53	35.55
5	7311.00	54.6 PK	74.00	-19.4	1.21 H	240	12.56	42.04
6	7311.00	44.0 AV	54.00	-10.0	1.21 H	240	1.96	42.04
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	60.3 PK	74.00	-13.7	1.40 V	91	30.64	29.66
2	2288.00	50.4 AV	54.00	-3.6	1.40 V	91	20.74	29.66
3	2390.00	59.9 PK	74.00	-14.1	1.31 V	295	29.83	30.06
4	2390.00	49.6 AV	54.00	-4.5	1.31 V	295	19.49	30.06
5	*2437.00	111.7 PK			1.31 V	224	81.45	30.24
6	*2437.00	101.3 AV			1.31 V	224	71.10	30.24
7	2483.50	59.3 PK	74.00	-14.7	1.28 V	274	28.85	30.43
8	2483.50	47.1 AV	54.00	-6.9	1.28 V	274	16.63	30.43
9	4874.00	63.3 PK	74.00	-10.7	1.30 V	177	27.73	35.55
10	4874.00	50.0 AV	54.00	-4.0	1.30 V	177	14.49	35.55
11	7311.00	54.3 PK	74.00	-19.7	1.30 V	0	12.27	42.04
12	7311.00	44.4 AV	54.00	-9.6	1.30 V	0	2.36	42.04

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	94.7 PK			1.04 H	69	64.36	30.34
2	*2462.00	83.2 AV			1.04 H	69	52.86	30.34
3	2483.50	61.7 PK	74.00	-12.3	1.01 H	72	31.30	30.43
4	2483.50	46.1 AV	54.00	-7.9	1.01 H	72	15.67	30.43
5	4924.00	47.2 PK	74.00	-26.8	1.27 H	69	11.57	35.63
6	4924.00	34.1 AV	54.00	-19.9	1.27 H	69	-1.53	35.63
7	7386.00	55.7 PK	74.00	-18.3	1.29 H	244	13.47	42.23
8	7386.00	46.0 AV	54.00	-8.0	1.29 H	244	3.77	42.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	58.5 PK	74.00	-15.5	1.40 V	95	28.87	29.66
2	2288.00	49.4 AV	54.00	-4.6	1.40 V	95	19.78	29.66
3	*2462.00	106.3 PK			1.27 V	254	75.96	30.34
4	*2462.00	95.2 AV			1.27 V	254	64.86	30.34
5	2483.50	70.5 PK	74.00	-3.5	1.49 V	100	40.07	30.43
6	2483.50	50.7 AV	54.00	-3.3	1.49 V	100	20.28	30.43
7	4924.00	49.7 PK	74.00	-24.3	1.35 V	84	14.07	35.63
8	4924.00	34.5 AV	54.00	-19.5	1.35 V	84	-1.13	35.63
9	7386.00	54.7 PK	74.00	-19.3	1.31 V	29	12.47	42.23
10	7386.00	45.3 AV	54.00	-8.7	1.31 V	29	3.07	42.23

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, HORIZONTAL)





RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, VERTICAL)



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, HORIZONTAL)



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, VERTICAL)



DRAFT 802.11n (40MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.4 PK	74.00	-12.6	1.00 H	147	31.38	30.06
2	2390.00	46.9 AV	54.00	-7.1	1.00 H	147	16.82	30.06
3	*2422.00	102.4 PK			1.36 H	267	72.18	30.19
4	*2422.00	90.3 AV			1.36 H	267	60.13	30.19
5	4844.00	46.2 PK	74.00	-27.8	1.21 H	57	10.70	35.50
6	4844.00	33.6 AV	54.00	-20.4	1.21 H	57	-1.90	35.50
7	7266.00	50.5 PK	74.00	-23.5	1.21 H	235	8.57	41.93
8	7266.00	38.4 AV	54.00	-15.6	1.21 H	235	-3.53	41.93
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	58.1 PK	74.00	-15.9	1.45 V	89	28.44	29.66
2	2288.00	45.8 AV	54.00	-8.2	1.45 V	89	16.14	29.66
3	2390.00	70.5 PK	74.00	-3.5	1.35 V	195	40.43	30.06
4	2390.00	49.4 AV	54.00	-4.6	1.35 V	195	19.35	30.06
5	*2422.00	102.4 PK			1.36 V	267	72.18	30.19
6	*2422.00	90.3 AV			1.36 V	267	60.13	30.19
7	4844.00	46.4 PK	74.00	-27.6	1.26 V	120	10.90	35.50
8	4844.00	32.1 AV	54.00	-21.9	1.26 V	120	-3.40	35.50
9	7266.00	50.7 PK	74.00	-23.3	1.25 V	123	8.77	41.93
10	7266.00	38.6 AV	54.00	-15.4	1.25 V	123	-3.33	41.93

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 4	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	95.7 PK			1.00 H	155	65.46	30.24
2	*2437.00	85.6 AV			1.00 H	155	55.36	30.24
3	4874.00	46.4 PK	74.00	-27.6	1.26 H	66	10.85	35.55
4	4874.00	33.5 AV	54.00	-20.5	1.26 H	66	-2.05	35.55
5	7311.00	50.4 PK	74.00	-23.6	1.20 H	233	8.36	42.04
6	7311.00	38.1 AV	54.00	-15.9	1.20 H	233	-3.94	42.04
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	59.8 PK	74.00	-14.2	1.40 V	110	30.14	29.66
2	2288.00	49.2 AV	54.00	-4.8	1.40 V	110	19.54	29.66
3	2390.00	69.7 PK	74.00	-4.3	1.29 V	77	39.60	30.06
4	2390.00	51.0 AV	54.00	-3.0	1.29 V	77	20.92	30.06
5	*2437.00	105.0 PK			1.24 V	162	74.72	30.24
6	*2437.00	93.3 AV			1.24 V	162	63.02	30.24
7	2483.50	69.3 PK	74.00	-4.7	1.24 V	178	38.83	30.43
8	2483.50	50.1 AV	54.00	-3.9	1.24 V	178	19.63	30.43
9	4874.00	46.8 PK	74.00	-27.2	1.27 V	119	11.25	35.55
10	4874.00	32.7 AV	54.00	-21.3	1.27 V	119	-2.85	35.55
11	7311.00	50.9 PK	74.00	-23.1	1.26 V	124	8.86	42.04
12	7311.00	38.7 AV	54.00	-15.3	1.26 V	124	-3.34	42.04



REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 7	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 63%RH 1024 hPa	TESTED BY	Phoenix Huang



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	92.4 PK			1.00 H	156	62.10	30.30
2	*2452.00	82.9 AV			1.00 H	156	52.60	30.30
3	2483.50	62.6 PK	74.00	-11.4	1.00 H	151	32.20	30.43
4	2483.50	48.4 AV	54.00	-5.6	1.00 H	151	17.94	30.43
5	4904.00	46.1 PK	74.00	-27.9	1.21 H	74	10.50	35.60
6	4904.00	33.6 AV	54.00	-20.4	1.21 H	74	-2.00	35.60
7	7356.00	50.9 PK	74.00	-23.1	1.24 H	241	8.74	42.16
8	7356.00	38.5 AV	54.00	-15.5	1.24 H	241	-3.66	42.16
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2288.00	59.0 PK	74.00	-15.0	1.40 V	90	29.34	29.66
2	2288.00	49.5 AV	54.00	-4.5	1.40 V	90	19.84	29.66
3	*2452.00	102.1 PK			1.27 V	162	71.76	30.30
4	*2452.00	91.0 AV			1.27 V	162	60.68	30.30
5	2483.50	69.6 PK	74.00	-4.4	1.24 V	124	39.15	30.43
6	2483.50	50.7 AV	54.00	-3.3	1.24 V	124	20.31	30.43
7	4904.00	45.5 PK	74.00	-28.5	1.31 V	118	9.90	35.60
8	4904.00	32.4 AV	54.00	-21.6	1.31 V	118	-3.20	35.60
9	7356.00	50.7 PK	74.00	-23.3	1.24 V	129	8.54	42.16
10	7356.00	38.4 AV	54.00	-15.6	1.24 V	129	-3.76	42.16

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH1, HORIZONTAL)





RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH1, VERTICAL)



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH7, HORIZONTAL)



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH7, VERTICAL)



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 03, 2009	Aug. 02, 2010

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	12.04	0.5	PASS
6	2437	12.02	0.5	PASS
11	2462	11.32	0.5	PASS


CH1



802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.44	0.5	PASS
6	2437	16.48	0.5	PASS
11	2462	16.51	0.5	PASS


CH11



802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.71	0.5	PASS
6	2437	17.71	0.5	PASS
11	2462	17.70	0.5	PASS


CH6



802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2422	36.46	0.5	PASS
4	2437	36.49	0.5	PASS
7	2452	36.50	0.5	PASS

CH7



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Anritsu Power Meter	ML2495A	0824006	April 25, 2009	April 24, 2010
Pulse Power Sensor	MA2411B	0738172	April 25, 2009	April 24, 2010

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

1. The transmitter output was connected to the power meter through an attenuator; the bandwidth of the fundamental frequency was measured with the power meter.
2. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER OUTPUT (mW)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	17.5	56.2	30	PASS
6	2437	18.2	66.1	30	PASS
11	2462	18.8	75.9	30	PASS

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER OUTPUT (mW)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	19.1	81.3	30	PASS
6	2437	20.8	120.2	30	PASS
11	2462	18.8	75.9	30	PASS

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		Chain(0)	Chain(1)				
1	2412	17.8	17.5	116.5	20.7	30	PASS
6	2437	21.2	20.3	239.0	23.8	30	PASS
11	2462	18.0	17.3	116.8	20.7	30	PASS

802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)				
1	2422	16.5	15.9	83.6	19.2	30	PASS
4	2437	18.8	17.9	137.5	21.4	30	PASS
7	2452	16.0	15.1	72.2	18.6	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 03, 2009	Aug. 02, 2010

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz.


The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION


Same as Item 4.3.6

4.5.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-10.3	8	PASS
6	2437	-4.3	8	PASS
11	2462	-11.2	8	PASS


CH6



802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-13.5	8	PASS
6	2437	-11.1	8	PASS
11	2462	-14.5	8	PASS


CH6



802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)		TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)			
1	2412	-15.8	-18.3	-14.0	8	PASS
6	2437	-10.7	-12.5	-10.0	8	PASS
11	2462	-17.5	-18.1	-15.2	8	PASS


CH6



802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)		TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)			
1	2422	-21.2	-22.8	-20.0	8	PASS
4	2437	-19.2	-19.7	-17.0	8	PASS
7	2452	-22.9	-24.1	-20.0	8	PASS

CH4



4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 03, 2009	Aug. 02, 2010

NOTE:

- 1.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set RBW of spectrum analyzer to 100kHz and VBW of spectrum analyzer to 300kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (RBW = 100kHz, VBW = 300kHz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION


Same as Item 4.3.6

4.6.6 TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

802.11b DSSS MODULATION:


CH1




CH11



CH1




CH11




802.11g OFDM MODULATION:


CH1




CH11



CH1




CH11




802.11n (20MHz) OFDM MODULATION:


CH1




CH11



CH1




CH11




802.11n (40MHz) OFDM MODULATION:


CH1




CH7



CH1



CH7



5. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025:

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Email: service@adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

--- END ---



A D T

6.APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---