



# RF EXPOSURE EVALUATION REPORT

**APPLICANT** : Lierda Science & Technology Group Co., Ltd

**PRODUCT NAME** : K series LoRa gateway module

**MODEL NAME** : LSD4WNC-2K930NE0

**BRAND NAME** : lierda

**FCC ID** : N8N4WNC-2K930NE0

**STANDARD(S)** : 47 CFR Part 2(2.1091)

**RECEIPT DATE** : 2025-05-19

**TEST DATE** : 2025-06-02 to 2025-06-24

**ISSUE DATE** : 2025-07-22

Edited by:

Zeng Xiaoying  
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng  
Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB**

Shenzhen Morlab Communications Technology Co., Ltd.  
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555      Fax: 86-755-36698525  
Http://www.morlab.cn      E-mail: service@morlab.cn





## DIRECTORY

<b>1. Technical Information.....</b>	<b>3</b>
<b>1.1 Applicant and Manufacturer Information.....</b>	<b>3</b>
<b>1.2 Equipment under Test (EUT) Description.....</b>	<b>3</b>
<b>1.3 Applied Reference Documents .....</b>	<b>4</b>
<b>2. Device Category and RF Exposure Limit .....</b>	<b>5</b>
<b>3. Maximum Average Power Summary .....</b>	<b>6</b>
<b>4. RF Exposure Assessment .....</b>	<b>7</b>
<b>Annex A Testing Laboratory Information .....</b>	<b>8</b>

Change History		
Version	Date	Reason for Change
1.0	2025-07-22	First edition



# 1. Technical Information

**Note:** Provide by applicant.

## 1.1 Applicant and Manufacturer Information

<b>Applicant:</b>	Lierda Science & Technology Group Co., Ltd
<b>Applicant Address:</b>	Building 1#, Lierda IOT park, No.1326 Wenyi Xi Rd, Hangzhou, China
<b>Manufacturer:</b>	Lierda Science & Technology Group Co., Ltd
<b>Manufacturer Address:</b>	Building 1#, Lierda IOT park, No.1326 Wenyi Xi Rd, Hangzhou, China

## 1.2 Equipment under Test (EUT) Description

<b>Product Name:</b>	K series LoRa gateway module
<b>Sample No.:</b>	1#, 2#
<b>Hardware Version:</b>	V01
<b>Software Version:</b>	V01
<b>Equipment Type:</b>	LoRa
<b>Operating Frequency:</b>	902.3MHz–927.7MHz
<b>Antenna Type:</b>	Rod Antenna
<b>Antenna Gain:</b>	3.36dBi

**Note 1:** The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



## 1.3 Applied Reference Documents

### Leading reference documents for testing:

Identity	Document Title	Remark
47 CFR Part 2(2.1091)	Radio Frequency Radiation Exposure Assessment: mobile devices	/
KDB 447498 D01v06	General RF Exposure Guidance	/
<b>Note 1:</b> Any additions, deviation, or exclusions from the method shall be noted in the "Remark".		



## 2. Device Category and RF Exposure Limit

Based on 47 CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

### Mobile Devices:

47 CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

### General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

**Table 1—Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density



### 3. Maximum Average Power Summary

Frequency (MHz)	Max. Average Power (dBm)	Tune-up Limit (dBm)
914.9	26.15	26.50

**Note 1:** According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

**Note 2:** The maximum output power refers to report (Report No.: SZ25050118W01).



## 4. RF Exposure Assessment

### ➤ Standalone Transmission Assessment:

Frequency (MHz)	Tune-up Power(dBm)	Antenna Gain(dBi)	E.I.R.P. (mW)	Power Density (mW/cm <sup>2</sup> )	Limit for MPE (mW/cm <sup>2</sup> )
914.9	26.50	3.36	968.28	0.193	0.609

#### Note:

1. According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. MPE calculate method

$$S = PG/4\pi R^2$$

Where: S= Power density (in appropriate units, e.g. mW/cm<sup>2</sup> )

P = Time-average maximum tune-up power (in appropriate units, e.g. dBm)

G = numeric gain of the antenna (in appropriate units, e.g. dBi)

R = Separation distance to the centre of radiation of the antenna (20cm)

### ➤ Simultaneous Transmission Assessment:

This device only incorporates one transmitter, therefore simultaneous SAR assessment is not required.

### ➤ Conclusion:

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.



## Annex A Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

<b>Laboratory Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Laboratory Address:</b>	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
<b>Telephone:</b>	+86 755 36698555
<b>Facsimile:</b>	+86 755 36698525

### 2. Identification of the Responsible Testing Location

<b>Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Address:</b>	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.

— END OF REPORT —