



RF Exposure Evaluation Declaration

Product Name : BlueNRG-A BLE Module

Model No. : LSD1BT-STBLEPCB

FCC ID : N8NLS1BTSTBLEPCB

Applicant : Lierda Science & Technology Group Co.,Ltd

Address : Building 1#, Lierda IOT park, No.1326 Wenyi Xi
Rd, HangZhou City, ZheJiang, China

Date of Receipt : Sep. 06, 2017

Test Date : Sep. 09, 2017~ Nov. 15, 2017

Issued Date : Jan. 08, 2018

Report No. : 1792029R-RF-US- P20V01

Report Version : V 1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, A2LA or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou) Co., Ltd.

Test Report Certification

Issued Date : Jan. 08, 2018
Report No. : 1792029R-RF-US-P20V01



Product Name : BlueNRG-A BLE Module
Applicant : Lierda Science & Technology Group Co.,Ltd
Address : Building 1#, Lierda IOT park, No.1326 Wenyi Xi Rd, HangZhou City, ZheJiang, China
Manufacturer : Lierda Science & Technology Group Co.,Ltd
Address : Building 1#, Lierda IOT park, No.1326 Wenyi Xi Rd, HangZhou City, ZheJiang, China
Model No. : LSD1BT-STBLEPCB
FCC ID : N8NLSD1BTSTBLEPCB
EUT Voltage : DC 3.3V
Test Voltage : AC 120V/60Hz
Applicable Standard : KDB 447498D01V06
FCC Part1.1310
Test Result : Complied
Performed Location : DEKRA Testing & Certification (Suzhou) Co., Ltd.
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006,
Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Designation Number: CN1199

Documented By : 

(Project Assistant: Kathy Feng)

Reviewed By : 

(Senior Project Manager: Frank He)

Approved By : 

(Engineering Manager: Harry Zhao)

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/ cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	BlueNRG-A BLE Module
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

● Antenna Information:

Antenna manufacturer	ACX					
Antenna Delivery	<input checked="" type="checkbox"/>	1*TX+1*RX	<input type="checkbox"/>	2*TX+2*RX	<input type="checkbox"/>	3*TX+3*RX
Antenna technology	<input checked="" type="checkbox"/>	SISO				
	<input type="checkbox"/>	MIMO	<input type="checkbox"/>	Basic		
	<input type="checkbox"/>		<input type="checkbox"/>	CDD		
	<input type="checkbox"/>		<input type="checkbox"/>	Beam-forming		
Antenna Type	<input type="checkbox"/>	External	<input type="checkbox"/>	Dipole		
	<input type="checkbox"/>		<input type="checkbox"/>	PIFA		
	<input type="checkbox"/>		<input type="checkbox"/>	PCB		
	<input type="checkbox"/>		<input type="checkbox"/>	Ceramic Chip Antenna		
	<input checked="" type="checkbox"/>	Internal	<input type="checkbox"/>	Multilayer Chip Antenna		
	<input type="checkbox"/>		<input type="checkbox"/>	Stamping Antenna		
	<input type="checkbox"/>		<input type="checkbox"/>	Metal plate type F antenna		
	<input type="checkbox"/>		<input type="checkbox"/>	Monopole antenna		
Antenna Gain	0.5dBi					

- **Power Density:**

The maximum conducted tune-up power is 9dBm.

Test Mode	Frequency Band (MHz)	EIRP (dBm)	Limit of Power Density S(mW/cm ²)	Power Density at R = 20 cm (mW/cm ²)
BLE	2402 ~ 2480	9.44	1	0.017

Note:

1. The maximum power of related plane is calculated for simultaneous MPE.
2. The power density is 0.017mW/cm² for BlueNRG-A BLE Module without any other radio equipment.

The End
