



WHEN THE BUTTON ON THE TRANSMITTER IS BEING PRESSED, A ONE-SHOT TYPE SIGNAL (A SHORT PERIODS OF MODULATED SIGNAL) IS BEING TRANSMITTED.

1. - U1 : BUILT-IN FUNCTION WITH ENCODER, TIMING OSCILLATOR WITH AN EXTERNAL RESISTOR R3 (FREQ.: 80kHz)
2. - L1, L2, C2, C4, C5, C6, R1, R2 & Q3 FUNCTION AS A SINGLE-ENDED L-C TUNED MODULATOR OPERATING AT 320MHz

ITEM	PART NUMBER	DESCRIPTION	QTY. REG.	MATERIAL	REMARK
PARTS LIST					
UNLESS OTHERWISE SPECIFIED DIMENSION ARE IN MM TOLERANCE DECIMALS ANGULAR .X ± ± ° .XX ±		TITLE BLOCK DIAGRAM FOR 320MHZ TRANSMITTER (TRANSMITTER FOR THE LANTERN WITH REMOTE CONTROL FUNCTION)			
DO NOT SCALE DRAWING		SCALE 1 : 1	MATERIAL —	DRAWN BY C.K.C	DATE AUG 9, 2005
RELEASED TOOLING: WORKING: DAYS PRODUCTION:		PART NUMBER 5317-702	DRAWING NUMBER XX-XXX	APPROVED BY	NO. OF CAVITY — REV. —