

MEASUREMENT/TECHNICAL REPORT**APPLICANT:** Sunpark Electronics (Taiwan) Corporation**MODEL NO.:** 12055D**FCC ID:** N9612055D

This report concerns (check one) : **Original Grant**
 Class II Change

Equipment type: TORCHIERE FLUORESCENT FIXTURE

Deferred grant requested per 47CFR 0.457(d)(1)(ii)?

Yes No If yes, defer until: _____ (date)

We, the undersigned, agree to notify the Commission by (date) _____ / _____ / _____ of the intended date of announcement of the product so that the grant can be issued on that date.

Transiyion Rules Request per 15.37?

Yes No

If no, assumed Part 18, Consumer equipment of RF lighting device for new 47 CFR (10-1-90 Edition) provision.

Report Prepared

by Testing House : Neutron Engineering Inc.

for Company Name: Sunpark Electronics (Taiwan) Corporation

Address: No. 1, Lane 392, Futeh 1st Road, Hsichih, Taipei County, Taiwan, R.O.C.

Applicant Signature :



Jim C.F. Chao / President

CERTIFICATION

We hereby certify that:

The test data , data evaluation , test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (1992) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 18, Subpart C. Consumer Class.

Prepared by : Carol Chen



Reviewed by : Vincent Su



Approved by : George Yao



Issued Date : May 16, 2002

Report No. : NEI-FCCB-02103

Company Stamp :



NEUTRON ENGINEERING INC.

No. 132-1, Lane 329, Sec. 2, Palain Rd.,

Shijr Jen, Taipei, Taiwan

TEL : (02) 2646-5426 FAX : (02) 2646-6815

Table of Contents

1. General Information	
1-1 Product Description.....	4
1-2 Related Submittal(s)/Grant(s).....	4
1-3 Tested System Details.....	5
1-4 Test Methodology.....	6
1-5 Test Facility.....	6
2. Product Labeling	
Figure 2-1 FCC ID Label.....	7
Figure 2-2 Location of Label on EUT.....	7
3. System Test Configuration	
3-1 Justification.....	8
3-2 EUT Exercise Software.....	8
3-3 Special Accessories.....	9
3-4 Equipment Modifications.....	9
3-5 Configuration of Tested System.....	10
Figure 3-1 Configuration of Tested System.....	12
4. Block Diagram(s)	14
5. Conducted and Radiated Measurement Photos	
Figure 5-1 Conducted Measurement Photos.....	15
Figure 5-2 Radiated Measurement Photos.....	16
6. Conducted Emission Datas	17
7. Radiated Emission Datas	
7-1 Radiated Emission Data.....	18
7-2 Field Strength Calculation.....	19
8. Attachment	
Photos of Tested EUT.....	20
User's Manual.....	21

1. GENERAL INFORMATION**1-1. Product Description**

The Sunpark Electronics (Taiwan) Corporation Model: 12055D(referred to as the EUT in this report) was designed as a generic RF light socket(EUT). The EUT was plugged directly into the power outlet. And for 120Vac G.E. 2D/2C 55W lamp only.

Operating frequency : 43KHz.

1-2. Related Submittal(s) / Grant (s)**1-2-1. Models Covered**

Models covering in this test report is : 12055D

1-2-2. Models Difference

N/A

1-3. Tested System Details

The FCC IDs for all equipment, plus descriptions of all cables used in the tested system (including inserted cards, which have grants) are:

Model No.	FCC ID	Equipment	Cable
12055D	N9612055D	TORCHIERE FLUORESCENT FIXTURE	Un-Shielded Data Cable AC Power Cable.

Notes:

- (1) EUT submitted for grant.
- (2) The support equipment was authorized by Declaration of Conformity.

1-4. Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (1992). Radiated testing was performed at an antenna to EUT distance 3 meters.

1-5. Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the address of No. 132-1, Lane 329, Sec. 2, Palain Road, Shijr 221, Taipei, Taiwan, R.O.C. of NEUTRON ENGINEERING INC. This site has been fully described in report dated Jun. 25, 1999 Submitted to your office, and accepted in a letter dated Sep. 02, 1999 (Reg. No. 95335).

3. System Test Configuration

3-1. Justification

The system was configured for testing in a typical fashion (as a customer would normally use it). The EUT(TORCHIERE FLUORESCENT FIXTURE) was placed on a supportor. Which is 10cm away from the ground plane. This system in order to comply with the ANSI C63.4 Rules requirement.

3-2. EUT Exercise Software

N/A


3-3. Special Accessories

Not available for this EUT intended for grant.

3-4. Equipment Modifications

Not available for this EUT intended for grant.

Applicant Signature :



Date:

May 04, 2002

Type/Printed Name:

Jim C.F. Chao

Position:

President

3.5 Configuration of Tested System

The configuration of tested system is described as the block diagram shown in next page Figure 3.1 and details information of I/O cable an power cord connection are tabulated as Table A and B. The monitor is powered from a floor mounted receptacle (referred to as the wall outlet in the previous described)was tested.

TABLE A - Test Equipment

Item	Equipment	Mfr/Brand	Model/Type No.	Port Connected	FCC ID	Series No.	Note
E-1	TORCHIERE FLUORESCENT FIXTURE	Sunpark	12055D		N9612055D	N/A	EUT

Remark:

- (1) Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment.
- (2) Unless otherwise marked as 『※』 in 『Remark』 column, Neutron consigns the supporting equipment(s) to the tested system.
- (3) The support equipment was authorized by Declaration of Conformity.


Table B. - Informations Cable Information

Item	I/O Cable	Device Connected	Shielded Type	Ferrite Core	Detachable/ Permanently	Length	Note
	N/A						

Note:

(1) Unless otherwise marked as in (Remark) column, Neutron consigns the supporting equipment(s) to the tested system.

Figure 3.1 Configuration of Tested System



3-2 Test Equipment

Item	Instruments	Mfr/Brand	Model/Type No.	Serial No.	Calibrated Date	Next Cali. Date	Note
1	LISN	EMCO	3825/2	9605-2539	2001-06-22	2002-06-21	
2	LISN	Rolf Heine	NNB-2/16Z	98083	2001-10-20	2002-10-19	✓
3	LISN	Rolf Heine	NNB-2/16Z	98053	2001-11-22	2002-11-21	✓
4	Pulse Limiter	Electro-Metrics	EM-7600	112644	2001-12-10	2002-12-19	✓
5	50 Terminator	N/A	N/A	N/A	2001-05-21	2002-05-20	
6	Test Cable	N/A	C01	N/A	2001-12-08	2002-12-07	✓
7	Log-Bicon Antenna	MESS-ELEKTRONIK	VULB 9160	3058	2001-10-27	2002-10-26	
8	Log-Bicon Antenna	MESS-ELEKTRONIK	VULB 9160	3060	2001-10-20	2002-10-19	✓
9	Log-Bicon Antenna	MESS-ELEKTRONIK	VULB 9161	4022	2001-07-04	2002-07-03	
10	Test Cable	N/A	10M_OS01	N/A	2001-12-08	2002-12-07	
11	Test Cable	N/A	OS01-1/-2	N/A	2001-12-08	2002-12-07	
12	Test Cable	N/A	10M_OS02	N/A	2001-12-08	2002-12-07	✓
13	Test Cable	N/A	OS02-1/-2/-3	N/A	2001-12-08	2002-12-07	✓
14	RF Switch	Anritsu	MP59B	M65982	2001-12-10	2002-12-09	✓
15	Quasi-Peak Adapter	HP	85650A	2521A00844	2002-04-08	2002-10-07	✓
16	RF Pre-Selector	HP	85685A	2648A00417	2002-04-08	2002-10-07	✓
17	Spectrum Analyzer	HP	85680B	2634A03025	2002-04-08	2002-10-07	✓
18	Spectrum Monitor	HP	85662B	2648A13616	2002-04-08	2002-10-07	✓
19	Pre-Amplifier	Anritsu	MH648A	M09961	2001-12-10	2002-12-09	✓
20	Spectrum Analyzer	ADVAN TEST	R3261C	81720298	2001-08-17	2002-08-16	
21	Test Receiver	R&S	ESH3	860156/018	2001-10-23	2002-10-22	
22	Test Receiver	R&S	ESVP	860687/009	2001-10-23	2002-10-22	
23	Test Receiver	MEB	SMV41	130	2001-12-05	2002-12-04	✓
24	Test Receiver	PMM	PMM 9000	4310J01002	2001-12-31	2002-12-30	
25	Horn Antenna	EMCO	3115	9605-4803	2001-05-09	2002-05-08	
26	Test Receiver	R&S	ESMI	843977/005	2001-11-14	2002-11-05	
27	Pre-Amplifier	R&S	ESMI-Z7	1045.5020	2001-05-21	2002-05-20	
28	Absorbing Clamp	R&S	MDS-21	841077/011	2001-08-18	2002-08-17	
29	Voltage Probe	R&S	ESH2-Z3	841.800/023	2001-08-20	2002-08-19	
30	Signal Generator	HP	8648A	3426A01034	2000-02-10	2003-09-23	
31	Antenna Mast	Chance Most	CMTB-1.5	N/A	N/A	N/A	✓
32	Turn Table	Chance Most	CMTB-1.5	N/A	N/A	N/A	✓

Remark :

- (1) ✓ indicates the instrument used in Test Report.
- (2) N/A denotes No Model No. / Serial No. and No Calibration specified.

4. Block Diagram(s)

Figure 4.1 Block diagram of system, Page 13.A

6. Conducted Emission Datas

6.1 Standard Applicable

According to 18.307(C) , Consumer equipment for conduction limits.

6.2 The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Judgement: Passed by **-2.30 dB** in mode of **Neutral** terminal **0.60 MHz**

Freq. (MHz)	Terminal	Measured(dBuV)		Safe Margins	
		QP-Mode	Limits(dBuV)	(dBuV)	Note
0.61	Line	44.61	48.00	-3.39	(QP)
0.87	Line	44.01	48.00	-3.99	(QP)
1.13	Line	42.99	48.00	-5.01	(QP)
2.12	Line	37.63	48.00	-10.37	(QP)
15.91	Line	41.73	48.00	-6.27	(QP)
28.77	Line	39.29	48.00	-8.71	(QP)
0.60	Neutral	44.41	48.00	-3.59	(QP)
0.87	Neutral	44.21	48.00	-3.79	(QP)
1.12	Neutral	42.99	48.00	-5.01	(QP)
8.09	Neutral	35.97	48.00	-12.03	(QP)
15.58	Neutral	41.50	48.00	-6.50	(QP)

Remark :

- (1) Reading in which marked as QP means measurements by using are Quasi-Peak Mode with Detector BW=9KHz ; SPA setting in RBW=10KHz,VBW =10KHz, Swp. Time = 0.3 sec./MHz.
- (2) Measuring frequency range from 450KHz to 30MHz.

Review:



Test Engr.:



Test Date : May 04, 2002

7. Radiated Emission Data

7.1 Standard Applicable

According to 18.305(c). Consumer equipment for Field Strength limits.

7.2 The following data lists the significant emission frequencies, measured levels, correction factor (includes cable and antenna corrections), the corrected reading, as well as the limit. Explanation of the Correction Factor is given in paragraph 7.3.

Judgement: Passed by **-2.39 dB** in polarity of **Vertical 57.20 MHz**

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(OP) (dBuV/m)	Safe Margins (dBuV/m)	Note
57.20	V	50.10	- 12.49	37.61	40.00	- 2.39	
68.40	H	37.50	- 14.21	23.29	40.00	- 16.71	
74.00	H	44.60	- 15.20	29.40	40.00	- 10.60	
75.79	V	51.20	- 15.50	35.70	40.00	- 4.30	
80.40	V	50.80	- 15.93	34.87	40.00	- 5.13	
81.80	H	47.60	- 15.77	31.83	40.00	- 8.17	
212.90	V	49.60	- 13.44	36.16	43.50	- 7.34	
214.40	H	46.60	- 13.37	33.23	43.50	- 10.27	
222.70	V	41.80	- 13.07	28.73	46.00	- 17.27	
248.80	H	35.50	- 12.13	23.37	46.00	- 22.63	
335.00	V	42.50	- 9.33	33.17	46.00	- 12.83	
338.40	H	40.70	- 9.26	31.44	46.00	- 14.56	

Remark :

- (1) Test Spectrum Analyzer measurement condition setting are RBW=100KHz, Video BW =100KHz, Sweep. Time = 0.2 sec; Receiver setting. RBW, VBW=120KHz, Sweep time=0.2 sec.
- (2) All readings are Peak unless otherwise stated QP in column of **『Note』**
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.
- (5) If the peak scan value lower limit less than 20dB, then this signal data will be listed. But if these signal data are more than 10 frequencies, then only the Top 10 be listed.

Review:

TimenK

Test Engr.:

Jeff

Test Date :

May 09, 2002

7-3. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where **FS** = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor (1)

CL = Cable Attenuation Factor (1)

AG = Amplifier Gain (1) (2)

Remark :

(1) The Correction Factor = AF + CL - AG, as shown in the data tables' Correction Factor column.

(2) AG is not available for Neutron's Open Site Facility

Example of Calculation:

Assume a Receiver Reading of 23.7 dBuV is obtained with an Antenna Factor of 7.2 dB and a Cable Factor of 1.1 dB. Then:

1. The Correction Factor will be calculated by

$$\text{Correction Factor} = AF + CL - AG = 7.2 + 1.1 - 0 = 8.3 \text{ (dB)}$$

as shown in the data tables' Correction Factor column.

2. The Field Strength will be calculated by

$$FS = RA + \text{Correction Factor} = 23.7 + 8.3 = 32 \text{ (dBuV/m).}$$

FS is the value shown in the data tables' Corrected Reading column and RA is the value shown in the data tables' Receiver Reading column. The 32 dBuV/m value was mathematically converted to its corresponding level in uV/m as:

$$\text{Log}^{-1}\{(32.0 \text{dBuV/m})/20\} = 39.8 \text{ (uV/m)}$$

8. Photos of Tested EUT:

- 1. Photo # 1 Front View, Rear View**
- 2. Photo # 2 Unit Partially Disassembled**

Attachment

User's Manual