



FCC TEST REPORT

for

CISPR PUB. 22 Class B

Equipment : Mouse

Model No. : 99NS22P

FCC ID : N9Q99NS22P

Filing Type : Original Grant

**Applicant : XNTC NEW TECH CORP.
4F, No. 112, Cheng-Kong Rd. Cinching City.,
Taipei, Taiwan, R.O.C.**

- The test result refers exclusively to the test presented test model / sample.
- Without the written authorization of the test lab., the Test Report may not be copied.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

Table of Contents

| | |
|--|----------------|
| CERTIFICATE OF COMPLIANCE | 3 |
| 1. General Description of Equipment under Test | 4 |
| 1.1. Applicant..... | 4 |
| 1.2. Manufacturer..... | 4 |
| 1.3. Basic Description of Equipment under Test..... | 4 |
| 1.4. Feature of Equipment under Test..... | 4 |
| 2. Test Configuration of Equipment under Test..... | 5 |
| 2.1. Test Manner..... | 5 |
| 2.2. Description of Test System | 5 |
| 2.3. Connection Diagram of Test System..... | 7 |
| 3. Test Software..... | 8 |
| 4. General Information of Test | 9 |
| 4.1. Test Facility..... | 9 |
| 4.2. Standard for Methods of Measurement..... | 9 |
| 4.3. Test in Compliance with | 9 |
| 4.4. Frequency Range Investigated | 9 |
| 4.5. Test Distance..... | 9 |
| 5. Test of Conducted Powerline..... | 10 |
| 5.1. Major Measuring Instruments | 10 |
| 5.2. Test Procedures..... | 11 |
| 5.3. Typical Test Setup Layout of Conducted Powerline..... | 12 |
| 5.4. Test Result of AC Powerline Conducted Emission | 13 |
| 5.5. Photographs of Counducted Powerline Test Configuration..... | 14 |
| 6. Test of Radiated Emission | 16 |
| 6.1. Major Measuring Instruments | 16 |
| 6.2. Test Procedures..... | 17 |
| 6.3. Typical Test Setup Layout of Radiated Emission..... | 18 |
| 6.4. Test Result of Radiated Emission | 19 |
| 6.5. Photographs of Radiated Emission Test Configuration..... | 20 |
| 7. Antenna Factor & Cable Loss | 21 |
| 8. List of Measuring Equipments Used | 22 |
| Appendix A. Photographs of EUT | A1 ~ A3 |



Certificate No. : F972906

CERTIFICATE OF COMPLIANCE

for

CISPR PUB. 22 Class B

Equipment : Mouse

Model No. : 99NS22P

FCC ID : N9Q99NS22P

**Applicant : XNTC NEW TECH CORP.
4F, No. 112, Cheng-Kong Rd. Cinching City.,
Taipei, Taiwan, R.O.C.**

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 - 1992** and the energy emitted by this equipment was **passed CISPR PUB. 22** both radiated and conducted emission class B limits. Testing was carried out on Jul. 30, 1999 at **SPORTON International Inc.** LAB. in Lin Kou.

W. L. Huang
W. L. Huang
General Manager

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

1. General Description of Equipment under Test**1.1. Applicant**

XNTC NEW TECH. CORP.
4F, No. 112, Cheng-Kong Rd. Cinching City.
Taipei, Taiwan, R.O.C.

1.2. Manufacturer

Same as 1.1.

1.3. Basic Description of Equipment under Test

Equipment : Mouse
Model No. : 99NS22P
FCC ID : N9Q99NS22P
Trade Name : XN Tech
PS/2 mouse data cable : Shielded, 1.7 m
Power Supply Type : From PC
Power Cord : N/A

1.4. Feature of Equipment under Test

- For 2D 2-BUTTON
- PS/2 PORT/ 2-KEY
- Resolution: 6MHz/ 800dpi
- Power Supply: DC 5V, 50mA max.

2. Test Configuration of Equipment under Test

2.1. Test Manner

- a. The EUT has been associated with personal computer and peripherals pursuant to ANSI C63.4-1992 and configuration operated in a manner which tended to maximize its emission characteristics in a typical application.
- b. The SONY Monitor, DELL PS/2 Keyboard, HP Printer, ACEEX Modem and EUT were connected to the DELL PC for EMI test.
- c. Frequency range investigated: conduction 150 KHz to 30 MHz, radiation 30 MHz to 1000MHz.

2.2. Description of Test System

Support Unit 1. -- Personal Computer (DELL)

| | |
|-------------------|---|
| FCC ID | : N/A |
| Model No. | : DCS |
| Power Supply Type | : Switching |
| Power Cord | : Non-Shielded |
| Serial No. | : SP0038 |
| Data Cable | : Shielded, 360 degree via metal backshells |
| Remark | : This support device was tested to comply with FCC standards and authorized under a declaration of conformity. |

Support Unit 2. -- Monitor (SONY)

| | |
|-------------------|---|
| FCC ID | : AK8GDM17SE2T |
| Model No. | : GDM-17SE2T |
| Power Supply Type | : Switching |
| Power Cord | : Non-Shielded |
| Serial No. | : SP0013 |
| Data Cable | : Shielded, 360 degree via metal backshells, 1.7m |

Support Unit 3. -- PS/2 Keyboard (DELL)


| | |
|------------|---|
| FCC ID | : GYUM92SK |
| Model No. | : AT101(DE8M) |
| Serial No. | : SP0054 |
| Data Cable | : Shielded, 360 degree via metal backshells, 1.9m |

Support Unit 4. -- Printer (HP)

| | |
|-------------------|--|
| FCC ID | : DSI6XU2225 |
| Model No. | : 2225C |
| Power Supply Type | : Linear |
| Power Cord | : Non-Shielded |
| Serial No. | : SP0024 |
| Data Cable | : Shielded, 360 degree via metal backshells, 1.35m |

Support Unit 5. -- Modem (ACEEX)

| | |
|-------------------|--|
| FCC ID | : IFAXDM1414 |
| Model No. | : DM1414 |
| Power Supply Type | : Linear |
| Power Cord | : N/A |
| Serial No. | : SP0076 |
| Data Cable | : Braided-Shielded, 360 degree via metal backshells, 1.15m |

2.3. Connection Diagram of Test System

1. The I/O cable is connected from PC to the support unit 4.
2. The I/O cable is connected from PC to the support unit 2.
3. The I/O cable is connected from PC to the support unit 3.
4. The I/O cable is connected from PC to the support unit 5.
5. The I/O cable is connected from PC to the EUT.

3. Test Software

An executive program, EMITEST.EXE under WIN 98, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The PC reads the test program from the floppy disk drive and runs it.
- c. The PC sends " H " messages to the monitor, and the monitor displays " H " patterns on the screen.
- d. The PC sends " H " messages to the printer, then the printer prints them on the paper.
- e. The PC sends " H " messages to the modem.
- f. The PC sends " H " messages to the internal Hard Disk, and the Hard Disk reads and writes the message.
- g. Repeat the steps from b to f.

4. General Information of Test

4.1. Test Facility

This test was carried out by SPORTON International Inc. in an openarea test site.

Openarea Test Site Location : No. 30-2, Lin 6, Diing-Fwu Tsuen, Lin-Kou-Hsiang,
Taipei Hsien, Taiwan, R.O.C.
TEL : 886-2-2601-1640
FAX : 886-2-2601-1695

4.2. Standard for Methods of Measurement

ANSI C63.4-1992

4.3. Test in Compliance with

CISPR PUB. 22 Class B

4.4. Frequency Range Investigated

- a. Conduction: from 150 kHz to 30 MHz
- b. Radiation : from 30 MHz to 1,000 MHz

4.5. Test Distance

The test distance of radiated emission from antenna to EUT is 10 M.

5. Test of Conducted Powerline

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 115 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-1992 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 5.3. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


5.1. Major Measuring Instruments

| | |
|-----------------|-----------|
| Test Receiver | HP 8591EM |
| Attenuation | 0 dB |
| Start Frequency | 0.15 MHz |
| Stop Frequency | 30 MHz |
| Step MHz | 0.007 MHz |
| IF Bandwidth | 9 kHz |

5.2. Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connect to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- i. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 6 dB margin will be retested one by one using the quasi-peak method and reported.

5.3. Typical Test Setup Layout of Conducted Powerline



5.4. Test Result of AC Powerline Conducted Emission


- Frequency Range of Test : from 0.15 MHz to 30 MHz
- Temperature : 28°C
- Relative Humidity : 52 %
- Test Date : Jul. 30, 1999

The Conducted Emission test was passed at minimum margin

NEUTRAL 0.249 MHz / 45.00 dBuV.

| Freq. (MHz) | Line or Neutral | Meter Reading | | | | Limits | | | | Margin | |
|----------------|-----------------------|----------------|----------------|--------------|--------------|----------------|----------------|--------------|--------------|--------------|--------------|
| | | Q.P. (dBuV) | A.V. (dBuV) | Q.P. (uV) | A.V. (uV) | Q.P. (dBuV) | A.V. (dBuV) | Q.P. (uV) | A.V. (uV) | Q.P. (dB) | A.V. (dB) |
| 0.245 | L | 44.00 | 42.10 | 158.49 | 127.35 | 61.92 | 51.92 | 1248.10 | 394.68 | -17.92 | -9.82 |
| 0.514 | L | 30.60 | 28.50 | 33.88 | 26.61 | 56.00 | 46.00 | 630.96 | 199.53 | -25.40 | -17.50 |
| 28.560 | L | 34.50 | 33.20 | 53.09 | 45.71 | 60.00 | 50.00 | 1000.00 | 316.23 | -25.50 | -16.80 |
| 0.249 | N | 45.00 | 43.50 | 177.83 | 149.62 | 61.79 | 51.79 | 1228.92 | 388.62 | -16.79 | -8.29 |
| 0.454 | N | 31.50 | 29.50 | 37.58 | 29.85 | 56.81 | 46.81 | 692.29 | 218.92 | -25.31 | -17.31 |
| 28.554 | N | 32.20 | 28.20 | 40.74 | 25.70 | 60.00 | 50.00 | 1000.00 | 316.23 | -27.80 | -21.80 |

Test Engineer :


KENNY CHUANG

6. Test of Radiated Emission


Radiated emissions from 30 MHz to 1,000 MHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-1992. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

6.1. Major Measuring Instruments

| | |
|----------------------|---|
| Amplifier | (HP 8447D) |
| Attenuation | 0 dB |
| RF Gain | 25 dB |
| Signal Input | 0.1 MHz to 1.3 GHz |
| Spectrum Analyzer | (HP 8568B) |
| Attenuation | 0 dB |
| Start Frequency | 30 MHz |
| Stop Frequency | 1,000 MHz |
| Resolution Bandwidth | 1 MHz |
| Video Bandwidth | 1 MHz |
| Signal Input | 100 Hz to 1.5 GHz |
| Quasi-Peak Adapter | (85650A) |
| Resolution Bandwidth | 120 KHz |
| Frequency Band | 30 MHz to 1 GHz |
| Quasi-Peak Detector | ON for Quasi-Peak Mode OFF for Peak Mode |

6.2. Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 10 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 6 dB margin will be repeated one by one using the quasi-peak method and reported.

6.3. Typical Test Setup Layout of Radiated Emission

6.4. Test Result of Radiated Emission

- Frequency Range of Test : from 30 MHz to 1,000 MHz
- Test Distance : 10 M
- Temperature : 28°C
- Relative Humidity : 72 %
- Test Date : Jul. 30, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin

208.000 MHz / 24.27 dBuV (HORIZONTAL) Antenna Height 4 Meter, Turntable Degree 65 °.

| Frequency (MHz) | Polarity | Antenna Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Limits | | Emission (dBuV/m) | Level (uV/m) | Margin (dB) |
|--------------------|----------|-----------------------------|-----------------------|-------------------|----------|--------|----------------------|-----------------|----------------|
| | | | | | (dBuV/m) | (uV/m) | | | |
| 67.916 | V | 5.55 | 0.90 | 15.74 | 30.00 | 31.62 | 22.19 | 12.87 | -7.81 |
| 208.000 | V | 9.52 | 1.53 | 10.22 | 30.00 | 31.62 | 21.27 | 11.57 | -8.73 |
| 216.000 | V | 10.18 | 1.64 | 9.04 | 30.00 | 31.62 | 20.86 | 11.04 | -9.14 |
| 168.240 | H | 10.01 | 1.40 | 11.38 | 30.00 | 31.62 | 22.79 | 13.79 | -7.21 |
| 200.000 | H | 8.78 | 1.40 | 10.45 | 30.00 | 31.62 | 20.63 | 10.75 | -9.37 |
| 208.000 | H | 9.52 | 1.53 | 13.22 | 30.00 | 31.62 | 24.27 | 16.35 | -5.73 |

Test Engineer :

Terry Chang
Terry Chang

7. Antenna Factor & Cable Loss

| Frequency (MHz) | Antenna Factor (dB) | Cable Loss (dB) |
|-------------------|-----------------------|-------------------|
| 30 | 17.9 | 0.6 |
| 35 | 16.1 | 0.7 |
| 40 | 14.0 | 0.7 |
| 45 | 10.5 | 0.8 |
| 50 | 7.9 | 0.7 |
| 55 | 6.7 | 0.8 |
| 60 | 5.5 | 1.0 |
| 65 | 5.5 | 0.9 |
| 70 | 5.6 | 0.9 |
| 75 | 6.5 | 1.0 |
| 80 | 7.5 | 0.9 |
| 85 | 8.5 | 1.0 |
| 90 | 9.4 | 1.0 |
| 95 | 10.4 | 1.1 |
| 100 | 11.5 | 1.1 |
| 110 | 12.1 | 1.2 |
| 120 | 12.6 | 1.2 |
| 130 | 12.0 | 1.3 |
| 140 | 11.6 | 1.3 |
| 150 | 10.5 | 1.3 |
| 160 | 10.5 | 1.4 |
| 170 | 9.8 | 1.4 |
| 180 | 9.2 | 1.5 |
| 190 | 9.0 | 1.6 |
| 200 | 8.8 | 1.4 |
| 220 | 10.5 | 1.7 |
| 240 | 12.2 | 1.5 |
| 260 | 13.1 | 1.8 |
| 280 | 13.2 | 1.8 |
| 300 | 13.4 | 1.9 |
| 320 | 13.4 | 1.9 |
| 340 | 13.4 | 2.0 |
| 360 | 13.9 | 2.2 |
| 380 | 14.9 | 2.1 |
| 400 | 15.6 | 2.1 |
| 450 | 16.4 | 2.3 |
| 500 | 16.6 | 2.5 |
| 550 | 19.7 | 2.4 |
| 600 | 19.3 | 2.8 |
| 650 | 20.0 | 2.9 |
| 700 | 19.5 | 2.9 |
| 750 | 18.5 | 2.7 |
| 800 | 17.8 | 3.5 |
| 850 | 18.3 | 3.3 |
| 900 | 20.5 | 3.2 |
| 950 | 21.4 | 4.5 |
| 1000 | 21.2 | 3.5 |

8. List of Measuring Equipments Used

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Remark |
|--------------------------------------|--------------|-----------|------------|-----------------|------------------|------------|
| EMC Receiver (site 2) | HP | 8591EM | 3635A00673 | 9 KHz – 1.8 GHz | Aug. 27, 1998 | Conduction |
| EMC Receiver (site 2) | HP | 8591EM | 3710A01187 | 9 KHz - 18 GHz | Sep. 18, 1998 | Conduction |
| LISN (EUT) (site 2) | Telemeter | NNB-2/16Z | 98009 | 50 ohm / 50 uH | Jan. 22, 1999 | Conduction |
| LISN (Support Unit) (site 2) | EMCO | 3810/2NM | 9703-1839 | 50 ohm / 50 uH | Jul. 05, 1999 | Conduction |
| Quasi-peak Adapter (site 5) | HP | 85650A | 2521A00821 | 9KHz -1 GHz | Nov. 14, 1998 | Radiation |
| Spectrum Analyzer (Site 5) | HP | 8568B | 2634A03000 | 100Hz - 1.5GHz | Nov. 14, 1998 | Radiation |
| Amplifier (Site 5) | HP | 8447D | 2944A08290 | 0.1MHz -1.3GHz | Nov. 13, 1998 | Radiation |
| Bilog Antenna (Site 5) | CHASE | CBL6112A | 2287 | 30MHz -2GHz | Jan. 07, 1999 | Radiation |
| Half-wave dipole antenna (Site 5) | EMCO | 3121C | 9705-1285 | 28 M - 1GHz | May 18, 1999 | Radiation |
| Turn Table (site 5) | EMCO | 2080 | 9711-2021 | 0 ~ 360 degree | N/A | Radiation |
| Antenna Mast (site 5) | EMCO | 2075 | 9711-2115 | 1 m- 4 m | N/A | Radiation |