



FCC RF EXPOSURE REPORT

Applicant	:	HELLA GmbH & Co. KGaA
Address of Applicant	:	Rixbecker Strasse, 75, 59552 Lippstadt, Germany
Manufacturer	:	HELLA GmbH & Co. KGaA
Address of Manufacturer	:	Rixbecker Strasse, 75, 59552 Lippstadt, Germany
Equipment under Test	:	Smart Car Access Device
Model No.	:	FBD6
FCC ID	:	NBGFBD6
Test Standard(s)	:	447498 D04 Interim General RF Exposure Guidance v01, TCBC WORKSHOP 2022 Oct Part II - RF Exposure Policies & Procedures Eqpt Auth_r1
Report No.	:	DDT-RE24101724-2E07V1
Issue Date	:	2025/01/15
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd.
Address of Laboratory	:	Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

	Test report declares.....	3
1.	General Information	5
1.1.	Description of equipment	5
1.2.	Assess laboratory.....	5
2.	RF Exposure Evaluation	6
2.1.	Requirement-BLE.....	6
2.2.	Estimation result-BLE.....	7
2.3.	Requirement-UWB	7

Test Report Declare

Applicant	:	HELLA GmbH & Co. KGaA
Address of Applicant	:	Rixbecker Strasse, 75, 59552 Lippstadt, Germany
Equipment under Test	:	Smart Car Access Device
Model No.	:	FBD6
Manufacturer	:	HELLA GmbH & Co. KGaA
Address of Manufacturer	:	Rixbecker Strasse, 75, 59552 Lippstadt, Germany

Standard Used: 447498 D04 Interim General RF Exposure Guidance v01, TCBC WORKSHOP 2022 Oct Part II - RF Exposure Policies & Procedures Eqpt Auth_r1

We Declare:

The equipment described above is assessed by Guangdong Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Guangdong Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No.:	DDT-RE24101724-2E07V1		
Date of Receipt:	2024/10/29	Date of Test:	2024/10/29 - 2024/11/13

Prepared By:

Tiger Mo

Tiger Mo/Engineer

Approved By:

Damon Hu

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/11/13	Tiger Mo
V1	This report Report Updated exposure assessment criteria, the original report DDT-RE24101724-2E07 is invalid after the new version is released.	2025/01/15	Tiger Mo

1. General Information

1.1. Description of equipment

EUT* Name	: Smart Car Access Device
Model Number	: FBD6
EUT Function Description	: Please reference user manual of this device
Power Supply	: 12V DC from vehicle power supply system
Hardware Version	: 7.1
Software Version	: SXX
Radio Specification	: Bluetooth LE, UWB
Operation Frequency	: Bluetooth LE: 2402MHz-2480MHz UWB: CH8: 7.22GHz – 7.738GHz, CH9: 7.73GHz – 8.25GHz
Modulation	: Bluetooth LE: GFSK, $\pi/4$ -DQPSK, 8DPSK UWB: Impulse radio
Antenna	: Integrated PCB Antenna

Note: EUT is the abbreviation of equipment under test.

Note: This EUT support Bluetooth LE, UWB.

1.2. Assess laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No.17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure Evaluation

2.1. Requirement-BLE

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 1.1307(b)(3)(i)(B) this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

From the peak EUT RF output power, the minimum mobile separation distance, $20\text{cm} < d < 40\text{cm}$, as well as the gain of the used antenna, the RF power density can be obtained.

2.2. Estimation result-BLE

Mode	Output power (dBm)	Output power (mW)	tune up power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	MPE Values (mW)	MPE Limit (mW)
BLE	10.33	10.78	11	-1	10	10	3060

Note: The BLE estimation distance is 20 cm

Conclusion: MPE evaluation required since transmitter power is below FCC threshold

2.3. Requirement-UWB

1mW test exemption allowed with 6-8.5 GHz UWB in multi-transmitter end products

Mode	Output power (dBm)	Output power (mW)	tune up power (dBm)	MPE Values (mW)	MPE Limit (mW)
UWB	-9.57	0.11	-9	0.13	1

Then SAR evaluation is not required.

Estimtion Result

BLE and UWB choose the maximum transmission power, the Simultaneous transmit evaluation result: $BLE+UWB=10/3060+0.13/1=0.13<1$.

END OF REPORT