



REPORT No.: SZ24080214W02

TEST REPORT

APPLICANT : Allied Universal Electronic
Monitoring US, Inc.

PRODUCT NAME : Smartwatch

MODEL NAME : NC3-6605AVL

BRAND NAME : aWatch

FCC ID : NC3-6605AVL

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2024-11-07

TEST DATE : 2024-11-14 to 2025-06-17

ISSUE DATE : 2025-07-15

Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
2. General Description	9
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	11
2.4. Test Configuration of EUT	12
2.5. Test Conditions	12
2.6. Test Setup Layout Diagram	12
3. Test Results	15
3.1. Antenna Requirement	15
3.2. Hopping Mechanism	16
3.3. Number of Hopping Frequency	17
3.4. Duty Cycle of Test Signal	18
3.5. Maximum Peak Conducted Output Power	19
3.6. Maximum Average Conducted Output Power	20
3.7. 20 dB Bandwidth	21
3.8. Carried Frequency Separation	22
3.9. Time of Occupancy (Dwell time)	23
3.10. Conducted Spurious Emissions and Band Edge	24
3.11. Conducted Emission	25
3.12. Restricted Frequency Bands	26
3.13. Radiated Emission	27



Annex A Test Data and Result..... 29

Change History		
Version	Date	Reason for change
1.0	2025-07-15	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	15.247(a) 15.247(h)	Hopping Mechanism	N/A	N/A	PASS	/
3	15.247(a)	Number of Hopping Frequency	Nov. 25, 2025	Li Xinpeng	PASS	/
4	ANSI C63.10	Duty Cycle	Nov. 18, 2025	Li Xinpeng	PASS	/
5	15.247(b)	Maximum Peak Conducted Output Power	Nov. 18, 2025	Li Xinpeng	PASS	/
6	15.247(b)	Maximum Average Conducted Output Power	Nov. 18, 2025	Li Xinpeng	PASS	/
7	15.247(a)	20dB Bandwidth	Nov. 18, 2025	Li Xinpeng	PASS	/
8	15.247(a)	Carrier Frequency Separation	Nov. 25, 2025	Li Xinpeng	PASS	/
9	15.247(a)	Time of Occupancy (Dwell time)	Nov. 25, 2025	Li Xinpeng	PASS	/
10	15.247(d)	Conducted Spurious Emission and Band Edge	Nov. 25, 2025	Li Xinpeng	PASS	/
11	15.207	Conducted Emission	Jun. 17, 2025	Fan Shengquan	PASS	/
12	15.247(d)	Restricted Frequency Bands	Jun. 17, 2025	Gao Jianrou	PASS	/
13	15.209, 15.247(d)	Radiated Emission	Jun. 14&17, 2025	Gao Jianrou	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013, KDB 558074 D01 v05r02 and DA 00-075.



Note 2: Any additions, deviation, or exclusions from the method shall be noted in the "Remark".

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2024.02.19	2025.02.18
				2025.01.15	2026.01.14
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2024.01.25	2025.01.24
				2025.01.06	2026.01.05
LISN	8127449	NSLK 8127	Schwarzbeck	2024.03.19	2025.03.20
				2025.03.20	2026.03.19
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2024.07.02	2025.07.01

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2024.06.03	2025.06.02
				2025.05.16	2026.05.15
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2024.07.03	2025.07.02
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.11.30	2025.11.29



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Number of Hopping Frequency	±5%	Confidence levels of 95%
Peak Output Power	±2.22dB	Confidence levels of 95%
Bandwidth	±5%	Confidence levels of 95%
Carrier Frequency Separation	±5%	Confidence levels of 95%
Time of Occupancy (Dwell time)	±5%	Confidence levels of 95%
Conducted Spurious Emission	±2.77dB	Confidence levels of 95%
Restricted Frequency Bands	±5%	Confidence levels of 95%
Radiated Emission	±2.95dB	Confidence levels of 95%
Conducted Emission	±2.44dB	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Allied Universal Electronic Monitoring US, Inc.
Applicant Address:	1838 Gunn Highway, Odessa, Florida, United States, 33556
Manufacturer:	Rhino Mobility LLC
Manufacturer Address:	8 The Green, Suite A, Dover, Delaware, 19901, USA

2.2. Information of EUT

Product Name:	Smartwatch	
Sample No.:	2#, 6#, 7#	
Hardware Version:	Wear_TickTock-MB V02	
Software Version:	V2_004_20250613	
Equipment Type:	Bluetooth classic	
Bluetooth Version:	5.3	
Modulation Type:	FHSS (GFSK(1Mbps), $\pi/4$ -DQPSK(EDR 2Mbps), 8-DPSK(EDR 3Mbps))	
Operating Frequency Range:	2402MHz-2480MHz	
Antenna Type:	LDS Antenna	
Antenna Gain:	-2.45dBi	
Accessory Information:	Battery	
	Brand Name:	NA
	Model No.:	BPV2
	Serial No.:	N/A
	Capacity:	920mAh
	Rated Voltage:	3.87V
	Charge Limit:	4.45V
	Manufacturer:	Phenix New Energy (Huizhou) Co., Ltd.
	AC Adapter	
	Brand Name:	RHINO
	Model No.:	TPA-10S120150UU01
	Serial No.:	N/A
	Rated Output:	3.6-6.0V $\Rightarrow$ 3.0A, 6.0-9.0V $\Rightarrow$ 2.0A, 9.0-12.0V $\Rightarrow$ 1.5A



REPORT No.: SZ24080214W02

	Rated Input:	100-240V~50/60Hz, 0.6A
	Manufacturer:	Shenzhen Tianyin Electronics Co., Ltd.
	USB Cable	
	Model No.:	USB A/M TO POGO PIN*4 OD 3.2 Black L=2M
	Manufacturer:	JIANGXI JIEYE Electronics Co., Ltd.

Note 1: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.3.Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT


Test mode is used to control the EUT under the maximum power level during test.

2.5. Test Conditions

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement



2.6.2. Conducted Emission Measurement



2.6.3.Radiation Measurement

1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☐ PCB Antenna ☐ PIFA Antenna ☒ LDS Antenna	☐ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☒ Metal Shrapnel ☐ Layout



3.2. Hopping Mechanism

3.2.1. Requirement

According to FCC section 15.247(a)(1), a frequency hopping spread spectrum system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

According to FCC section 15.247(h), the incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

3.2.2. Test Result

The hopping mechanism of the EUT is in compliance with the document "**Bluetooth core specification v5.1**".



3.3. Number of Hopping Frequency

3.3.1. Requirement

According to FCC section 15.247(a)(1)(iii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 15 hopping frequencies.

3.3.2. Test Procedures

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.1 in this report.



3.4. Duty Cycle of Test Signal

3.4.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.4.2. Test Result

Refer to Annex A.2 in this report.



3.5. Maximum Peak Conducted Output Power

3.5.1. Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.5.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.5.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.4. Test Result

Refer to Annex A.3 in this report.



3.6. Maximum Average Conducted Output Power

3.6.1. Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.6.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.4 in this report.



3.7.20 dB Bandwidth

3.7.1.Requirement

According to FCC section 15.247(a)(1), the 20 dB bandwidth is known as the 99% emission bandwidth, or 20 dB bandwidth ($10 \cdot \log 1\% = 20 \text{ dB}$) taking the total RF output power.

3.7.1.Test Procedures

Use the following spectrum analyzer settings:

Span = between 2 to 5 times the OBW, centered on the test channel

RBW= 1% to 5% of the OBW

VBW $\geq 3 \times$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

3.7.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.3.Test Result

Refer to Annex A.5 in this report.



3.8. Carried Frequency Separation

3.8.1. Requirement

According to FCC section 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

3.8.2. Test Procedures

The EUT must have its hopping function enabled. According to DA 00-705, use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.8.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.8.4. Test Result

Refer to Annex A.6 in this report.



3.9. Time of Occupancy (Dwell time)

3.9.1. Requirement

According to FCC section 15.247(a) (1) (iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.9.2. Test Procedures

Normal Mode:

DH1: Dwell time equal to Pulse time (ms) $\times (1600 / 2 / 79) \times 31.6$ Millisecond
DH3: Dwell time equal to Pulse time (ms) $\times (1600 / 4 / 79) \times 31.6$ Millisecond
DH5: Dwell time equal to Pulse Time (ms) $\times (1600 / 6 / 79) \times 31.6$ Millisecond

AFH Mode:

DH1: Dwell time equal to Pulse time (ms) $\times (800 / 2 / 20) \times (0.4 \times 20)$ Millisecond
DH3: Dwell time equal to Pulse time (ms) $\times (800 / 4 / 20) \times (0.4 \times 20)$ Millisecond
DH5: Dwell time equal to Pulse Time (ms) $\times (800 / 6 / 20) \times (0.4 \times 20)$ Millisecond.

3.9.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.9.4. Test Result

Refer to Annex A.7 in this report.



3.10. Conducted Spurious Emissions and Band Edge

3.10.1.Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.10.2.Test Procedures

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

3.10.3.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.10.4.Test Result

Refer to Annex A.8 and A.9 in this report.

3.11. Conducted Emission

3.11.1.Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.11.2.Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.11.3.Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.11.4.Test Result

Refer to Annex A.10 in this report.

3.12. Restricted Frequency Bands

3.12.1.Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.12.2.Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.12.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.12.4.Test Result

Refer to Annex A.11 in this report.

3.13. Radiated Emission

3.13.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2:For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.13.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.13.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.13.4.Test Result

Refer to Annex A.12 in this report.




Annex A Test Data and Result

A.1. Number of Hopping Frequency


Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH5	Ant1	79	15	Pass
NVNT	2-DH5	Ant1	79	15	Pass
NVNT	3-DH5	Ant1	79	15	Pass

Test Graphs

Hopping No. NVNT 1-DH5 2441MHz Ant1




Hopping No. NVNT 2-DH5 2441MHz Ant1





Hopping No. NVNT 3-DH5 2441MHz Ant1




**A.2. Duty Cycle of Test Signal**


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	1-DH5	2402	Ant1	76.96	1.14	0.35
NVNT	1-DH5	2441	Ant1	77.01	1.13	0.35
NVNT	1-DH5	2480	Ant1	77.01	1.13	0.35
NVNT	2-DH5	2402	Ant1	77.01	1.13	0.35
NVNT	2-DH5	2441	Ant1	77.01	1.13	0.35
NVNT	2-DH5	2480	Ant1	77.07	1.13	0.35
NVNT	3-DH5	2402	Ant1	77.07	1.13	0.35
NVNT	3-DH5	2441	Ant1	77.07	1.13	0.35
NVNT	3-DH5	2480	Ant1	77.07	1.13	0.35

Test Graphs


Duty Cycle NVNT 1-DH5 2402MHz Ant1




Duty Cycle NVNT 1-DH5 2441MHz Ant1



Duty Cycle NVNT 1-DH5 2480MHz Ant1




Duty Cycle NVNT 2-DH5 2402MHz Ant1






Duty Cycle NVNT 2-DH5 2441MHz Ant1




Duty Cycle NVNT 2-DH5 2480MHz Ant1






Duty Cycle NVNT 3-DH5 2402MHz Ant1




Duty Cycle NVNT 3-DH5 2441MHz Ant1





Duty Cycle NVNT 3-DH5 2480MHz Ant1



**A.3. Maximum Peak Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	8.26	0	8.26	0.0067	30	Pass
NVNT	1-DH5	2441	Ant1	8.62	0	8.62	0.00728	30	Pass
NVNT	1-DH5	2480	Ant1	6.83	0	6.83	0.00482	30	Pass
NVNT	2-DH5	2402	Ant1	7.49	0	7.49	0.00561	30	Pass
NVNT	2-DH5	2441	Ant1	7.79	0	7.79	0.00601	30	Pass
NVNT	2-DH5	2480	Ant1	6.05	0	6.05	0.00403	30	Pass
NVNT	3-DH5	2402	Ant1	7.76	0	7.76	0.00597	30	Pass
NVNT	3-DH5	2441	Ant1	8.07	0	8.07	0.00641	30	Pass
NVNT	3-DH5	2480	Ant1	6.35	0	6.35	0.00432	30	Pass

Test Graphs


Peak Power NVNT 1-DH5 2402MHz Ant1




Peak Power NVNT 1-DH5 2441MHz Ant1




Peak Power NVNT 1-DH5 2480MHz Ant1




Peak Power NVNT 2-DH5 2402MHz Ant1




Peak Power NVNT 2-DH5 2441MHz Ant1




Peak Power NVNT 2-DH5 2480MHz Ant1



Peak Power NVNT 3-DH5 2402MHz Ant1




Peak Power NVNT 3-DH5 2441MHz Ant1





Peak Power NVNT 3-DH5 2480MHz Ant1



**A.4. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	6.64	1.14	7.78	0.006	30	Pass
NVNT	1-DH5	2441	Ant1	6.55	1.13	7.68	0.00586	30	Pass
NVNT	1-DH5	2480	Ant1	5.56	1.13	6.69	0.00467	30	Pass
NVNT	2-DH5	2402	Ant1	4.12	1.13	5.25	0.00335	30	Pass
NVNT	2-DH5	2441	Ant1	3.98	1.13	5.11	0.00324	30	Pass
NVNT	2-DH5	2480	Ant1	2.24	1.13	3.37	0.00217	30	Pass
NVNT	3-DH5	2402	Ant1	3.85	1.13	4.98	0.00315	30	Pass
NVNT	3-DH5	2441	Ant1	4.31	1.13	5.44	0.0035	30	Pass
NVNT	3-DH5	2480	Ant1	2.11	1.13	3.24	0.00211	30	Pass



Test Graphs

Average Power NVNT 1-DH5 2402MHz Ant1



Average Power NVNT 1-DH5 2441MHz Ant1



Average Power NVNT 1-DH5 2480MHz Ant1




Average Power NVNT 2-DH5 2402MHz Ant1





Average Power NVNT 2-DH5 2441MHz Ant1



Average Power NVNT 2-DH5 2480MHz Ant1





Average Power NVNT 3-DH5 2402MHz Ant1




Average Power NVNT 3-DH5 2441MHz Ant1





Average Power NVNT 3-DH5 2480MHz Ant1



**A.5. 20 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)
NVNT	1-DH5	2402	Ant1	0.934
NVNT	1-DH5	2441	Ant1	0.94
NVNT	1-DH5	2480	Ant1	0.94
NVNT	2-DH5	2402	Ant1	1.332
NVNT	2-DH5	2441	Ant1	1.309
NVNT	2-DH5	2480	Ant1	1.316
NVNT	3-DH5	2402	Ant1	1.31
NVNT	3-DH5	2441	Ant1	1.3
NVNT	3-DH5	2480	Ant1	1.302



Test Graphs

-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1






-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1




-20dB Bandwidth NVNT 3-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2480MHz Ant1



**A.6. Carried Frequency Separation**

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	Ant1	2401.968	2402.97	1.002	0.623	Pass
NVNT	1-DH5	Ant1	2441.014	2442.018	1.004	0.627	Pass
NVNT	1-DH5	Ant1	2478.976	2480.02	1.044	0.627	Pass
NVNT	2-DH5	Ant1	2402.02	2403.014	0.994	0.888	Pass
NVNT	2-DH5	Ant1	2441.018	2442.022	1.004	0.873	Pass
NVNT	2-DH5	Ant1	2479.028	2480.022	0.994	0.877	Pass
NVNT	3-DH5	Ant1	2401.912	2403.02	1.108	0.873	Pass
NVNT	3-DH5	Ant1	2441.03	2442.028	0.998	0.867	Pass
NVNT	3-DH5	Ant1	2479.024	2480.026	1.002	0.868	Pass

Test Graphs

CFS NVNT 1-DH5 2402MHz Ant1



CFS NVNT 1-DH5 2441MHz Ant1






CFS NVNT 1-DH5 2480MHz Ant1




CFS NVNT 2-DH5 2402MHz Ant1






CFS NVNT 2-DH5 2441MHz Ant1




CFS NVNT 2-DH5 2480MHz Ant1






CFS NVNT 3-DH5 2402MHz Ant1




CFS NVNT 3-DH5 2441MHz Ant1





CFS NVNT 3-DH5 2480MHz Ant1




**A.7. Time of Occupancy (Dwell time)**


Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH5	2402	Ant1	2.885	328.89	114	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.885	288.5	100	31600	400	Pass
NVNT	1-DH5	2480	Ant1	2.885	300.04	104	31600	400	Pass
NVNT	2-DH5	2402	Ant1	2.878	342.482	119	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.878	305.068	106	31600	400	Pass
NVNT	2-DH5	2480	Ant1	2.887	337.779	117	31600	400	Pass
NVNT	3-DH5	2402	Ant1	2.885	317.35	110	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.884	331.66	115	31600	400	Pass
NVNT	3-DH5	2480	Ant1	2.888	311.904	108	31600	400	Pass

Test Graphs


Dwell NVNT 1-DH5 2402MHz Ant1 One Burst




Dwell NVNT 1-DH5 2402MHz Ant1 Accumulated




Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated





Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555


Fax: 86-755-36698525

[Http://www.morlab.cn](http://www.morlab.cn)


E-mail: service@morlab.cn



Dwell NVNT 2-DH5 2402MHz Ant1 One Burst




Dwell NVNT 2-DH5 2402MHz Ant1 Accumulated





Dwell NVNT 2-DH5 2441MHz Ant1 One Burst




Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated







Dwell NVNT 2-DH5 2480MHz Ant1 One Burst




Dwell NVNT 2-DH5 2480MHz Ant1 Accumulated



Dwell NVNT 3-DH5 2402MHz Ant1 One Burst




Dwell NVNT 3-DH5 2402MHz Ant1 Accumulated






Dwell NVNT 3-DH5 2441MHz Ant1 One Burst




Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated






Dwell NVNT 3-DH5 2480MHz Ant1 One Burst



Dwell NVNT 3-DH5 2480MHz Ant1 Accumulated



**A.8. Conducted Spurious Emissions**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	-57.25	-20	Pass
NVNT	1-DH5	2441	Ant1	-56.9	-20	Pass
NVNT	1-DH5	2480	Ant1	-54.63	-20	Pass
NVNT	2-DH5	2402	Ant1	-54.72	-20	Pass
NVNT	2-DH5	2441	Ant1	-54.51	-20	Pass
NVNT	2-DH5	2480	Ant1	-52.39	-20	Pass
NVNT	3-DH5	2402	Ant1	-54.66	-20	Pass
NVNT	3-DH5	2441	Ant1	-55.01	-20	Pass
NVNT	3-DH5	2480	Ant1	-52.58	-20	Pass

Test Graphs

Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission



Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission



Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission



Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Emission






Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Emission



**A.9. Band Edge**


Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	No-Hopping	-60.16	-20	Pass
NVNT	1-DH5	2480	Ant1	No-Hopping	-60.93	-20	Pass
NVNT	2-DH5	2402	Ant1	No-Hopping	-55.56	-20	Pass
NVNT	2-DH5	2480	Ant1	No-Hopping	-58.85	-20	Pass
NVNT	3-DH5	2402	Ant1	No-Hopping	-58.36	-20	Pass
NVNT	3-DH5	2480	Ant1	No-Hopping	-57.38	-20	Pass
NVNT	1-DH5	2402	Ant1	Hopping	-63.06	-20	Pass
NVNT	1-DH5	2480	Ant1	Hopping	-61.82	-20	Pass
NVNT	2-DH5	2402	Ant1	Hopping	-59.18	-20	Pass
NVNT	2-DH5	2480	Ant1	Hopping	-59.39	-20	Pass
NVNT	3-DH5	2402	Ant1	Hopping	-59.63	-20	Pass
NVNT	3-DH5	2480	Ant1	Hopping	-58.76	-20	Pass

Test Graphs

Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Ref




Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref




Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Emission




Test Graphs

Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission







Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission






Page 92 of 114

Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Emission



**A.10. Conducted Emission**

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Adapter+Data Cable+Router+SIM Card+BT TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1815	42.61	24.15	64.42	54.42	Line	PASS
2	0.3300	28.34	21.99	59.45	49.45		PASS
3	0.6225	30.02	22.04	56.00	46.00		PASS
4	1.1535	26.91	21.24	56.00	46.00		PASS
5	1.6486	24.05	18.09	56.00	46.00		PASS
6	14.2028	32.50	18.04	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1545	48.32	27.41	65.75	55.75	Neutral	PASS
2	0.2265	37.65	23.55	62.58	52.58		PASS
3	0.6269	38.48	34.53	56.00	46.00		PASS
4	0.8971	26.49	20.89	56.00	46.00		PASS
5	1.7744	24.95	18.74	56.00	46.00		PASS
6	14.3741	30.10	19.25	60.00	50.00		PASS


A.11. Restricted Frequency Bands

Note 1: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Horizontal) was recorded in this test report.

Note 2: All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.

GFSK Mode


Plot for Channel 0



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2365.97	20.6	58.10	37.470	74.00	15.90	150	275	PK	PASS
2374.15	8.6	46.06	37.480	54.00	7.94	150	322	AV	PASS
2382.94	20.6	58.09	37.480	74.00	15.91	150	223	PK	PASS
2384.53	8.5	45.96	37.490	54.00	8.04	150	247	AV	PASS
2387.94	20.6	58.12	37.490	74.00	15.88	150	1	PK	PASS
2388.13	8.7	46.16	37.490	54.00	7.84	150	336	AV	PASS




Plot for Channel 78



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2484.01	20.5	58.76	38.270	74.00	15.24	150	260	PK	PASS
2484.63	8.5	46.78	38.270	54.00	7.22	150	335	AV	PASS
2485.62	21.1	59.39	38.270	74.00	14.61	150	56	PK	PASS
2485.76	8.3	46.60	38.270	54.00	7.40	150	357	AV	PASS
2487.61	8.2	46.44	38.270	54.00	7.56	150	9	AV	PASS
2493.90	21.0	59.28	38.250	74.00	14.72	150	9	PK	PASS

**8-DPSK Mode**


Plot for Channel 0



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2375.56	21.2	58.70	37.480	74.00	15.30	150	122	PK	PASS
2378.91	20.8	58.24	37.480	74.00	15.76	150	267	PK	PASS
2379.89	8.6	46.03	37.480	54.00	7.97	150	56	AV	PASS
2384.22	8.5	45.94	37.490	54.00	8.06	150	126	AV	PASS
2386.79	20.7	58.19	37.490	74.00	15.81	150	253	PK	PASS
2388.92	8.6	46.12	37.490	54.00	7.88	150	70	AV	PASS



Plot for Channel 78



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2484.08	20.2	58.51	38.270	74.00	15.49	150	194	PK	PASS
2484.39	8.3	46.59	38.270	54.00	7.41	150	355	AV	PASS
2485.78	8.2	46.42	38.270	54.00	7.58	150	104	AV	PASS
2487.06	21.1	59.38	38.270	74.00	14.62	150	24	PK	PASS
2488.16	8.1	46.40	38.270	54.00	7.60	150	2	AV	PASS
2493.64	20.5	58.73	38.260	74.00	15.27	150	141	PK	PASS



A.12. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 4: All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.

Field strength of fundamental:


Frequency [MHz]	Reading [dB μ V]	Level [dB μ V/m]	Factor [dB/m]	Limit [dB μ V/m]	Detector	Polarity
2401.80	61.8	99.35	37.530	-	PK	Horizontal

The field strength (the lowest) of fundamenta is more than 20dB higher than the unwanted emissions, in accordance with FCC part 15.215(b).




GFSK Mode

Plot for Channel 0




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.32	64.4	35.94	-28.460	40.00	4.06	150	360	PK	PASS
100.52	65.0	35.33	-29.690	43.50	8.17	150	85	PK	PASS
152.57	66.5	34.24	-32.210	43.50	9.26	150	98	PK	PASS
194.86	64.6	35.31	-29.280	43.50	8.19	150	92	PK	PASS
235.41	62.8	34.93	-27.910	46.00	11.07	150	194	PK	PASS
717.81	48.5	32.84	-15.640	46.00	13.16	150	153	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1161.63	49.7	47.91	-1.760	74.00	26.09	150	96	PK	PASS
1166.03	34.9	33.21	-1.690	54.00	20.79	150	89	AV	PASS
2391.48	40.9	46.10	5.200	74.00	27.90	150	257	PK	PASS
2402.28	30.3	35.59	5.250	54.00	18.41	150	294	AV	PASS
3990.03	52.2	44.08	-8.070	74.00	29.92	150	78	PK	PASS
3997.31	43.5	35.39	-8.130	54.00	18.61	150	98	AV	PASS
4803.91	47.6	42.45	-5.150	74.00	31.55	150	259	PK	PASS
4804.34	43.0	37.83	-5.140	54.00	16.17	150	259	AV	PASS
7206.12	37.7	42.73	5.030	54.00	11.27	150	42	AV	PASS
7206.12	44.2	49.21	5.030	74.00	24.79	150	259	PK	PASS
14678.91	36.2	56.69	20.540	74.00	17.31	150	278	PK	PASS
14688.76	27.7	48.28	20.570	54.00	5.72	150	98	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.76	60.1	31.94	-28.190	40.00	8.06	150	297	PK	PASS
99.02	63.9	34.24	-29.610	43.50	9.26	150	126	PK	PASS
195.68	61.7	32.53	-29.210	43.50	10.97	150	1	PK	PASS
272.51	61.5	34.94	-26.550	46.00	11.06	150	229	PK	PASS
399.93	48.9	26.60	-22.260	46.00	19.40	150	173	PK	PASS
720.00	43.7	28.03	-15.670	46.00	17.97	150	243	PK	PASS




(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1164.43	50.6	48.87	-1.720	74.00	25.13	150	111	PK	PASS
1164.43	38.1	36.36	-1.720	54.00	17.64	150	147	AV	PASS
1996.60	32.6	35.24	2.600	54.00	18.76	150	140	AV	PASS
1999.80	46.4	49.07	2.640	74.00	24.93	150	125	PK	PASS
3993.89	59.6	51.44	-8.110	74.00	22.56	150	60	PK	PASS
3995.17	48.9	40.74	-8.110	54.00	13.26	150	60	AV	PASS
7205.69	44.2	49.25	5.030	74.00	24.75	150	0	PK	PASS
7206.55	39.0	44.05	5.020	54.00	9.95	150	278	AV	PASS
10726.51	32.0	44.22	12.200	54.00	9.78	150	133	AV	PASS
11095.09	39.4	53.37	14.020	74.00	20.63	150	351	PK	PASS
14684.48	26.8	47.35	20.560	54.00	6.65	150	351	AV	PASS
14688.33	36.7	57.27	20.570	74.00	16.73	150	169	PK	PASS




Plot for Channel 39




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.76	63.4	35.18	-28.190	40.00	4.82	150	360	PK	PASS
105.32	65.5	36.21	-29.300	43.50	7.29	150	77	PK	PASS
151.89	64.6	32.53	-32.040	43.50	10.97	150	98	PK	PASS
195.59	63.5	34.26	-29.200	43.50	9.24	150	70	PK	PASS
235.36	62.6	34.66	-27.910	46.00	11.34	150	201	PK	PASS
719.95	48.4	32.76	-15.670	46.00	13.24	150	153	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1329.27	34.1	33.25	-0.880	54.00	20.75	150	132	AV	PASS
1330.47	46.8	45.95	-0.870	74.00	28.05	150	132	PK	PASS
2441.09	45.9	51.75	5.840	-	-	150	308	PK	NA
2441.49	44.5	50.31	5.840	-	-	150	308	AV	NA
3485.59	53.4	43.67	-9.700	74.00	30.33	150	43	PK	PASS
3486.01	42.3	32.58	-9.710	54.00	21.42	150	61	AV	PASS
4882.34	44.4	39.40	-5.020	54.00	14.60	150	258	AV	PASS
4882.34	48.5	43.50	-5.020	74.00	30.50	150	258	PK	PASS
11148.23	30.8	44.59	13.790	54.00	9.41	150	258	AV	PASS
11163.23	40.3	54.01	13.700	74.00	19.99	150	26	PK	PASS
14683.62	36.1	56.66	20.560	74.00	17.34	150	314	PK	PASS
14686.19	26.8	47.34	20.560	54.00	6.66	150	97	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.85	59.7	31.58	-28.130	40.00	8.42	150	296	PK	PASS
61.14	57.3	28.52	-28.790	40.00	11.48	150	119	PK	PASS
100.04	63.5	33.90	-29.600	43.50	9.60	150	180	PK	PASS
194.76	59.6	30.23	-29.360	43.50	13.27	150	11	PK	PASS
271.98	61.1	34.46	-26.650	46.00	11.54	150	248	PK	PASS
480.05	50.7	29.54	-21.180	46.00	16.46	150	139	PK	PASS




(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1196.84	50.9	49.77	-1.150	74.00	24.23	150	118	PK	PASS
1197.24	38.7	37.57	-1.140	54.00	16.43	150	111	AV	PASS
2441.09	40.3	46.10	5.840	-	-	150	141	PK	NA
2441.49	36.3	42.14	5.840	-	-	150	156	AV	NA
3984.03	58.0	49.92	-8.030	74.00	24.08	150	96	PK	PASS
3984.03	46.1	38.08	-8.030	54.00	15.92	150	113	AV	PASS
5309.64	51.1	48.44	-2.640	74.00	25.56	150	171	PK	PASS
5310.07	40.3	37.70	-2.640	54.00	16.30	150	188	AV	PASS
7196.69	45.0	50.07	5.080	74.00	23.93	150	77	PK	PASS
14617.62	36.0	56.39	20.390	74.00	17.61	150	113	PK	PASS
14677.19	27.2	47.72	20.540	54.00	6.28	150	224	AV	PASS




Plot for Channel 78




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.80	63.3	35.15	-28.160	40.00	4.85	150	348	PK	PASS
100.33	65.5	35.82	-29.660	43.50	7.68	150	50	PK	PASS
152.32	65.4	33.28	-32.140	43.50	10.22	150	97	PK	PASS
195.44	62.9	33.75	-29.180	43.50	9.75	150	83	PK	PASS
235.60	63.2	35.25	-27.910	46.00	10.75	150	211	PK	PASS
722.23	47.3	31.69	-15.560	46.00	14.31	150	144	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1329.67	32.5	31.60	-0.880	54.00	22.40	150	128	AV	PASS
1330.47	45.7	44.78	-0.870	74.00	29.22	150	123	PK	PASS
2469.09	39.6	45.48	5.920	74.00	28.52	150	150	PK	PASS
2480.30	32.4	38.27	5.890	-	-	150	299	AV	NA
3984.89	55.0	46.94	-8.030	74.00	27.06	150	192	PK	PASS
3985.31	41.2	33.15	-8.030	54.00	20.85	150	192	AV	PASS
4960.34	49.5	44.93	-4.610	54.00	9.07	150	285	AV	PASS
4960.34	52.2	47.62	-4.610	74.00	26.38	150	272	PK	PASS
11060.37	39.9	53.50	13.570	74.00	20.50	150	297	PK	PASS
11098.09	30.5	44.59	14.050	54.00	9.41	150	312	AV	PASS
14678.05	35.9	56.39	20.540	74.00	17.61	150	257	PK	PASS
14777.91	27.9	47.77	19.920	54.00	6.23	150	351	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.80	59.4	31.23	-28.160	40.00	8.77	150	337	PK	PASS
100.67	63.5	33.79	-29.720	43.50	9.71	150	214	PK	PASS
145.19	60.3	28.74	-31.520	43.50	14.76	150	76	PK	PASS
195.54	60.3	31.14	-29.190	43.50	12.36	150	330	PK	PASS
271.93	61.3	34.59	-26.660	46.00	11.41	150	221	PK	PASS
719.95	43.8	28.08	-15.670	46.00	17.92	150	241	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1196.84	38.3	37.10	-1.150	54.00	16.90	150	129	AV	PASS
1199.64	51.5	50.44	-1.090	74.00	23.56	150	129	PK	PASS
2656.33	48.7	54.99	6.270	74.00	19.01	150	75	PK	PASS
2663.13	33.9	40.09	6.240	54.00	13.91	150	75	AV	PASS
3986.60	45.3	37.29	-8.050	54.00	16.71	150	57	AV	PASS
3996.03	57.5	49.41	-8.120	74.00	24.59	150	111	PK	PASS
4960.34	44.0	39.41	-4.610	54.00	14.59	150	218	AV	PASS
4960.77	48.2	43.62	-4.600	74.00	30.38	150	218	PK	PASS
7197.98	46.6	51.66	5.100	74.00	22.34	150	111	PK	PASS
7198.41	36.7	41.81	5.110	54.00	12.19	150	124	AV	PASS
14733.76	27.0	47.35	20.310	54.00	6.65	150	311	AV	PASS
14750.05	36.6	56.72	20.170	74.00	17.28	150	245	PK	PASS

————— END OF REPORT —————