



REPORT No.: SZ24080214W03

TEST REPORT

APPLICANT : Allied Universal Electronic
Monitoring US, Inc.

PRODUCT NAME : Smartwatch

MODEL NAME : NC3-6605AVL

BRAND NAME : aWatch

FCC ID : NC3-6605AVL

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2024-11-07


TEST DATE : 2024-11-14 to 2025-06-17

ISSUE DATE : 2025-07-15

Edited by:


Zeng Xiaoying (Rapporteur)

Approved by:


Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	4
1.2. Test Equipment List	5
1.3. Measurement Uncertainty	7
1.4. Testing Laboratory	7
2. General Description	8
2.1. Information of Applicant and Manufacturer	8
2.2. Information of EUT	8
2.3. Channel List of EUT	9
2.4. Test Configuration of EUT	10
2.5. Test Conditions	10
2.6. Test Setup Layout Diagram	11
3. Test Results	14
3.1. Antenna Requirement	14
3.2. Duty Cycle of Test Signal	15
3.3. Maximum Peak and Average Conducted Output Power	16
3.4. 6 dB Bandwidth	17
3.5. Conducted Spurious Emissions and Band Edge	18
3.6. Power Spectral Density	19
3.7. Conducted Emission	20
3.8. Restricted Frequency Bands	21
3.9. Radiated Emission	22
Annex A Test Data and Result	24



REPORT No.: SZ24080214W03

Change History		
Version	Date	Reason for change
1.0	2025-07-15	First edition

1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	N/A	Duty Cycle of Test Signal	Nov. 18, 2025	Li Xinpeng	PASS	/
3	15.247(b)	Maximum Peak Conducted Output Power	Nov. 18, 2025	Li Xinpeng	PASS	/
4	15.247(b)	Maximum Average Conducted Output Power	Nov. 18, 2025	Li Xinpeng	PASS	/
5	15.247(a)	Bandwidth	Nov. 18, 2025	Li Xinpeng	PASS	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	Nov. 25, 2025	Li Xinpeng	PASS	/
7	15.247(e)	Power Spectral Density	Nov. 25, 2025	Li Xinpeng	PASS	/
8	15.207	Conducted Emission	Jun. 17, 2025	Fan Shengquan	PASS	/
9	15.247(d)	Restricted Frequency Bands	Jun. 17, 2025	Gao Jianrou	PASS	/
10	15.209, 15.247(d)	Radiated Emission	Jun. 14&17, 2025	Gao Jianrou	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013 and KDB 558074 D01 v05r02.

Note 2: Any additions, deviation, or exclusions from the method shall be noted in the “Remark”.

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2024.02.19	2025.02.18
				2025.01.15	2026.01.14
Power Sensor	MY54180008	U2021XA	Agilent	2024.09.11	2025.09.10
Attenuator	MTJ6004-20	VAT-10+	MTJ Cooperation	N/A	N/A
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2024.01.25	2025.01.24
				2025.01.06	2026.01.05
LISN	8127449	NSLK 8127	Schwarzbeck	2024.03.19	2025.03.20
				2025.03.20	2026.03.19
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2024.07.02	2025.07.01

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2024.06.03	2025.06.02
				2025.05.16	2026.05.15
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2024.07.03	2025.07.02
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.11.30	2025.11.29



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174

2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Allied Universal Electronic Monitoring US, Inc.
Applicant Address:	1838 Gunn Highway, Odessa, Florida, United States, 33556
Manufacturer:	Rhino Mobility LLC
Manufacturer Address:	8 The Green, Suite A, Dover, Delaware, 19901, USA

2.2. Information of EUT

Product Name:	Smartwatch	
Sample No.:	2#, 6#, 7#	
Hardware Version:	Wear_TickTock-MB V02	
Software Version:	V2_004_20250613	
Modulation Technology:	DSSS, OFDM	
Modulation Type:	Refer to section 2.4.1	
Wireless Technology:	802.11b, 802.11g, 802.11n (HT20)	
Operating Frequency Range:	2412MHz-2462MHz	
Antenna Type:	LDS Antenna	
Antenna Gain:	-2.45dBi	
Accessory Information:	Battery	
	Brand Name:	NA
	Model No.:	BPV2
	Serial No.:	N/A
	Capacity:	920mAh
	Rated Voltage:	3.87V
	Charge Limit:	4.45V
	Manufacturer:	Phenix New Energy (Huizhou) Co., Ltd.
	AC Adapter	
	Brand Name:	RHINO
	Model No.:	TPA-10S120150UU01
	Serial No.:	N/A
	Rated Output:	3.6-6.0V=3.0A, 6.0-9.0V=2.0A, 9.0-12.0V=1.5A
	Rated Input:	100-240V~50/60Hz, 0.6A



	Manufacturer:	Shenzhen Tianyin Electronics Co., Ltd.
	USB Cable	
	Model No.:	USB A/M TO POGO PIN*4 OD 3.2 Black L=2M
	Manufacturer:	JIANGXI JIEYE Electronics Co., Ltd.

Note 1: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.3.Channel List of EUT

Nominal Channel Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432		
	6	2437		
	7	2442		

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT

2.4.1. Modulation Type and Data Rate of EUT

Mode	Bandwidth (MHz)	Modulation Technology	Modulation Type	Data Rate
802.11b	20	DSSS	DBPSK	1/2/5.5/11Mbps
			DQPSK	
			CCK	
802.11g	20	OFDM	BPSK	6/9/12/18/24/36/48/54Mbps
			QPSK	
			16QAM	
			64QAM	
802.11n	20 (HT20)	OFDM	BPSK	MCS0~MCS7
			QPSK	
			16QAM	
			64QAM	

Note1: The worst-case mode (bold face) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.


Note2: The RF signal transmission of EUT is controlled by the build-in engineering mode which is provided by the manufacturer. The recorded power setting value is the maximum that the engineering mode has configuration during testing.

2.5. Test Conditions


Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☐ PCB Antenna ☐ PIFA Antenna ☒ LDS Antenna	☐ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☒ Metal Shrapnel ☐ Layout

3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak and Average Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 and A.3 in this report.



3.4.6 dB Bandwidth

3.4.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.4.1.Test Procedures

KDB 558074 Section 8.2 was used in order to prove compliance.

3.4.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.3.Test Result

Refer to Annex A.4 in this report.



3.5. Conducted Spurious Emissions and Band Edge

3.5.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.5.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.5.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.6. Power Spectral Density

3.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.6.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 30kHz
- d) Set VBW to 100kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level and recorded as PD
- j) Use below formula to calculate the Conducted PSD value that at specified RBW:

Conducted PSD = PD - 10lg(30k/3k)

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.7 in this report.

3.7. Conducted Emission

3.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.7.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.7.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.7.4. Test Result

Refer to Annex A.8 in this report.

3.8. Restricted Frequency Bands

3.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.8.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.8.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.8.4. Test Result

Refer to Annex A.9 in this report.

3.9. Radiated Emission

3.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.9.2. Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4. Test Result

Refer to Annex A.10 in this report.




Annex A Test Data and Result

A.1. Duty Cycle of Test Signal


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	Ant1	98.99	0.04	0.08
NVNT	b	2437	Ant1	99.03	0.04	0.08
NVNT	b	2462	Ant1	98.91	0.05	0.08
NVNT	g	2412	Ant1	98.26	0.08	0.49
NVNT	g	2437	Ant1	98.26	0.08	0.49
NVNT	g	2462	Ant1	98.35	0.07	0.49
NVNT	n20	2412	Ant1	98.13	0.08	0.53
NVNT	n20	2437	Ant1	98.13	0.08	0.53
NVNT	n20	2462	Ant1	98.23	0.08	0.53

Test Graphs

Duty Cycle NVNT b 2412MHz Ant1




Duty Cycle NVNT b 2437MHz Ant1



Duty Cycle NVNT b 2462MHz Ant1




Duty Cycle NVNT g 2412MHz Ant1







Duty Cycle NVNT g 2437MHz Ant1




Duty Cycle NVNT g 2462MHz Ant1



Duty Cycle NVNT n20 2412MHz Ant1




Duty Cycle NVNT n20 2437MHz Ant1





Duty Cycle NVNT n20 2462MHz Ant1




**A.2. Maximum Peak Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	b	2412	Ant1	18.75	0	18.75	0.07499	30	Pass
NVNT	b	2437	Ant1	18.83	0	18.83	0.07638	30	Pass
NVNT	b	2462	Ant1	18.82	0	18.82	0.07621	30	Pass
NVNT	g	2412	Ant1	21.58	0	21.58	0.14388	30	Pass
NVNT	g	2437	Ant1	21.62	0	21.62	0.14521	30	Pass
NVNT	g	2462	Ant1	21.55	0	21.55	0.14289	30	Pass
NVNT	n20	2412	Ant1	19.59	0	19.59	0.09099	30	Pass
NVNT	n20	2437	Ant1	19.39	0	19.39	0.0869	30	Pass
NVNT	n20	2462	Ant1	19.5	0	19.5	0.08913	30	Pass

Test Graphs


Peak Power NVNT b 2412MHz Ant1




Peak Power NVNT b 2437MHz Ant1




Peak Power NVNT b 2462MHz Ant1




Peak Power NVNT g 2412MHz Ant1




Peak Power NVNT g 2437MHz Ant1




Peak Power NVNT g 2462MHz Ant1




Peak Power NVNT n20 2412MHz Ant1



Peak Power NVNT n20 2437MHz Ant1






**A.3. Maximum Average Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	b	2412	Ant1	16.23	0.04	16.27	0.04236	30	Pass
NVNT	b	2437	Ant1	16.28	0.04	16.32	0.04285	30	Pass
NVNT	b	2462	Ant1	16.18	0.05	16.23	0.04198	30	Pass
NVNT	g	2412	Ant1	13.76	0.08	13.84	0.02421	30	Pass
NVNT	g	2437	Ant1	13.77	0.08	13.85	0.02427	30	Pass
NVNT	g	2462	Ant1	13.8	0.07	13.87	0.02438	30	Pass
NVNT	n20	2412	Ant1	11.75	0.08	11.83	0.01524	30	Pass
NVNT	n20	2437	Ant1	11.69	0.08	11.77	0.01503	30	Pass
NVNT	n20	2462	Ant1	11.78	0.08	11.86	0.01535	30	Pass

Test Graphs


Average Power NVNT b 2412MHz Ant1




Average Power NVNT b 2437MHz Ant1




Average Power NVNT b 2462MHz Ant1




Average Power NVNT g 2412MHz Ant1




Average Power NVNT g 2437MHz Ant1




Average Power NVNT g 2462MHz Ant1



Average Power NVNT n20 2412MHz Ant1




Average Power NVNT n20 2437MHz Ant1





Average Power NVNT n20 2462MHz Ant1



**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	8.539	0.5	Pass
NVNT	b	2437	Ant1	8.559	0.5	Pass
NVNT	b	2462	Ant1	9.063	0.5	Pass
NVNT	g	2412	Ant1	16.286	0.5	Pass
NVNT	g	2437	Ant1	16.303	0.5	Pass
NVNT	g	2462	Ant1	15.752	0.5	Pass
NVNT	n20	2412	Ant1	17.152	0.5	Pass
NVNT	n20	2437	Ant1	16.526	0.5	Pass
NVNT	n20	2462	Ant1	16.383	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1




-6dB Bandwidth NVNT b 2437MHz Ant1



-6dB Bandwidth NVNT b 2462MHz Ant1



-6dB Bandwidth NVNT g 2412MHz Ant1



-6dB Bandwidth NVNT g 2437MHz Ant1




-6dB Bandwidth NVNT g 2462MHz Ant1







-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2437MHz Ant1



-6dB Bandwidth NVNT n20 2462MHz Ant1



**A.5. Conducted Spurious Emissions**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-37.08	-20	Pass
NVNT	b	2437	Ant1	-36.01	-20	Pass
NVNT	b	2462	Ant1	-37.04	-20	Pass
NVNT	g	2412	Ant1	-30.53	-20	Pass
NVNT	g	2437	Ant1	-30.97	-20	Pass
NVNT	g	2462	Ant1	-31.91	-20	Pass
NVNT	n20	2412	Ant1	-29.65	-20	Pass
NVNT	n20	2437	Ant1	-29.47	-20	Pass
NVNT	n20	2462	Ant1	-29.54	-20	Pass

Test Graphs

Tx. Spurious NVNT b 2412MHz Ant1 Ref




Tx. Spurious NVNT b 2412MHz Ant1 Emission



Tx. Spurious NVNT b 2437MHz Ant1 Ref




Tx. Spurious NVNT b 2437MHz Ant1 Emission




Tx. Spurious NVNT b 2462MHz Ant1 Ref




Tx. Spurious NVNT b 2462MHz Ant1 Emission




Tx. Spurious NVNT g 2412MHz Ant1 Ref




Tx. Spurious NVNT g 2412MHz Ant1 Emission




Tx. Spurious NVNT g 2437MHz Ant1 Ref




Tx. Spurious NVNT g 2437MHz Ant1 Emission




Tx. Spurious NVNT g 2462MHz Ant1 Ref




Tx. Spurious NVNT g 2462MHz Ant1 Emission



Tx. Spurious NVNT n20 2412MHz Ant1 Ref




Tx. Spurious NVNT n20 2412MHz Ant1 Emission



Tx. Spurious NVNT n20 2437MHz Ant1 Ref




Tx. Spurious NVNT n20 2437MHz Ant1 Emission



Tx. Spurious NVNT n20 2462MHz Ant1 Ref



Tx. Spurious NVNT n20 2462MHz Ant1 Emission



**A.6. Band Edge**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-43.27	-20	Pass
NVNT	b	2462	Ant1	-53.62	-20	Pass
NVNT	g	2412	Ant1	-35.42	-20	Pass
NVNT	g	2462	Ant1	-44.33	-20	Pass
NVNT	n20	2412	Ant1	-32.97	-20	Pass
NVNT	n20	2462	Ant1	-45.96	-20	Pass

Test Graphs

Band Edge NVNT b 2412MHz Ant1 Ref



Band Edge NVNT b 2412MHz Ant1 Emission



Band Edge NVNT b 2462MHz Ant1 Ref




Band Edge NVNT b 2462MHz Ant1 Emission



Band Edge NVNT g 2412MHz Ant1 Ref



Band Edge NVNT g 2412MHz Ant1 Emission



Band Edge NVNT g 2462MHz Ant1 Ref




Band Edge NVNT g 2462MHz Ant1 Emission




Band Edge NVNT n20 2412MHz Ant1 Ref




Band Edge NVNT n20 2412MHz Ant1 Emission



Band Edge NVNT n20 2462MHz Ant1 Ref



Band Edge NVNT n20 2462MHz Ant1 Emission



**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	Ant1	-4.66	0	-4.66	8	Pass
NVNT	b	2437	Ant1	-5.69	0	-5.69	8	Pass
NVNT	b	2462	Ant1	-6.06	0	-6.06	8	Pass
NVNT	g	2412	Ant1	-11.03	0	-11.03	8	Pass
NVNT	g	2437	Ant1	-11.25	0	-11.25	8	Pass
NVNT	g	2462	Ant1	-11.08	0	-11.08	8	Pass
NVNT	n20	2412	Ant1	-12.53	0	-12.53	8	Pass
NVNT	n20	2437	Ant1	-13.07	0	-13.07	8	Pass
NVNT	n20	2462	Ant1	-13.52	0	-13.52	8	Pass

Test Graphs

PSD NVNT b 2412MHz Ant1



PSD NVNT b 2437MHz Ant1



PSD NVNT b 2462MHz Ant1




PSD NVNT g 2412MHz Ant1





PSD NVNT g 2437MHz Ant1




PSD NVNT g 2462MHz Ant1





PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2437MHz Ant1







A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Adapter+Data Cable+Router+SIM Card+WIFI TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1905	39.94	24.30	64.01	54.01	Line	PASS
2	0.5055	30.79	22.86	56.00	46.00		PASS
3	0.6225	38.97	30.73	56.00	46.00		PASS
4	0.8431	25.99	20.43	56.00	46.00		PASS
5	1.8330	23.43	17.77	56.00	46.00		PASS
6	14.0991	33.66	19.16	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1815	44.16	25.79	64.42	54.42	Neutral	PASS
2	0.2760	33.25	23.27	60.94	50.94		PASS
3	0.6090	39.46	31.98	56.00	46.00		PASS
4	1.2481	27.67	20.81	56.00	46.00		PASS
5	3.0794	23.90	15.24	56.00	46.00		PASS
6	14.2584	32.32	20.88	60.00	50.00		PASS


A.9. Restricted Frequency Bands

Note 1: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Horizontal) was recorded in this test report.

Note 2 All test modes and bandwidth were considered and evaluated respectively by performing full test, only the worst data were recorded for each bandwidth.


802.11b Mode

Plot for Channel 1



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2372.44	21.4	58.92	37.480	74.00	15.08	150	351	PK	PASS
2379.16	21.2	58.69	37.480	74.00	15.31	150	261	PK	PASS
2379.40	8.6	46.07	37.480	54.00	7.93	150	355	AV	PASS
2384.71	8.8	46.29	37.490	54.00	7.71	150	337	AV	PASS
2387.76	21.7	59.21	37.490	74.00	14.79	150	309	PK	PASS
2389.35	9.0	46.50	37.490	54.00	7.50	150	299	AV	PASS

Plot for Channel 11



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2484.25	8.4	46.64	38.270	54.00	7.36	150	291	AV	PASS
2484.37	20.0	58.26	38.270	74.00	15.74	150	94	PK	PASS
2486.15	8.4	46.66	38.280	54.00	7.34	150	305	AV	PASS
2486.55	20.5	58.74	38.270	74.00	15.26	150	80	PK	PASS
2487.83	8.4	46.65	38.270	54.00	7.35	150	273	AV	PASS
2489.65	21.0	59.24	38.260	74.00	14.76	150	338	PK	PASS



A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note 2 All test modes and bandwidth were considered and evaluated respectively by performing full test, only the worst data were recorded for each bandwidth.

Note 3 For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 4 For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


Field strength of fundamental:

Frequency [MHz]	Reading [dB μ V]	Level [dB μ V/m]	Factor [dB/m]	Limit [dB μ V/m]	Detector	Polarity
2411.99	63.8	101.53	37.700	-	PK	Horizontal

The field strength (the lowest) of fundamenta is more than 20dB higher than the unwanted emissions, in accordance with FCC part 15.215(b).


**802.11b Mode**

Plot for Channel 1




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.90	63.5	35.35	-28.100	40.00	4.65	150	351	PK	PASS
60.90	58.9	30.13	-28.800	40.00	9.87	150	28	PK	PASS
107.51	65.4	36.31	-29.110	43.50	7.19	150	62	PK	PASS
166.63	66.0	34.57	-31.470	43.50	8.93	150	351	PK	PASS
237.49	63.5	35.64	-27.900	46.00	10.36	150	199	PK	PASS
726.30	48.5	32.95	-15.500	46.00	13.05	150	117	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1329.67	46.6	45.76	-0.880	74.00	28.24	150	80	PK	PASS
1331.27	33.4	32.54	-0.870	54.00	21.46	150	124	AV	PASS
2411.48	48.7	54.06	5.390	-	-	150	297	AV	NA
2411.88	53.1	58.54	5.400	-	-	150	302	PK	NA
3986.60	53.1	45.02	-8.050	74.00	28.98	150	169	PK	PASS
3999.89	42.1	33.91	-8.150	54.00	20.09	150	249	AV	PASS
4824.05	54.1	49.11	-5.000	74.00	24.89	150	289	PK	PASS
4824.48	51.6	46.58	-4.990	54.00	7.42	150	289	AV	PASS
7210.41	44.5	49.47	4.970	74.00	24.53	150	276	PK	PASS
7237.41	37.6	42.12	4.550	54.00	11.88	150	360	AV	PASS
14612.90	36.6	57.01	20.370	74.00	16.99	150	9	PK	PASS
14681.48	27.1	47.67	20.550	54.00	6.33	150	36	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.37	60.8	32.37	-28.430	40.00	7.63	150	9	PK	PASS
60.36	55.6	26.97	-28.640	40.00	13.03	150	125	PK	PASS
166.15	63.9	32.28	-31.570	43.50	11.22	150	91	PK	PASS
274.02	62.0	35.76	-26.260	46.00	10.24	150	256	PK	PASS
723.15	44.9	29.41	-15.510	46.00	16.59	150	248	PK	PASS
936.51	42.1	30.30	-11.790	46.00	15.70	150	111	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1661.33	47.5	47.51	0.000	74.00	26.49	150	154	PK	PASS
1666.13	32.6	32.65	0.030	54.00	21.35	150	154	AV	PASS
2411.48	41.5	46.89	5.390	54.00	7.11	150	28	AV	PASS
2411.88	47.5	52.86	5.400	-	-	150	148	PK	NA
3988.74	58.0	49.97	-8.060	74.00	24.03	150	156	PK	PASS
3997.74	46.8	38.69	-8.130	54.00	15.31	150	64	AV	PASS
4798.77	55.4	50.19	-5.190	74.00	23.81	150	77	PK	PASS
4824.48	43.4	38.42	-4.990	54.00	15.58	150	235	AV	PASS
7234.84	46.7	51.25	4.590	74.00	22.75	150	302	PK	PASS
7235.26	40.5	45.10	4.590	54.00	8.90	150	287	AV	PASS
14614.19	27.3	47.64	20.380	54.00	6.36	150	195	AV	PASS
14686.19	36.2	56.75	20.560	74.00	17.25	150	129	PK	PASS




Plot for Channel 6




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.32	61.0	32.49	-28.460	40.00	7.51	150	16	PK	PASS
62.55	60.5	31.67	-28.790	40.00	8.33	150	85	PK	PASS
100.33	66.6	36.94	-29.660	43.50	6.56	150	64	PK	PASS
201.89	62.9	33.93	-29.000	43.50	9.57	150	43	PK	PASS
278.04	63.2	36.94	-26.240	46.00	9.06	150	268	PK	PASS
598.35	43.5	26.39	-17.150	46.00	19.61	150	139	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1328.87	31.9	31.05	-0.880	54.00	22.95	150	138	AV	PASS
1330.07	45.6	44.67	-0.880	74.00	29.33	150	127	PK	PASS
2433.89	47.1	52.78	5.720	-	-	150	302	PK	NA
2434.29	42.7	48.39	5.740	-	-	150	307	AV	NA
3331.72	51.5	40.81	-10.660	74.00	33.19	150	75	PK	PASS
3333.01	42.2	31.60	-10.640	54.00	22.40	150	75	AV	PASS
4874.20	49.6	44.63	-4.960	54.00	9.37	150	263	AV	PASS
4874.20	52.4	47.42	-4.960	74.00	26.58	150	276	PK	PASS
7582.42	44.7	49.50	4.780	74.00	24.50	150	330	PK	PASS
7594.42	35.0	39.94	4.900	54.00	14.06	150	196	AV	PASS
14693.48	26.9	47.53	20.590	54.00	6.47	150	360	AV	PASS
14782.62	37.2	57.12	19.880	74.00	16.88	150	209	PK	PASS



(Antenna Vertical, 30MHz to 1GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.32	60.8	32.32	-28.460	40.00	7.68	150	324	PK	PASS
100.04	63.1	33.53	-29.600	43.50	9.97	150	208	PK	PASS
166.53	63.2	31.74	-31.490	43.50	11.76	150	92	PK	PASS
274.16	62.9	36.72	-26.220	46.00	9.28	150	256	PK	PASS
705.54	50.6	34.98	-15.610	46.00	11.02	150	57	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1197.64	51.9	50.74	-1.130	74.00	23.26	150	137	PK	PASS
1200.04	38.4	37.29	-1.090	54.00	16.71	150	137	AV	PASS
2433.49	41.5	47.23	5.720	-	-	150	18	PK	NA
2434.29	35.1	40.86	5.740	-	-	150	29	AV	NA
3989.60	60.6	52.49	-8.070	74.00	21.51	150	63	PK	PASS
3990.03	45.5	37.41	-8.070	54.00	16.59	150	63	AV	PASS
4873.77	48.5	43.52	-4.960	74.00	30.48	150	48	PK	PASS
4874.20	42.6	37.65	-4.960	54.00	16.35	150	236	AV	PASS
7310.27	39.0	43.17	4.180	54.00	10.83	150	288	AV	PASS
7310.27	45.1	49.28	4.180	74.00	24.72	150	302	PK	PASS
14680.19	27.7	48.26	20.550	54.00	5.74	150	23	AV	PASS
14720.05	37.1	57.55	20.430	74.00	16.45	150	360	PK	PASS

Plot for Channel 11




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.85	62.5	34.41	-28.130	40.00	5.59	150	351	PK	PASS
107.41	65.2	36.09	-29.140	43.50	7.41	150	77	PK	PASS
166.10	66.5	34.93	-31.590	43.50	8.57	150	344	PK	PASS
274.60	62.8	36.65	-26.140	46.00	9.35	150	276	PK	PASS
480.01	49.0	27.81	-21.190	46.00	18.19	150	282	PK	PASS
914.93	42.4	30.24	-12.150	46.00	15.76	150	0	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1194.84	44.1	42.90	-1.180	74.00	31.10	150	95	PK	PASS
1200.44	37.9	36.83	-1.100	54.00	17.17	150	12	AV	PASS
2461.49	42.9	48.80	5.940	-	-	150	312	AV	NA
2461.89	48.1	54.03	5.940	-	-	150	0	PK	NA
3984.03	54.1	46.08	-8.030	74.00	27.92	150	263	PK	PASS
3996.46	43.2	35.04	-8.120	54.00	18.96	150	249	AV	PASS
4923.91	54.8	49.82	-4.980	74.00	24.18	150	276	PK	PASS
4924.34	52.7	47.72	-4.980	54.00	6.28	150	276	AV	PASS
7384.84	38.0	42.67	4.670	54.00	11.33	150	224	AV	PASS
7418.27	44.6	49.33	4.690	74.00	24.67	150	184	PK	PASS
14537.47	27.5	47.51	20.010	54.00	6.49	150	9	AV	PASS
14742.34	36.1	56.32	20.230	74.00	17.68	150	344	PK	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.17	60.7	32.13	-28.560	40.00	7.87	150	331	PK	PASS
61.09	57.2	28.40	-28.800	40.00	11.60	150	147	PK	PASS
99.99	63.0	33.44	-29.590	43.50	10.06	150	174	PK	PASS
273.19	63.4	36.97	-26.420	46.00	9.03	150	235	PK	PASS
480.01	51.1	29.88	-21.190	46.00	16.12	150	154	PK	PASS
916.24	42.7	30.67	-11.990	46.00	15.33	150	58	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1164.83	50.1	48.39	-1.700	74.00	25.61	150	105	PK	PASS
1166.03	36.1	34.45	-1.690	54.00	19.55	150	100	AV	PASS
2461.49	36.9	42.86	5.940	-	-	150	149	AV	NA
2461.49	43.8	49.69	5.940	-	-	150	149	PK	NA
3990.03	58.9	50.85	-8.070	74.00	23.15	150	128	PK	PASS
3990.46	45.6	37.49	-8.080	54.00	16.51	150	115	AV	PASS
4924.34	44.9	39.94	-4.980	54.00	14.06	150	143	AV	PASS
4924.34	49.2	44.26	-4.980	74.00	29.74	150	143	PK	PASS
7385.27	37.8	42.45	4.670	54.00	11.55	150	275	AV	PASS
7446.98	44.6	49.19	4.610	74.00	24.81	150	328	PK	PASS
14472.33	37.3	56.78	19.490	74.00	17.22	150	102	PK	PASS
14702.91	27.0	47.56	20.580	54.00	6.44	150	102	AV	PASS

END OF REPORT