


SPECIFICATION



Shenzhen Daxian Technology Co., Ltd.

W2 LDS Antenna Assembly

Product Specification

connection		frequency range	4G:2/4/5/12/13/17/66/71 GPS/WiFi GPS L5
entry name	W2	edition	V1.0
Material No	1W-2DHSB-061	Color	Black
Antenna type	LDS PIFA Antenna (8 antennas)	Test Engineer	
R F Design	YuanQing.Zhu	Structural Design	RuiBin.Zhou
Quality Manager	YongJie.Pan	Technical Director	Lei.Zhang
Date	2025-07-08		

Customer confirmation:

Whether the assembly meets your company's requirements: ☐OK ☐NG

Shenzhen Topant Technology Co., Ltd.

Buji Town, Longgang District, Shenzhen, China Jihua Road 513, Shangshuijing Village (opposite the national defense training base) Dacheng Industrial Park, Building 7.

TEL:0755-28576002

FAX:0755-84276383

Room201,Building8,LongDongRoad3000#,Semiconductor Industry Park,ZhangJiang Hitech Zone,ShangHai

TEL:021-61630552

FAX:755-84276383

Revision history

[illegible]

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

Indexes

I 、 Project Description.....	4
II 、 LDS Antenna Assembly.....	4
1、 specifications.....	4
1.1 Electrical specifications and standards.....	4
1.1.1 Electrical performance index.....	5
1.1.2 Antenna matching.....	6-8
1.2 Structural specifications and standards.....	8
1.2.1 Antenna composition.. ..	8
2、 Testing environment.....	9
3、 Test.	10
3.1 Test of standing wave (VSWR).....	10
3.1.1 Test connection.....	10
3.2 Testing of efficiency, power (TRP), sensitivity (TIS).....	10
3.2.1 Test site.....	10
3.2.2 Tested Instruments.....	10
3.2.3 Test data.....	10-14
4、 VSWR Parameter diagram.....	15-17
5、 Conclusion.....	17
III、 Schedule drawing.....	18

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd


I 、 Project Description

Customer Name:	
Type of complete machine:	Phone watch
Antenna band:	4G:2/4/5/12/13/17/66/71 GPS/WiFi GPS L5
Antenna form:	LDS
Feed form:	Springfoot
Number of feed legs:	Main: Three、 GPS: Three、 WGB: Three
Test Software Name:	

II 、 LDS Antenna Assembly

1 specifications

This report mainly provides the testing status of various electrical and structural performance parameters of the antenna for the W2 project. The following image shows an antenna with a large display design.



antenna appearing diagram

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

1.1 Electrical specifications and standards

1.1.1 Electrical performance index

The operating frequency band of the antenna is between 1850~1990MHz、1710 ~2155MHz、824~894MHz、699 ~746MHz、746 ~787MHz、1710 ~2200MHz、617 ~ 698MHz、32400~ 2500 MHz、5150~5850MHz、1575 MHz. The following table shows the electrical performance indicators of large display design and mass production antennas.

LTE -band B2				
band	band (MHz)	VSWR	band (MHz)	VSWR
	The transmitter TX		The receiving end RX	
LTE -B 2	1850~1910	≤4	1930~1990	≤4
LTE -band B4				
band	band (MHz)	VSWR	band (MHz)	VSWR
	The transmit TX		The receiving end RX	
LTE -B 4	1710~1755	≤4	2110~2155	≤4
LTE -band B5				
band	band (MHz)	VSWR	band (MHz)	VSWR
	The transmitter TX		The receiving end RX	
LTE -B 5	824~849	≤4	869~894	≤4
LTE -band B12				
band	band (MHz)	VSWR	band (MHz)	VSWR
	The transmitter TX		The receiving end RX	
LTE -B12	669~716	≤4	729~746	≤4
LTE -band B13				
band	band (MHz)	VSWR	band (MHz)	VSWR
	The transmitter TX		The receiving end RX	
LTE -B13	777~787	≤4	746~756	≤4
LTE -band 66				
band	band (MHz)	VSWR	band (MHz)	VSWR
	The transmitter TX		The receiving end RX	
LTE -B66	1710~1780	≤4	2110~2200	≤4
LTE -band B71				
band	band (MHz)	VSWR	band (MHz)	VSWR
	The transmitter TX		The receiving end RX	
LTE -B13	663~698	≤4	617~652	≤4

Frequency Range	Frequency (MHz)	VSWR
WiFi	2400 ~ 2500, 5150~ 5850	≤ 2
GPS	1575MHz	≤ 2

www.Topant.com.cn



Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

1.2.1 Antenna matching: MIAN

Antenna switching logic	
RF1: on	LTE: B2/4/5/66
RF2: on	B13
RF3: on	B12/B17
RF4: on	N/C
permanent sea	B71



Main Antenna Main Circuit Mat ching		Main Antenna Switch Hatching	
Bit muber	numerical value		
C4715	N/C	R4702	33PF
R4703	N/C	R4101	0Ω
		C4102	33NH
		L4103	0Ω
C4700	0Ω	L4104	15NH
L4701	6.2NH	L4105	27NH
R4700	6PF	L4106	N/C
J4701	Get rid of		
J4700	Get rid of		



www.10pant.com.cn


Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd



GPS


Element		GPS L5
C411		unchanged
C4714		0 Ω
D4703		unchanged
R4708		0 Ω
C4712		N/C
J4706		Get rid of



www.Topant.com.cn
Confidentiality requirements


Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

ANT GPS




WGB

Element		WGB
C4704		0Ω
D4702		Unchanged
C4705		Unchanged
L4704		Unchanged



ANT WLAN



2 Structural specifications and standards

1.2.1 Antenna composition

The antenna is mainly composed of LDS.

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

2、 The Equipment of Active Test

Satimo 3D Chamber $6 \times 4 \times 4$ (m)

Agilent 8960 E5515c

Network analyzer-R&S ZVL



Figure 2

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

3 test

3.1 Test of standing wave (VSWR)

3.1.1 Test connection: The VSWR test device is sequentially connected as follows: R&S ZVL network analyzer → test line → Test fixture

Actual measurement (attached drawing)

3.2 Gain and efficiency, power (TRP), sensitivity (TIS) testing

3.2.1 Test site:

Large display microwave anechoic chamber. The test frequency range is 400MHz - 6GHz, the static zone range is 50cm circumferential, and the reflectivity is less than - 50dB.

3.2.2 Tested Instruments:

R&S ZVL network analyzer, Agilent 8960 E5515C, standard horn antenna, French SATIMO-SG24SYSTEM system, printer, etc.

3.2.3 Test data: In a microwave anechoic chamber, the values related to the power and sensitivity tested are shown in the table below

OTA active test data:

Band	TRP	TIS	Motherboard conduction data		
2	15.17		Band	TRP	TIS
	15.69		2	23.47	
	15.23	-91.13		23.69	
4	14.47			23.53	-98.13
	14.89		4	23.57	
	15.04	-90.51		23.59	
5	13.22			23.64	-98.21
	13.16		5	23.72	
	13.14	-83.18		23.86	
12	10.17			23.84	-99.58
	10.24		12	23.77	
	10.12	-83.05		23.84	
13	11.19			23.82	-99.45
	11.12		13	23.79	
	11.17	-81.09		23.72	
66	14.52			23.67	-99.28
	14.61		66	23.72	
	15.16	-90.37		23.71	
71	7.15			23.86	-98.37
	7.47		71	23.45	
	7.32	-73.27		23.47	
				23.52	-98.37

Armed WIFI 2.4G		
Band	TRP	TIS
WIFI_B	7.5	
WIFI_B	8.45	
WIFI_B	8.16	-74.05

Armed GPS		
Band	TRP	TIS
GNSS		-134.88

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

Antenna Passive Test Data**B5**

Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
820	-7.45	-12	6.31
830	-6.92	-11.65	6.84
840	-6.57	-11.37	7.29
850	-6.33	-11.05	7.85
860	-6.11	-10.79	8.34
870	-6.07	-10.52	8.87
880	-6.08	-10.35	9.23
890	-6.02	-10.16	9.64
900	-6.11	-10.04	9.92

B12

Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
700	-7.23	-11.65	6.84
710	-6.77	-11.1	7.76
720	-6.41	-10.79	8.33
730	-6.2	-10.5	8.92
740	-7.51	-11.07	7.82
750	-7.96	-11.61	6.9

B13

Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
740	-7.45	-12	6.31
750	-6.92	-11.65	6.84
760	-6.57	-11.37	7.29
770	-6.33	-11.05	7.85
780	-6.11	-10.79	8.34
790	-6.07	-10.52	8.87
800	-6.08	-10.35	9.23

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

B71

Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
620	-8.2	-13.96	4.02
630	-8.08	-13.82	4.15
640	-7.74	-13.8	4.17
650	-7.34	-13.7	4.26
660	-7.15	-13.59	4.38
670	-7.16	-13.59	4.38
680	-7.11	-13.36	4.61
690	-7.37	-13.33	4.65
700	-6.09	-12.9	5.13

Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)	Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
1700	-0.61	-7.74	16.81	1960	-0.62	-7.7	16.99
1710	-0.7	-7.85	16.41	1970	-0.65	-7.53	17.66
1720	-0.91	-7.92	16.13	1980	-0.63	-7.29	18.65
1730	-0.93	-8.01	15.8	1990	-0.54	-7.04	19.75
1740	-0.67	-8.02	15.78	2000	-2.86	-7.3	18.62
1750	-0.65	-8.03	15.76	2010	-3.05	-7.23	18.9
1760	-0.66	-8.01	15.8	2020	-2.97	-7.23	18.9
1770	-0.58	-7.85	16.42	2030	-2.79	-7.32	18.52
1780	-0.54	-7.78	16.69	2040	-2.59	-7.28	18.7
1790	-0.56	-7.72	16.9	2050	-2.44	-7.11	19.44
1800	-0.6	-7.76	16.77	2060	-2.42	-7.09	19.55
1810	-0.8	-7.78	16.68	2070	-2.28	-7.02	19.85
1820	-1.11	-7.91	16.17	2080	-2.09	-6.86	20.59
1830	-1.26	-7.94	16.07	2090	-2.03	-6.83	20.76
1840	-1.43	-7.93	16.09	2100	-1.95	-6.74	21.16
1850	-1.71	-8.02	15.79	2110	-1.76	-6.65	21.61
1860	-1.03	-7.65	17.2	2120	-1.59	-6.64	21.69
1870	-0.58	-7.39	18.26	2130	-1.45	-6.65	21.63
1880	-0.27	-7.16	19.24	2140	-1.38	-6.51	22.32
1890	-1.53	-7.38	18.27	2150	-1.3	-6.49	22.46
1900	-1.67	-7.58	17.46	2160	-1.04	-6.49	22.45
1910	-1.82	-7.84	16.44	2170	-0.72	-6.31	23.4
1920	-1.86	-8.04	15.69	2180	-0.56	-6.2	23.99
1930	-1.88	-8.22	15.07	2190	-0.53	-6.2	23.97
1940	-0.69	-8.16	15.26	2200	-1.07	-6.37	23.25
1950	-0.66	-7.94	16.09				

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

WGB

Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
1500	-4.43	-9.87	10.32
1510	-4.16	-9.65	10.84
1520	-4.02	-9.52	11.16
1530	-4.26	-9.43	11.39
1540	-4.21	-9.28	11.8
1550	-4.33	-9.19	12.06
1560	-4.54	-9.12	12.24
1570	-4.73	-8.94	12.77
1580	-3.98	-9.01	12.57
1590	-4.14	-9.1	12.31
1600	-5.21	-9.06	12.42

Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
2400	-2.46	-7.18	19.16
2410	-2.52	-7.27	18.73
2420	-2.45	-7.29	18.66
2430	-2.61	-7.33	18.49
2440	-2.76	-7.4	18.19
2450	-2.93	-7.53	17.68
2460	-3.16	-7.7	16.99
2470	-3.34	-7.83	16.47
2480	-3.49	-7.94	16.08
2490	-3.77	-8.23	15.04
2500	-3.95	-8.47	14.22

GPS-L5

Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
1160	-0.93	-9.04	12.46
1170	-0.86	-9.11	12.26
1180	-0.69	-9.09	12.34
1190	-0.71	-9.13	12.21
1200	-0.72	-9.2	12.03
1210	-0.64	-9.14	12.2
1220	-0.7	-9.1	12.29
1230	-0.64	-9.05	12.46
1240	-0.73	-8.88	12.93

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

WIFI

Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)	Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
5000	-2.45	-7.47	17.92	5520	-3.26	-6.47	22.54
5020	-2.55	-7.35	18.42	5540	-3.15	-6.51	22.31
5040	-2.49	-7.35	18.42	5560	-3.11	-6.51	22.32
5060	-2.13	-7.32	18.52	5580	-3.27	-6.43	22.76
5080	-2.02	-7.38	18.29	5600	-3.64	-6.52	22.29
5100	-2.06	-7.21	19.02	5620	-3.44	-6.62	21.8
5120	-2.18	-7.03	19.83	5640	-3.11	-6.66	21.59
5140	-1.9	-6.9	20.42	5660	-3.13	-6.78	20.98
5160	-1.77	-6.77	21.05	5680	-3.2	-6.82	20.81
5180	-1.86	-6.73	21.23	5700	-3.45	-6.92	20.35
5200	-1.69	-6.58	21.98	5720	-3.59	-7	19.93
5220	-1.73	-6.39	22.96	5740	-3.64	-7.09	19.56
5240	-1.86	-6.24	23.74	5760	-3.62	-7.2	19.07
5260	-1.82	-6.12	24.46	5780	-3.72	-7.28	18.7
5280	-2.04	-6.26	23.66	5800	-4.03	-7.34	18.45
5300	-2.12	-6.15	24.26	5820	-4.28	-7.42	18.11
5320	-2.44	-6.28	23.55	5840	-4.33	-7.45	17.99
5340	-2.66	-6.36	23.11	5860	-4.11	-7.47	17.92
5360	-2.77	-6.29	23.49	5880	-3.97	-7.46	17.93
5380	-2.57	-6.23	23.81	5900	-3.43	-7.35	18.39
5400	-2.53	-6.34	23.25	5920	-2.93	-7.23	18.94
5420	-2.54	-6.5	22.38	5940	-2.55	-7.1	19.52
5440	-2.71	-6.66	21.59	5960	-2.28	-6.85	20.64
5460	-3	-6.68	21.46	5980	-2.4	-6.84	20.69
5480	-3.32	-6.64	21.66	6000	-2.54	-6.79	20.94
5500	-3.31	-6.57	22.02				


www.Topant.com.cn

Confidentiality requirements


Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

4、VSWR parameter diagram

B5




B12




www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

B13




B71



www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

GPS L5



5、 conclusion

This antenna is designed based on the prototype provided by the customer. The electrical parameters and structural performance have met the technical requirements, please confirm!

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

