

TEST REPORT FROM RFI GLOBAL SERVICES LTD

Test of: XT3318

To: FCC Part 15: 2008 Subpart B Clauses 15.107 and 15.109

Test Report Serial No:
RFI/RPT1/RP75527JD06A

This Test Report Is Issued Under The Authority
Of Brian Watson, Operations Director:

pp 

Checked By:	Robert Graham
Signature:	
Date of Issue:	28 September 2009

This report is issued in Adobe Acrobat portable document format (PDF). It is only a valid copy of the report if it is being viewed in PDF format with the following security options not allowed: Changing the document, Selecting text and graphics, Adding or changing notes and form fields.

This report may not be reproduced other than in full, except with the prior written approval of RFI Global Services Ltd. The results in this report apply only to the sample(s) tested.

This page has been left intentionally blank.

Table of Contents

1. Customer Information	4
2. Summary of Testing	5
3. Equipment Under Test (EUT)	6
4. Operation and Monitoring of the EUT during Testing	8
5. Measurements, Examinations and Derived Results	9
6. Measurement Uncertainty	15
Appendix 1. Test Equipment Used.....	16

1. Customer Information

Company Name:	Pro Tech Monitoring Inc.
Address:	2549 Success Drive Odessa FL 33556

2. Summary of Testing

2.1. General Information

Specification Reference:	47CFR15.107 & 47CFR15.109
Specification Title:	Code of Federal Regulations, Part 15 (47CFR15) Radio Frequency Devices: Digital Devices –Sections 15.107 & 15.109
Site Registration No:	209735
Location of Testing:	RFI Global Services Ltd, Wade Road, Basingstoke, Hampshire, RG24 8AH.
Test Dates:	04 September 2009

2.2. Summary of Test Results

FCC Reference (47CFR)	Measurement	Port Type	Result
Part 15.107(a)	Receiver / Idle AC Conducted Emissions	AC Mains	
Part 15.109(a)	Receiver / Idle Radiated Spurious Emissions	Enclosure	

Key to Results

= Complied = Did not comply

2.3. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

3. Equipment Under Test (EUT)

3.1. Identification of Equipment Under Test (EUT)

Brand Name:	X-Tech
Model Name or Number:	XT3318
Serial Number:	36984440
IMEI:	01152600026127207
FCC ID Number:	NC3FTD3318

Description:	AC Charger
Brand Name:	Elmo Tech
Model Name or Number:	SE120100
Serial Number:	None Stated

3.2. Description of EUT

The equipment under test was a GSM/GPRS/GPS tracker fitted with a 318 MHz transceiver.

3.3. Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

3.4. Additional Information Related to Testing

Type of Unit:	Transceiver		
Mode:	GSM		
GSM850 Receive Frequency Range:	869.2 MHz to 893.8 MHz		
GSM850 Receive Channels Tested:	Channel ID	Channel Number	Channel Frequency (MHz)
	Bottom	128	869.2
	Middle	190	881.6
	Top	251	893.8
PCS1900 Receive Frequency Range:	1930.2 MHz to 1989.8 MHz		
PCS1900 Receive Channels Tested:	Channel ID	Channel Number	Channel Frequency (MHz)
	Bottom	512	1930.2
	Middle	660	1959.8
	Top	810	1989.8

3.5. Support Equipment

The following support equipment was used to exercise the EUT during testing:

Description:	Infra Red Wireless Interface
Brand Name:	ACTiSYS
Model Name or Number:	ACT-IR220LN57
Serial Number:	LN001248

4. Operation and Monitoring of the EUT during Testing

4.1. Operating Modes

The EUT was tested in the following operating modes, unless otherwise stated.

- Receiver/Idle mode (GSM850 & PCS1900 bands)

4.2. Configuration and Peripherals

The EUT was tested in the following configuration unless otherwise stated:

- Tests were performed with the GSM module enabled but not transmitting, The EUT was not connected to a network but scanning on all supported bands.
- All tests were performed with the EUT connected to the charger as this was the worst case.

5. Measurements, Examinations and Derived Results

5.1. General Comments

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to *Section 6. Measurement Uncertainty* for details.

This report has been produced to cover the idle mode operation of the GSM/GPRS part of the product and covers the frequency range 30 MHz to 10 GHz to cover the required 5 x 1.9 GHz unintentional requirement.

5.2. Test Results

5.2.1. Receiver/Idle AC Conducted Spurious Emissions

Test Summary:

FCC Part:	15.107(a)
Test Method Used:	As detailed in ANSI C63.4 Section 7 and relevant annexes

Environmental Conditions:


Temperature (°C):	25
Relative Humidity (%):	32

Results: Quasi Peak Detector Measurements

Frequency (MHz)	Line	Quasi Peak Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.150000	Neutral	48.6	66.0	17.4	Complied
0.154500	Live	43.7	65.8	22.1	Complied
0.186000	Neutral	29.9	64.2	34.3	Complied
0.285000	Neutral	41.1	60.7	19.6	Complied
0.289500	Neutral	43.1	60.5	17.4	Complied
0.424500	Neutral	31.5	57.4	25.9	Complied
0.456000	Neutral	30.5	56.8	26.4	Complied

Results: Average Detector Measurements

Frequency (MHz)	Line	Average Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.150000	Neutral	30.3	56.0	25.7	Complied
0.285000	Neutral	30.0	50.7	20.7	Complied

Receiver/Idle Mode AC Conducted Spurious Emissions (continued)

Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

5.2.2. Receiver/Idle Radiated Spurious Emissions

Test Summary:

FCC Part:	15.109(a)
Test Method Used:	As detailed in ANSI C63.4 Section 8 and relevant annexes
Frequency Range:	30 to 1000 MHz

Environmental Conditions:


Temperature (°C):	23
Relative Humidity (%):	23

Highest Peak Level:

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
968.898	Horizontal	28.6	54.0	25.4	Complied

Note(s):

1. No spurious emissions were detected above the noise floor of the measuring receiver; therefore, the highest peak noise floor reading of the measuring receiver was recorded as shown in the table above.



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

Receiver/Idle Radiated Spurious Emissions (continued)**Test Summary:**

FCC Part:	15.109(a)
Test Method Used:	As detailed in ANSI C63.4 Section 8 and relevant annexes
Frequency Range:	1 to 10 GHz

Environmental Conditions:




Temperature (°C):	24
Relative Humidity (%):	29

Results: Highest Peak Level:

Frequency (GHz)	Antenna Polarity	Detector Level (dB μ V)	Antenna Factor (dB)	Peak Level (dB μ V/m)	Average Limit (dB μ V/m)	Margin (dB)	Result
9.587	Horizontal	40.5	8.4	48.9	54.0	5.1	Complied

Note(s):

1. No spurious emissions were detected above the noise floor of the measuring receiver; therefore, the highest peak noise floor reading of the measuring receiver was recorded as shown in the table above. The peak level was compared to the average limit as opposed to being compared to the peak limit because this is the more onerous limit.

Receiver/Idle Radiated Spurious Emissions (continued)

These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

6. Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently, the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor, such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level	Calculated Uncertainty
AC Conducted Spurious Emissions	150 kHz to 30 MHz	95%	± 3.72 dB
Radiated Spurious Emissions	30 MHz to 10 GHz	95%	±2.94 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty, the published guidance of the appropriate accreditation body is followed.

Appendix 1. Test Equipment Used

RFI No.	Instrument	Manufacturer	Type No.	Serial No.	Date Last Calibrated	Cal. Interval (Months)
A1534	Pre Amplifier	Hewlett Packard	8449B OPT H02	3008A00405	Calibrated before use	-
A1818	Antenna	EMCO	3115	00075692	25 Oct 2008	12
A1830	Pulse Limiter	Rhode & Schwarz	ESH3-Z2	100668	05 Jan 2009	12
A288	Antenna	Chase	CBL6111A	1589	13 Mar 2009	12
A649	LISN	Rohde & Schwarz	ESH3-Z5	825562/008	19 Mar 2009	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	01 Sep 2009	12
M1124	Test Receiver	Rohde & Schwarz	ESIB26	100046K	09 Mar 2009	12
M1263	Test Receiver	Rohde & Schwarz	ESIB7	100265	22 Apr 2009	12

NB In accordance with UKAS requirements all the measurement equipment is on a calibration schedule.