

*April 2, 2003*

*CCT Telecom (HK) Limited  
18/F., CCT Telecom Building,  
11 Wo Shing Street, Fo Tan,  
Shatin, N.T., Hong Kong..  
Tel. : (852) 2695 8333  
Fax. : (852) 2694 8660*

*Dear Mr. Boni Baniqued:*

*Enclosed you will find your file copy of a Part 15 Certification (FCC ID: NC8MD450).*

*For your reference, TCB will normally take another 15 to 20 days for reviewing the report.  
Approval will then be granted when no query is sorted.*

*Please contact me if you have any questions regarding the enclosed material.*

*Sincerely,*



*Tommy Leung  
Supervisor*

*Enclosure*

FCC ID: NC8MD450

**Intertek Testing Services Hong Kong Ltd.**

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.  
Tel: (852) 2173 8888 Fax: (852) 2741 1693

CCT Telecom (HK) Limited

Application  
For  
Certification

2.4GHz Frequency Hopping Spread Spectrum Cordless Phone

**(FCC ID: NC8MD450)**

WO# 03026281

WL/Ann Choy

April 2, 2003

- The test results reported in this report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Giant Electronics Limited Limited

FCC ID: NC8MD450

**Intertek Testing Services Hong Kong Ltd.**

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.  
Tel: (852) 2173 8888 Fax: (852) 2741 1693

## LIST OF EXHIBITS

### *INTRODUCTION*

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labelling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual
<i>EXHIBIT 9:</i>	Security Code Information

# INTERTEK TESTING SERVICES

---

## MEASUREMENT/TECHNICAL REPORT

**CCT Telecom (HK) Limited- MODEL: MD45X series**  
**FCC ID: NC8MD450**

This report concerns (check one)      Original Grant       Class II Change \_\_\_\_\_

Equipment Type: DSS-Part 15 Spread Spectrum Transmitter

---

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?      Yes \_\_\_\_\_      No

If yes, defer until : \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on  
that date.

---

Transition Rules Request per 15.37?      Yes \_\_\_\_\_      No

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [08-20-02  
Edition] provision.

---

Report prepared by:

Tommy Leung  
Intertek Testing Services  
2/F., Garment Centre,  
576 Castle Peak Road,  
Kowloon, Hong Kong.  
Phone: 852-2173-8538  
Fax: 852-2741-1693

**Table of Contents**

<b>1.0 <u>Summary of test results</u></b> .....	2
<b>2.0 <u>General Description</u></b> .....	4
2.1 Product Description .....	4
2.2 Related Submittal(s) Grants .....	5
2.3 Test Methodology .....	5
2.4 Test Facility .....	5
<b>3.0 <u>System Test Configuration</u></b> .....	7
3.1 Justification .....	7
3.2 EUT Exercising Software .....	7
3.3 Support Equipment List and Description .....	8
3.4 Equipment Modification .....	9
<b>4.0 <u>Measurement Results</u></b> .....	11
4.1 Maximum Conducted Output Power at Antenna Terminals .....	11
4.2 Maximum 20 dB RF Bandwidth .....	13
4.3 Minimum Number of Hopping Frequencies .....	15
4.4 Minimum Hopping Channel Carrier Frequency Separation .....	16
4.5 Average Time of Occupancy .....	18
4.6 Out of Band Conducted Emissions .....	19
4.7 Out of Band Radiated Emissions .....	20
4.8 Transmitter Radiated Emissions in Restricted Bands .....	21
4.9 Field Strength Calculation .....	22
4.10 Radiated Emission Configuration Photograph - Base Unit .....	23
4.11 Radiated Emission Data - Base Unit .....	24
4.12 Radiated Emission Configuration Photograph - Handset .....	28
4.13 Radiated Emission Data - Handset .....	29
4.14 AC Line Conducted Emission .....	33
4.15 Line Conducted Configuration Photograph - Base Unit .....	34
4.16 Line Conducted Emission Configuration Data .....	35
4.17 Radiated Emission from Digital Section of Transceiver .....	36
4.18 Transmitter Duty Cycle Calculation and Measurements .....	39
<b>5.0 <u>Equipment Photographs</u></b> .....	41
<b>6.0 <u>Product Labelling</u></b> .....	43
<b>7.0 <u>Technical Specifications</u></b> .....	45
<b>8.0 <u>Instruction Manual</u></b> .....	47
<b>9.0 <u>Security Code Information</u></b> .....	49

## INTERTEK TESTING SERVICES

---

### List of attached file

Exhibit type	File Description	filename
Test Report	Test Report	report.pdf
Operation Description	Technical Description	descri.pdf
Test Setup Photo	Radiated Emission for Base	config photos.doc
Test Setup Photo	Radiated Emission for Handset	config photos.doc
Test Report	Maximum Output Power Plot	bmaxop.pdf, hmaxop.pdf
Test Report	20 dB Bandwidth Plot	b20dB.pdf, h20dB.pdf
Test Report	Minimum Number of Hopping Frequencies	chno.pdf
Test Report	Minimum Hopping Channel Carrier Frequency Separation	bfsepa.pdf, hfsepa.pdf
Test Report	Average Channel Occupancy Time	bavetime.pdf, havetime.pdf
Test Report	Out Band Antenna Conducted Emission Plot	bobantcon.pdf, hobantcon.pdf
Test Setup Photo	Conducted Emission	config photos.doc
Test Report	Conducted Emission Test Result	conduct.pdf
External Photo	External Photo	external photos.doc
Internal Photo	Internal Photo	internal photos.doc
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
User Manual	FCC Information	FCC information.pdf
RF Exposure Info	RF Safety	RF exposure info.pdf
Operation Description	Security Code Information	security code.pdf

---

INTERTEK TESTING SERVICES

---

**EXHIBIT 1**  
**SUMMARY OF TEST RESULTS**

## INTERTEK TESTING SERVICES

---

### 1.0 Summary of Test

#### **CCT Telecom (HK) Limited- MODEL: MD45X series FCC ID: NC8MD450**

TEST	REFERENCE	RESULTS
Max. Output Power	15.247(b)	Pass
20 dB Bandwidth	15.247(a)(1)	Pass
Min. No. of Hopping Frequencies	15.247(a)(1)	Pass
Min. Hopping Channel Carrier Frequency Separation	15.247(a)(1)	Pass
Average Time of Occupancy	15.247(a)(1)	Pass
Out of Band Antenna Conducted Emission	15.247(c)	Pass
Radiated Emission in Restricted Bands	15.247(c)	Pass
AC Conducted Emission	15.207	Pass
Radiated Emission from Digital Part	15.109	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses a permanently attached antenna which, in accordance to Section 15.203, is considered sufficient to comply with the provisions of this section.

INTERTEK TESTING SERVICES

---

**EXHIBIT 2**  
**GENERAL DESCRIPTION**

## INTERTEK TESTING SERVICES

---

### 2.0 **General Description**

#### 2.1 Product Description

The MD45X series are a 2.4GHz Frequency Hopping Spread Spectrum Cordless Phone with Caller ID feature. It operates at frequency range of 2401.808 MHz to 2479.401 MHz with 88 hopping frequencies. The unit is capable of either tone or pulse dialing. The internal power supply's isolation is accomplished through a power transformer having an adequate dielectric rating. The circuit wiring is consistent under the requirement of part 68.

The handset unit consists of a keypad with twelve standard keys (0,...9, \*, #), five function keys (Redial, Intercom, Handsfree, Left soft key, Right Soft key). A ON key and OFF key are provided to control pick/release telephone line in a toggle base.

The base unit has a intercom key, which is used to communicate with handset unit.

The antennas used in base unit and handset are integral, and the test sample is a prototype.

The circuit description and frequency hopping algorithm is saved with filename: descri.pdf.

#### 1) System Receiver Input Bandwidth

The manufacturer use RFIC (Radio Frequency Integrated Circuit) with used on-chip image rejection mixer to downconvertor to a lower IF frequency (2MHz). Integrated Bandpass Filter provide rejection of unwanted signal. It can use as the matches the bandwidth of IF filters and match the transmitted bandwidth.

#### 2) System Receiver Hopping Capability

Both handset and base using same hopping sequences, they used same hopping sequence to get synchronization in Talk mode. In Idle, the base will continuously TX a fixed hopping sequence called Beacon, the handset will keep monitor the its receiver to get synchronization on it.

The difference of model number last digit (0-9) serve as marketing strategy and cosmetic change such as color difference.

Connection between the device and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

## INTERTEK TESTING SERVICES

---

### 2.2 Related Submittal(s) Grants

This is an application for Certification of a DSS-Part 15 Spread Spectrum Cordless Telephone System. Two Transmitters are included in this application. The device is also subject to Part 68 Registration.

### 2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (1992). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

### 2.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

INTERTEK TESTING SERVICES

---

**EXHIBIT 3**  
**SYSTEM TEST CONFIGURATION**

### 3.0 System Test Configuration

#### 3.1 Justification

For emission testing, the equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). During testing, all cables were manipulated to produce worst case emissions. The handset was powered by a fully charged battery.

For the measurements, the EUT is attached to a cardboard box if necessary and placed on the wooden turntable. If the base unit attaches to peripherals, they are connected and operational (as typical as possible). The handset is remotely located as far from the antenna and the base as possible to ensure full power transmission from the base. Else, the base is wired to transmit full power without modulation.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Detector function is in peak mode. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1MHz or greater for frequencies above 1000MHz.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9kHz to 25GHz.

#### 3.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

For emissions testing, the units were setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing.

## INTERTEK TESTING SERVICES

---

### 3.3 Support Equipment List and Description

The FCC ID's for all equipment, plus descriptions of all cables used in the tested system (included inserted cards, which have grants) are:

#### *HARDWARE:*

The unit was operated standalone. An AC adapter (provided with the unit) was used to power the device. Its description is listed below.

- (1) AC adapter with two meter unshielded power cord permanently affixed.

#### *CABLES:*

- (1) Telecommunication cable with RJ11C connectors (1m, unshielded), terminated

#### *OTHERS:*

- (1) A headset for telephone use with 1.2m unshielded cable permanently affixed.  
(Supplied by ITS)

## INTERTEK TESTING SERVICES

---

### 3.4 Equipment Modification

Any modifications installed previous to testing by CCT Telecom (HK) Limited will be incorporated in each production model sold/leased in the United States.

No modifications were installed by ETL Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 2.0 of this report are confirmed by:

*Confirmed by:*

*Tommy Leung  
Supervisor  
Intertek Testing Services Hong Kong Ltd.  
Agent for CCT Telecom (HK) Limited*



\_\_\_\_\_  
Signature

\_\_\_\_\_  
April 2, 2003 \_\_\_\_\_ Date

---

INTERTEK TESTING SERVICES

---

**EXHIBIT 4**  
**MEASUREMENT RESULTS**

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

### 4.0 Measurement Results

#### 4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b) :

- [ ] The antenna power of the EUT was connected to the input of a power meter. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.
- [x] The antenna port of the EUT was connected to the input of a spectrum analyzer. The analyzer was set for maximum RES > 20dB bandwidth and power was read directly in dBm. External attenuation and cable loss were compensated for using the OFFSET function of the analyzer.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm).

For antennas with gains greater than 6 dBi, transmitter output level must be decreased by an amount equal to (GAIN - 6) dBm.

(Base Unit) Antenna Gain = 2 dBi		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2401.681	19.59	90.99
Middle Channel: 2440.020	18.69	73.96
High Channel: 2479.187	17.91	61.80

Cable loss : 0.5 dB External Attenuation : N/A dB

Cable loss, external attenuation: [ x ] included in OFFSET function  
[ ] added to SA raw reading

EUT Transmit Antenna Gain (dBi) +dBm max. output level = 21.59dBm (36 dBm or less)

Please refer to the attached plots for details:

Plot B1a: Low Channel Output Power  
Plot B1b: Middle Channel Output Power  
Plot B1c: High Channel Output Power

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited      Date of Test: February 26, 2003 to March 25, 2003  
Model: MD450

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b) - Continued:

(Handset Unit) Maximum Antenna Gain = 2 dBi		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2401.638	20.34	108.14
Middle Channel: 2439.999	21.63	145.55
High Channel: 2479.381	22.53	179.06

Cable loss : 0.5 dB External Attenuation : N/A dB

Cable loss, external attenuation: [ x ] included in OFFSET function  
[ ] added to SA raw reading

EUT Transmit Antenna Gain(dBi)+dBm max. output level = 24.53dBm (36 dBm or less)  
Please refer to the attached plots for details:

Plot H1a: Low Channel Output Power  
Plot H1b: Middle Channel Output Power  
Plot H1c: High Channel output Power

For electronic filing, the above plots are saved with filename: bmaxop.pdf, hmaxop.pdf

For RF Safety, the information is saved with filename: RF exposure info.pdf.

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

### 4.2 Maximum 20 dB RF Bandwidth, FCC Rule 15.247(a)(1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 20 dB lower than PEAK level. The 20 dB bandwidth was determined from where the channel output spectrum intersected the display line.

(Base Unit)	
Frequency (MHz)	20 dB Bandwidth (kHz)
2440.059	1564

Refer to the following plots for 20 dB bandwidth sharp:

Plot B2a: Low Channel 20 dB RF Bandwidth

Plot B2b: Middle Channel 20 dB RF Bandwidth

Plot B2c: High Channel 20 dB RF Bandwidth

For electronic filing, the above plots are saved with filename: b20dB.pdf

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

Maximum 20 dB RF Bandwidth, FCC Rule 15.247(a)(1) - Continued:

(Handset Unit)	
Frequency (MHz)	20 dB Bandwidth (kHz)
2440.152	1279

Refer to the following plots for 20 dB bandwidth sharp:

Plot H2a: Low Channel 20 dB RF Bandwidth

Plot H2b: Middle Channel 20 dB RF Bandwidth

Plot H2c: High Channel 20 dB RF Bandwidth

For electronic filing, the above plots are saved with filename: h20dB.pdf

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

### 4.3 Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1) :

The RF passband of the EUT was divided into 5 approximately equal bands. With the analyzer set to MAX HOLD readings were taken for 2-3 minutes in each band. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

No. of hopping channels	75 in each hopping sequence
-------------------------	-----------------------------

Minimum Requirements: at least 15 non-overlapping channels for 2400-2483.5MHz.

For electronic filing, the above plots are saved with filename: chno.pdf

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

### 4.4 Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1) :

Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit.

[ ] 25 kHz    [ x ] 20 dB bandwidth of hopping channel

Channel Separation	1750 kHz
--------------------	----------

Plot B4: Channel 44 and Channel 46

For electronic filing, the above plots are saved with filename: bfsepa.pdf

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

4.4 Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1) -  
Continued:

Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit.

[ ] 25 kHz    [ x ] 20 dB bandwidth of hopping channel

Channel Separation	1757 kHz
--------------------	----------

Plot H4: Channel 44 and Channel 46

For electronic filing, the above plots are saved with filename: hfsepa.pdf

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

### 4.5 Average Channel Occupancy Time, FCC Ref: 15.247(a)(1)

The spectrum analyzer center frequency was set to one of the known hopping channels. The SWEEP was set to 10ms, the SPAN was set to ZERO SPAN, and the TRIGGER was set to VIDEO. The time duration of the transmission so captured was measured with the MARKER DELTA function.

The SWEEP was then set to the time required by the regulation (20 seconds for 902-928 MHz devices, 30 seconds for all other bands). The analyzer was set to SINGLE SWEEP, the total ON time was added and compared against the limit (0.4 seconds).

Average 0.4 seconds maximum occupancy in 30 seconds, (0.4sec. x 75) for 2400-2483.5MHz.

Base Unit	
Average Occupancy Time = $928.6\mu\text{s} \times 4 \times 40$	148.6 ms

Refer to attached spectrum analyzer plots B5a and B5b

Handset Unit	
Average Occupancy Time = $928.6\mu\text{s} \times 40$	37.1 ms

Refer to attached spectrum analyzer plots H5a and H5b

For electronic filing, the above plots are saved with filename: bavetime.pdf, havetime.pdf.

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited      Date of Test: February 26, 2003 to March 25, 2003  
Model: MD450

### 4.6 Out of Band Radiated Emissions, FCC Rule 15.247(c):

In any 100 kHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the following plots for out of band conducted emissions data:

Plot B6a.1 - B6a.2: Low Channel Emissions  
Plot B6b.1 - B6b.2: Middle Channel Emissions  
Plot B6c.1 - B6c.2: High Channel Emissions  
Plot B6d.1 - B6d.2: Modulation Products Emissions  
Plot H6a.1 - H6a.2: Low Channel Emissions  
Plot H6b.1 - H6b.2: Middle Channel Emissions  
Plot H6c.1 - H6c.2: High Channel Emissions  
Plot H6d.1- H6d.2: Modulation Products Emissions

The plots showed the 2<sup>nd</sup> harmonic and modulation products at the band edges of 2400 MHz and 2483.5 MHz. In addition, all spurious emission and up to the tenth harmonic was measured and they were found to be at least 26 dB below the highest level of the desired power in the passband.

Furthermore, delta measurement technique for measuring bandedge emissions was incorporated in the test of the edge at 2483.5MHz.

For electronic filing, the above plots are saved with filenames: bobantcon.pdf, hobantcon.pdf

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

4.7 Out of Band Radiated Emissions (for emissions in 4.6 above that are less than 26 dB below carrier), FCC Rule 15.247(c):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- Not required, all emissions more than 26 dB below fundamental
- See attached data sheet

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

### 4.8 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

### 4.9 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

where  $FS$  = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

$RA$  = Receiver Amplitude (including preamplifier) in  $\text{dB}\mu\text{V}$

$CF$  = Cable Attenuation Factor in dB

$AF$  = Antenna Factor in dB

$AG$  = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:-

$$FS = RR + LF$$

where  $FS$  = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

$RR$  =  $RA - AG$  in  $\text{dB}\mu\text{V}$

$LF$  =  $CF + AF$  in dB

Assume a receiver reading of 52.0  $\text{dB}\mu\text{V}$  is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32  $\text{dB}\mu\text{V}/\text{m}$ . This value in  $\text{dB}\mu\text{V}/\text{m}$  was converted to its corresponding level in  $\mu\text{V}/\text{m}$ .

$$RA = 52.0 \text{ dB}\mu\text{V}/\text{m}$$

$$AF = 7.4 \text{ dB}$$

$$RR = 23.0 \text{ dB}\mu\text{V}$$

$$CF = 1.6 \text{ dB}$$

$$LF = 9.0 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 23 + 9 = 32 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V}/\text{m})/20] = 39.8 \mu\text{V}/\text{m}$$

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited      Date of Test: February 26, 2003 to March 25, 2003  
Model: MD450

### 4.10 Radiated Emission Configuration Photograph - Base Unit

Worst Case Radiated Emission  
at  
4880.318 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003


### 4.11 Radiated Emission Data - Base Unit

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by -3.1 dB

\*\*\*\*\*

#### **TEST PERSONNEL:**



*Tester Signature*

Yvonne Leung, Engineer  
*Typed/Printed Name*

April 2, 2003  
*Date*

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited

Date of Test: February 26, 2003 to March 25, 2003

Model: MD450

Mode : TX-Channel 1

Table 1, Base Unit

### Radiated Emissions

Polarity	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Average Factor (-dB)	Net 3m at (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2401.808	101.0	29.1	34	-8.6	104.7	---	---
V	*4803.616	41.7	34.0	34	-8.6	50.3	54	-3.7
V	*12009.040	35.4	40.2	34	-8.6	50.2	54	-3.8

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1 GHz also meet corresponding 20 dB permitted peak limit with a peak detector function.

Test Engineer: Yvonne Leung

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited

Date of Test: February 26, 2003 to March 25, 2003

Model: MD450

Mode : TX-Channel 44

Table 2, Base unit

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Average Factor (-dB)	Net 3m at (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2440.159	96.2	29.1	34	-8.6	99.9	---	---
V	*4880.318	47.2	29.1	34	-8.6	50.9	54	-3.1
V	*7320.477	37.8	37.0	34	-8.6	49.4	54	-4.6
V	*12200.785	34.6	40.2	34	-8.6	49.4	54	-4.6

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1 GHz also meet corresponding 20 dB permitted peak limit with a peak detector function.

Test Engineer: Yvonne Leung

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited

Date of Test: February 26, 2003 to March 25, 2003

Model: MD450

Mode : TX-Channel 88

Table 3, Base unit

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Average Factor (-dB)	Net 3m at (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	**2479.401	99.2	29.1	34	-8.6	102.9	---	---
V	*4958.802	40.7	34.0	34	-8.6	49.3	54	-4.7
V	*7438.203	35.8	37.0	34	-8.6	47.4	54	-6.6
V	*12397.005	30.6	40.2	34	-8.6	45.4	54	-8.6

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1 GHz also meet corresponding 20 dB permitted peak limit with a peak detector function.

\*\* Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

Test Engineer: Yvonne Leung

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited      Date of Test: February 26, 2003 to March 25, 2003  
Model: MD450

### 4.12 Radiated Emission Configuration Photograph - Handset

Worst Case Radiated Emission  
at  
7320.477 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003


### 4.13 Radiated Emission Data - Handset

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by -8.8 dB

\*\*\*\*\*

#### **TEST PERSONNEL:**



*Tester Signature*

Yvonne Leung, Engineer  
*Typed/Printed Name*

April 2, 2003  
*Date*

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited

Date of Test: February 26, 2003 to March 25, 2003

Model: MD450

Mode : TX-Channel 1

Table 4, Handset

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Average Factor (-dB)	Net 3m at (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2401.808	79.7	29.1	34	-20.6	95.4	---	---
H	*4803.616	20.3	34.0	34	-20.6	40.9	54	-13.1
H	*12009.040	19.0	37.0	34	-20.6	42.6	54	-11.4

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1 GHz also meet corresponding 20 dB permitted peak limit with a peak detector function.

Test Engineer: Yvonne Leung

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited

Date of Test: February 26, 2003 to March 25, 2003

Model: MD450

Mode : TX-Channel 44

Table 5, Handset

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Average Factor (-dB)	Net 3m at (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2440.159	81.3	29.1	34	-20.6	97.0	---	---
H	*4880.318	23.0	34.0	34	-20.6	43.6	54	-10.4
H	*7320.477	21.6	37.0	34	-20.6	45.2	54	-8.8
H	*12200.785	15.4	40.2	34	-20.6	42.2	54	-11.8

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1 GHz also meet corresponding 20 dB permitted peak limit with a peak detector function.

Test Engineer: Yvonne Leung

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited

Date of Test: February 26, 2003 to March 25, 2003

Model: MD450

Mode : TX-Channel 88

Table 6, Handset

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Average Factor (-dB)	Net 3m at (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	**2479.401	81.3	29.1	34	-20.6	97.0	---	---
H	*4958.802	22.6	34.0	34	-20.6	43.2	54	-10.8
H	*7438.197	19.0	37.0	34	-20.6	42.6	54	-11.4
H	*12397.005	17.7	40.2	34	-20.6	44.5	54	-9.5

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1 GHz also meet corresponding 20 dB permitted peak limit with a peak detector function.

\*\* Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

Test Engineer: Yvonne Leung

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited      Date of Test: February 26, 2003 to March 25, 2003  
Model: MD450

### 4.14 AC Line Conducted Emission, FCC Rule 15.207:

Not required; battery operation only

Test data attached

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

### 4.15 Line Conducted Configuration Photograph - Base Unit

#### Worst Case Line-Conducted Configuration

For electronic filing, the worst case line conducted configuration photographs are saved with filename: config photos.doc

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003


### 4.16 Line Conducted Emission Data

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by more than 20 dB margin

For electronic filing, the worst case line conducted emission data are saved with filename: conduct.pdf

#### **TEST PERSONNEL:**



---

*Tester Signature*

Yvonne Leung, Engineer  
*Typed/Printed Name*

April 2, 2003

*Date*

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited      Date of Test: February 26, 2003 to March 25, 2003  
Model: MD450

### 4.17 Radiated Emissions from Digital Section of Transceiver (Transmitter), FCC Ref: 15.109

- Not required - No digital part
- Test results are attached
- Included in the separated DOC report.

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

Table 7, Base

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Net at 3m (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Magin (dB)
H	131.345	37.2	12.3	16	33.5	43.5	-10.0
H	262.681	36.1	12.4	16	32.5	46.0	-13.5
H	394.031	31.2	15.4	16	30.6	46.0	-15.4
H	525.375	28.0	18.2	16	30.2	46.0	-15.8

NOTES:

1. Quasi-peak data is used for the emission below or equal to 1000MHz
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

Test Engineer: Yvonne Leung

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

Table 8, Handset

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Net at 3m (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Magin (dB)
H	131.305	37.2	12.3	16	33.5	43.5	-10.0
H	262.684	36.1	12.4	16	32.5	46.0	-13.5
H	394.031	31.2	15.4	16	30.6	46.0	-15.4
H	525.375	28.0	18.2	16	30.2	46.0	-15.8

NOTES:

1. Quasi-peak data is used for the emission below or equal to 1000MHz
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

Test Engineer: Yvonne Leung

## INTERTEK TESTING SERVICES

---

Company: CCT Telecom (HK) Limited  
Model: MD450

Date of Test: February 26, 2003 to March 25, 2003

### 4.18 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The transmitter ON time was determined from the resultant time-amplitude display:

Base Unit:

Duty cycle = Maximum ON time is  $928.6\mu\text{s} \times 4 = 3.71/10\text{msec}$  for four handset operation

$$\begin{aligned}\text{Duty cycle correction, dB} &= 20 * \log (\text{DC}) \\ &= 20 * \log (0.3714) \\ &= -8.6\text{dB}\end{aligned}$$

Handset:

Duty cycle = Maximum ON time is  $928.6\mu\text{s}/10\text{msec}$

$$\begin{aligned}\text{Duty cycle correction, dB} &= 20 * \log (\text{DC}) \\ &= 20 * \log (0.093) \\ &= -20.6\text{dB}\end{aligned}$$

X	See attached spectrum analyzer chart (s) for transmitter timing (Base Unit = Plot B7, Handset = Plot H7)
	See transmitter timing diagram provided by manufacturer
	Not applicable, duty cycle was not used.

INTERTEK TESTING SERVICES

---

**EXHIBIT 5**  
**EQUIPMENT PHOTOGRAPHS**

## INTERTEK TESTING SERVICES

---

### 5.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.doc

**EXHIBIT 6**  
**PRODUCT LABELLING**

## INTERTEK TESTING SERVICES

---

### 6.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and location is saved with filename:  
label.pdf

**EXHIBIT 7**  
**TECHNICAL SPECIFICATIONS**

7.0 **Technical Specifications**

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf, circuit.pdf respectively.

---

INTERTEK TESTING SERVICES

---

**EXHIBIT 8**  
**INSTRUCTION MANUAL**

## INTERTEK TESTING SERVICES

---

### 8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

Please note that the required FCC Information to the User is saved with filename: FCC information.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

**EXHIBIT 9**  
**SECURITY CODE INFORMATION**

## INTERTEK TESTING SERVICES

---

### 9.0 Security code information

The security code is saved with filename: security code.pdf.