

CCT R&D Ltd.

Application
For
Certification

2.4GHz Frequency Hopping Spread Spectrum Cordless Phone with with Caller ID, Speakerphone, and Digital Answering Machine

(FCC ID: NC8MD451)

04027571
TL/Ann Choy
March 30, 2004

- The test results reported in this report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Giant Electronics Limited Limited

FCC ID: NC8MD451

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

| | |
|-------------------|---------------------------|
| <i>EXHIBIT 1:</i> | Summary of Tests |
| <i>EXHIBIT 2:</i> | General Description |
| <i>EXHIBIT 3:</i> | System Test Configuration |
| <i>EXHIBIT 4:</i> | Measurement Results |
| <i>EXHIBIT 5:</i> | Equipment Photographs |
| <i>EXHIBIT 6:</i> | Product Labelling |
| <i>EXHIBIT 7:</i> | Technical Specifications |
| <i>EXHIBIT 8:</i> | Instruction Manual |
| <i>EXHIBIT 9:</i> | Security Code Information |

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

**CCT R&D Ltd.- MODEL: MD49X series, MD400 Series
FCC ID: NC8MD451**

This report concerns (check one) Original Grant Class II Change

Equipment Type: DSS-Part 15 Spread Spectrum Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No X

If yes, defer until : _____
dae

Company Name agrees to notify the Commission by: _____
date _____

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes _____ No X

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [12-08-03 Edition] provision.

Report prepared by:

Tommy Leung
Intertek Testing Services
2/F., Garment Centre,
576 Castle Peak Road,
Kowloon, Hong Kong.
Phone: 852-2173-85
Fax: 852-2741-16

Table of Contents

| | |
|---|----|
| 1.0 <u>Summary of test results</u> | 2 |
| 2.0 <u>General Description</u> | 4 |
| 2.1 Product Description | 4 |
| 2.2 Related Submittal(s) Grants | 5 |
| 2.3 Test Methodology | 5 |
| 2.4 Test Facility | 5 |
| 3.0 <u>System Test Configuration</u> | 7 |
| 3.1 Justification | 7 |
| 3.2 EUT Exercising Software | 7 |
| 3.3 Support Equipment List and Description | 8 |
| 3.4 Measurement Uncertainty | 9 |
| 3.5 Equipment Modification | 9 |
| 4.0 <u>Measurement Results</u> | 11 |
| 4.1 Maximum Conducted Output Power at Antenna Terminals | 11 |
| 4.2 Maximum 20 dB RF Bandwidth | 13 |
| 4.3 Minimum Number of Hopping Frequencies | 15 |
| 4.4 Minimum Hopping Channel Carrier Frequency Separation | 16 |
| 4.5 Average Time of Occupancy | 18 |
| 4.6 Out of Band Conducted Emissions | 19 |
| 4.7 Out of Band Radiated Emissions | 20 |
| 4.8 Transmitter Radiated Emissions in Restricted Bands | 21 |
| 4.9 Field Strength Calculation | 22 |
| 4.10 Radiated Emission Configuration Photograph - Base Unit | 23 |
| 4.11 Radiated Emission Data - Base Unit | 24 |
| 4.12 Radiated Emission Configuration Photograph - Handset | 28 |
| 4.13 Radiated Emission Data - Handset | 29 |
| 4.14 AC Line Conducted Emission | 33 |
| 4.15 Line Conducted Configuration Photograph - Base Unit | 34 |
| 4.16 Line Conducted Emission Configuration Data | 35 |
| 4.17 Radiated Emission from Digital Section of Transceiver | 36 |
| 4.18 Transmitter Duty Cycle Calculation and Measurements | 39 |
| 5.0 <u>Equipment Photographs</u> | 41 |
| 6.0 <u>Product Labelling</u> | 43 |
| 7.0 <u>Technical Specifications</u> | 45 |
| 8.0 <u>Instruction Manual</u> | 47 |
| 9.0 <u>Security Code Information</u> | 49 |

INTERTEK TESTING SERVICES

List of attached file

| Exhibit type | File Description | filename |
|-----------------------|--|-------------------------------|
| Test Report | Test Report | report.pdf |
| Operation Description | Technical Description | descri.pdf |
| Test Setup Photo | Radiated Emission for Base | config photos.doc |
| Test Setup Photo | Radiated Emission for Handset | config photos.doc |
| Test Report | Maximum Output Power Plot | bmaxop.pdf, hmaxop.pdf |
| Test Report | 20 dB Bandwidth Plot | b20dB.pdf, h20dB.pdf |
| Test Report | Minimum Number of Hopping Frequencies | bchno.pdf, hchno.pdf |
| Test Report | Minimum Hopping Channel Carrier Frequency Separation | bfsepa.pdf, hfsepa.pdf |
| Test Report | Average Channel Occupancy Time | bavetime.pdf, havetime.pdf |
| Test Report | Out Band Antenna Conducted Emission Plot | bobantcon.pdf, hobantcon.pdf |
| Test Report | Duty Cycle Calculation and Measurement | bdcc.pdf, hdcc.pdf |
| Test Setup Photo | Conducted Emission | config photos.doc |
| Test Report | Conducted Emission Test Result | conduct.pdf |
| External Photo | External Photo | external photos.doc |
| Internal Photo | Internal Photo | internal photos.doc |
| Block Diagram | Block Diagram | block.pdf |
| Schematics | Circuit Diagram | circuit.pdf |
| ID Label/Location | Label Artwork and Location | label.pdf |
| User Manual | User Manual | manual.pdf |
| User Manual | FCC Information | FCC information.pdf |
| RF Exposure Info | RF Safety | RF exposure info.pdf |
| Operation Description | Security Code Information | security code information.pdf |

INTERTEK TESTING SERVICES

EXHIBIT 1
SUMMARY OF TEST RESULTS

INTERTEK TESTING SERVICES

1.0 Summary of Test

CCT R&D Ltd.- MODEL: MD49X series, MD400 Series
FCC ID: NC8MD451

| TEST | REFERENCE | RESULTS |
|---|--------------|------------------|
| Max. Output Power | 15.247(b) | Pass |
| Min. No. of Hopping Frequencies | 15.247(a)(1) | Pass |
| Min. Hopping Channel Carrier Frequency Separation | 15.247(a)(1) | Pass |
| Average Time of Occupancy | 15.247(a)(1) | Pass |
| Out of Band Antenna Conducted Emission | 15.247(c) | Pass |
| Radiated Emission in Restricted Bands | 15.247(c) | Pass |
| AC Conducted Emission | 15.207 | Pass |
| Radiated Emission from Digital Part | 15.109 | Pass |
| Antenna Requirement | 15.203 | Pass (See Notes) |

Notes: The EUT uses a permanently attached antenna which, in accordance to Section 15.203, is considered sufficient to comply with the provisions of this section.

EXHIBIT 2
GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

2.0 General Description

2.1 Product Description

The MD491 is a 2.4GHz Frequency Hopping Spread Spectrum Cordless Phone with Caller ID, Speakerphone, and Digital Answering Machine. It operates at frequency range of 2401.808MHz to 2478.509MHz with 86 physical hopping frequencies and 75 logical hopping frequencies. The unit is capable of either tone or pulse dialing. The internal power supply's isolation is accomplished through a power transformer having an adequate dielectric rating. The circuit wiring is consistent under the requirement of part 68.

The handset unit consists of a keypad with twelve standard keys (0,...9,*,#), five function keys (Redial, Intercom, Handsfree, Left soft key, Right soft key). A ON key and a OFF key are provided to control pick and release telephone line in a toggle base.

The base unit has a page key, which is used to communicate with handset unit. In addition, the unit also has another feature, Corded Handset.

The antennas used in base unit and handset are integral, and the test sample is a prototype.

The model: MD491 is one of the model: MD49X series, and the letter "X" at the end of the model numbers is in term of number from "0" to "9" with different color. The model MD400 Series is an additional handset with charger for selling a handset standalone, and it is the same as the handset of model MD49X series in hardware aspect. The difference in model number serves as marketing strategy.

The circuit description and frequency hopping algorithm is saved with filename: descri.pdf

Connection between the device and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

INTERTEK TESTING SERVICES

2.2 Related Submittal(s) Grants

This is an application for Certification of a DSS-Part 15 Spread Spectrum Cordless Telephone System. Two transmitters are included in this application. The device is also subject to Part 68 Registration.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2001). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **"Justification Section"** of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

INTERTEK TESTING SERVICES

EXHIBIT 3
SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

3.0 System Test Configuration

3.1 Justification

For emission testing, the equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). During testing, all cables were manipulated to produce worst case emissions. The handset was powered by a fully charged battery.

For the measurements, the EUT is attached to a plastic stand if necessary and placed on the wooden turntable. If the base unit attaches to peripherals, they are connected and operational (as typical as possible). The handset is remotely located as far from the antenna and the base as possible to ensure full power transmission from the base. Else, the base is wired to transmit full power without modulation.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Detector function is in peak mode. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1MHz or greater for frequencies above 1000MHz.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9kHz to 25GHz.

3.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

For emissions testing, the units were setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing.

INTERTEK TESTING SERVICES

3.3 Support Equipment List and Description

The FCC ID's for all equipment, plus descriptions of all cables used in the tested system (included inserted cards, which have grants) are:

HARDWARE:

The unit was operated standalone. An AC adapter (provided with the unit) was used to power the device. Its description is listed below.

- (1) AC adapter with two meter unshielded power cord permanently affixed.

CABLES:

- (1) Telecommunication cable with RJ11C connectors (1m, unshielded), terminated

OTHERS:

- (1) A headset for telephone use with 1.2m unshielded cable permanently affixed.
(Supplied by Intertek)
- (2) 4 x "AAA" size 1.5VDC backup battery.

INTERTEK TESTING SERVICES

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification

Any modifications installed previous to testing by CCT R&D Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by ETL Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 3.0 of this report are confirmed by:

Confirmed by:

*Tommy Leung
Supervisor
Intertek Testing Services Hong Kong Ltd.
Agent for CCT R&D Ltd.*



Signature

March 30, 2004 _____ Date

INTERTEK TESTING SERVICES

EXHIBIT 4
MEASUREMENT RESULTS

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b) :

[] The antenna power of the EUT was connected to the input of a power meter. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

[x] The antenna port of the EUT was connected to the input of a spectrum analyzer. The analyzer was set for RBW>20dB bandwidth and power was read directly in dBm. External attenuation and cable loss were compensated for using the OFFSET function of the analyser.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm).

For antennas with gains greater than 6 dBi, transmitter output level must be decreased by an amount equal to (GAIN - 6) dBm.

| (Base Unit) Antenna Gain = 1 dBi | | |
|----------------------------------|---------------|-----------------|
| Frequency (MHz) | Output in dBm | Output in mWatt |
| Low Channel: 2401.892 | 19.12 | 81.66 |
| Middle Channel: 2440.040 | 19.39 | 86.90 |
| High Channel: 2478.684 | 19.35 | 86.10 |

Cable loss : 0.5 dB External Attenuation : N/A dB

Cable loss, external attenuation: [x] included in OFFSET function
[] added to SA raw reading

EUT Transmit Antenna Gain(dBi) + dBm max. output level = 20.39 dBm (36 dBm or less)

Please refer to the attached plots for details:

Plot B1a: Low Channel Output Power
Plot B1b: Middle Channel Output Power
Plot B1c: High Channel Output Power

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b) -
Continued:

| (Handset Unit) Maximum Antenna Gain = 1 dBi | | |
|---|---------------|-----------------|
| Frequency (MHz) | Output in dBm | Output in mWatt |
| Low Channel: 2401.549 | 19.40 | 87.10 |
| Middle Channel: 2439.863 | 19.46 | 88.31 |
| High Channel: 2478.194 | 19.45 | 88.10 |

Cable loss : 0.5 dB External Attenuation : N/A dB

Cable loss, external attenuation: [x] included in OFFSET function
[] added to SA raw reading

EUT Transmit Antenna Gain(dBi) + dBm max. output level = 20.46 dBm (36 dBm or less)

Please refer to the attached plots for details:

Plot H1a: Low Channel Output Power

Plot H1b: Middle Channel Output Power

Plot H1c: High Channel output Power

For electronic filing, the above plots are saved with filename: bmaxop.pdf, hmaxop.pdf

For RF Safety, the information is saved with filename: RF exposure info.pdf.

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.2 Maximum 20 dB RF Bandwidth, FCC Rule 15.247(a)(1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 20 dB lower than PEAK level. The 20 dB bandwidth was determined from where the channel output spectrum intersected the display line.

| (Base Unit) | |
|-----------------|-----------------------|
| Frequency (MHz) | 20 dB Bandwidth (kHz) |
| 2478.549 | 772 |

Refer to the following plots for 20 dB bandwidth sharp:

Plot B2a: Low Channel 20 dB RF Bandwidth

Plot B2b: Middle Channel 20 dB RF Bandwidth

Plot B2c: High Channel 20 dB RF Bandwidth

For electronic filing, the above plots are saved with filename: b20dB.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

Maximum 20 dB RF Bandwidth, FCC Rule 15.247(a)(1) - Continued:

| (Handset Unit) | |
|-----------------|-----------------------|
| Frequency (MHz) | 20 dB Bandwidth (kHz) |
| 2478.537 | 728 |

Refer to the following plots for 20 dB bandwidth sharp:

Plot H2a: Low Channel 20 dB RF Bandwidth
Plot H2b: Middle Channel 20 dB RF Bandwidth
Plot H2c: High Channel 20 dB RF Bandwidth

For electronic filing, the above plots are saved with filename: h20dB.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.3 Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1) :

The RF passband of the EUT was divided into 5 approximately equal bands. With the analyzer set to MAX HOLD readings were taken for 2-3 minutes in each band. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

| Base Unit and Handset | |
|-------------------------|----|
| No. of hopping channels | 75 |

Minimum Requirements: at least 15 non-overlapping channels for 2400MHz-2483.5MHz.

For electronic filing, the above plots are saved with filename: bchno.pdf, hchno.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.4 Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1) :

Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit.

[] 25 kHz [x] 20 dB bandwidth of hopping channel: 772kHz

| Base Unit | |
|--------------------|---------|
| Channel Separation | 906 kHz |

Plot B4: Channel 44 and Channel 45

Requirement: The frequency separation is more than 20dB bandwidth of hopping channel.

For electronic filing, the above plots are saved with filename: bfsepa.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.4 Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1) -
Continued:

Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit.

[] 25 kHz [x] 20 dB bandwidth of hopping channel: 728kHz

| Handset | |
|--------------------|---------|
| Channel Separation | 858 kHz |

Plot H4: Channel 44 and Channel 45

Requirement: The frequency separation is more than 20dB bandwidth of hopping channel.

For electronic filing, the above plots are saved with filename: hfsepa.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.5 Average Channel Occupancy Time, FCC Ref: 15.247(a)(1)

The spectrum analyzer center frequency was set to one of the known hopping channels. The SWEEP was set to 10ms, the SPAN was set to ZERO SPAN, and the TRIGGER was set to VIDEO. The time duration of the transmission so captured was measured with the MARKER DELTA function.

The SWEEP was then set to the time required by the regulation (20 seconds for 902-928 MHz devices, if the 20dB bandwidth is less than 250kHz, 10 seconds for 902-928 MHz if the 20dB bandwidth is or greater than 250kHz, "0.4 seconds x Number of hopping channels employed" seconds for 2400-2483.5 MHz, 30 seconds for 5725-5850 MHz). The analyzer was set to SINGLE SWEEP, the total ON time was added and compared against the limit (0.4 seconds).

Average 0.4 seconds maximum occupancy in 30 seconds, (0.4sec. x 75) for 2400MHz-2483.5MHz.

| Base Unit | |
|--|----------|
| Average Occupancy Time = $920\mu\text{s} \times 4 \times 40$ | 147.2 ms |

Refer to attached spectrum analyzer plots B5a-c

| Hanset Unit | |
|---|---------|
| Average Occupancy Time = $920\mu\text{s} \times 40$ | 36.8 ms |

Refer to attached spectrum analyzer plots H5a-c

For electronic filing, the above plots are saved with filename: bavetime.pdf, havetime.pdf.

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.6 Out of Band Radiated Emissions, FCC Rule 15.247(c):

In any 100 kHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the following plots for out of band conducted emissions data:

Plot B6a.1- B6a.2: Low Channel Emissions
Plot B6b.1- B6b.2: Middle Channel Emissions
Plot B6c.1- B6c.2: High Channel Emissions
Plot B6d.1- B6d.2: Modulation Products Emissions*
Plot H6a.1- H6a.2: Low Channel Emissions
Plot H6b.1- H6b.2: Middle Channel Emissions
Plot H6c.1- H6c.2: High Channel Emissions
Plot H6d.1- H6d.2: Modulation Products Emissions*

The plots showed the 2nd harmonic and modulation products at the band edges of 2400 MHz and 2483.5 MHz. In addition, all spurious emission and up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

Furthermore, delta measurement technique for measuring bandedge emissions was incorporated in the test of the edge at 2483.5MHz.

*These 2 plots are shown the worst-case which has been already considered between enable and disable the hopping function of the EUT.

For electronic filing, the above plots are saved with filenames: bobantcon.pdf, hobantcon.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.7 Out of Band Radiated Emissions (for emissions in 4.6 above that are less than 20 dB below carrier), FCC Rule 15.247(c):

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- Not required, all emissions more than 20 dB below fundamental
- See attached data sheet

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.8 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.9 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in $\text{dB}\mu\text{V}/\text{m}$

RA = Receiver Amplitude (including preamplifier) in $\text{dB}\mu\text{V}$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example

Assume a receiver reading of 62.0 $\text{dB}\mu\text{V}$ is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 $\text{dB}\mu\text{V}/\text{m}$. This value in $\text{dB}\mu\text{V}/\text{m}$ was converted to its corresponding level in $\mu\text{V}/\text{m}$.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V}/\text{m})/20] = 39.8 \mu\text{V}/\text{m}$$

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.10 Radiated Emission Configuration Photograph - Base Unit

Worst Case Radiated Emission
at
7320.477 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491


Date of Test: February 25-March 13, 2004

4.11 Radiated Emission Data - Base Unit

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 14.4 dB compare with the peak limit

TEST PERSONNEL:



Tester Signature

Yvonne Leung, Engineer
Typed/Printed Name

March 30, 2004

Date

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.

Date of Test: February 25-March 13, 2004

Model: MD491

Mode : TX-Channel 1

Table 1, Base Unit

Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Average Factor (-dB) | Net 3m at (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------|--------------------|-------------------------|-------------------------|---------------------------|----------------------------|--------------------------------|----------------------------------|----------------|
| H | *4803.617 | 51.1 | 34 | 34.0 | 28.6 | 22.5 | 54 | -31.5 |
| H | *12009.042 | 41.9 | 34 | 40.2 | 28.6 | 19.5 | 54 | -34.5 |
| H | *19214.468 | 38.0 | 34 | 45.3 | 28.6 | 20.7 | 54 | -33.3 |

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Yvonne Leung

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.

Date of Test: February 25-March 13, 2004

Model: MD491

Mode : TX-Channel 44

Table 2, Base unit

Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Average Factor (-dB) | Net 3m at (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------|--------------------|-------------------------|-------------------------|---------------------------|----------------------------|--------------------------------|----------------------------------|----------------|
| H | *4880.318 | 51.4 | 34 | 34.0 | 28.6 | 22.8 | 54 | -31.2 |
| H | *7320.477 | 56.6 | 34 | 37.0 | 28.6 | 31.0 | 54 | -23.0 |
| H | *12200.795 | 42.3 | 34 | 40.2 | 28.6 | 19.9 | 54 | -34.1 |
| H | *19521.271 | 38.4 | 34 | 45.3 | 28.6 | 21.1 | 54 | -32.9 |

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function, and this is the worst-case of 14.4dB margin at 7320.477MHz.

Test Engineer: Yvonne Leung

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.

Date of Test: February 25-March 13, 2004

Model: MD491

Mode : TX-Channel 87

Table 3, Base unit

Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Average Factor (-dB) | Net 3m at (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------|--------------------|-------------------------|-------------------------|---------------------------|----------------------------|--------------------------------|----------------------------------|----------------|
| H | **2478.509 | 117.3 | 34 | 29.1 | 28.6 | 83.8 | --- | --- |
| H | *4957.019 | 51.4 | 34 | 34.0 | 28.6 | 22.8 | 54 | -31.2 |
| H | *7435.528 | 55.9 | 34 | 37.0 | 28.6 | 30.3 | 54 | -23.7 |
| H | *12392.547 | 42.1 | 34 | 40.2 | 28.6 | 19.7 | 54 | -34.3 |
| H | *19828.075 | 38.6 | 34 | 45.3 | 28.6 | 21.3 | 54 | -32.7 |
| H | *22306.584 | 38.6 | 34 | 45.3 | 28.6 | 21.3 | 54 | -32.7 |

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

** Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

Test Engineer: Yvonne Leung

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.12 Radiated Emission Configuration Photograph - Handset

Worst Case Radiated Emission
at
12392.547 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491


Date of Test: February 25-March 13, 2004

4.13 Radiated Emission Data - Handset

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 7.1 dB compare with the peak limit

TEST PERSONNEL:



Tester Signature

Yvonne Leung, Engineer
Typed/Printed Name

March 30, 2004

Date

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.

Date of Test: February 25-March 13, 2004

Model: MD491

Mode : TX-Channel 1

Table 4, Handset

Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Average Factor (-dB) | Net 3m at (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------|--------------------|-------------------------|-------------------------|---------------------------|----------------------------|--------------------------------|----------------------------------|----------------|
| H | *4803.617 | 62.0 | 34 | 34.0 | 40.7 | 21.3 | 54 | -32.7 |
| H | *12009.042 | 57.9 | 34 | 40.2 | 40.7 | 23.4 | 54 | -30.6 |
| H | *19214.468 | 37.1 | 34 | 45.3 | 40.7 | 7.7 | 54 | -46.3 |

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Yvonne Leung

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.

Date of Test: February 25-March 13, 2004

Model: MD491

Mode : TX-Channel 44

Table 5, Handset

Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Average Factor (-dB) | Net 3m at (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------|--------------------|-------------------------|-------------------------|---------------------------|----------------------------|--------------------------------|----------------------------------|----------------|
| H | *4880.318 | 59.4 | 34 | 34.0 | 40.7 | 18.7 | 54 | -35.3 |
| H | *7320.477 | 63.7 | 34 | 37.0 | 40.7 | 26.0 | 54 | -28.0 |
| H | *12200.795 | 59.7 | 34 | 40.2 | 40.7 | 25.2 | 54 | -28.8 |
| H | *19521.271 | 37.4 | 34 | 45.3 | 40.7 | 8.0 | 54 | -46.0 |

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Yvonne Leung

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.

Date of Test: February 25-March 13, 2004

Model: MD491

Mode : TX-Channel 87

Table 6, Handset

Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Average Factor (-dB) | Net 3m at (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------|-----------------|----------------------|-------------------|---------------------|----------------------|--------------------------|----------------------------|-------------|
| H | **2478.509 | 120.8 | 34 | 29.1 | 40.7 | 75.2 | --- | --- |
| H | *4957.019 | 59.0 | 34 | 34.0 | 40.7 | 18.3 | 54 | -35.7 |
| H | *7435.528 | 63.3 | 34 | 37.0 | 40.7 | 25.6 | 54 | -28.4 |
| H | *12392.547 | 60.7 | 34 | 40.2 | 40.7 | 26.2 | 54 | -27.8 |
| H | *19828.075 | 37.6 | 34 | 45.3 | 40.7 | 8.2 | 54 | -45.8 |
| H | *22306.584 | 37.9 | 34 | 45.3 | 40.7 | 8.5 | 54 | -45.5 |

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function, and this is the worst-case of 7.1dB margin at 12392.545MHz.

** Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

Test Engineer: Yvonne Leung

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.14 AC Line Conducted Emission, FCC Rule 15.207:

- Not required; battery operation only
- Test data attached

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.15 Line Conducted Configuration Photograph - Base

Worst Case Line-Conducted Configuration

at 0.895 MHz

For electronic filing, the worst case line conducted configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004


4.16 Line Conducted Emission Data

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by more than 5.9 dB margin

For electronic filing, the worst case line conducted emission data are saved with filename: conduct.pdf

TEST PERSONNEL:



Tester Signature

Yvonne Leung, Engineer
Typed/Printed Name

March 30, 2004
Date

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.17 Radiated Emissions from Digital Section of Transceiver (Transmitter), FCC Ref: 15.109

- Not required - No digital part
- Test results are attached
- Included in the separated DOC report.

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

Table 7, Base Unit

Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|--------------|--------------------|-------------------------|-------------------------|---------------------------|--------------------------------|-------------------------|----------------|
| V | 30.274 | 28.9 | 16 | 11.6 | 24.5 | 40.0 | -15.5 |
| V | 35.891 | 30.5 | 16 | 11.2 | 25.7 | 40.0 | -14.3 |
| V | 45.384 | 30.5 | 16 | 11.9 | 26.4 | 40.0 | -13.6 |
| V | 55.271 | 32.3 | 16 | 11.0 | 27.3 | 40.0 | -12.7 |
| V | 65.428 | 33.7 | 16 | 8.5 | 26.2 | 40.0 | -13.8 |
| V | 120.462 | 29.6 | 16 | 12.8 | 26.4 | 43.5 | -17.1 |
| V | 150.339 | 31.4 | 16 | 11.9 | 27.3 | 43.5 | -16.2 |
| V | 180.171 | 26.9 | 16 | 16.2 | 27.1 | 43.5 | -16.4 |

NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

Test Engineer: Yvonne Leung

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

Table 8, Handset

Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|--------------|--------------------|-------------------------|-------------------------|---------------------------|--------------------------------|-------------------------|----------------|
| V | 32.874 | 28.5 | 16 | 11.6 | 24.1 | 40.0 | -15.9 |
| V | 38.461 | 29.4 | 16 | 11.2 | 24.6 | 40.0 | -15.4 |
| V | 43.912 | 29.6 | 16 | 11.7 | 25.3 | 40.0 | -14.7 |
| V | 47.167 | 29.7 | 16 | 11.9 | 25.6 | 40.0 | -14.4 |
| V | 54.319 | 30.7 | 16 | 11.7 | 26.4 | 40.0 | -13.6 |
| V | 58.123 | 31.2 | 16 | 11.0 | 26.2 | 40.0 | -13.8 |

NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

Test Engineer: Yvonne Leung

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: MD491

Date of Test: February 25-March 13, 2004

4.18 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEEP function on the analyzer was set to ZERO SPAN. The transmitter ON time was determined from the resultant time-amplitude display:

Base Unit:

$$\begin{aligned}\text{Duty cycle (DC)} &= \text{Maximum ON time in 100ms/100ms} \\ &= 0.920\text{ms} \times 4/100\text{ms} \text{ for 4 handsets operation}\end{aligned}$$

$$\begin{aligned}\text{Duty cycle correction, dB} &= 20 * \log (\text{DC}) \\ &= 20 * \log (0.0368) \\ &= -28.6 \text{ dB}\end{aligned}$$

Handset:

$$\begin{aligned}\text{Duty cycle (DC)} &= \text{Maximum ON time in 100ms/100ms} \\ &= 0.920\text{ms}/100\text{ms}\end{aligned}$$

$$\begin{aligned}\text{Duty cycle correction, dB} &= 20 * \log (\text{DC}) \\ &= 20 * \log (0.0092) \\ &= -40.7 \text{ dB}\end{aligned}$$

| | |
|---|---|
| X | See attached spectrum analyzer chart (s) for transmitter timing Base Unit: Plot B7, Handset: Plot H7 |
| | See transmitter timing diagram provided by manufacturer |
| | Not applicable, duty cycle was not used. |

For electronic filing, the above plots are saved with filenames: bdcc.pdf, hdcc.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 5
EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.doc

INTERTEK TESTING SERVICES

EXHIBIT 6
PRODUCT LABELLING

INTERTEK TESTING SERVICES

6.0 Product Labelling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf

INTERTEK TESTING SERVICES

EXHIBIT 7
TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

INTERTEK TESTING SERVICES

EXHIBIT 8
INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

Please note that the required FCC Information to the User is saved with filename: FCC information.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 9
SECURITY CODE INFORMATION

INTERTEK TESTING SERVICES

9.0 **Security code information**

For electronic filing, security code information is saved with filename: security code information.pdf.