

- Inform you of your right to bring a complaint to the Commission pursuant to procedures set forth in Subpart E of Part 68, FCC Rules and Regulations.

The telephone company may make changes in its facilities, equipment, operations, or procedures that could affect the operation of the equipment. If this happens, the telephone company will provide advance notice in order for you to make necessary modifications to maintain uninterrupted service.

Interference Information

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

This device may not cause harmful interference.

This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

CAUTION: To maintain compliance with the FCC's RF exposure guidelines place the base unit at least 20cm from the nearby persons.

Intertek Testing Services

For SAR evaluation of the handset, refer to TCB Exclusions List Revised on 17 July 2002. Portable transmitter with output power less than 60/fGHz ($d < 2.5\text{cm}$) can be certified by TCB without the SAR evaluation.

In fact, the Output power for portable transmitters is the higher of the conducted or radiated (EIRP) source-based time-averaged output. And the $f\text{GHz}$ is mid-band frequency in GHz, and d is the distance to a person's body, excluding hands, wrists, feet, and ankles.

For the tested model of SD4581, the measured peak conducted power was 106.91mW.

$$\begin{aligned}\text{The conducted source-based time averaged output power} \\ &= (106.91 * 0.188) \text{ mW} \\ &= 20.10\text{mW}\end{aligned}$$

The maximum field strength (FS) was $114.8\text{B}\mu\text{V/m}$ at 2478.509MHz. The distance (D) between the antenna and the equipment under test (EUT) was 3 meters.

From these data, the EIRP can be calculated by:

$$\begin{aligned}\text{EIRP} &= (\text{FS} * \text{D})^2 / 30 \\ &= 90.60\text{mW}\end{aligned}$$

$$\begin{aligned}\text{The radiated source-based time averaged output power} \\ &= (90.60 * 0.188) \text{ mW} \\ &= 17.03\text{mW}\end{aligned}$$

Based on the above calculation, it is concluded that the handset can be certified by TCB without the SAR evaluation and the maximum source-based time-averaging duty factor is 18.8%.