
Appendix for the Report

Dosimetric Assessment of the GlobeTrotter Express from Option (FCC ID: NCMOGE0301E)

According to the FCC Requirements

SAR Distribution Plots

August 06, 2007
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
7layers AG
Borsigstrasse 11
D-40880 Ratingen

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, GPRS 850 BODY	3
2	SAR DISTRIBUTION PLOTS, GPRS 1900 BODY	6
3	SAR DISTRIBUTION PLOTS, WCDMA II (FDD) BODY	9
4	SAR DISTRIBUTION PLOTS, WCDMA V (FDD) BODY	13
5	SAR Z-AXIS SCANS (VALIDATION)	17
6	SAR Z-AXIS SCANS (MEASUREMENTS)	20

1 SAR Distribution Plots, GPRS 850 Body

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [FS 393_bahm_1.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: GPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.66

Medium parameters used: $f = 836.6$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 53.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(6.22, 6.22, 6.22); Calibrated: 15.02.2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.02.2007
- Phantom: SAM Sugar 1059; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.371 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.0 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 0.495 W/kg

SAR(1 g) = 0.347 mW/g; SAR(10 g) = 0.236 mW/g

Maximum value of SAR (measured) = 0.376 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.0 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 0.337 W/kg

SAR(1 g) = 0.224 mW/g; SAR(10 g) = 0.157 mW/g

Maximum value of SAR (measured) = 0.270 mW/g




Fig. 1: SAR distribution for GPRS 850 (Class 11), channel 190, Lap Held Position (Fujitsu Siemens AMILO Pro V3205, March 28, 2007; Ambient Temperature: 22.4°C; Liquid Temperature: 21.4°C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [AC_393_bahm_1.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: GPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.66

Medium parameters used: $f = 836.6$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 53.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(6.22, 6.22, 6.22); Calibrated: 15.02.2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.02.2007
- Phantom: SAM Sugar 1059; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.699 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.2 V/m; Power Drift = -0.158 dB

Peak SAR (extrapolated) = 0.893 W/kg

SAR(1 g) = 0.655 mW/g; SAR(10 g) = 0.450 mW/g

Maximum value of SAR (measured) = 0.700 mW/g




Fig. 2: SAR distribution for GPRS 850 (Class 11), channel 190, Lap Held Position (Acer TravelMate, March 28, 2007; Ambient Temperature: 22.4°C; Liquid Temperature: 21.4°C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [HP_393_bahl_1.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: GPRS 850; Frequency: 824.2 MHz; Duty Cycle: 1:2.66

Medium parameters used: $f = 824.2$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 53.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(6.22, 6.22, 6.22); Calibrated: 15.02.2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.02.2007
- Phantom: SAM Sugar 1059; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.06 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 34.2 V/m; Power Drift = -0.036 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 0.989 mW/g; SAR(10 g) = 0.663 mW/g




Fig. 3: SAR worst case distribution for GPRS 850 (Class 11), channel 128, Lap Held Position (HP Compaq nc6320, March 28, 2007; Ambient Temperature: 22.4°C; Liquid Temperature: 21.4°C).

2 SAR Distribution Plots, GPRS 1900 Body

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [FS_393_yphm_1.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:2

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.07, 8.07, 8.07); Calibrated: 27.09.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.214 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.43 V/m; Power Drift = -0.179 dB

Peak SAR (extrapolated) = 0.327 W/kg

SAR(1 g) = 0.212 mW/g; SAR(10 g) = 0.136 mW/g

Maximum value of SAR (measured) = 0.229 mW/g

Body Worn/Zoom Scan 2 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.43 V/m; Power Drift = -0.179 dB

Peak SAR (extrapolated) = 0.302 W/kg

SAR(1 g) = 0.187 mW/g; SAR(10 g) = 0.114 mW/g

Maximum value of SAR (measured) = 0.204 mW/g




Fig. 4: SAR distribution for GPRS 1900 (Class 12), channel 661, Lap Held Position (Fujitsu Siemens AMILO Pro V3205, March 28, 2007; Ambient Temperature: 22.1° C; Liquid Temperature: 21.3 C).

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [AC_393_yphm_1.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:2

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.07, 8.07, 8.07); Calibrated: 27.09.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.362 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.9 V/m; Power Drift = -0.186 dB

Peak SAR (extrapolated) = 0.532 W/kg

SAR(1 g) = 0.337 mW/g; SAR(10 g) = 0.204 mW/g

Maximum value of SAR (measured) = 0.365 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.9 V/m; Power Drift = -0.186 dB

Peak SAR (extrapolated) = 0.501 W/kg

SAR(1 g) = 0.302 mW/g; SAR(10 g) = 0.178 mW/g

Maximum value of SAR (measured) = 0.325 mW/g




Fig. 5: SAR distribution for GPRS 1900 (Class 12), channel 661, Lap Held Position (Acer TravelMate, March 28, 2007; Ambient Temperature: 22.1° C; Liquid Temperature: 21.3 C).

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [HP_393_yphm_1.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:2

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.07, 8.07, 8.07); Calibrated: 27.09.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.241 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.20 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 0.368 W/kg

SAR(1 g) = 0.233 mW/g; SAR(10 g) = 0.146 mW/g

Maximum value of SAR (measured) = 0.252 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.20 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 0.384 W/kg

SAR(1 g) = 0.219 mW/g; SAR(10 g) = 0.124 mW/g

Maximum value of SAR (measured) = 0.239 mW/g




Fig. 6: SAR distribution for GPRS 1900 (Class 12), channel 661, Lap Held Position (HP Compaq nc6320, March 28, 2007; Ambient Temperature: 22.1° C; Liquid Temperature: 21.0C).

3 SAR Distribution Plots, WCDMA II (FDD) Body

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [FS_393_yullhm_1_wdh.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: WCDMA FDD Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.59$ mho/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.07, 8.07, 8.07); Calibrated: 27.09.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (9x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.086 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.40 V/m; Power Drift = -0.165 dB

Peak SAR (extrapolated) = 0.128 W/kg

SAR(1 g) = 0.081 mW/g; SAR(10 g) = 0.050 mW/g

Maximum value of SAR (measured) = 0.087 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.40 V/m; Power Drift = -0.165 dB

Peak SAR (extrapolated) = 0.137 W/kg

SAR(1 g) = 0.082 mW/g; SAR(10 g) = 0.049 mW/g

Maximum value of SAR (measured) = 0.091 mW/g




Fig. 7: SAR distribution for WCDMA II (FDD), channel 9400, Lap Held Position (Fujitsu Siemens AMILO Pro V3205, April 02, 2007; Ambient Temperature: 22.1° C; Liquid Temperature: 21.0° C).

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [AC_393_yullhm_1.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: WCDMA FDD Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.59$ mho/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.07, 8.07, 8.07); Calibrated: 27.09.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (9x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.168 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.55 V/m; Power Drift = 0.074 dB

Peak SAR (extrapolated) = 0.271 W/kg

SAR(1 g) = 0.167 mW/g; SAR(10 g) = 0.098 mW/g

Maximum value of SAR (measured) = 0.183 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.55 V/m; Power Drift = 0.074 dB

Peak SAR (extrapolated) = 0.222 W/kg

SAR(1 g) = 0.135 mW/g; SAR(10 g) = 0.079 mW/g

Maximum value of SAR (measured) = 0.149 mW/g




Fig. 8: SAR distribution for WCDMA II (FDD), channel 9400, Lap Held Position (Acer TravelMate, April 02, 2007; Ambient Temperature: 22.1° C; Liquid Temperature: 21.0° C).

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [HP_393_yullhm_1_wdh.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: WCDMA FDD Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.59$ mho/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.07, 8.07, 8.07); Calibrated: 27.09.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (9x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.111 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.95 V/m; Power Drift = 0.113 dB

Peak SAR (extrapolated) = 0.165 W/kg

SAR(1 g) = 0.104 mW/g; SAR(10 g) = 0.064 mW/g

Maximum value of SAR (measured) = 0.112 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.95 V/m; Power Drift = 0.113 dB

Peak SAR (extrapolated) = 0.156 W/kg

SAR(1 g) = 0.089 mW/g; SAR(10 g) = 0.050 mW/g

Maximum value of SAR (measured) = 0.098 mW/g




Fig. 9: SAR distribution for WCDMA II (FDD), channel 9400, Lap Held Position (HP Compaq nc6320, April 02, 2007; Ambient Temperature: 22.1° C; Liquid Temperature: 21.0° C).

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [AC_393_yullhm_1_hsdpa.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: WCDMA FDD Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.59$ mho/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.07, 8.07, 8.07); Calibrated: 27.09.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (9x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.172 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.79 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.307 W/kg

SAR(1 g) = 0.188 mW/g; SAR(10 g) = 0.109 mW/g

Maximum value of SAR (measured) = 0.205 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.79 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.245 W/kg

SAR(1 g) = 0.142 mW/g; SAR(10 g) = 0.081 mW/g

Maximum value of SAR (measured) = 0.156 mW/g




Fig. 10: SAR distribution for WCDMA II (FDD), HSDPA, channel 9400, Lap Held Position (Acer TravelMate, April 02, 2007; Ambient Temperature: 22.1° C; Liquid Temperature: 21.0° C).

4 SAR Distribution Plots, WCDMA V (FDD) Body

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [FS_393_buVhm_1.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: WCDMA (FDD) Band V; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 836.6$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(6.22, 6.22, 6.22); Calibrated: 15.02.2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.02.2007
- Phantom: SAM Sugar 1059; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.219 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.4 V/m; Power Drift = -0.023 dB

Peak SAR (extrapolated) = 0.299 W/kg

SAR(1 g) = 0.200 mW/g; SAR(10 g) = 0.132 mW/g

Maximum value of SAR (measured) = 0.223 mW/g




Fig. 11: SAR distribution for WCDMA V (FDD), channel 4183, Lap Held Position (Fujitsu Siemens AMILO Pro V3205, April 02, 2007; Ambient Temperature: 22.0° C; Liquid Temperature: 21.0° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [AC_393_buVhm_1.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: WCDMA (FDD) Band V; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 836.6$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(6.22, 6.22, 6.22); Calibrated: 15.02.2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.02.2007
- Phantom: SAM Sugar 1059; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.187 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.0 V/m; Power Drift = 0.163 dB

Peak SAR (extrapolated) = 0.260 W/kg

SAR(1 g) = 0.191 mW/g; SAR(10 g) = 0.136 mW/g

Maximum value of SAR (measured) = 0.203 mW/g




Fig. 12: SAR distribution for WCDMA V (FDD), channel 4183, Lap Held Position (Acer TravelMate, April 02, 2007; Ambient Temperature: 22.0° C; Liquid Temperature: 21.0° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [HP_393_buVhm_1.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: WCDMA (FDD) Band V; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 836.6$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(6.22, 6.22, 6.22); Calibrated: 15.02.2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.02.2007
- Phantom: SAM Sugar 1059; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.332 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.8 V/m; Power Drift = -0.032 dB

Peak SAR (extrapolated) = 0.461 W/kg

SAR(1 g) = 0.316 mW/g; SAR(10 g) = 0.209 mW/g

Maximum value of SAR (measured) = 0.344 mW/g




Fig. 13: SAR distribution for WCDMA V (FDD), channel 4183, Lap Held Position (HP Compaq nc6320, April 02 2007; Ambient Temperature: 22.0° C; Liquid Temperature: 21.0° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [HP_393_buVhm_1_hsdpa.da4](#)

DUT: Option; Type: Globetrotter Express; Serial: 004401440325393

Program Name: Body Worn

Communication System: WCDMA (FDD) Band V; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 836.6$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(6.22, 6.22, 6.22); Calibrated: 15.02.2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.02.2007
- Phantom: SAM Sugar 1059; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.335 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.1 V/m; Power Drift = 0.038 dB

Peak SAR (extrapolated) = 0.470 W/kg

SAR(1 g) = 0.326 mW/g; SAR(10 g) = 0.217 mW/g

Maximum value of SAR (measured) = 0.349 mW/g




Fig. 14: SAR distribution for WCDMA V (FDD), HSDPA, channel 4183, Lap Held Position (HP Compaq nc6320, March 29, 2007; Ambient Temperature: 22.0° C; Liquid Temperature: 21.0° C).

5 SAR z-axis scans (Validation)




Fig. 15: SAR versus liquid depth, 835 MHz (GPRS 850), body (March 28, 2007; Ambient Temperature: 22.4° C; Liquid Temperature : 21.4° C).




Fig. 16: SAR versus liquid depth, 1900 MHz (GPRS 1900), body (March 28, 2007; Ambient Temperature: 22.1° C; Liquid Temperature : 21.2° C).




Fig. 17: SAR versus liquid depth, 835 MHz (WCDMA V), body (April 02, 2007; Ambient Temperature: 22.1° C; Liquid Temperature : 21.2° C).




Fig. 18: SAR versus liquid depth, 1900 MHz (WCDMA II), body (April 02, 2007; Ambient Temperature: 22.1° C; Liquid Temperature : 21.0° C).




Fig. 19: SAR versus liquid depth, 835 MHz (WCDMA V), body May 03, 2007; Ambient Temperature: 21.4° C; Liquid Temperature : 20.8° C).




Fig. 20: SAR versus liquid depth, 1900 MHz (WCDMA II), body (May 03, 2007; Ambient Temperature: 22.0° C; Liquid Temperature : 21.2° C).

6 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 21: SAR versus liquid depth, body: GPRS 850, channel 128 (HP Compaq nc 6320, March 28, 2007; Ambient Temperature: 22.4° C; Liquid Temperature: 21.4° C).




Fig. 22: SAR versus liquid depth, body: GPRS 1900, channel 661 (Acer TravelMate, March 28, 2007; Ambient Temperature: 22.1° C; Liquid Temperature: 21.3° C).




Fig. 23: SAR versus liquid depth, body: WCDMA II (FDD) in HSDPA, channel 9400 (Acer TravelMate, April 02, 2007; Ambient Temperature: 22.1° C; Liquid Temperature: 21.0° C).




Fig. 24: SAR versus liquid depth, body: WCDMA V (FDD), channel 4183 (HP Compaq nc 6230, April 02, 2007; Ambient Temperature: 22.0° C; Liquid Temperature: 21.0° C).