



# InterLab®

## Final Report on

### GI0644

**Report Reference:** MDE\_OPTI\_1202\_FCCc  
acc. Title 47 CFR chapter I part 22 subpart H  
**Date:** May 03, 2012

#### Test Laboratory:

7Layers AG  
Borsigstr. 11  
40880 Ratingen  
Germany

Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7Layers AG  
Borsigstrasse 11  
40880 Ratingen, Germany  
Phone: +49 (0) 2102 749 0  
Fax: +49 (0) 2102 749 350  
[www.7Layers.com](http://www.7Layers.com)

Aufsichtsratsvorsitzender •  
Chairman of the Supervisory Board:  
Ralf Mertens  
Vorstand • Board:  
Dr. H.-J. Meckelburg



Registergericht • registered in:  
Düsseldorf, HRB 44096  
UST-IdNr • VAT No.:  
DE 203159652  
TAX No. 147/5869/0385

## 1 Administrative Data

### 1.1 Project Data

*Project Responsible:* Yao Jing  
*Date Of Test Report:* 2012/05/03  
*Date of first test:* 2012/03/01  
*Date of last test:* 2012/04/26

### 1.2 Applicant Data

*Company Name:* Option nv  
*Street:* Gaston Geenslaan 14,  
*City:* B-3001 Leuven  
*Country:* Belgium  
*Contact Person:* Mr. Jan Willems  
*Phone:* +32 16 311 516  
*E-Mail:* j.willems@option.com

### 1.3 Test Laboratory Data

The following list shows all places and laboratories involved for test result generation:

#### 7 layers DE

*Company Name :* 7 layers AG  
*Street :* Borsigstrasse 11  
*City :* 40880 Ratingen  
*Country :* Germany  
*Contact Person :* Mr. Michael Albert  
*Phone :* +49 2102 749 201  
*Fax :* +49 2102 749 444  
*E Mail :* michael.albert@7Layers.de

#### Laboratory Details


Lab ID	Identification	Responsible	Accreditation Info
Lab 1	Radiated Emissions	Mr. Robert Machulec Mr. Andreas Petz	DAkkS-Registration no. D-PL-12140-01-01
Lab 2	Radio Lab	Mr. Robert Machulec Mr. Andreas Petz	DAkkS-Registration no. D-PL-12140-01-01

#### 1.4 Signature of the Testing Responsible



Robert Machulec  
responsible for tests performed in: Lab 1, Lab 2

#### 1.5 Signature of the Accreditation Responsible



Accreditation scope responsible person  
responsible for Lab 1, Lab 2

### 2 Test Object Data

#### 2.1 General OUT Description

The following section lists all OUTs (Object's Under Test) involved during testing.

##### OUT: GI0644

Product Category:	Computer Accessory
Manufacturer:	
Company Name:	Please see applicant data
<i>Contact Person:</i>	
	Please see applicant data
<i>Parameter List:</i>	
Parameter name	Value
<b>Parameter for Scope FCC_v2:</b>	
highest channel	251 (848.8MHz) for GSM850, 810 (1909.8MHz) for GSM1900, 4233 (846.6MHz) for FDD5, 9538 (1907.6MHz) for FDD2
lowest channel	128 (824.2MHz) for GSM850, 512 (1850.2MHz) for GSM1900, 4132 (826.4MHz) for FDD5, 9262 (1852.4MHz) for FDD2 (MHz)
mid channel	190 (836.6MHz) for GSM850, 661 (1880.0MHz) for GSM1900, 4183 (836.6MHz) for FDD5, 9400 (1880MHz) for FDD2

## 2.2 Detailed Description of OUT Samples

### Sample : b01

<i>OUT Identifier</i>	GI0644		
<i>Sample Description</i>	Sample #2		
<i>Serial No.</i>	YA2LC29005		
<i>HW Status</i>	2.0.2.0		
<i>SW Status</i>	2.2.19.0		
<i>Low Voltage</i>	5 V	<i>Low Temp.</i>	0 °C
<i>High Voltage</i>	5 V	<i>High Temp.</i>	40 °C
<i>Nominal Voltage</i>	5 V	<i>Normal Temp.</i>	23 °C

#### *Parameter List:*

<i>Parameter Description</i>	<i>Value</i>
------------------------------	--------------

#### **Parameter for Scope FCC\_v2**

IMEI 004401441450661

### Sample : c01

<i>OUT Identifier</i>	GI0644		
<i>Sample Description</i>	Sample #3		
<i>Serial No.</i>	YA2LC29003		
<i>HW Status</i>	2.0.2.0		
<i>SW Status</i>	2.2.19.0		
<i>Date of Receipt</i>	2012/03/09		
<i>Low Voltage</i>	5 V	<i>Low Temp.</i>	0 °C
<i>High Voltage</i>	5 V	<i>High Temp.</i>	40 °C
<i>Nominal Voltage</i>	5 V	<i>Normal Temp.</i>	+23 °C

#### *Parameter List:*

<i>Parameter Description</i>	<i>Value</i>
------------------------------	--------------

#### **Parameter for Scope FCC\_v2**

IMEI 004401441450646

## 2.3 OUT Features

### Features for OUT: GI0644

Designation	Description	Allowed Values	Supported Value(s)
<b>Features for scope: FCC_v2</b>			
DC	The OUT is powered by or connected to DC Mains		
EDGE850	EUT supports EDGE in the band 824 MHz - 849 MHz		
EDGE1900	EUT supports EDGE in the band 1850 MHz - 1910 MHz		
FDD2	EUT supports UMTS FDD2 in the band 1850 MHz - 1910 MHz		
GSM850	EUT supports GSM850 band 824MHz - 849MHz		
HSDPA-FDD2	EUT supports UMTS FDD2 HSDPA in the band 1850 MHz - 1910 MHz		
HSDPA-FDD5	EUT supports UMTS FDD5 HSDPA in the band 824 MHz - 849 MHz		
HSUPA-FDD2	EUT supports UMTS FDD2 HSUPA in the band 1850 MHz - 1910 MHz		
HSUPA-FDD5	EUT supports UMTS FDD5 HSUPA in the band 824 MHz - 849 MHz		
Iant	Integral Antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment		
PantC	permanent fixed antenna connector, which may be built-in, designed as an indispensable part of the equipment		
PCS1900	EUT supports PCS1900 band 1850MHz - 1910MHz		
Wb	EUT supports WLAN in mode b in the band 2400 MHz - 2483.5 MHz		
Wg	EUT supports WLAN in mode g in the band 2400 MHz - 2483.5 MHz		
Wn	EUT supports WLAN in mode n in the band 2400 MHz - 2483.5 MHz		

## 2.4 Auxiliary Equipment

AE No.	Type Designation	Serial No.	HW Status	SW Status	Description
AE LAPAC1	PA-1750-08 P/N: PA3469E-1AC3	PK10000AC00-A05-085Q-15727	-	-	AC/DC adapter of Laptop LAPT01
AE LAPT01	Toshiba Tecra M9	87060248H	-	WinXP Prof. Engl.	Toshiba Laptop

## 2.5 Setups used for Testing

For each setup a relation is given to determine if and which samples and auxiliary equipment is used. The left side list all OUT samples and the right side lists all auxiliary equipment for the given setup.

Setup No.	<i>List of OUT samples</i>	<i>List of auxiliary equipment</i>	
Sample No.	Sample Description	AE No.	AE Description

### RSE\_1\_b01 (Representative configuration for spuri + radiated output power)

Sample: b01	Sample #2	AE LAPAC1	AC/DC adapter of Laptop LAPT01
		AE LAPT01	Toshiba Laptop

### RSE\_1\_c01 (Representative configuration for spuri + radiated output power)

Sample: c01	Sample #3	AE LAPAC1	AC/DC adapter of Laptop LAPT01
		AE LAPT01	Toshiba Laptop

### S03\_b01

Sample: b01	Sample #2
-------------	-----------

## 3 Results

### 3.1 General

#### Documentation of tested devices:

Available at the test laboratory.

#### Interpretation of the test results:

The results of the inspection are described on the following pages, where 'Conformity' or 'Passed' means that the certification criteria were verified and that the tested device is conform to the applied standard.

In cases where 'Declaration' is printed, the required documents are available in the manufacturers product documentation.

In cases where 'not applicable' is printed, the test case requirements are not relevant to the specific equipment implementation.

#### Note:

The tested Product GI0644 is a USB modem with 2G/3G/WLAN function, and can also act as a WLAN hot spot.

In accordance to the change description made by the applicant, the difference between the previous product GI0643 (FCC ID: NCMOGI0643) and the new product GI0644 (FCC ID: NCMOGI0644) is band FDDVIII replaced by band FDDV. No changes are made in the other functionalities of the Product. Therefore the conducted output power and spurious emissions radiated of GI0644 was measured and compared to the results of the original product GI0643 to confirm that no changes are made in the previous tested parts. The result of the original Product GI0643 can be found in the report reference No. MDE\_OPTI\_1101\_FCCe dated on November 10, 2011. A comparison of conducted output power values between this product GI0644 and the original product GI0643 was made(see annex). They are very near with each other and inside the tolerance of output power (see document "tune-up procedure for GI0644").

This test report replaces test report MDE\_OPTI\_1202\_FCCa.



---

Reference: MDE\_OPTI\_1202\_FCCc

acc. Title 47 CFR chapter I part 22 subpart H

### **3.2 List of the Applicable Body**

(Body for Scope: FCC\_v2)

<i>Designation</i>	<i>Description</i>
FCC47CFRChIPART22PUBLIC MOBILE SERVICES	Part 22, Subpart H - Cellular Radiotelephone Service

### **3.3 List of Test Specification**

<i>Test Specification:</i>	<b>FCC part 2 and 22</b>
<i>Version</i>	10-1-11 Edition
<i>Title:</i>	PART 2 - GENERAL RULES AND REGULATIONS PART 22 - PUBLIC MOBILE SERVICES

### 3.4 Summary

Test Case Identifier / Name Test (condition)	Result	Date of Test	Lab Ref.	Setup
<b>22.1 RF Power Output §2.1046, §22.913</b>				
22.1; Frequency Band = 850, Mode = EDGE, Channel = 190, Frequency = 836.6MHz, Method = radiated	Passed	2012/04/26	Lab 1	RSE_1_b01
22.1; Frequency Band = 850, Mode = GSM, Channel = 190, Frequency = 836.6MHz, Method = radiated	Passed	2012/04/26	Lab 1	RSE_1_b01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_1, Channel = 4132, Frequency = 826.4MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_1, Channel = 4183, Frequency = 836.6MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_1, Channel = 4233, Frequency = 846.6MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_2, Channel = 4132, Frequency = 826.4MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_2, Channel = 4183, Frequency = 836.6MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_2, Channel = 4233, Frequency = 846.6MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_3, Channel = 4132, Frequency = 826.4MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_3, Channel = 4183, Frequency = 836.6MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_3, Channel = 4233, Frequency = 846.6MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_4, Channel = 4132, Frequency = 826.4MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_4, Channel = 4183, Frequency = 836.6MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_4, Channel = 4233, Frequency = 846.6MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_5, Channel = 4132, Frequency = 826.4MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_5, Channel = 4183, Frequency = 836.6MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = HSUPA_subtest_5, Channel = 4233, Frequency = 846.6MHz, Method = radiated	Passed	2012/03/21	Lab 1	RSE_1_c01
22.1; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4132, Frequency = 826.4MHz, Method = radiated	Passed	2012/03/01	Lab 1	RSE_1_b01
22.1; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4183, Frequency = 836.6MHz, Method = radiated	Passed	2012/03/01	Lab 1	RSE_1_b01
22.1; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4233, Frequency = 846.6MHz, Method = radiated	Passed	2012/03/01	Lab 1	RSE_1_b01

Test Case Identifier / Name		acc. Title 47 CFR chapter I part 22 subpart H			
Test (condition)	Result	Date of Test	Lab	Ref.	Setup
<b>22.2 Frequency stability §2.1055</b>					
22.2; Frequency Band = FDD5, Mode = HSUPA, Channel = 4183, Frequency = 836.6MHz	Passed	2012/03/22	Lab 2	S03_b01	
22.2; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4183, Frequency = 836.6MHz	Passed	2012/03/22	Lab 2	S03_b01	
<b>22.3 Spurious emissions at antenna terminals §2.1051, §22.917</b>					
22.3; Frequency Band = FDD5, Mode = HSUPA, Channel = 4132, Frequency = 826.4MHz	Passed	2012/03/22	Lab 2	S03_b01	
22.3; Frequency Band = FDD5, Mode = HSUPA, Channel = 4183, Frequency = 836.6MHz	Passed	2012/03/22	Lab 2	S03_b01	
22.3; Frequency Band = FDD5, Mode = HSUPA, Channel = 4233, Frequency = 846.6MHz	Passed	2012/03/22	Lab 2	S03_b01	
22.3; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4132, Frequency = 826.4MHz	Passed	2012/03/22	Lab 2	S03_b01	
22.3; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4183, Frequency = 836.6MHz	Passed	2012/03/22	Lab 2	S03_b01	
22.3; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4233, Frequency = 846.6MHz	Passed	2012/03/22	Lab 2	S03_b01	
<b>22.4 Field strength of spurious radiation §2.1053, §22.917</b>					
22.4; Frequency Band = 850, Mode = EDGE, Channel = 190, Frequency = 836.6MHz	Passed	2012/03/10	Lab 1	RSE_1_c01	
22.4; Frequency Band = 850, Mode = GSM, Channel = 190, Frequency = 836.6MHz	Passed	2012/03/09	Lab 1	RSE_1_c01	
22.4; Frequency Band = FDD5, Mode = HSUPA, Channel = 4132, Frequency = 826.4MHz	Passed	2012/03/09	Lab 1	RSE_1_b01	
22.4; Frequency Band = FDD5, Mode = HSUPA, Channel = 4183, Frequency = 836.6MHz	Passed	2012/03/09	Lab 1	RSE_1_b01	
22.4; Frequency Band = FDD5, Mode = HSUPA, Channel = 4233, Frequency = 846.6MHz	Passed	2012/03/09	Lab 1	RSE_1_b01	
22.4; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4132, Frequency = 826.4MHz	Passed	2012/03/01	Lab 1	RSE_1_b01	
22.4; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4183, Frequency = 836.6MHz	Passed	2012/03/01	Lab 1	RSE_1_b01	
22.4; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4233, Frequency = 846.6MHz	Passed	2012/03/01	Lab 1	RSE_1_b01	

Test Case Identifier / Name Test (condition)	Result	acc. Title 47 CFR chapter I part 22 subpart H			
		Lab	Date of Test	Ref.	
<b>22.5 Emission and Occupied Bandwidth §2.1049, §22.917</b>					
22.5; Frequency Band = FDD5, Mode = HSUPA, Channel = 4132, Frequency = 826.4MHz	Passed		2012/03/22	Lab 2	S03_b01
22.5; Frequency Band = FDD5, Mode = HSUPA, Channel = 4183, Frequency = 836.6MHz	Passed		2012/03/22	Lab 2	S03_b01
22.5; Frequency Band = FDD5, Mode = HSUPA, Channel = 4233, Frequency = 846.6MHz	Passed		2012/03/22	Lab 2	S03_b01
22.5; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4132, Frequency = 826.4MHz	Passed		2012/03/22	Lab 2	S03_b01
22.5; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4183, Frequency = 836.6MHz	Passed		2012/03/22	Lab 2	S03_b01
22.5; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4233, Frequency = 846.6MHz	Passed		2012/03/22	Lab 2	S03_b01
<b>22.6 Band edge compliance §2.1053, §22.917</b>					
22.6; Frequency Band = FDD5, Mode = HSUPA, Channel = 4132, Frequency = 826.4MHz	Passed		2012/03/22	Lab 2	S03_b01
22.6; Frequency Band = FDD5, Mode = HSUPA, Channel = 4233, Frequency = 846.6MHz	Passed		2012/03/22	Lab 2	S03_b01
22.6; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4132, Frequency = 826.4MHz	Passed		2012/03/22	Lab 2	S03_b01
22.6; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4233, Frequency = 846.6MHz	Passed		2012/03/22	Lab 2	S03_b01

### 3.5 Detailed Results

#### 3.5.1 22.1 RF Power Output §2.1046, §22.913

**Test: 22.1; Frequency Band = 850, Mode = EDGE, Channel = 190, Frequency = 836.6MHz, Method = radiated**

*Result:* Passed


*Setup No.:* RSE\_1\_b01

*Date of Test:* 2012/04/26 21:51

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

#### Detailed Results:




detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	300	836.59	24.57	38.45	13.88	135.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 30 dB

**Test: 22.1; Frequency Band = 850, Mode = GSM, Channel = 190, Frequency = 836.6MHz, Method = radiated**

*Result:* Passed  
*Setup No.:* RSE\_1\_b01  
*Date of Test:* 2012/04/26 22:27  
*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES  
*Test Specification:* FCC part 2 and 22


**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	300	836.65	28.00	38.45	10.45	0.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 30 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_1, Channel = 4132, Frequency = 826.4MHz, Method = radiated**

*Result:* Passed  
*Setup No.:* RSE\_1\_c01  
*Date of Test:* 2012/03/21 4:35  
*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES  
*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	826	17.39	38.45	21.06	135.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_1, Channel = 4183, Frequency = 836.6MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 4:46

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	837	16.90	38.45	21.55	135.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_1, Channel = 4233, Frequency = 846.6MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 4:57

*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	826	17.39	38.45	21.06	135.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_2, Channel = 4132, Frequency = 826.4MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 2:33

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	826	15.58	38.45	22.87	135.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_2, Channel = 4183, Frequency = 836.6MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 2:41

*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	837	13.98	38.45	24.47	60.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_2, Channel = 4233, Frequency = 846.6MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 2:47

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	847	16.13	38.45	22.32	60.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_3, Channel = 4132, Frequency = 826.4MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 2:59

*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	826	18.04	38.45	20.41	135.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_3, Channel = 4183, Frequency = 836.6MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 3:07

*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	837	15.54	38.45	22.91	60.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_3, Channel = 4233, Frequency = 846.6MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 3:15

*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22


**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	847	17.63	38.45	20.82	0.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_4, Channel = 4132, Frequency = 826.4MHz, Method = radiated**

*Result:* Passed  
*Setup No.:* RSE\_1\_c01  
*Date of Test:* 2012/03/21 3:25  
*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES  
*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	825	16.63	38.45	21.82	135.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_4, Channel = 4183, Frequency = 836.6MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 3:32

*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	837	14.62	38.45	23.83	0.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_4, Channel = 4233, Frequency = 846.6MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 3:41

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	847	16.87	38.45	21.58	60.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_5, Channel = 4132, Frequency = 826.4MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 3:52

*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	826	17.18	38.45	21.27	135.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_5, Channel = 4183, Frequency = 836.6MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 4:05

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	837	15.07	38.45	23.38	135.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = HSUPA\_subtest\_5, Channel = 4233, Frequency = 846.6MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/21 4:13

*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
rms	maxhold	10000	847	17.48	38.45	20.97	60.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 6 dB

**Test: 22.1; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4132, Frequency = 826.4MHz, Method = radiated**


*Result:* Passed

*Setup No.:* RSE\_1\_b01

*Date of Test:* 2012/03/01 8:35

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22


**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	10000	826	24.42	38.45	14.03	135.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 30 dB

**Test: 22.1; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4183, Frequency = 836.6MHz, Method = radiated**

*Result:* Passed  
*Setup No.:* RSE\_1\_b01  
*Date of Test:* 2012/03/01 7:50  
*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES  
*Test Specification:* FCC part 2 and 22


**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	10000	834	23.98	38.45	14.47	105.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 30 dB

**Test: 22.1; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4233, Frequency = 846.6MHz, Method = radiated**

*Result:* Passed  
*Setup No.:* RSE\_1\_b01  
*Date of Test:* 2012/03/01 7:23  
*Body:* FCC47CFRCHIPART22PUBLIC MOBILE SERVICES  
*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	10000	848	26.21	38.45	12.24	105.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 30 dB

### 3.5.2 22.2 Frequency stability §2.1055

**Test: 22.2; Frequency Band = FDD5, Mode = HSUPA, Channel = 4183, Frequency = 836.6MHz**

Result: Passed  
 Setup No.: S03\_b01  
 Date of Test: 2012/03/22 16:08  
 Body: FCC47CFRChIPART22PUBLIC MOBILE SERVICES  
 Test Specification: FCC part 2 and 22

**Detailed Results:**

Temp. °C	Duration min	Voltage	Limit Hz	Freq. error Average (Hz)	Freq. error Max. (Hz)	Verdict
-30	0	normal	2095.5	-5	-28	passed
-30	5			-3	-23	passed
-30	10			-4	-10	passed
-20	0	normal	2095.5	-5	-24	passed
-20	5			-4	-13	passed
-20	10			-4	-11	passed
-10	0	normal	2095.5	-6	-14	passed
-10	5			-5	-13	passed
-10	10			-5	-14	passed
0	0	normal	2095.5	-6	-15	passed
0	5			-5	-9	passed
0	10			-4	-12	passed
10	0	normal	2095.5	-5	-14	passed
10	5			-4	-13	passed
10	10			-4	-12	passed
20	0	normal = high = low <sup>1)</sup>	2095.5	-5	-12	passed
20	5			-3	-14	passed
20	10			-4	-20	passed
30	0	normal	2095.5	-7	-16	passed
30	5			-5	-15	passed
30	10			-6	-16	passed
40	0	normal	2095.5	-5	-14	passed
40	5			-6	-14	passed
40	10			-5	-14	passed
50	0	normal	2095.5	-4	-13	passed
50	5			-3	-26	passed
50	10			-4	-17	passed

1) The manufacturer declared that normal voltage is equivalent with high and low voltage.

**Test: 22.2; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4183, Frequency = 836.6MHz**

Result: Passed  
 Setup No.: S03\_b01  
 Date of Test: 2012/03/22 16:07  
 Body: FCC47CFRCHIPART22PUBLIC MOBILE SERVICES  
 Test Specification: FCC part 2 and 22

**Detailed Results:**

Temp. °C	Duration min	Voltage	Limit Hz	Freq. error Average (Hz)	Freq. error Max. (Hz)	Verdict
-30	0	normal	2095.5	-5	-22	passed
-30	5			1	-15	passed
-30	10			0	-14	passed
-20	0	normal	2095.5	-5	-19	passed
-20	5			-1	-13	passed
-20	10			-1	-14	passed
-10	0	normal	2095.5	-4	-20	passed
-10	5			-3	-13	passed
-10	10			-2	-16	passed
0	0	normal	2095.5	-1	-18	passed
0	5			-3	-15	passed
0	10			-3	-14	passed
10	0	normal	2095.5	-2	-13	passed
10	5			-3	-14	passed
10	10			-4	-14	passed
20	0	normal = high = low <sup>1)</sup>	2095.5	-5	-24	passed
20	5			-4	-26	passed
20	10			-3	-15	passed
30	0	normal	2095.5	-2	-16	passed
30	5			-2	-17	passed
30	10			-3	-14	passed
40	0	normal	2095.5	-3	-14	passed
40	5			-4	-18	passed
40	10			-3	-20	passed
50	0	normal	2095.5	-4	-15	passed
50	5			-3	-16	passed
50	10			-3	-14	passed

1) The manufacturer declared that normal voltage is equivalent with high and low voltage.



---

Reference: MDE\_OPTI\_1202\_FCCc

acc. Title 47 CFR chapter I part 22 subpart H

### **3.5.3 22.3 Spurious emissions at antenna terminals §2.1051, §22.917**

**Test: 22.3; Frequency Band = FDD5, Mode = HSUPA, Channel = 4132, Frequency = 826.4MHz**


*Result:* Passed

*Setup No.:* S03\_b01

*Date of Test:* 2012/03/22 4:37

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22


**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	margin to limit /dB	limit /dBm	verdict
rms	maxhold	50	823.982	-44.00	31.00	-13	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.3; Frequency Band = FDD5, Mode = HSUPA, Channel = 4183, Frequency = 836.6MHz**

*Result:* Passed  
*Setup No.:* S03\_b01  
*Date of Test:* 2012/03/22 4:51  
*Body:* FCC47CFRChI PART22PUBLIC MOBILE SERVICES  
*Test Specification:* FCC part 2 and 22


**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	margin to limit /dB	limit /dBm	verdict
rms	maxhold	100	2418.838	-51.33	38.33	-13	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.3; Frequency Band = FDD5, Mode = HSUPA, Channel = 4233, Frequency = 846.6MHz**

*Result:* Passed  
*Setup No.:* S03\_b01  
*Date of Test:* 2012/03/22 4:44  
*Body:* FCC47CFRChI PART22PUBLIC MOBILE SERVICES  
*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	margin to limit /dB	limit /dBm	verdict
rms	maxhold	50	849.034	-37.75	24.75	-13	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.3; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4132, Frequency = 826.4MHz**


*Result:* Passed

*Setup No.:* S03\_b01

*Date of Test:* 2012/03/22 4:14

*Body:* FCC47CFRChI PART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	margin to limit /dB	limit /dBm	verdict
rms	maxhold	100	823.000	-40.77	27.77	-13	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.3; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4183, Frequency = 836.6MHz**


Result: Passed

Setup No.: S03\_b01

Date of Test: 2012/03/22 4:26

Body: FCC47CFRChI PART22PUBLIC MOBILE SERVICES

Test Specification: FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	margin to limit /dB	limit /dBm	verdict
rms	maxhold	100	2410.822	-46.48	33.48	-13	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.3; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4233, Frequency = 846.6MHz**


*Result:* Passed

*Setup No.:* S03\_b01

*Date of Test:* 2012/03/22 4:20

*Body:* FCC47CFRChI PART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	margin to limit /dB	limit /dBm	verdict
rms	maxhold	100	850.234	-37.54	24.54	-13	passed

no further values have been found with a margin of less than 20 dB

### 3.5.4 22.4 Field strength of spurious radiation §2.1053, §22.917

**Test: 22.4; Frequency Band = 850, Mode = EDGE, Channel = 190, Frequency = 836.6MHz**

*Result:* Passed


*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/10 0:23

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

#### Detailed Results:



detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	1000	989.2	-41.55	-13.00	28.55	-180.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.4; Frequency Band = 850, Mode = GSM, Channel = 190, Frequency = 836.6MHz**


*Result:* Passed

*Setup No.:* RSE\_1\_c01

*Date of Test:* 2012/03/09 17:24

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	1000	2509.0	-38.81	-13.00	25.81	-45.0	horizontal	vertical	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.4; Frequency Band = FDD5, Mode = HSUPA, Channel = 4132, Frequency = 826.4MHz**


Result: Passed

Setup No.: RSE\_1\_b01

Date of Test: 2012/03/09 18:29

Body: FCC47CFRChIPART22PUBLIC MOBILE SERVICES

Test Specification: FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	1000	7228.5	-36.76	-13.00	23.76	-90.0	vertical	vertical	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.4; Frequency Band = FDD5, Mode = HSUPA, Channel = 4183, Frequency = 836.6MHz**


Result: Passed

Setup No.: RSE\_1\_b01

Date of Test: 2012/03/09 19:06

Body: FCC47CFRChI PART22PUBLIC MOBILE SERVICES

Test Specification: FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	1000	9464.9	-42.03	-13.00	29.03	0.0	vertical	vertical	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.4; Frequency Band = FDD5, Mode = HSUPA, Channel = 4233, Frequency = 846.6MHz**


Result: Passed

Setup No.: RSE\_1\_b01

Date of Test: 2012/03/09 19:45

Body: FCC47CFRChIPART22PUBLIC MOBILE SERVICES

Test Specification: FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	1000	890.6	-41.30	-13.00	28.30	0.0	horizontal	vertical	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.4; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4132, Frequency = 826.4MHz**


Result: Passed

Setup No.: RSE\_1\_b01

Date of Test: 2012/03/01 2:59

Body: FCC47CFRChIPART22PUBLIC MOBILE SERVICES

Test Specification: FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	100	822.98	-23.52	-13.00	10.52	0.0	horizontal	horizontal	passed
peak	maxhold	50	823.82	-32.99	-13.00	19.99	-180.0	vertical	vertical	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.4; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4183, Frequency = 836.6MHz**


Result: Passed

Setup No.: RSE\_1\_b01

Date of Test: 2012/03/01 4:44

Body: FCC47CFRChIPART22PUBLIC MOBILE SERVICES

Test Specification: FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	1000	985.6	-42.25	-13.00	29.25	90.0	horizontal	vertical	passed

no further values have been found with a margin of less than 20 dB

**Test: 22.4; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4233, Frequency = 846.6MHz**


Result: Passed

Setup No.: RSE\_1\_b01

Date of Test: 2012/03/01 6:42

Body: FCC47CFRChI PART22PUBLIC MOBILE SERVICES

Test Specification: FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	50	849.03	-27.11	-13.00	14.11	-180.0	horizontal	vertical	passed
peak	maxhold	50	849.13	-27.76	-13.00	14.76	0.0	horizontal	horizontal	passed
peak	maxhold	50	849.18	-31.30	-13.00	18.30	-180.0	horizontal	horizontal	passed
peak	maxhold	100	850.07	-29.28	-13.00	16.28	90.0	vertical	vertical	passed
peak	maxhold	100	850.25	-32.94	-13.00	19.94	0.0	vertical	horizontal	passed
peak	maxhold	100	850.41	-26.92	-13.00	13.92	0.0	horizontal	horizontal	passed

no further values have been found with a margin of less than 20 dB



---

Reference: MDE\_OPTI\_1202\_FCCc

acc. Title 47 CFR chapter I part 22 subpart H

### **3.5.5 22.5 Emission and Occupied Bandwidth §2.1049, §22.917**

**Test: 22.5; Frequency Band = FDD5, Mode = HSUPA, Channel = 4132, Frequency = 826.4MHz**


*Result:* Passed


*Setup No.:* S03\_b01

*Date of Test:* 2012/03/22 4:31

*Body:* FCC47CFRChI PART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**




---

Reference: MDE\_OPTI\_1202\_FCCc

acc. Title 47 CFR chapter I part 22 subpart H

detector	trace	resolution bandwidth /kHz	type of measurement	measured value /kHz	verdict
peak	maxhold	100	-26dB bandwidth	4689.4	passed
peak	maxhold	100	99% bandwidth	4168.3	passed

**Test: 22.5; Frequency Band = FDD5, Mode = HSUPA, Channel = 4183, Frequency = 836.6MHz**


*Result:* Passed


*Setup No.:* S03\_b01

*Date of Test:* 2012/03/22 4:53

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**




detector	trace	resolution bandwidth /kHz	type of measurement	measured value /kHz	verdict
peak	maxhold	100	-26dB bandwidth	4689.4	passed
peak	maxhold	100	99% bandwidth	4168.3	passed

**Test: 22.5; Frequency Band = FDD5, Mode = HSUPA, Channel = 4233, Frequency = 846.6MHz**

*Result:* Passed

*Setup No.:* S03\_b01


*Date of Test:* 2012/03/22 4:45

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


Title: bandwidth measurement  
 Comment A: 37500, FDD V, 26dB bandwidth,  
 channel 4233 (846.6MHz)  
 Date: 22.MAR.2012 04:50:58



detector	trace	resolution bandwidth /kHz	type of measurement	measured value /kHz	verdict
peak	maxhold	100	-26dB bandwidth	4709.4	passed
peak	maxhold	100	99% bandwidth	4168.3	passed

**Test: 22.5; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4132, Frequency = 826.4MHz**


*Result:* Passed

*Setup No.:* S03\_b01


*Date of Test:* 2012/03/22 4:15

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


Reference: MDE\_OPTI\_1202\_FCCc



detector	trace	resolution bandwidth /kHz	type of measurement	measured value /kHz	verdict
peak	maxhold	100	-26dB bandwidth	4709.4	passed
peak	maxhold	100	99% bandwidth	4168.3	passed

**Test: 22.5; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4183, Frequency = 836.6MHz**


*Result:* Passed

*Setup No.:* S03\_b01


*Date of Test:* 2012/03/22 4:27

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


Reference: MDE\_OPTI\_1202\_FCCc



detector	trace	resolution bandwidth /kHz	type of measurement	measured value /kHz	verdict
peak	maxhold	100	-26dB bandwidth	4689.4	passed
peak	maxhold	100	99% bandwidth	4148.3	passed

**Test: 22.5; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4233, Frequency = 846.6MHz**


*Result:* Passed


*Setup No.:* S03\_b01

*Date of Test:* 2012/03/22 4:21

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**




---

Reference: MDE\_OPTI\_1202\_FCCc

acc. Title 47 CFR chapter I part 22 subpart H

detector	trace	resolution bandwidth /kHz	type of measurement	measured value /kHz	verdict
peak	maxhold	100	-26dB bandwidth	4689.4	passed
peak	maxhold	100	99% bandwidth	4128.3	passed



---

Reference: MDE\_OPTI\_1202\_FCCc

acc. Title 47 CFR chapter I part 22 subpart H

### **3.5.6 22.6 Band edge compliance §2.1053, §22.917**

**Test: 22.6; Frequency Band = FDD5, Mode = HSUPA, Channel = 4132, Frequency = 826.4MHz**


*Result:* Passed

*Setup No.:* S03\_b01

*Date of Test:* 2012/03/22 4:39

*Body:* FCC47CFRChI PART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	margin to limit /dB	limit /dBm	verdict
peak	maxhold	50	823.953	-34.51	21.51	-13.0	passed
average	maxhold	50	824.000	-37.79	24.79	-13.0	passed
rms	maxhold	50	823.988	-37.79	24.79	-13.0	passed

no further values have been found by test instrument with a margin of less than 20 dB

**Test: 22.6; Frequency Band = FDD5, Mode = HSUPA, Channel = 4233, Frequency = 846.6MHz**


*Result:* Passed

*Setup No.:* S03\_b01

*Date of Test:* 2012/03/22 4:46

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


Title: band edge compliance measurement  
 Comment A: 37500, FDD V, band edge compliance,  
 channel 4233 (846.6MHz)  
 Date: 22.MAR.2012 04:51:57

detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	margin to limit /dB	limit /dBm	verdict
peak	maxhold	50	849.082	-28.49	15.49	-13.0	passed
average	maxhold	50	849.070	-31.34	18.34	-13.0	passed
rms	maxhold	50	849.454	-31.67	18.67	-13.0	passed

no further values have been found by test instrument with a margin of less than 20 dB

**Test: 22.6; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4132, Frequency = 826.4MHz**


*Result:* Passed

*Setup No.:* S03\_b01

*Date of Test:* 2012/03/22 4:16

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	margin to limit /dB	limit /dBm	verdict
peak	maxhold	50	823.907	-21.98	8.98	-13.0	passed
average	maxhold	50	824.000	-24.08	11.08	-13.0	passed
rms	maxhold	50	823.837	-24.95	11.95	-13.0	passed

no further values have been found by test instrument with a margin of less than 20 dB

**Test: 22.6; Frequency Band = FDD5, Mode = W-CDMA, Channel = 4233, Frequency = 846.6MHz**


*Result:* Passed

*Setup No.:* S03\_b01

*Date of Test:* 2012/03/22 4:22

*Body:* FCC47CFRChIPART22PUBLIC MOBILE SERVICES

*Test Specification:* FCC part 2 and 22

**Detailed Results:**


Title: band edge compliance measurement  
 Comment A: 37500, FDD V, band edge compliance,  
 channel 4233 (846.6MHz)  
 Date: 22.MAR.2012 04:28:04

detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	margin to limit /dB	limit /dBm	verdict
peak	maxhold	50	849.047	-28.91	15.91	-13.0	passed
average	maxhold	50	849.140	-32.36	19.36	-13.0	passed
rms	maxhold	50	849.000	-31.02	18.02	-13.0	passed

no further values have been found by test instrument with a margin of less than 20 dB

## 4 Test Equipment Details

### 4.1 List of Used Test Equipment

The calibration, hardware and software states are shown for the testing period.

#### Test Equipment Anechoic Chamber

Lab ID:	Lab 1
Manufacturer:	Frankonia
Description:	Anechoic Chamber for radiated testing
Type:	10.58x6.38x6.00 m <sup>3</sup>

#### Single Devices for Anechoic Chamber

Single Device Name	Type	Serial Number	Manufacturer
Air compressor	none	-	Atlas Copco
Anechoic Chamber	10.58 x 6.38 x 6.00 m <sup>3</sup> <i>Calibration Details</i>	none	Frankonia <i>Last Execution</i> <i>Next Execution</i>
	FCC listing 96716 3m Part15/18	2011/01/11	2014/01/10
	IC listing 3699A-1 3m	2011/02/07	2014/02/06
Controller Maturo	MCU	961208	Maturo GmbH
EMC camera	CE-CAM/1	-	CE-SYS
EMC camera Nr.2	CCD-400E	0005033	Mitsubishi
Filter ISDN	B84312-C110-E1		Siemens&Matsushita
Filter Universal 1A	BB4312-C30-H3	-	Siemens&Matsushita

#### Test Equipment Auxiliary Equipment for Radiated emissions

Lab ID:	Lab 1
Description:	Equipment for emission measurements
Serial Number:	see single devices

#### Single Devices for Auxiliary Equipment for Radiated emissions

Single Device Name	Type	Serial Number	Manufacturer
Antenna mast	AS 620 P	620/37	HD GmbH
Biconical dipole	VUBA 9117 <i>Calibration Details</i>	9117-108	Schwarzbeck <i>Last Execution</i> <i>Next Execution</i>
	Standard Calibration	2008/10/27	2013/10/26
	Standard Calibration	2012/01/18	2015/01/17
Broadband Amplifier 18MHz-26GHz	JS4-18002600-32-5P <i>Calibration Details</i>	849785	Miteq <i>Last Execution</i> <i>Next Execution</i>
	Path Calibration	2011/11/15	2012/05/14
Broadband Amplifier 1GHz-4GHz	AFS4-01000400-1Q-10P-4 <i>Calibration Details</i>	-	Miteq <i>Last Execution</i> <i>Next Execution</i>
	Path Calibration	2011/11/15	2012/05/14
Broadband Amplifier 30MHz-18GHz	JS4-00101800-35-5P <i>Calibration Details</i>	896037	Miteq <i>Last Execution</i> <i>Next Execution</i>
	Path Calibration	2011/11/15	2012/05/14
Cable "ESI to EMI Antenna"	EcoFlex10	W18.01-2+W38.01-2	Kabel Kusch

**Single Devices for Auxiliary Equipment for Radiated emissions (continued)**

Single Device Name	Type	Serial Number	Manufacturer	
			Last Execution	Next Execution
	<i>Calibration Details</i>			
	Path Calibration		2011/11/15	2012/05/14
Cable "ESI to Horn Antenna"	UFB311A+UFB293C	W18.02-2+W38.02-2	Rosenberger Micro-Coax	
	<i>Calibration Details</i>			
	Path Calibration		2011/11/15	2012/05/14
Double-ridged horn	HF 906	357357/001	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>			
	Standard Calibration		2009/04/16	2012/04/15
Double-ridged horn	HF 906	357357/002	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>			
	Standard Calibration		2009/04/28	2012/04/27
High Pass Filter	4HC1600/12750-1.5-KK	9942011	Trilithic	
	<i>Calibration Details</i>			
	Path Calibration		2011/11/15	2012/05/14
High Pass Filter	5HC2700/12750-1.5-KK	9942012	Trilithic	
	<i>Calibration Details</i>			
	Path Calibration		2011/11/15	2012/05/14
High Pass Filter	5HC3500/12750-1.2-KK	200035008	Trilithic	
	<i>Calibration Details</i>			
	Path Calibration		2011/11/15	2012/05/14
High Pass Filter	WHKX 7.0/18G-8SS	09	Wainwright	
	<i>Calibration Details</i>			
	Path Calibration		2011/11/15	2012/05/14
Log.-per. Antenna	HL 562 Ultralog	830547/003	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>			
	Standard Calibration		2009/05/27	2012/05/26
Loop Antenna	HFH2-Z2	829324/006	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>			
	Standard calibration		2011/10/27	2014/10/26
Pyramidal Horn Antenna 26,5 GHz	3160-09	00083069	EMCO Elektronik GmbH	
Pyramidal Horn Antenna 40 GHz	3160-10	00086675	EMCO Elektronik GmbH	
Tilt device Maturo (Rohacell)	Antrieb TD1.5-10kg	TD1.5-10kg/024/379070	Maturo GmbH	
		9		

### Test Equipment Auxiliary Test Equipment

**Lab ID:** **Lab 1, Lab 2**  
**Manufacturer:** see single devices  
**Description:** Single Devices for various Test Equipment  
**Type:** various  
**Serial Number:** none

### Single Devices for Auxiliary Test Equipment

Single Device Name	Type	Serial Number	Manufacturer
Broadband Power Divider N (Aux)	1506A / 93459	LM390	Weinschel Associates
Broadband Power Divider SMA	WA1515	A855	Weinschel Associates
Digital Multimeter 03 (Multimeter)	Fluke 177	86670383	Fluke Europe B.V.
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Execution</i>
	Customized calibration		2011/10/19 2013/10/18
Fibre optic link Satellite (Aux)	FO RS232 Link	181-018	Pontis
Fibre optic link Transceiver (Aux)	FO RS232 Link	182-018	Pontis
Isolating Transformer	LTS 604	1888	Thalheimer Transformatorenwerke GmbH
Notch Filter Ultra Stable (Aux)	WRCA800/960-6EEK	24	Wainwright
Vector Signal Generator	SMIQ 03B	832492/061	Rohde & Schwarz GmbH & Co.KG

### Test Equipment Digital Signalling Devices

**Lab ID:**
**Lab 1, Lab 2**
**Description:**

Signalling equipment for various wireless technologies.

### Single Devices for Digital Signalling Devices

Single Device Name	Type	Serial Number	Manufacturer
Bluetooth Signalling Unit CBT	CBT	100589	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Execution</i>
	Standard calibration	2011/11/24	2014/11/23
Universal Radio Communication Tester	CMU 200	102366	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Execution</i>
	Standard calibration	2011/05/26	2013/05/25
	<i>HW/SW Status</i>	<i>Date of Start</i>	<i>Date of End</i>
	Hardware: B11, B21V14, B21-2, B41, B52V14, B52-2, B53-2, B56V14, B68 3v04, PCMCIA, U65V04	2007/07/16	
	Software: K21 4v21, K22 4v21, K23 4v21, K24 4v21, K42 4v21, K43 4v21, K53 4v21, K56 4v22, K57 4v22, K58 4v22, K59 4v22, K61 4v22, K62 4v22, K63 4v22, K64 4v22, K65 4v22, K66 4v22, K67 4v22, K68 4v22, K69 4v22		
	Firmware: μP1 8v50 02.05.06		
	---		
Universal Radio Communication Tester	CMU 200	837983/052	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Execution</i>
	Standard calibration	2011/12/07	2014/12/06
	<i>HW/SW Status</i>	<i>Date of Start</i>	<i>Date of End</i>
	HW options: B11, B21V14, B21-2, B41, B52V14, B52-2, B53-2, B54V14, B56V14, B68 3v04, B95, PCMCIA, U65V02	2007/01/02	
	SW options: K21 4v11, K22 4v11, K23 4v11, K24 4v11, K27 4v10, K28 4v10, K42 4v11, K43 4v11, K53 4v10, K65 4v10, K66 4v10, K68 4v10,		
	Firmware: μP1 8v40 01.12.05		
	---		
	SW: K62, K69	2008/11/03	

**Test Equipment Emission measurement devices**
**Lab ID:**

Description:

Serial Number:

**Lab 1**

Equipment for emission measurements

see single devices

**Single Devices for Emission measurement devices**

Single Device Name	Type	Serial Number	Manufacturer
Personal Computer	Dell	30304832059	Dell
Power Meter	NRVD	828110/016	Rohde & Schwarz GmbH & Co.KG
	<i>Calibration Details</i>		<i>Last Execution Next Execution</i>
	Standard calibration		2011/05/03 2012/05/02
Sensor Head A	NRV-Z1	827753/005	Rohde & Schwarz GmbH & Co.KG
	<i>Calibration Details</i>		<i>Last Execution Next Execution</i>
	Standard calibration		2011/05/02 2012/05/01
Signal Generator	SMR 20	846834/008	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution Next Execution</i>
	standard calibration		2011/05/12 2014/05/11
Spectrum Analyzer	ESIB 26	830482/004	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution Next Execution</i>
	Standard Calibration		2011/12/05 2013/12/04
	<i>HW/SW Status</i>		<i>Date of Start Date of End</i>
	Firmware-Update 4.34.4 from 3.45 during calibration		2009/12/03

**Test Equipment Radio Lab Test Equipment**

**Lab ID:** **Lab 2**  
**Description:** Radio Lab Test Equipment

**Single Devices for Radio Lab Test Equipment**

Single Device Name	Type	Serial Number	Manufacturer
Broadband Power Divider SMA	WA1515	A856	Weinschel Associates
Coax Attenuator 10dB 4T-10 SMA 2W		F9401	Weinschel Associates
Coax Attenuator 10dB 56-10 SMA 2W		W3702	Weinschel Associates
Coax Attenuator 10dB 56-10 SMA 2W		W3711	Weinschel Associates
Coax Cable Huber&Suhner	Sucotest 2,0m		Rosenberger Micro-Coax
Coax Cable Rosenberger Micro Coax FA210A0010003030 SMA/SMA 1,0m	FA210A0010003030	54491-2	Rosenberger Micro-Coax
Power Meter	NRVD	828110/016	Rohde & Schwarz GmbH & Co.KG
<i>Calibration Details</i>			<i>Last Execution Next Execution</i>
Standard calibration		2011/05/03	2012/05/02
RF Step Attenuator RSP	RSP	833695/001	Rohde & Schwarz GmbH & Co.KG
Rubidium Frequency Standard	Datum, Model: MFL	2689/001	Datum-Beverly
<i>Calibration Details</i>			<i>Last Execution Next Execution</i>
Standard calibration		2011/06/17	2012/06/16
Sensor Head A	NRV-Z1	827753/005	Rohde & Schwarz GmbH & Co.KG
<i>Calibration Details</i>			<i>Last Execution Next Execution</i>
Standard calibration		2011/05/02	2012/05/01
Signal Generator	SMY02	829309/018	Rohde & Schwarz GmbH & Co. KG
<i>Calibration Details</i>			<i>Last Execution Next Execution</i>
Standard calibration		2011/11/04	2014/11/03
Signal Generator SME	SME03	827460/016	Rohde & Schwarz GmbH & Co.KG
<i>Calibration Details</i>			<i>Last Execution Next Execution</i>
Standard calibration		2011/11/25	2014/11/24
Signal Generator SMP	SMP02	836402/008	Rohde & Schwarz GmbH & Co. KG
Spectrum Analyser	FSIQ26	840061/005	Rohde & Schwarz GmbH & Co. KG
<i>Calibration Details</i>			<i>Last Execution Next Execution</i>
Standard calibration		2011/02/10	2013/02/09
Temperature Chamber Vötsch 03	VT 4002	58566002150010	Vötsch
<i>Calibration Details</i>			<i>Last Execution Next Execution</i>
Customized calibration		2012/03/12	2014/03/11



---

Reference: MDE\_OPTI\_1202\_FCCc

acc. Title 47 CFR chapter I part 22 subpart H

**Single Devices for Radio Lab Test Equipment (continued)**

<i>Single Device Name</i>	<i>Type</i>	<i>Serial Number</i>	<i>Manufacturer</i>
	Specific calibration	2010/03/16	2012/03/15



---

Reference: MDE\_OPTI\_1202\_FCCc

acc. Title 47 CFR chapter I part 22 subpart H

## **5 Annex**

### **5.1 Additional Information for Report**



---

Reference: MDE\_OPTI\_1202\_FCCc

acc. Title 47 CFR chapter I part 22 subpart H

Summary of Test Results

---

---

The EUT complied with all performed tests as listed in the summary section of this report.

---

Technical Report Summary

---

---

Type of Authorization :

Certification for a GSM cellular radiotelephone device

Applicable FCC Rules

Prepared in accordance with the requirements of FCC Rules and Regulations as listed in 47 CFR Ch.1 Parts 0 to 69. The following subparts are applicable to the results in this test report.

Part 2, Subpart J - Equipment Authorization Procedures, Certification

§ 2.1046 Measurement required: RF power output  
§ 2.1049 Measurement required: Occupied bandwidth  
§ 2.1051 Measurement required: Spurious emissions at antenna terminals  
§ 2.1053 Measurement required: Field strength of spurious radiation  
§ 2.1055 Measurement required: Frequency stability  
§ 2.1057 Frequency spectrum to be investigated

Part 22, Subpart C – Operational and Technical Requirements

§ 22.355 Frequency tolerance

Part 22, Subpart H – Cellular Radiotelephone Service

§ 22.913 Effective radiated power limits  
§ 22.917 Emission limitations for cellular equipment

additional documents

ANSI TIA-603-C-2004

Description of Methods of Measurements

---

---

RF Power Output

---

Standard     FCC Part 22, Subpart H

The test was performed according to: FCC §2.1046

#### Test Description (conducted measurement procedure)

- 1) The EUT was coupled to a Spectrum Analyser and a Digital Communication Tester through a Power Divider. Refer to chapter "Setup Drawings".
- 2) The total insertion losses for signal path 1 and signal path 2 were measured. The values were used to correct the readings from the Spectrum Analyser and the Digital Communication Tester.
- 3) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester.  
Important Settings:
  - Channel (Frequency): please refer to the detailed results
- 4) The transmitted power of the EUT was recorded by using a CMU200.

#### Test Description (radiated measurement procedure)

- 1) The EUT was placed inside an anechoic chamber. Refer to chapter "Setup Drawings". The EUT was coupled to a Digital Communication Tester which was located outside the chamber via a small signalling antenna.
- 2) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester.  
Important Settings:
  - Output Power: Maximum
  - Channel: please refer to the detailed results
- 3) A substitution procedure is used so that the readings from the spectrum analyser are corrected and represent directly the equivalent radiated power (related to a lamda/2 dipole).
- 4) The output power was measured in both vertical and horizontal antenna polarisation during the call is established on the lowest channel, mid channel and on the highest channel. To find the worst case power all orientations (X, Y, Z) of the EUT have been measured.
- 5) The test procedure according to TIA-603-C-2004 has been considered.

#### Test Requirements / Limits

##### §2.1046 Measurements Required: RF Power Output

- (a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in § 2.1033(c)(8). The electrical characteristics of the output terminals when this test is made shall be stated.
- §22.913 Effective radiated power limits
- (a)(2) Maximum ERP. ... The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

---

#### Emission and Occupied Bandwidth

---

Standard    FCC Part 22, Subpart H

The test was performed according to: FCC §2.1049

#### Test Description

- 1) The EUT was coupled to a Spectrum Analyser and a Digital Communication Tester through a Power Divider. Refer to chapter "Setup Drawings".
- 2) The total insertion losses for signal path 1 and signal path 2 were measured. The values were used to correct the readings from the Spectrum Analyser and the Digital Communication Tester.
- 3) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester.  
Important Settings:
  - Output Power: Maximum
  - Channel: please refer to the detailed results
- 4) Important Analyser Settings:
  - Resolution Bandwidth: >1% of the manufacturer's stated occupied bandwidth
- 5) The maximum spectral level of the modulated signal was recorded as the reference.
- 6) The emission bandwidth is measured as follows:  
the two furthest frequencies above and below the frequency of the maximum reference level where the

acc. Title 47 CFR chapter I part 22 subpart H

spectrum is -26 dB down have to be found.

7) The occupied bandwidth (99% Bandwidth) is measured as follows:

the occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 percent of the total mean power.

#### Test Requirements / Limits

##### § 2.1049 Measurements required: Occupied bandwidth

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions (as applicable):

(h) Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudo-random generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at the discretion of the user.

---

#### Spurious emissions at antenna terminals

---

##### Standard    FCC Part 22, Subpart H

The test was performed according to FCC §2.1051

#### Test Description

1) The EUT was coupled to a Spectrum Analyser and a Digital Communication Tester through a Power Divider. Refer to chapter "Setup Drawings".

2) The total insertion losses for signal path 1 and signal path 2 were measured. The values were used to correct the readings from the Spectrum Analyser and the Digital Communication Tester.

3) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester.

Important Settings:

- Output Power: Maximum

- Channel: please refer to the detailed results

4) Important Analyser Settings

- [Resolution Bandwidth]:

a) [>=1% of wanted signal bandwidth] in the Span of 1 MHz directly below and above the PCS-Band,  
b) otherwise [100 kHz] (or [1 MHz] for accelerated sweep times)

c) [reduced resolution bandwidth] in case the curve of the analyser IF-Filter or the wanted EUT signal leads to an exceeding of the limit, in this case a correction factor was used

- Sweep Time: depending on the transmitting signal, the span and the resolution bandwidth

5) The spurious emissions peaks were measured in the frequency range from 9 kHz to 10 GHz (up to the 10th harmonic) during the call was established

#### Test Requirements / Limits

##### § 2.1051 Spurious emissions at antenna terminals

The radio frequency voltage or power generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna.

Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in Sec. 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

##### § 2.1057 Frequency spectrum to be investigated.

(a) In all of the measurements set forth in Secs. 2.1051 and 2.1053, the spectrum shall be investigated from the lowest radio frequency signal generated in the equipment, without going below 9 kHz, up to at least the frequency shown below:

acc. Title 47 CFR chapter I part 22 subpart H

- (1) If the equipment operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (b) Particular attention should be paid to harmonics and subharmonics of the carrier frequency as well as to those frequencies removed from the carrier by multiples of the oscillator frequency. Radiation at the frequencies of multiplier stages should also be checked.
- (c) The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.
- (d) Unless otherwise specified, measurements above 40 GHz shall be performed using a minimum resolution bandwidth of 1 MHz.

#### § 22.917 Emission limitations for cellular equipment

- (a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

Remark of the test laboratory: This is calculated to be -13 dBm.

- (b) Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

- (c) Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas [...].

- (d) If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

For reporting only spurious emission levels reaching to the 20dB margin to limit were noted.

---

#### Field strength of spurious radiation

---

Standard    FCC Part 22, Subpart H

The test was performed according to: FCC §2.1053

#### Test Description

1) The EUT was placed inside an anechoic chamber. Refer to chapter "Setup Drawings". The EUT was coupled to a Digital Communication Tester which was located outside the chamber via a small signalling antenna.

2) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester.

##### Important Settings:

- Output Power: Maximum

- Channel: please refer to the detailed results

3) A pre-calibration procedure is used so that the readings from the spectrum analyser are corrected and represent directly the equivalent radiated power (related to a lambda/2 dipole).

4) All spurious radiation measurements were made with spectrum analyser and the appropriate calibrated antennas for the frequency range of 30 MHz to 10 GHz (up to the 10th harmonic of the transmit frequency). The frequency range from 9 kHz to 30 MHz has been examined during the conducted spurious emission measurements.

5) Important Analyser Settings

- [Resolution Bandwidth / Video Bandwidth]:

a) [3 kHz / 10 kHz] in the Span of 1 MHz directly below and above the Band,

b) [10 kHz / 30 kHz] in case the curve of the analyser IF-Filter leads to an exceeding of the limit, in this case a worst case correction factor of 20 dB (1 MHz -> 10 kHz) was used

c) [1 MHz / 3 MHz] otherwise

- Sweep Time: depending on the transmitting signal, the span and the resolution bandwidth

6) The spurious emissions peaks were measured in both vertical and horizontal antenna polarization during the call is established on the lowest channel, mid channel and on the highest channel. To find the worst case peaks all orientations (X, Y, Z) of the EUT have been measured.

## Test Requirements / Limits

## § 2.1053 Measurements required: Field strength of spurious radiation.

Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph (c) of Sec. 2.1049, as appropriate. For equipment operating on frequencies below 890 MHz, an open field test is normally required, with the measuring instrument antenna located in the far-field at all test frequencies. In the event it is either impractical or impossible to make open field measurements (e.g. a broadcast transmitter installed in a building) measurements will be accepted of the equipment as installed. Such measurements must be accompanied by a description of the site where the measurements were made showing the location of any possible source of reflections which might distort the field strength measurements. Information submitted shall include the relative radiated power of each spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from halfwave dipole antennas.

(b) The measurements specified in paragraph (a) of this section shall be made for the following equipment:  
(2) All equipment operating on frequencies higher than 25 MHz.

## § 2.1057 Frequency spectrum to be investigated.

(a) In all of the measurements set forth in Secs. 2.1051 and 2.1053, the spectrum shall be investigated from the lowest radio frequency signal generated in the equipment, without going below 9 kHz, up to at least the frequency shown below:  
(1) If the equipment operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.  
(b) Particular attention should be paid to harmonics and subharmonics of the carrier frequency as well as to those frequencies removed from the carrier by multiples of the oscillator frequency. Radiation at the frequencies of multiplier stages should also be checked.  
(c) The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.  
(d) Unless otherwise specified, measurements above 40 GHz shall be performed using a minimum resolution bandwidth of 1 MHz.

## § 22.917 Emission limitations for cellular equipment

(a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.  
This is calculated to be -13 dBm (effective radiated power) which corresponds to 84.6 dB $\mu$ V/m (field strength) in a distance of 3 m.

(b) Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.  
(c) Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas [...].  
(d) If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

For reporting only spurious emission levels reaching to the 20dB margin to limit were noted.

---

Frequency stability

---

## Standard    FCC Part 22, Subpart H

The test was performed according to FCC §2.1055

#### Test Description

- 1) The EUT was placed inside a temperature chamber.
- 2) The EUT was coupled to a Digital Communication Tester. Refer to chapter "Setup Drawings".
- 3) The climatic chamber was cycled down/up to a certain temperature, starting with the EUT minimum temperature.
- 4) After the temperature was stabilized the EUT was switched on and a call was established on a Traffic Channel between the EUT and the Digital Communication Tester.

#### Important Settings:

- Output Power: Maximum
- Mid Channel

5) The frequency error of the EUT was recorded by using an internal measurement function of the Digital Communication Tester immediately after the call was established, five minutes after the call was established and ten minutes after the call was established.

6) This measurement procedure was performed for temperature variation from  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  in increments of  $10^{\circ}\text{C}$ , if not otherwise stated in the detailed results.

When the EUT did not operate at certain temperature levels, these measurements were left out.

#### Test Requirements / Limits

##### §2.1055 Measurements required: Frequency stability

(a) The frequency stability shall be measured with variation of ambient temperature as follows:

(1) From  $-30^{\circ}$  to  $+50^{\circ}$  centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section.

(b) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than  $10^{\circ}$  centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stabilizing circuitry need be subjected to the temperature variation test.

(d) The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

(3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.

##### §22.355 Frequency tolerance

...the carrier frequency of each transmitter in the Public Mobile Service must be maintained within the tolerances given in table C-1 of this section.

Table C-1.- Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency range (MHz)	Base, fixed (ppm)	Mobile up to 3 watts (ppm)	Mobile above 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10.0	n/a	n/a

For the mid channel (836.6 MHz) the frequency tolerance is 2.5 ppm (2091.5 Hz).

---

#### Band edge compliance

---



---

Reference: MDE\_OPTI\_1202\_FCCc

Standard    FCC Part 22, Subpart H

acc. Title 47 CFR chapter I part 22 subpart H

The test was performed according to: FCC §22.913

#### Test Description

1) The EUT was coupled to a Spectrum Analyser and a Digital Communication Tester through a Power Divider. Refer to chapter "Setup Drawings".

2) The total insertion losses for signal path 1 and signal path 2 were measured. The values were used to correct the readings from the Spectrum Analyser and the Digital Communication Tester.

3) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester.

#### Important Settings:

- Output Power: Maximum

- Channel: please refer to the detailed results

4) Important Analyser Settings:

- Resolution Bandwidth = Video Bandwidth: >1% of the manufacturer's stated occupied bandwidth

#### Test Requirements / Limits

§ 22.917 Emission limitations for cellular equipment

Refer to chapter "Field strength of spurious radiation".

## Subtests HSDPA

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1:  $\beta_{ACK}, \beta_{NACK}$  and  $\beta_{CQI} = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ .  
 Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA,  $\beta_{ACK}$  and  $\beta_{NACK} = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ , and  $\beta_{CQI} = 24/15$  with  $\beta_{hs} = 24/15 * \beta_c$ .  
 Note 3: CM = 1 for  $\beta_c/\beta_d = 12/15, \beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.  
 Note 4: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

## Subtests HSUPA


Subtest	Mode	Loopback Mode	Rel99 RMC	HSDPA FRC	HSUPA Test	Number of E-DPDCH Channels
1	Rel6 HSUPA	Test Mode 1	12.2kbps RMC	H-Set1	HSUPA Loopback	1
2	Rel6 HSUPA	Test Mode 1	12.2kbps RMC	H-Set1	HSUPA Loopback	1
3	Rel6 HSUPA	Test Mode 1	12.2kbps RMC	H-Set1	HSUPA Loopback	2
4	Rel6 HSUPA	Test Mode 1	12.2kbps RMC	H-Set1	HSUPA Loopback	1
5	Rel6 HSUPA	Test Mode 1	12.2kbps RMC	H-Set1	HSUPA Loopback	1

Subtest	Max UL Data Rate (kb/s)	$\beta_c/\beta_d$	$\beta_{hs}$	$\beta_{ed}$	CM
1	242.1	11/15	22/15	1309/225	1
2	161.3	6/15	12/15	94/75	3
3	524.7	15/9	30/15	47/15	2
4	197.6	2/15	4/15	56/75	3
5	299.6	15/15	30/15	134/15	1

---


Setup Drawings

---




**Remark:** Depending on the frequency range suitable antenna types, attenuators or preamplifiers are used.

Principle set-up for radiated measurements



Remark: Depending on the frequency range suitable attenuators and/or filters and/or amplifiers are used.

Principle set-up for conducted measurements under nominal conditions



Principle set-up for tests under extreme test conditions

### Comparison RF conducted output power

EUT Mode	Frequency (MHz)	Channel	av/dBm (1TS) FCC ID: NCMOGI0644	av/dBm (1TS) FCC ID: NCMOGI0643
GPRS 850	824.2	128	32.1	31.8
	836.6	190	31.9	31.9
	848.8	251	31.7	31.8

EUT Mode	Frequency (MHz)	Channel	av/dBm (1TS) FCC ID: NCMOGI0644	av/dBm (1TS) FCC ID: NCMOGI0643
EDGE 850	824.2	128	26.9	26.6
	836.6	190	26.8	26.6
	848.8	251	26.6	26.5

### New measurement for GI0644

EUT Mode	Frequency (MHz)	Channel	av/dBm (1TS) FCC ID: NCMOGI0644
WCDMA FDD5	824.2	128	22.72
	836.6	190	21.89
	848.8	251	22.31

Mode	Sub-test	rms/dBm (FCC ID:NCMOGI0644) Channel		
		824.2	836.6	848.8
HSDPA	1	21.64	21.72	21.87
	2	21.11	21.11	21.33
	3	21.09	21.08	21.31
	4	21.14	21.14	21.31

Mode	Sub-test	rms/dBm (FCC ID:NCMOGI0644) Channel		
		824.2	836.6	848.8
HSUPA	1	20.53	21.28	21.17
	2	20.67	19.65	20.63
	3	21.17	20.50	20.72
	4	20.31	20.02	20.84
	5	22.30	21.30	21.22

## 6 Index

1	Administrative Data	2
1.1	Project Data	2
1.2	Applicant Data	2
1.3	Test Laboratory Data	2
1.4	Signature of the Testing Responsible	3
1.5	Signature of the Accreditation Responsible	3
2	Test Object Data	3
2.1	General OUT Description	3
2.2	Detailed Description of OUT Samples	4
2.3	OUT Features	5
2.4	Auxiliary Equipment	5
2.5	Setups used for Testing	6
3	Results	6
3.1	General	6
3.2	List of the Applicable Body	7
3.3	List of Test Specification	7
3.4	Summary	8
3.5	Detailed Results	11
3.5.1	22.1 RF Power Output §2.1046, §22.913	11
3.5.2	22.2 Frequency stability §2.1055	31
3.5.3	22.3 Spurious emissions at antenna terminals §2.1051, §22.917	33
3.5.4	22.4 Field strength of spurious radiation §2.1053, §22.917	40
3.5.5	22.5 Emission and Occupied Bandwidth §2.1049, §22.917	48
3.5.6	22.6 Band edge compliance §2.1053, §22.917	67
4	Test Equipment Details	76
4.1	List of Used Test Equipment	76
5	Annex	83
5.1	Additional Information for Report	83
6	Index	95