


Site: AC1	Time: 2014/09/25 - 11:42
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5745MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5686.397	75.024	67.317	-13.176	88.200	7.707	PK
2			5715.000	72.747	64.975	-15.453	88.200	7.772	PK
3			5725.000	73.142	65.351	-25.058	98.200	7.791	PK
4		*	5748.958	110.087	102.246	N/A	N/A	7.842	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 11:45
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5745MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	61.958	54.186	-6.242	68.200	7.772	AV
2			5725.000	62.285	54.494	-15.915	78.200	7.791	AV
3		*	5748.325	97.813	89.973	N/A	N/A	7.840	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 11:47
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5829.130	137.083	129.024	N/A	N/A	8.059	PK
2			5850.000	90.997	82.863	-7.203	98.200	8.134	PK
3			5860.000	81.934	73.745	-6.266	88.200	8.189	PK
4			5860.337	84.359	76.168	-3.841	88.200	8.191	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 11:50
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5819.297	124.399	116.358	N/A	N/A	8.042	AV
2			5850.000	71.825	63.691	-6.375	78.200	8.134	AV
3			5860.000	67.591	59.402	-0.609	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 11:51
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5824.333	110.803	102.754	N/A	N/A	8.049	PK
2			5850.000	73.457	65.323	-24.743	98.200	8.134	PK
3			5860.000	72.751	64.562	-15.449	88.200	8.189	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 11:52
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5830.223	98.907	90.845	N/A	N/A	8.062	AV
2			5850.000	62.483	54.349	-15.717	78.200	8.134	AV
3			5860.000	62.516	54.327	-5.684	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 11:55
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5180MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	64.103	56.927	-9.897	74.000	7.176	PK
2		*	5177.635	103.589	96.519	N/A	N/A	7.070	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 11:57
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5180MHz Ant 1 TP=12	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	51.108	43.932	-2.892	54.000	7.176	AV
2		*	5184.970	89.637	82.614	N/A	N/A	7.023	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 11:57
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5180MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5149.060	72.845	65.668	-1.155	74.000	7.176	PK
2			5150.000	72.320	65.144	-1.680	74.000	7.176	PK
3		*	5177.455	125.194	118.123	N/A	N/A	7.072	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 12:01
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5180MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	53.545	46.369	-0.455	54.000	7.176	AV
2		*	5176.600	109.988	102.912	N/A	N/A	7.076	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 13:10
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5745MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5712.158	78.390	70.624	-9.810	88.200	7.766	PK
2			5715.000	77.317	69.545	-10.883	88.200	7.772	PK
3			5725.000	77.562	69.771	-20.638	98.200	7.791	PK
4		*	5749.015	117.855	110.014	N/A	N/A	7.842	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 13:11
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5745MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	62.165	54.393	-6.035	68.200	7.772	AV
2			5725.000	63.531	55.740	-14.669	78.200	7.791	AV
3		*	5739.355	105.541	97.719	N/A	N/A	7.822	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 13:15
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5745MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5714.285	85.555	77.785	-2.645	88.200	7.770	PK
2			5715.000	82.738	74.966	-5.462	88.200	7.772	PK
3			5725.000	98.043	90.252	-0.157	98.200	7.791	PK
4		*	5746.658	137.835	129.999	N/A	N/A	7.836	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 13:21
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5745MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	67.402	59.630	-0.798	68.200	7.772	AV
2			5725.000	77.440	69.649	-0.760	78.200	7.791	AV
3		*	5749.187	125.200	117.358	N/A	N/A	7.842	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 13:24
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5820.913	118.956	110.912	N/A	N/A	8.044	PK
2			5850.000	77.492	69.358	-20.708	98.200	8.134	PK
3			5860.000	77.853	69.664	-10.347	88.200	8.189	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 13:25
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5820.295	106.340	98.297	N/A	N/A	8.043	AV
2			5850.000	64.905	56.771	-13.295	78.200	8.134	AV
3			5860.000	64.666	56.477	-3.534	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 13:25
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5820.817	139.745	131.701	N/A	N/A	8.045	PK
2			5850.000	92.588	84.454	-5.612	98.200	8.134	PK
3			5860.000	85.715	77.526	-2.485	88.200	8.189	PK
4			5860.480	86.558	78.367	-1.642	88.200	8.191	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 13:31
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5819.772	126.537	118.495	N/A	N/A	8.042	AV
2			5850.000	72.912	64.778	-5.288	78.200	8.134	AV
3			5860.000	67.740	59.551	-0.460	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:23
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5180MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	72.957	65.781	-1.043	74.000	7.176	PK
2		*	5183.755	123.405	116.375	N/A	N/A	7.030	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:30
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5180MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	53.404	46.228	-0.596	54.000	7.176	AV
2		*	5185.825	108.834	101.816	N/A	N/A	7.018	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:34
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5180MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5146.630	72.213	65.036	-1.787	74.000	7.178	PK
2			5150.000	70.717	63.541	-3.283	74.000	7.176	PK
3		*	5174.665	127.377	120.288	N/A	N/A	7.089	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:36
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5180MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	53.680	46.504	-0.320	54.000	7.176	AV
2		*	5184.430	111.287	104.261	N/A	N/A	7.027	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:37
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5745MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5714.745	86.481	78.710	-1.719	88.200	7.771	PK
2			5715.000	83.561	75.789	-4.639	88.200	7.772	PK
3			5725.000	95.798	88.007	-2.402	98.200	7.791	PK
4		*	5740.045	135.846	128.023	N/A	N/A	7.823	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:40
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5745MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	67.110	59.338	-1.090	68.200	7.772	AV
2			5725.000	77.454	69.663	-0.746	78.200	7.791	AV
3		*	5739.527	121.000	113.178	N/A	N/A	7.822	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:45
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5745MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	85.532	77.760	-2.668	88.200	7.772	PK
2			5724.692	97.990	90.200	-0.210	98.200	7.790	PK
3			5725.000	96.778	88.987	-1.422	98.200	7.791	PK
4		*	5747.002	138.877	131.041	N/A	N/A	7.836	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:48
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5745MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	67.617	59.845	-0.583	68.200	7.772	AV
2			5725.000	77.831	70.040	-0.369	78.200	7.791	AV
3		*	5750.165	123.142	115.298	N/A	N/A	7.844	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:49
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5823.240	135.267	127.219	N/A	N/A	8.048	PK
2			5850.000	87.653	79.519	-10.547	98.200	8.134	PK
3			5850.268	89.191	81.055	-9.009	98.200	8.136	PK
4			5860.000	80.790	72.601	-7.410	88.200	8.189	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:51
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5829.748	120.356	112.296	N/A	N/A	8.060	AV
2			5850.000	71.049	62.915	-7.151	78.200	8.134	AV
3			5860.000	67.504	59.315	-0.696	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:53
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5819.962	140.635	132.593	N/A	N/A	8.043	PK
2			5850.000	97.752	89.618	-0.448	98.200	8.134	PK
3			5860.000	85.767	77.578	-2.433	88.200	8.189	PK
4			5860.290	86.280	78.090	-1.920	88.200	8.190	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:55
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 2: Transmit by 802.11n-HT20 at channel 5825MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5819.725	124.379	116.337	N/A	N/A	8.042	AV
2			5850.000	74.166	66.032	-4.034	78.200	8.134	AV
3			5860.000	67.852	59.663	-0.348	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 14:57
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5149.825	73.300	66.124	-0.700	74.000	7.176	PK
2			5150.000	70.055	62.879	-3.945	74.000	7.176	PK
3		*	5177.815	123.124	116.055	N/A	N/A	7.069	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:02
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	53.520	46.344	-0.480	54.000	7.176	AV
2		*	5186.230	109.038	102.022	N/A	N/A	7.016	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:02
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	65.093	57.917	-8.907	74.000	7.176	PK
2		*	5183.800	97.288	90.258	N/A	N/A	7.030	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:04
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	52.220	45.044	-1.780	54.000	7.176	AV
2		*	5183.575	83.356	76.324	N/A	N/A	7.032	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:23
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5714.400	86.930	79.160	-1.270	88.200	7.771	PK
2			5715.000	86.693	78.921	-1.507	88.200	7.772	PK
3			5725.000	97.944	90.153	-0.256	98.200	7.791	PK
4		*	5739.527	136.859	129.037	N/A	N/A	7.822	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:23
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	67.507	59.735	-0.693	68.200	7.772	AV
2			5725.000	77.500	69.709	-0.700	78.200	7.791	AV
3		*	5739.010	122.701	114.880	N/A	N/A	7.821	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:24
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	74.579	66.807	-13.621	88.200	7.772	PK
2			5725.000	75.178	67.387	-23.022	98.200	7.791	PK
3		*	5742.288	112.557	104.730	N/A	N/A	7.827	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:25
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	62.012	54.240	-6.188	68.200	7.772	AV
2			5725.000	62.356	54.565	-15.844	78.200	7.791	AV
3		*	5748.785	97.359	89.518	N/A	N/A	7.840	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:27
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5822.575	137.159	129.112	N/A	N/A	8.047	PK
2			5850.000	87.441	79.307	-10.759	98.200	8.134	PK
3			5852.120	88.479	80.333	-9.721	98.200	8.146	PK
4			5860.000	83.055	74.866	-5.145	88.200	8.189	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:29
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5819.725	123.145	115.103	N/A	N/A	8.042	AV
2			5850.000	71.439	63.305	-6.761	78.200	8.134	AV
3			5860.000	67.845	59.656	-0.355	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:30
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5821.055	110.935	102.891	N/A	N/A	8.044	PK
2			5850.000	75.524	67.390	-22.676	98.200	8.134	PK
3			5860.000	75.325	67.136	-12.875	88.200	8.189	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:31
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5830.507	98.580	90.517	N/A	N/A	8.063	AV
2			5850.000	62.554	54.420	-15.646	78.200	8.134	AV
3			5860.000	62.540	54.351	-5.660	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:33
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5131.825	67.342	60.162	-6.658	74.000	7.180	PK
2			5150.000	64.271	57.095	-9.729	74.000	7.176	PK
3		*	5179.570	102.857	95.800	N/A	N/A	7.057	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:33
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	51.137	43.961	-2.863	54.000	7.176	AV
2		*	5183.395	89.787	82.754	N/A	N/A	7.032	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:34
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5148.790	72.316	65.139	-1.684	74.000	7.177	PK
2			5150.000	70.704	63.528	-3.296	74.000	7.176	PK
3		*	5177.770	124.976	117.907	N/A	N/A	7.069	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:39
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	52.612	45.436	-1.388	54.000	7.176	AV
2		*	5184.835	110.659	103.636	N/A	N/A	7.023	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:45
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	74.302	66.530	-13.898	88.200	7.772	PK
2			5718.540	76.602	68.824	-21.598	98.200	7.778	PK
3			5725.000	75.678	67.887	-22.522	98.200	7.791	PK
4		*	5748.900	118.199	110.358	N/A	N/A	7.841	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:46
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	62.098	54.326	-6.102	68.200	7.772	AV
2			5725.000	63.015	55.224	-15.185	78.200	7.791	AV
3		*	5750.337	104.808	96.964	N/A	N/A	7.843	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:46
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	83.588	75.816	-4.612	88.200	7.772	PK
2			5725.000	96.298	88.507	-1.902	98.200	7.791	PK
3		*	5739.527	138.096	130.274	N/A	N/A	7.822	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:51
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	67.377	59.605	-0.823	68.200	7.772	AV
2			5725.000	77.013	69.222	-1.187	78.200	7.791	AV
3		*	5740.792	123.737	115.913	N/A	N/A	7.824	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:55
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5820.200	117.217	109.174	N/A	N/A	8.043	PK
2			5850.000	77.434	69.300	-20.766	98.200	8.134	PK
3			5855.397	79.259	71.095	-18.941	98.200	8.163	PK
4			5860.000	77.029	68.840	-11.171	88.200	8.189	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:55
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5819.440	104.615	96.573	N/A	N/A	8.042	AV
2			5850.000	64.796	56.662	-13.404	78.200	8.134	AV
3			5860.000	64.697	56.508	-3.503	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 15:55
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5819.915	138.456	130.414	N/A	N/A	8.043	PK
2			5850.000	89.988	81.854	-8.212	98.200	8.134	PK
3			5860.000	82.654	74.465	-5.546	88.200	8.189	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:00
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5819.297	124.579	116.537	N/A	N/A	8.042	AV
2			5850.000	71.692	63.558	-6.508	78.200	8.134	AV
3			5860.000	67.845	59.656	-0.355	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:04
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5149.690	72.537	65.361	-1.463	74.000	7.176	PK
2			5150.000	70.727	63.551	-3.273	74.000	7.176	PK
3		*	5184.250	121.536	114.509	N/A	N/A	7.027	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:10
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	53.476	46.300	-0.524	54.000	7.176	AV
2		*	5185.645	108.126	101.106	N/A	N/A	7.020	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:13
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	71.240	64.064	-2.760	74.000	7.176	PK
2		*	5175.565	126.261	119.178	N/A	N/A	7.083	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:15
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5180MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	53.414	46.238	-0.586	54.000	7.176	AV
2		*	5174.215	110.426	103.333	N/A	N/A	7.093	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:20
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	86.187	78.415	-2.013	88.200	7.772	PK
2			5725.000	97.905	90.114	-0.295	98.200	7.791	PK
3		*	5738.550	136.526	128.706	N/A	N/A	7.820	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:21
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	67.073	59.301	-1.127	68.200	7.772	AV
2			5725.000	78.184	70.393	-0.016	78.200	7.791	AV
3		*	5738.493	122.193	114.373	N/A	N/A	7.820	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:29
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5710.317	84.997	77.234	-3.203	88.200	7.763	PK
2			5715.000	84.149	76.377	-4.051	88.200	7.772	PK
3			5725.000	97.545	89.754	-0.655	98.200	7.791	PK
4		*	5739.355	139.947	132.125	N/A	N/A	7.822	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:37
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5745MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	67.504	59.732	-0.696	68.200	7.772	AV
2			5725.000	76.118	68.327	-2.082	78.200	7.791	AV
3		*	5742.518	125.501	117.673	N/A	N/A	7.828	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:38
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5820.010	134.909	126.866	N/A	N/A	8.043	PK
2			5850.000	85.578	77.444	-12.622	98.200	8.134	PK
3			5852.357	87.380	79.233	-10.820	98.200	8.147	PK
4			5860.000	81.271	73.082	-6.929	88.200	8.189	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:40
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5822.955	120.721	112.674	N/A	N/A	8.047	AV
2			5850.000	70.986	62.852	-7.214	78.200	8.134	AV
3			5860.000	67.550	59.361	-0.650	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:41
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5819.820	140.295	132.253	N/A	N/A	8.042	PK
2			5850.000	95.829	87.695	-2.371	98.200	8.134	PK
3			5860.000	84.022	75.833	-4.178	88.200	8.189	PK
4			5860.433	86.148	77.957	-2.052	88.200	8.191	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/25 - 16:46
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 3: Transmit by 802.11ac-VHT20 at channel 5825MHz Ant 0+1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5818.728	124.673	116.632	N/A	N/A	8.041	AV
2			5850.000	73.859	65.725	-4.341	78.200	8.134	AV
3			5860.000	67.693	59.504	-0.507	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 10:40
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5190MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5148.400	73.046	65.869	-0.954	74.000	7.176	PK
2			5150.000	70.115	62.939	-3.885	74.000	7.176	PK
3		*	5181.850	118.476	111.433	N/A	N/A	7.043	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 10:42
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5190MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	53.556	46.380	-0.444	54.000	7.176	AV
2		*	5183.700	100.067	93.037	N/A	N/A	7.030	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 10:45
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5190MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	64.144	56.968	-9.856	74.000	7.176	PK
2		*	5183.550	87.929	80.897	N/A	N/A	7.032	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 10:46
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5190MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	50.042	42.866	-3.958	54.000	7.176	AV
2		*	5177.900	73.689	66.621	N/A	N/A	7.068	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:00
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5755MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	86.797	79.025	-1.403	88.200	7.772	PK
2			5725.000	96.394	88.603	-1.806	98.200	7.791	PK
3		*	5746.937	131.999	124.162	N/A	N/A	7.837	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:09
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5755MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	67.478	59.706	-0.722	68.200	7.772	AV
2			5725.000	75.354	67.563	-2.846	78.200	7.791	AV
3		*	5743.375	112.982	105.154	N/A	N/A	7.828	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:11
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5755MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5697.125	75.370	67.640	-12.830	88.200	7.731	PK
2			5715.000	72.104	64.332	-16.096	88.200	7.772	PK
3			5725.000	72.381	64.590	-25.819	98.200	7.791	PK
4		*	5746.750	102.233	94.397	N/A	N/A	7.836	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:12
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5755MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	60.148	52.376	-8.052	68.200	7.772	AV
2			5725.000	60.196	52.405	-18.004	78.200	7.791	AV
3		*	5752.187	86.548	78.700	N/A	N/A	7.848	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:15
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5795MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5799.375	135.475	127.479	N/A	N/A	7.996	PK
2			5850.000	82.673	74.539	-15.527	98.200	8.134	PK
3			5851.937	86.010	77.865	-12.190	988.200	8.144	PK
4			5860.000	82.616	74.427	-5.584	88.200	8.189	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:16
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5795MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5803.125	116.689	108.683	N/A	N/A	8.006	AV
2			5850.000	68.186	60.052	-10.014	78.200	8.134	AV
3			5860.000	66.855	58.666	-1.345	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:16
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5795MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5784.750	105.463	97.516	N/A	N/A	7.946	PK
2			5850.000	70.888	62.754	-27.312	98.200	8.134	PK
3			5860.000	72.490	64.301	-15.710	88.200	8.189	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:17
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5795MHz Ant 0	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	5786.437	89.627	81.674	N/A	N/A	7.953	AV
2			5850.000	60.586	52.452	-17.614	78.200	8.134	AV
3			5860.000	60.636	52.447	-7.564	68.200	8.189	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:22
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5190MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	63.138	55.962	-10.862	74.000	7.176	PK
2		*	5183.950	88.311	81.282	N/A	N/A	7.028	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:24
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5190MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	49.993	42.817	-4.007	54.000	7.176	AV
2		*	5182.900	73.067	66.031	N/A	N/A	7.036	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:28
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5190MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5148.050	72.824	65.647	-1.176	74.000	7.177	PK
2			5150.000	69.854	62.678	-4.146	74.000	7.176	PK
3		*	5182.150	119.348	112.308	N/A	N/A	7.040	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:30
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5190MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5150.000	53.519	46.343	-0.481	54.000	7.176	AV
2		*	5194.700	100.833	93.868	N/A	N/A	6.965	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:31
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5755MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	72.416	64.644	-15.784	88.200	7.772	PK
2			5725.000	72.198	64.407	-26.002	98.200	7.791	PK
3		*	5767.625	104.091	96.204	N/A	N/A	7.887	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:35
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5755MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	60.153	52.381	-8.047	68.200	7.772	AV
2			5725.000	60.371	52.580	-17.829	78.200	7.791	AV
3		*	5767.562	89.266	81.379	N/A	N/A	7.887	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:39
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5755MHz Ant 1	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5714.500	87.414	79.643	-0.786	88.200	7.771	PK
2			5715.000	87.150	79.378	-1.050	88.200	7.772	PK
3			5725.000	97.685	89.894	-0.515	98.200	7.791	PK
4		*	5748.812	134.910	127.070	N/A	N/A	7.840	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Site: AC1	Time: 2014/09/26 - 11:42
Limit: FCC_15.407_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Altum AC600	Power: AC 120V/60Hz
Note: Mode 4: Transmit by 802.11n-HT40 at channel 5755MHz Ant 1	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			5715.000	67.795	60.023	-0.405	68.200	7.772	AV
2			5725.000	74.230	66.439	-3.970	78.200	7.791	AV
3		*	5759.062	118.505	110.645	N/A	N/A	7.860	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)