

Maximum Permissible Exposure

Equipment : Low Powered Camera Gateway
Brand Name : EDIMAX
Model No. : IC-3011 RX Gateway, IC-6230DC (Gateway),
IC-6220DC (Gateway), IC-3210W (Gateway)
FCC ID : NDD9530111504
Standard : ANSI/IEEE C95.1
Applicant : EDIMAX TECHNOLOGY CO., LTD.
Manufacturer : No.3,Wu-Chuan 3rd Road,Wu-Ku Industrial Park,
New Taipei City, Taiwan

The product sample received on Aug. 20, 2015 and completely tested on Apr. 08, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI/IEEE C95.1 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Kevin Liang / Assistant Manager



Table of Contents

1	HUMAN EXPOSURE ASSESSMENT	4
1.1	Maximum Permissible Exposure	4
1.1.1	Limit of Maximum Permissible Exposure.....	4
1.1.2	MPE Calculation Method	4
1.1.3	Result of Maximum Permissible Exposure (SRD)	5

Revision History

[illegible]

1 Human Exposure Assessment

1.1 Maximum Permissible Exposure

1.1.1 Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30
Note 1: f = frequency in MHz ; *Plane-wave equivalent power density				
Note 2: For the applicable limit, see FCC 1.1310				

1.1.2 MPE Calculation Method

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

1.1.3 Result of Maximum Permissible Exposure (SRD)

RF General Information					
Frequency Range (MHz)	Modulation	Ch. Frequency (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	RF Output Power (dBm)
2400-2483.5	GFSK	2405-2465	1-21 [21]	1	15.18
Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.					

Worst Maximum RF Output Power Result				
Exposure Environment	General Population / Uncontrolled Exposure			
Separation Distance (cm)	20			
Condition	RF Output Power (dBm)			
Modulation Mode	RF Output Power	Antenna Gain (dBi)	EIRP Power	PD (S) (mW/cm ²)
GFSK	15.18	1.91	17.09	0.01018
Maximum Permissible Exposure Limit (mW/cm ²)				1