

FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : 150N Wireless LAN Broadband Router
Model No. : BR-6228GN,GR-228GN
Brand Name : EDIMAX
Filing Type : New Application
Applicant : EDIMAX TECHNOLOGY CO., LTD.
No.3, Wu Chuan 3rd Road, Wu-Ku Industrial Park,
Taipei Hsien, Taiwan
FCC ID : NDD9562281011
Manufacturer : EDIMAX TECHNOLOGY CO., LTD.
No.3, Wu Chuan 3rd Road, Wu-Ku Industrial Park,
Taipei Hsien, Taiwan
Received Date : May 13, 2010
Final Test Date : Sep. 21, 2010
Multiple Listing : Please refer to section 2.5

Statement

Test result included is only for the 802.11n of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

Table of Contents

1 SUMMARY OF THE TEST RESULT	2
2 GENERAL INFORMATION.....	3
2.1 Product Details	3
2.2 Accessories.....	3
2.3 Table for Filed Antenna	3
2.4 Table for Carrier Frequencies	4
2.5 Table for Multiple Listing	4
2.6 Table for Test Modes	5
2.7 Table for Testing Locations.....	5
2.8 Table for Supporting Units.....	5
2.9 Table for Parameters of Test Software Setting	6
2.10 EUT Operation during Test	6
2.11 Test Configuration	7
3 TEST RESULT	9
3.1 AC Power Line Conducted Emissions Measurement.....	9
3.2 Maximum Conducted Output Power Measurement	13
3.3 Power Spectral Density Measurement.....	15
3.4 6dB Spectrum Bandwidth Measurement.....	21
3.5 Radiated Emissions Measurement.....	27
3.6 Band Edge and Fundamental Emissions Measurement	45
3.7 Antenna Requirements.....	50
4 LIST OF MEASURING EQUIPMENTS	51
5 TEST LOCATION.....	53
6 TAF CERTIFICATE OF ACCREDITATION	54
APPENDIX A. MAXIMUM PERMISSIBLE EXPOSURE.....	A1 ~ A3
APPENDIX B. TEST PHOTOS	B1 ~ B6
APPENDIX C. PHOTOGRAPHS OF EUT	C1 ~ C11

History of This Test Report

Original Issue Date: Oct. 04, 2010

Report No.: FR042904AI

- No additional attachment.
- Additional attachment were issued as following record:

CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : 150N Wireless LAN Broadband Router


Model No. : BR-6228GN,GR-228GN

Brand Name : EDIMAX

Applicant : EDIMAX TECHNOLOGY CO., LTD.

No.3, Wu Chuan 3rd Road, Wu-Ku Industrial
Park, Taipei Hsien, Taiwan

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on May 13, 2010 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Wayne Hsu / Vice Manager

SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

1 SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	10.84 dB
3.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	4.62 dB
3.3	15.247(e)	Power Spectral Density	Complies	15.09 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	1.12 dB
3.6	15.247(d)	Band Edge Emissions	Complies	1.24 dB
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2 GENERAL INFORMATION

2.1 Product Details

Only the radio detail of IEEE 802.11n is shown in this report. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Power Type	+5Vdc from adapter
Modulation	See the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	See the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS 0 (20MHz) : 17.80 MHz ; MCS 0 (40MHz) : 36.24 MHz
Conducted Output Power	MCS 0 (20MHz) : 25.28 dBm ; MCS 0 (40MHz) : 25.38 dBm

2.2 Accessories

Power	Brand	Model	Rating
Switching Adapter	DVE	DSC-6PFA-05 FUS 050100	INPUT : 100-240V ~ 50/60Hz 0.2A OUTPUT : +5V 1A

2.3 Table for Filed Antenna

Antenna & Bandwidth

Antenna	Single (TX)	
Bandwidth Mode	20 MHz	40 MHz
802.11n (2.4GHz)	V	V

EUT may match the three antennas use. Performed the worst configuration for higher gain was test in final test report.

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
A	Dipole Antenna	Fixed on Board	3.00	TX / RX

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
A	Dipole Antenna (Long)	Reversed-SMA	5.00	TX / RX

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
A	Dipole Antenna (Short)	Reversed-SMA	3.00	TX / RX

Note: Performed the worst configuration for higher gain was test in final test report.

(IEEE 802.11n the antennas is 1T1R Spatial Multiplexing MIMO configuration.)

IEEE 802.11n Modulation Scheme

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Data rate(Mbps)	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

2.4 Table for Carrier Frequencies

There are two bandwidth systems for IEEE 802.11n.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

2.5 Table for Multiple Listing

No.	Brand Name	Model Name
1	Edimax	BR-6228GN,GR-228GN
2	INTELLINET	524445
3	Phoebe Micro	AR575W
4	Digilink	DG-BR4000NG
5	Jensen	AL29150

2.6 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on the entire possible configuration for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
AC Power Line Conducted Emissions	Normal Mode	Auto	-
Maximum Conducted Output Power Power Spectral Density 6dB Spectrum Bandwidth Radiated Emissions Above 1GHz	MCS 0 (20MHz)	6.5 Mbps	1/6/11
	MCS 0 (40MHz)	13.5 Mbps	3/6/9
Radiated Emissions 9kHz~1GHz	Normal Mode	Auto	-
Fundamental Emissions	MCS 0 (20MHz)	6.5 Mbps	1/6/11
	MCS 0 (40MHz)	13.5 Mbps	3/6/9
Band Edge Emissions	MCS 0 (20MHz)	6.5 Mbps	1/11
	MCS 0 (40MHz)	13.5 Mbps	3/9

2.7 Table for Testing Locations

Test Site No.	Site Category	Location
CO01-HY	Conduction	Hwa Ya
TH01-HY	OVEN Room	Hwa Ya
03CH03-HY	SAC	Hwa Ya

Semi Anechoic Chamber (SAC).

2.8 Table for Supporting Units

Support Unit	Brand	Model	FCC ID	Remark
Notebook	DELL	PP32LB	N/A	Conducted Emissions
PS/2 Mouse	Microsoft	1004	N/A	
Modem	ACEEX	DM1414	IFAXDM1414	
PC (Remote Workstation)	HP	D330uT	DoC	
Notebook (Remote Workstation)	DELL	D400	DoC	
LCD Monitor (Remote Workstation)	Jean	JC278AA11U	N/A	
PS/2 Keyboard (Remote Workstation)	HP	KB-0133	DoC	
PS/2 Mouse (Remote Workstation)	LOGITECH	M-SBM96B	DoC	
Notebook	DELL	E5500	N/A	Radiated Emissions

2.9 Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11n

Test Software Version	MP N Test		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n(20MHz)	47	59	45
Frequency	2422 MHz	2437 MHz	2452 MHz
IEEE 802.11n(40MHz)	45	61	43

2.10 EUT Operation during Test

An executive program, "EMCTEST.EXE" under WIN XP, which generates a complete line of continuously repeating "H" pattern was used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The NB reads the test program from the hard disk drive and runs it.
- c. The NB sends "H" messages to the panel and displays "H" patterns on the screen.
- d. The NB sends messages to the modem.

At the same time, the following programs were executed:

-Executed "ping.exe" to link with the remote workstation to receive and transmit data by LAN and WLAN.


Radiated Emissions:


- Executed "MP N Test" to keep transmitting signals at fixed frequency.

2.11 Test Configuration

2.11.1 Radiation Emissions Test Configuration

For radiated emissions 9kHz~1GHz



For radiated emissions above 1GHz

3 TEST RESULT

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Class B

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

3.1.3 Test Procedures

1. The EUT warm up about 15 minutes then start test.
2. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
5. The frequency range from 150 KHz to 30 MHz was searched.
6. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. The measurement has to be done between each power line and ground at the power terminal.

3.1.4 Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5 Test Deviation

There is no deviation with the original standard.


3.1.6 EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


3.1.7 Results of AC Power Line Conducted Emissions Measurement

Final Test Date	Sep. 21, 2010	Test Site No.	CO01-HY
Temperature	26.6	Humidity	55%
Test Engineer	Nicky	Configuration	Normal Mode

Line



Freq	Level	Over Limit	Limit	Read		Cable	Loss	Remark
				Line	Level Factor			
MHz	dBuV	dB	dBuV					
1	0.421	38.20	-19.23	57.43	38.01	0.09	0.10	QP
2	0.421	32.20	-15.23	47.43	32.01	0.09	0.10	Average
3	4.970	33.30	-22.70	56.00	33.01	0.19	0.10	QP
4	4.970	23.71	-22.29	46.00	23.42	0.19	0.10	Average
5	17.690	33.62	-16.38	50.00	33.08	0.38	0.16	Average
6	17.690	40.65	-19.35	60.00	40.11	0.38	0.16	QP
7	19.860	34.00	-16.00	50.00	33.39	0.41	0.20	Average
8	19.860	37.04	-22.96	60.00	36.43	0.41	0.20	QP
9	24.450	39.16	-10.84	50.00	38.48	0.48	0.20	Average
10	24.450	43.58	-16.42	60.00	42.90	0.48	0.20	QP
11	26.700	34.32	-15.68	50.00	33.60	0.52	0.20	Average
12	26.700	37.22	-22.78	60.00	36.50	0.52	0.20	QP

Neutral

Freq	Level	Over Limit	Limit Line	Read	Probe	Cable Loss	Remark
				Level	Factor		
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.173	34.37	-30.44	64.81	34.21	0.06	0.10 QP
2	0.173	16.90	-37.91	54.81	16.74	0.06	0.10 Average
3	0.203	33.39	-30.10	63.49	33.23	0.06	0.10 QP
4	0.203	17.91	-35.58	53.49	17.75	0.06	0.10 Average
5	0.421	21.28	-26.15	47.43	21.11	0.07	0.10 Average
6	0.421	33.36	-24.07	57.43	33.19	0.07	0.10 QP
7	17.694	34.28	-25.72	60.00	33.73	0.39	0.16 QP
8	17.694	25.50	-24.50	50.00	24.95	0.39	0.16 Average
9	19.709	32.84	-27.16	60.00	32.21	0.43	0.20 QP
10	19.709	23.47	-26.53	50.00	22.84	0.43	0.20 Average
11	25.041	24.43	-25.57	50.00	23.71	0.52	0.20 Average
12	25.041	32.48	-27.52	60.00	31.76	0.52	0.20 QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limit has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-multipoint antenna reduction operation, the limit has to be reduced by 1dB for every dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	MA2411B

3.2.3 Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

3.2.4 Test Setup Layout



3.2.5 Test Deviation

There is no deviation with the original standard.

3.2.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.2.7 Test Result of Maximum Conducted Output Power

Final Test Date	May 13, 2010	Test Site No.	TH01-HY
Temperature	25	Humidity	61%
Test Engineer	Ian	Configuration	802.11n

Configuration of IEEE 802.11n (20MHz)

Channel	Frequency	Conducted Peak Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	23.39	30.00	Complies
6	2437 MHz	25.28	30.00	Complies
11	2462 MHz	22.88	30.00	Complies

Configuration of IEEE 802.11n (40MHz)

Channel	Frequency	Conducted Peak Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	22.96	30.00	Complies
6	2437 MHz	25.38	30.00	Complies
9	2452 MHz	22.26	30.00	Complies

3.3 Power Spectral Density Measurement

3.3.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.3.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

3.3.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

3.3.4 Test Setup Layout



3.3.5 Test Deviation

There is no deviation with the original standard.

3.3.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.3.7 Test Result of Power Spectral Density

Final Test Date	May 13, 2010	Test Site No.	TH01-HY
Temperature	25	Humidity	61%
Test Engineer	Ian	Configuration	802.11n


Configuration of IEEE 802.11n (20MHz)

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-12.61	8.00	Complies
6	2437 MHz	-7.09	8.00	Complies
11	2462 MHz	-11.68	8.00	Complies


Configuration of IEEE 802.11n (40MHz)

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-16.07	8.00	Complies
6	2437 MHz	-8.99	8.00	Complies
9	2452 MHz	-16.51	8.00	Complies


Power Density Plot on Configuration of IEEE 802.11n (20MHz) / 2412 MHz



Power Density Plot on Configuration of IEEE 802.11n (20MHz) / 2437 MHz




Power Density Plot on Configuration of IEEE 802.11n (20MHz) / 2462 MHz




Date: 13.MAY.2010 21:13:41

Power Density Plot on Configuration of IEEE 802.11n (40MHz) / 2422 MHz




Date: 13.MAY.2010 21:23:32

Power Density Plot on Configuration of IEEE 802.11n (40MHz) / 2437 MHz



Date: 13.MAY.2010 21:26:42

Power Density Plot on Configuration of IEEE 802.11n (40MHz) / 2452 MHz



Date: 13.MAY.2010 21:32:14

3.4 6dB Spectrum Bandwidth Measurement

3.4.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

3.4.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.4.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

3.4.4 Test Setup Layout



3.4.5 Test Deviation

There is no deviation with the original standard.

3.4.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.4.7 Test Result of 6dB Spectrum Bandwidth

Final Test Date	May 13, 2010	Test Site No.	TH01-HY
Temperature	25	Humidity	61%
Test Engineer	Ian	Configuration	802.11n


Configuration of IEEE 802.11n (20MHz)

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.80	17.68	500	Complies
6	2437 MHz	17.84	17.80	500	Complies
11	2462 MHz	17.84	17.68	500	Complies

Configuration of IEEE 802.11n (40MHz)


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.56	36.08	500	Complies
6	2437 MHz	36.64	36.24	500	Complies
9	2452 MHz	36.64	36.08	500	Complies

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (20MHz) / 2412 MHz




Date: 13.MAY.2010 21:04:22

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (20MHz) / 2437 MHz




Date: 13.MAY.2010 21:08:49

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (20MHz) / 2462 MHz




Date: 13.MAY.2010 21:12:42

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (40MHz) / 2422 MHz




Date: 13.MAY.2010 21:22:23

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (40MHz) / 2437 MHz



Date: 13.MAY.2010 21:25:26

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (40MHz) / 2452 MHz



Date: 13.MAY.2010 21:30:17

3.5 Radiated Emissions Measurement

3.5.1 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.5.3 Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.5.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.5.5 Test Deviation

There is no deviation with the original standard.

3.5.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.5.7 Results of Radiated Emissions (9kHz~30MHz)

Final Test Date	May 19, 2010	Test Site No.	03CH03-HY
Temperature	20	Humidity	50%
Test Engineer	Steven		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:


The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


3.5.8 Results of Radiated Emissions (30MHz~1GHz)

Final Test Date	May 19, 2010	Test Site No.	03CH03-HY
Temperature	20	Humidity	50%
Test Engineer	Steven	Configuration	Normal Mode

Horizontal

Freq	Level	Over Limit	Read		Antenna	Cable	Preamp	Remark
			Line	Level				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 238.550	24.01	-21.99	46.00	34.30	12.62	3.96	26.87	Peak
2 288.990	26.97	-19.03	46.00	35.77	13.55	4.45	26.80	Peak
3 338.460	35.19	-10.81	46.00	43.55	14.29	4.44	27.09	Peak
4 424.790	34.49	-11.51	46.00	41.02	15.76	5.50	27.79	Peak
5 459.710	38.80	-7.20	46.00	44.37	16.47	5.93	27.97	Peak
6 599.390	29.90	-16.10	46.00	30.44	20.15	7.48	28.17	Peak

Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 238.550	22.70	-23.30	46.00	32.99	12.62	3.96	26.87	Peak
2 338.460	30.69	-15.31	46.00	39.05	14.29	4.44	27.09	Peak
3 459.710	33.51	-12.49	46.00	39.08	16.47	5.93	27.97	Peak
4 490.750	31.92	-14.08	46.00	36.86	17.10	6.10	28.14	Peak
5 513.060	31.65	-14.35	46.00	35.88	17.67	6.28	28.18	Peak
6 982.540	35.74	-18.26	54.00	31.78	22.07	8.99	27.10	Peak

Note:


The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.5.9 Results for Radiated Emissions (1GHz~10th Harmonic)


Final Test Date	May 18, 2010	Test Site No.	03CH03-HY
Temperature	20	Humidity	50%
Test Engineer	Steven	Configuration	802.11n Ch. 1 (20MHz)

Horizontal

Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Line	Line	dBuV	dB/m	dB	dB	
MHz	dBuV/m	dB	dBuV/m					
1 4824.000	49.44	-4.56	54.00	43.61	35.76	4.58	34.51	PK
2 7236.000	52.17			42.98	37.85	5.63	34.29	Peak
3 9648.000	55.28			44.18	39.39	6.34	34.63	Peak

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @ 4824.000	49.11	-4.89	54.00	43.91	35.13	4.58	34.51	PK
2 7236.000	51.70			43.46	36.90	5.63	34.29	Peak
3 9648.000	54.05			43.75	38.59	6.34	34.63	Peak

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 19, 2010	Test Site No.	03CH03-HY
Temperature	20	Humidity	50%
Test Engineer	Steven	Configuration	802.11n Ch. 6 (20MHz)

Horizontal

Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 6 4874.000	63.65	-10.35	74.00	57.66	35.83	4.61	34.45	Peak
2 6 4874.000	48.16	-5.84	54.00	42.17	35.83	4.61	34.45	Average
3 6 7311.000	58.02	-15.98	74.00	48.81	37.86	5.64	34.29	Peak
4 6 7311.000	43.15	-10.85	54.00	33.94	37.86	5.64	34.29	Average
5 6 9748.000	54.38			43.09	39.51	6.36	34.58	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



Freq	Level	Over Limit	Limit Line	Antenna		Cable Loss	Preamp Factor	Remark
				MHz	dBuV/m			
1 @ 4874.000	52.41	-1.59	54.00	47.07	35.18	4.61	34.45	Average
2 @ 4874.000	69.42	-4.58	74.00	64.08	35.18	4.61	34.45	Peak
3 @ 7311.000	45.65	-8.35	54.00	37.38	36.92	5.64	34.29	Average
4 @ 7311.000	62.22	-11.78	74.00	53.95	36.92	5.64	34.29	Peak
5 @ 9748.000	56.13			45.64	38.71	6.36	34.58	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 18, 2010	Test Site No.	03CH03-HY
Temperature	20	Humidity	50%
Test Engineer	Steven	Configuration	802.11n Ch. 11 (20MHz)

Horizontal

Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @ 4924.000	50.15	-3.85	54.00	43.95	35.90	4.68	34.38	PK
2 @ 7386.000	50.74	-3.26	54.00	41.50	37.88	5.65	34.29	PK
3 @ 9848.000	56.00			44.55	39.61	6.38	34.54	Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 4924.000	54.97	-19.03	74.00	49.44	35.23	4.68	34.38	Peak
2 4924.000	40.22	-13.78	54.00	34.69	35.23	4.68	34.38	Average
3 @ 7386.000	50.91	-3.09	54.00	42.59	36.96	5.65	34.29	PK
4 9848.000	54.22			43.57	38.81	6.38	34.54	Peak


Note: The item 4 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	May 18, 2010	Test Site No.	03CH03-HY
Temperature	20	Humidity	50%
Test Engineer	Steven	Configuration	802.11n Ch. 3 (40MHz)

Horizontal

Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 8 4844.000	49.21	-4.79	54.00	43.30	35.78	4.61	34.48	PK
2 8 7266.000	50.50	-3.50	54.00	41.30	37.86	5.63	34.29	PK
3 9 9688.000	54.45			43.27	39.43	6.35	34.60	Peak


Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical

Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @ 4844.000	48.88	-5.12	54.00	43.61	35.14	4.61	34.48	PK
2 @ 7266.000	50.14	-3.86	54.00	41.89	36.91	5.63	34.29	PK
3 @ 9688.000	54.07			43.69	38.63	6.35	34.60	Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 19, 2010	Test Site No.	03CH03-HY
Temperature	20	Humidity	50%
Test Engineer	Steven	Configuration	802.11n Ch. 6 (40MHz)

Horizontal

Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		MHz	dBuV/m	dB	dBuV/m	Level	Factor	
1	4874.000	57.00	-17.00	74.00	51.01	35.83	4.61	34.45 Peak
2	4874.000	46.80	-7.20	54.00	40.81	35.83	4.61	34.45 Average
3	7311.000	53.45	-20.55	74.00	44.24	37.86	5.64	34.29 Peak
4	7311.000	42.79	-11.21	54.00	33.58	37.86	5.64	34.29 Average
5	9748.000	55.32			44.03	39.51	6.36	34.58 Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



Freq	Level	Over Limit	Limit Line	Antenna		Cable Loss	Preamp Factor	Remark
				dB	dBuV/m			
1 @ 4874.000	52.88	-1.12	54.00	47.54	35.18	4.61	34.45	Average
2 @ 4874.000	67.06	-6.94	74.00	61.72	35.18	4.61	34.45	Peak
3 @ 7311.000	58.89	-15.11	74.00	50.62	36.92	5.64	34.29	Peak
4 @ 7311.000	45.66	-8.34	54.00	37.39	36.92	5.64	34.29	Average
5 @ 9748.000	55.21			44.72	38.71	6.36	34.58	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	May 18, 2010	Test Site No.	03CH03-HY
Temperature	20	Humidity	50%
Test Engineer	Steven	Configuration	802.11n Ch. 9 (40MHz)

Horizontal

Freq	Level	Over Limit	Line	ReadAntenna		Cable Preamp		Remark
				dB	dBuV/m	dBuV	dB/m	
1 @ 4904.000	50.04	-3.96	54.00	43.94	35.88	4.64	34.42	PK
2 @ 7356.000	50.23	-3.77	54.00	41.01	37.87	5.64	34.29	PK
3 @ 9808.000	55.24			43.86	39.57	6.37	34.56	Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @ 4904.000	49.23	-4.77	54.00	43.80	35.21	4.64	34.42	PK
2 @ 7356.000	50.00	-4.00	54.00	41.71	36.94	5.64	34.29	PK
3 @ 9808.000	54.30			43.72	38.77	6.37	34.56	Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.6 Band Edge and Fundamental Emissions Measurement

3.6.1 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.6.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak

3.6.3 Test Procedures

1. The test procedure is the same as section 3.5.3; only the frequency range investigated is limited to 100MHz around band edges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

3.6.4 Test Setup Layout

This test setup layout is the same as that shown in section 3.5.4.

3.6.5 Test Deviation

There is no deviation with the original standard.

3.6.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.6.7 Test Result of Band Edge and Fundamental Emissions

Final Test Date	May 19, 2010	Test Site No.	03CH03-HY
Temperature	20	Humidity	50%
Test Engineer	Steven	Configuration	802.11n Ch. 1, 6, 11 (20MHz)

Channel 1

Freq	Level	Over Limit		ReadAntenna		Cable Preamp		Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @ 2326.340	52.76	-1.24	54.00	18.02	31.78	2.96	0.00	Average
2 @ 2417.540	106.48			71.37	32.09	3.02	0.00	Average
1 @ 2327.860	66.00	-8.00	74.00	31.26	31.78	2.96	0.00	Peak
2 @ 2418.300	117.11			82.00	32.09	3.02	0.00	Peak

The item 2 is Fundamental Emissions.

Channel 6

Freq	Level	Over Limit		ReadAntenna		Cable Preamp		Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @ 2430.650	120.66			85.46	32.15	3.05	0.00	Peak
1 @ 2431.410	108.70			73.50	32.15	3.05	0.00	Average

The item 1 is Fundamental Emissions.

Channel 11

Freq	Level	Over Limit		ReadAntenna		Cable Preamp		Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @ 2467.700	103.09			67.73	32.28	3.08	0.00	Average
2 @ 2483.500	52.34	-1.66	54.00	16.92	32.34	3.08	0.00	Average
1 @ 2468.460	115.78			80.42	32.28	3.08	0.00	Peak
2 @ 2483.500	71.90	-2.10	74.00	36.48	32.34	3.08	0.00	Peak

The item 1 is Fundamental Emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	May 19, 2010	Test Site No.	03CH03-HY
Temperature	20	Humidity	50%
Test Engineer	Steven	Configuration	802.11n Ch. 3, 6, 9 (40MHz)

Channel 3

Freq	Level	Over Limit		ReadAntenna		Cable Preamp		Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @ 2390.000	52.66	-1.34	54.00	17.61	32.03	3.02	0.00	Average
2 @ 2418.300	101.91			66.80	32.09	3.02	0.00	Average
1 @ 2388.090	68.41	-5.59	74.00	33.36	32.03	3.02	0.00	Peak
2 @ 2423.810	111.71			76.51	32.15	3.05	0.00	Peak

The item 2 is Fundamental Emissions.

Channel 6

Freq	Level	Over Limit		ReadAntenna		Cable Preamp		Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @ 2421.530	117.89			82.72	32.15	3.02	0.00	Peak
1 @ 2421.340	106.80			71.63	32.15	3.02	0.00	Average

The item 1 is Fundamental Emissions.

Channel 9

Freq	Level	Over Limit		ReadAntenna		Cable Preamp		Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @ 2468.460	99.36			64.00	32.28	3.08	0.00	Average
2 @ 2483.500	52.29	-1.71	54.00	16.87	32.34	3.08	0.00	Average
1 @ 2468.650	109.79			74.43	32.28	3.08	0.00	Peak
2 @ 2488.220	68.23	-5.77	74.00	32.75	32.40	3.08	0.00	Peak

The item 1 is Fundamental Emissions.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


Final Test Date	May 13, 2010	Test Site No.	TH01-HY
Temperature	25	Humidity	61%
Test Engineer	Ian	Configuration	802.11n

Low Band Edge Plot on Configuration of IEEE 802.11n (20MHz) / 2412 MHz




Date: 13.MAY.2010 21:03:08

High Band Edge Plot on Configuration of IEEE 802.11n (20MHz) / 2462 MHz




Date: 13.MAY.2010 21:11:23

Low Band Edge Plot on Configuration of IEEE 802.11n (40MHz) / 2422 MHz



Date: 13.MAY.2010 21:21:13

High Band Edge Plot on Configuration of IEEE 802.11n (40MHz) / 2452 MHz



Date: 13.MAY.2010 21:29:00

3.7 Antenna Requirements

3.7.1 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

3.7.2 Antenna Connector Construction

Please refer to section 2.3 in this test report; antenna connector complied with the requirements.

4 LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100132	9kHz – 2.75GHz	Sep. 14, 2010	Conduction (CO01-HY)
LISN	MessTec	NNB-2/16Z	2001/004	9kHz – 30MHz	Jan. 19, 2010	Conduction (CO01-HY)
LISN (Support Unit)	MessTec	NNB-2/16Z	2001/009	9kHz – 30MHz	Mar. 01, 2010	Conduction (CO01-HY)
EMI Filter	LINDGREN	LRE-2060	1004	< 450Hz	N/A	Conduction (CO01-HY)
EMI Filter	LINDGREN	N6006	201052	0 – 60Hz	N/A	Conduction (CO01-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832010001	9kHz – 30MHz	May 05, 2010	Conduction (CO01-HY)
Isolation Transformer	Erika Fiedler OHG	D-65396 Walluf	58	45MHz-2.15GHz	N/A	Conduction (CO01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSU26.5	100015	20Hz ~ 26.5GHz	Oct. 29, 2009	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 31, 2009	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 12, 2010	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Aug. 06, 2009	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 02, 2009	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 02, 2009	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	0917017	300MHz~40GHz	Dec. 03, 2009	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	0949003	300MHz~40GHz	Dec. 03, 2009	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jul. 12, 2009*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 07, 2009	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 24, 2010	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jul. 21, 2009	Radiation (03CH01-HY)
Spectrum Analyzer	R&S	FSP40	100004	9 kHz - 40 GHz	Oct. 03, 2009	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz - 1 GHz	Sep. 26, 2009	Radiation (03CH03-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1GHz~18GHz	Oct. 22, 2009	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan. 11, 2010	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Jan. 05, 2010	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Jan. 05, 2010	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 - 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 28, 2008*	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is two year.

5 TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6 TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-100529

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.**EMC & Wireless Communications Laboratory**No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities

Jay-San Chen
President, Taiwan Accreditation Foundation
Date : May 29, 2010

P1, total 23 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix.