

FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : Wireless LAN Broadband Router
Model No. : BR-6424NL / GR-424NL / BR-6424N
Brand Name : EDIMAX
Filing Type : New Application
Applicant : EDIMAX TECHNOLOGY CO., LTD.
No. 3, Wu Chuan 3rd Road, Wu-Ku Industrial Park Taipei
Hsien, Taiwan
FCC ID : NDD9564240809
Manufacturer : EDIMAX TECHNOLOGY CO., LTD.
No. 3, Wu Chuan 3rd Road, Wu-Ku Industrial Park Taipei
Hsien, Taiwan
Received Date : Jul. 03, 2008
Final Test Date : Jul. 30, 2008
Multiple Listing : Please refer to section 2.7

Statement

Test result included is only for the 802.11b/g part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



SPORTON International Inc.

6F, No. 106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

Table of Contents

1 SUMMARY OF THE TEST RESULT	2
2 GENERAL INFORMATION.....	3
2.1 Product Details	3
2.2 Accessories	3
2.3 Table for Filed Antenna	3
2.4 Table for Carrier Frequencies	3
2.5 Table for Test Modes	4
2.6 Table for Testing Locations	4
2.7 Table for Multiple Listing	4
2.8 Table for Supporting Units.....	4
2.9 Table for Parameters of Test Software Setting	5
2.10 EUT Operation during Test	5
2.11 Test Configurations	6
3 TEST RESULT	8
3.1 AC Power Line Conducted Emissions Measurement.....	8
3.2 Maximum Peak Output Power Measurement.....	12
3.3 Power Spectral Density Measurement.....	14
3.4 6dB Spectrum Bandwidth Measurement.....	19
3.5 Radiated Emissions Measurement.....	24
3.6 Band Edge and Fundamental Emissions Measurement	42
3.7 Antenna Requirements.....	47
4 LIST OF MEASURING EQUIPMENTS	48
5 TEST LOCATION.....	50
6 TAF CERTIFICATE OF ACCREDITATION	51
APPENDIX A. MAXIMUM PERMISSIBLE EXPOSURE.....	A1 ~ A3
APPENDIX B. TEST PHOTOS	B1 ~ B7
APPENDIX C. PHOTOGRAPHS OF EUT	C1 ~ C9

History of This Test Report

Original Issue Date: Aug. 06, 2008

Report No.: FR852624AC

☒ No additional attachment.

☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description


CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : Wireless LAN Broadband Router
Model No. : BR-6424NL / GR-424NL / BR-6424N
Brand Name : EDIMAX
Applicant : EDIMAX TECHNOLOGY CO., LTD.
No. 3, Wu Chuan 3rd Road, Wu-Ku Industrial Park
Taipei Hsien, Taiwan

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jul. 03, 2008 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Wayne Hsu

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

1 SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	9.36 dB
3.2	15.247(b)(3)	Maximum Peak Conducted Output Power	Complies	11.82 dB
3.3	15.247(e)	Power Spectral Density	Complies	14.29 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	1.24 dB
3.6	15.247(d)	Band Edge Emissions	Complies	0.05 dB
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2 GENERAL INFORMATION

2.1 Product Details

EUT is a Wireless LAN Broadband Router. Only the radio detail of IEEE 802.11b/g is shown in the table below. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Power Type	12VDC Switching Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 15.16 MHz ; 11g: 16.48 MHz
Conducted Output Power	11b: 18.18 dBm ; 11g: 16.51 dBm

2.2 Accessories

Power	Brand	Model	Rating
Switching Adapter	DVE	DSA-12R-12 AUS 120120	INPUT: 100-120VAC 50/60Hz 0.3A OUTPUT: 12V 1A

2.3 Table for Filed Antenna

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
1	Dipole Antenna	Fixed on Board	3.00	TX / RX

NOTE: For 802.11b and 802.11g mode, the signals can be transmitted only by antenna 1.

2.4 Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

2.5 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Mode	Auto	-	-
Maximum Peak Conducted Output Power	11b/CCK	11 Mbps	1/6/11	1
Power Spectral Density	11g/BPSK	6 Mbps	1/6/11	1
6dB Spectrum Bandwidth				
Radiated Emissions 9kHz~1GHz	Normal Mode	Auto	-	-
Radiated Emissions 1GHz~10 th Harmonic	11b/CCK	11 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Band Edge Emissions	11b/CCK	11 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1

2.6 Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4086B-1	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4086B-1	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

2.7 Table for Multiple Listing

The brand/model names in the following table are all refer to the identical product.

No.	Brand Name	Model Name
1	Edimax	BR-6424NL, GR-424NL, BR-6424N
2	Logitec	LAN-WN22/R

2.8 Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook x2	DELL	D400	DoC
Notebook	DELL	D505	DoC
Mouse (USB)	Microsoft	1004	DoC
Modem	ACEEX	DM1414	IFAXDM1414
P.C. (Remote Workstation)	HP	DC579AV	DoC

2.9 Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11b/g

Test Software Version	Hyper Terminal		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	15	16	17
IEEE 802.11g	16	17	17

2.10 EUT Operation during Test

An executive program, EMCTEST.EXE under WIN XP, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The P.C. sends " H " messages to the monitor, and the monitor displays " H " patterns on the screen.

The NB sends " H " messages to the panel, and the panel displays " H " patterns on the screen.

The P.C. sends " H " messages to the modem.


Executed "Hyper Terminal" to keep transmitting signals at fixed frequency.


Executed "ping.exe" to link with the remote workstation to receive and transmit data by LAN and WLAN.

2.11 Test Configurations

2.11.1 Radiation Emissions Test Configuration

For radiated emissions 9kHz~1GHz



For radiated emissions above 1GHz

3 TEST RESULT

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

3.1.3 Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

3.1.4 Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5 Test Deviation


There is no deviation with the original standard.

3.1.6 EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

3.1.7 Results of AC Power Line Conducted Emissions Measurement


Test date	Jul. 30, 2008	Test Site No.	CO04-HY
Temperature	25	Humidity	55%
Test Engineer	Chris	Phase	Line
Configuration	Normal Mode		



SPORTRON 000

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.3099790	40.61	-9.36	49.97	40.46	0.10	0.05	Average
2	0.3099790	44.54	-15.43	59.97	44.39	0.10	0.05	QP
3	0.4967340	38.63	-17.42	56.05	38.39	0.10	0.14	QP
4	0.4967340	32.70	-13.35	46.05	32.46	0.10	0.14	Average
5	0.8710300	37.65	-18.35	56.00	37.15	0.11	0.39	QP
6	0.8710300	32.43	-13.57	46.00	31.93	0.11	0.39	Average
7	1.990	34.79	-21.21	56.00	33.97	0.13	0.69	QP
8	1.990	27.43	-18.57	46.00	26.61	0.13	0.69	Average
9	6.385	25.93	-24.07	50.00	25.49	0.23	0.21	Average
10	6.385	33.98	-26.02	60.00	33.54	0.23	0.21	QP
11	9.970	39.52	-20.48	60.00	38.94	0.28	0.30	QP
12	9.970	35.08	-14.92	50.00	34.50	0.28	0.30	Average

Test date	Jul. 30, 2008	Test Site No.	CO04-HY
Temperature	25	Humidity	55%
Test Engineer	Chris	Phase	Neutral
Configuration	Normal Mode		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.3132810	40.33	-19.55	59.88	40.19	0.09	0.05	QP
2	0.3132810	30.43	-19.45	49.88	30.29	0.09	0.05	Average
3	0.4339490	24.42	-22.76	47.18	24.25	0.09	0.08	Average
4	0.4339490	32.75	-24.43	57.18	32.58	0.09	0.08	QP
5	0.9380970	25.11	-20.89	46.00	24.58	0.11	0.42	Average
6	0.9380970	34.20	-21.80	56.00	33.67	0.11	0.42	QP
7	1.313	32.86	-23.14	56.00	32.21	0.11	0.54	QP
8	1.313	23.89	-22.11	46.00	23.24	0.11	0.54	Average
9	7.582	28.71	-21.29	50.00	28.23	0.23	0.25	Average
10	7.582	33.99	-26.01	60.00	33.51	0.23	0.25	QP
11	13.166	34.11	-15.89	50.00	33.40	0.32	0.39	Average
12	13.166	39.50	-20.50	60.00	38.79	0.32	0.39	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

3.2 Maximum Peak Output Power Measurement

3.2.1 Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	NRV-Z32 (model 04)

3.2.3 Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

3.2.4 Test Setup Layout



3.2.5 Test Deviation

There is no deviation with the original standard.

3.2.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.2.7 Test Result of Maximum Peak Output Power

Test date	Jul. 09, 2008	Test Site No.	TH01-HY
Temperature	28	Humidity	58%
Test Engineer	Tom	Configurations	802.11b/g

Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	18.18	30.00	Complies
6	2437 MHz	18.06	30.00	Complies
11	2462 MHz	17.84	30.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	16.51	30.00	Complies
6	2437 MHz	16.22	30.00	Complies
11	2462 MHz	14.65	30.00	Complies

3.3 Power Spectral Density Measurement

3.3.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.3.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

3.3.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

3.3.4 Test Setup Layout



3.3.5 Test Deviation

There is no deviation with the original standard.

3.3.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.3.7 Test Result of Power Spectral Density

Test date	Jul. 09, 2008	Test Site No.	TH01-HY
Temperature	28	Humidity	58%
Test Engineer	Tom	Configurations	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-6.29	8.00	Complies
6	2437 MHz	-6.36	8.00	Complies
11	2462 MHz	-6.59	8.00	Complies

Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-12.32	8.00	Complies
6	2437 MHz	-12.85	8.00	Complies
11	2462 MHz	-12.82	8.00	Complies

Power Density Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 8 JUL 2008 20:16:24

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 8 JUL 2008 20:24:58

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 8 JUL 2008 20:33:23

Power Density Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 9 JUL 2008 10:35:43

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 9.JUL.2008 10:46:16

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 9.JUL.2008 11:06:50

3.4 6dB Spectrum Bandwidth Measurement

3.4.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

3.4.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.4.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

3.4.4 Test Setup Layout



3.4.5 Test Deviation

There is no deviation with the original standard.

3.4.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.4.7 Test Result of 6dB Spectrum Bandwidth

Test date	Jul. 09, 2008	Test Site No.	TH01-HY
Temperature	28	Humidity	58%
Test Engineer	Tom	Configurations	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.00	15.16	500	Complies
6	2437 MHz	12.16	15.16	500	Complies
11	2462 MHz	12.12	15.16	500	Complies

Configuration IEEE 802.11g


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.56	16.48	500	Complies
6	2437 MHz	16.56	16.48	500	Complies
11	2462 MHz	16.56	16.48	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 8 JUL 2008 20:11:38

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 8 JUL 2008 20:23:09

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 8.JUL.2008 20:30:04

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 9.JUL.2008 10:31:07

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 9.JUL.2008 10:42:29

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 9.JUL.2008 10:52:02

3.5 Radiated Emissions Measurement

3.5.1 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100KHz / 100KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.5.3 Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.5.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.5.5 Test Deviation

There is no deviation with the original standard.

3.5.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.5.7 Results of Radiated Emissions (9kHz~30MHz)

Test date	Jul. 15, 2008	Test Site No.	03CH03-HY
Temperature	27	Humidity	51%
Test Engineer	Duncan		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.5.8 Results of Radiated Emissions (30MHz~1GHz)


Test date	Jul. 15, 2008	Test Site No.	03CH03-HY
Temperature	27	Humidity	51%
Test Engineer	Duncan	Configurations	Normal Mode

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	168.710	37.02	-6.48	43.50	53.03	9.78	2.17	27.96	Peak
2	265.710	40.43	-5.57	46.00	52.45	13.55	2.74	28.31	Peak
3	400.540	40.23	-5.77	46.00	49.08	16.48	3.54	28.87	Peak
4	498.510	39.62	-6.38	46.00	46.69	18.09	3.76	28.92	Peak
5	800.180	33.44	-12.56	46.00	37.41	20.75	4.98	29.70	Peak
6	874.870	34.80	-11.20	46.00	37.88	20.94	5.15	29.17	Peak

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	105.660	37.47	-6.03	43.50	51.61	11.92	1.74	27.80 Peak
2	265.710	40.20	-5.80	46.00	52.22	13.55	2.74	28.31 Peak
3	400.540	38.25	-7.75	46.00	47.10	16.48	3.54	28.87 Peak
4	498.510	40.85	-5.15	46.00	47.92	18.09	3.76	28.92 Peak
5	625.580	37.20	-8.80	46.00	42.94	19.47	4.29	29.50 Peak
6	800.180	36.32	-9.68	46.00	40.29	20.75	4.98	29.70 Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.5.9 Results for Radiated Emissions (1GHz~10th Harmonic)


Test date	Jul. 03, 2008	Test Site No.	03CH03-HY
Temperature	27	Humidity	51%
Test Engineer	Duncan	Configurations	802.11b CH 1

Horizontal




	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp		Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos	Pol/Phase
			dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4824.240	46.72	-27.28	74.00	45.89	33.06	2.93	35.16	PEAK	195	325	HORIZONTAL
2	4824.260	41.15	-12.85	54.00	40.33	33.06	2.93	35.16	AVERAGE	195	325	HORIZONTAL

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	4824.250	48.82	-5.18	54.00	47.99	33.06	2.93	35.16	AVERAGE	101	268	VERTICAL
2	4824.300	51.83	-22.17	74.00	51.01	33.06	2.93	35.16	PEAK	101	268	VERTICAL

Test date	Jul. 03, 2008	Test Site No.	03CH03-HY
Temperature	27	Humidity	51%
Test Engineer	Duncan	Configurations	802.11b CH 6

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4874.240	44.85	-9.15	54.00	43.88	33.16	2.96	35.15 AVERAGE	186	326	HORIZONTAL
2	4874.320	48.97	-25.03	74.00	48.01	33.16	2.96	35.15 PEAK	186	326	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4874.220	54.51	-19.49	74.00	53.54	33.16	2.96	35.15	PEAK	101	286	VERTICAL
2	4874.240	52.76	-1.24	54.00	51.79	33.16	2.96	35.15	AVERAGE	101	286	VERTICAL

Test date	Jul. 03, 2008	Test Site No.	03CH03-HY
Temperature	27	Humidity	51%
Test Engineer	Duncan	Configurations	802.11b CH 11



Horizontal

TABLE 1: MEASUREMENT DATA


	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable Preamp	Loss Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4924.180	45.98	-28.02	74.00	44.87	33.26	2.98	35.14	107	124	HORIZONTAL
2	4924.220	36.86	-17.14	54.00	35.76	33.26	2.98	35.14	107	124	HORIZONTAL

Vertical



	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp		Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Pol/Phase
			dB	dBuV/m	dBuV		dB	dB	cm	deg	
1	4924.230	47.67	-6.33	54.00	46.57	33.26	2.98	35.14	100	347	VERTICAL
2	4924.240	51.15	-22.85	74.00	50.05	33.26	2.98	35.14	100	347	VERTICAL


Test date	Jul. 03, 2008	Test Site No.	03CH03-HY
Temperature	27	Humidity	51%
Test Engineer	Duncan	Configurations	802.11g CH 1

Horizontal

2008-07-03 18:22:42

	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp		Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos	Pol/Phase
			dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4824.080	42.71	-31.29	74.00	41.89	33.06	2.93	35.16	PEAK	100	332	HORIZONTAL
2	4829.120	28.45	-25.55	54.00	27.63	33.06	2.93	35.16	AVERAGE	100	332	HORIZONTAL


Vertical



20080703 18:17:17


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4826.200	32.44	-21.56	54.00	31.62	33.06	2.93	35.16	AVERAGE	100	294	VERTICAL
2	4826.200	45.81	-28.19	74.00	44.98	33.06	2.93	35.16	PEAK	100	294	VERTICAL

Test date	Jul. 03, 2008	Test Site No.	03CH03-HY
Temperature	27	Humidity	51%
Test Engineer	Duncan	Configurations	802.11g CH 6

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4874.500	38.60	-15.40	54.00	37.64	33.16	2.96	35.15	AVERAGE	100	227	HORIZONTAL
2	4875.300	51.54	-22.46	74.00	50.58	33.16	2.96	35.15	PEAK	100	227	HORIZONTAL


Vertical



DATA SUMMARY TABLE


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4874.300	45.34	-8.66	54.00	44.37	33.16	2.96	35.15	AVERAGE	101	300	VERTICAL
2	4875.500	58.32	-15.68	74.00	57.36	33.16	2.96	35.15	PEAK	101	300	VERTICAL

Test date	Jul. 03, 2008	Test Site No.	03CH03-HY
Temperature	27	Humidity	51%
Test Engineer	Duncan	Configurations	802.11g CH 11

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4925.700	31.35	-22.65	54.00	30.25	33.26	2.98	35.14	AVERAGE	102	81	HORIZONTAL
2	4926.800	43.66	-30.34	74.00	42.55	33.26	2.98	35.14	PEAK	102	81	HORIZONTAL

Vertical



SPURIOUS EMISSIONS

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4924.300	34.48	-19.52	54.00	33.38	33.26	2.98	35.14	AVERAGE	100	291	VERTICAL
2	4924.300	48.77	-25.23	74.00	47.67	33.26	2.98	35.14	PEAK	100	291	VERTICAL

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.6 Band Edge and Fundamental Emissions Measurement

3.6.1 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.6.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

3.6.3 Test Procedures

1. The test procedure is the same as section 3.5.3; only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

3.6.4 Test Setup Layout

This test setup layout is the same as that shown in section 3.5.4.

3.6.5 Test Deviation

There is no deviation with the original standard.

3.6.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.6.7 Test Result of Band Edge and Fundamental Emissions

Test date	Jul. 03, 2008	Test Site No.	03CH03-HY
Temperature	27	Humidity	51%
Test Engineer	Duncan	Configurations	802.11b CH 1, 6, 11

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss Factor	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	2389.200	62.88	-11.12	74.00	33.00	28.17	1.71	0.00 PEAK	100	300	VERTICAL
2 !	2390.000	53.54	-0.46	54.00	23.65	28.17	1.71	0.00 AVERAGE	100	300	VERTICAL
3 @	2409.400	102.93			72.99	28.21	1.73	0.00 AVERAGE	100	300	VERTICAL
4 over	2410.800	106.13			76.19	28.21	1.73	0.00 PEAK	100	300	VERTICAL
1	2389.800	58.04	-15.96	74.00	28.16	28.17	1.71	0.00 PEAK	125	239	HORIZONTAL
2 !	2390.000	48.14	-5.86	54.00	18.26	28.17	1.71	0.00 AVERAGE	125	239	HORIZONTAL
3 @	2409.400	98.60			68.67	28.21	1.73	0.00 AVERAGE	125	239	HORIZONTAL
4 over	2410.800	102.01			72.08	28.21	1.73	0.00 PEAK	125	239	HORIZONTAL

An item 3 and 4 are Fundamental Emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss Factor	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	2389.800	59.56	-14.44	74.00	29.68	28.17	1.71	0.00 PEAK	100	301	VERTICAL
2	2390.000	47.12	-6.88	54.00	17.24	28.17	1.71	0.00 AVERAGE	100	301	VERTICAL
3 @	2434.400	105.04			75.01	28.29	1.74	0.00 AVERAGE	100	301	VERTICAL
4 over	2435.800	108.53			78.51	28.29	1.74	0.00 PEAK	100	301	VERTICAL
5	2483.700	55.51	-18.49	74.00	25.37	28.37	1.77	0.00 PEAK	100	301	VERTICAL
6	2483.700	44.14	-9.86	54.00	14.00	28.37	1.77	0.00 AVERAGE	100	301	VERTICAL
1	2389.800	51.24	-22.76	74.00	21.36	28.17	1.71	0.00 PEAK	100	303	HORIZONTAL
2	2390.000	42.61	-11.39	54.00	12.73	28.17	1.71	0.00 AVERAGE	100	303	HORIZONTAL
3 @	2434.400	100.78			70.76	28.29	1.74	0.00 AVERAGE	100	303	HORIZONTAL
4 over	2436.200	104.31			74.28	28.29	1.74	0.00 PEAK	100	303	HORIZONTAL
5	2483.500	42.83	-11.17	54.00	12.68	28.38	1.77	0.00 AVERAGE	100	303	HORIZONTAL
6	2483.500	54.35	-19.65	74.00	24.20	28.38	1.77	0.00 PEAK	100	303	HORIZONTAL

An item 3 and 4 are Fundamental Emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss Factor	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 over	2463.600	107.27			77.19	28.33	1.76	0.00 PEAK	109	328	VERTICAL
2 @	2464.800	103.76			73.68	28.33	1.76	0.00 AVERAGE	109	328	VERTICAL
3 !	2483.500	53.41	-0.59	54.00	23.27	28.37	1.77	0.00 AVERAGE	109	328	VERTICAL
4	2483.700	61.30	-12.70	74.00	31.16	28.37	1.77	0.00 PEAK	109	328	VERTICAL
1 @	2459.400	96.19			66.10	28.33	1.76	0.00 AVERAGE	100	147	HORIZONTAL
2 over	2460.800	99.65			69.56	28.33	1.76	0.00 PEAK	100	147	HORIZONTAL
3	2483.500	47.71	-6.29	54.00	17.56	28.38	1.77	0.00 AVERAGE	100	147	HORIZONTAL
4	2483.900	57.46	-16.54	74.00	27.31	28.38	1.77	0.00 PEAK	100	147	HORIZONTAL

An item 1 and 2 are Fundamental Emissions.

Test date	Jul. 03, 2008	Test Site No.	03CH03-HY
Temperature	27	Humidity	51%
Test Engineer	Duncan	Configurations	802.11g CH 1, 6, 11

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss Factor	Preamplifier Loss Factor	Remark	Ant Pos	Table Pos	Pol/Phase	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		
1 !	2389.600	73.95	-0.05	74.00	44.07	28.17	1.71	0.00	PEAK	100	300	VERTICAL
2 !	2390.000	53.08	-0.92	54.00	23.20	28.17	1.71	0.00	AVERAGE	100	300	VERTICAL
3 over	2405.200	106.66			76.72	28.21	1.73	0.00	PEAK	100	300	VERTICAL
4 @	2405.800	97.18			67.25	28.21	1.73	0.00	AVERAGE	100	300	VERTICAL
1	2389.600	65.82	-8.18	74.00	35.94	28.17	1.71	0.00	PEAK	124	242	HORIZONTAL
2	2390.000	47.15	-6.85	54.00	17.26	28.17	1.71	0.00	AVERAGE	124	242	HORIZONTAL
3 over	2404.800	100.20			70.26	28.21	1.73	0.00	PEAK	124	242	HORIZONTAL
4 over	2405.800	90.97			61.03	28.21	1.73	0.00	AVERAGE	124	242	HORIZONTAL

An item 3 and 4 are Fundamental Emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss Factor	Preamplifier Loss Factor	Remark	Ant Pos	Table Pos	Pol/Phase	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		
1 !	2390.000	53.49	-0.51	54.00	23.61	28.17	1.71	0.00	AVERAGE	100	0	VERTICAL
2 !	2390.000	70.10	-3.90	74.00	40.21	28.17	1.71	0.00	PEAK	100	0	VERTICAL
3 @	2440.200	106.24			76.21	28.29	1.74	0.00	AVERAGE	100	0	VERTICAL
4 @	2443.400	115.91			85.88	28.29	1.74	0.00	PEAK	100	0	VERTICAL
5 !	2483.500	49.58	-4.42	54.00	19.44	28.37	1.77	0.00	AVERAGE	100	0	VERTICAL
6	2485.100	67.41	-6.59	74.00	37.23	28.41	1.77	0.00	PEAK	100	0	VERTICAL
1	2389.800	61.95	-12.05	74.00	32.07	28.17	1.71	0.00	PEAK	100	256	HORIZONTAL
2	2390.000	46.95	-7.05	54.00	17.07	28.17	1.71	0.00	AVERAGE	100	256	HORIZONTAL
3 @	2430.000	97.09			67.10	28.25	1.74	0.00	AVERAGE	100	256	HORIZONTAL
4 over	2430.200	106.60			76.61	28.25	1.74	0.00	PEAK	100	256	HORIZONTAL
5	2483.500	43.87	-10.13	54.00	13.72	28.38	1.77	0.00	AVERAGE	100	256	HORIZONTAL
6	2485.100	55.59	-18.41	74.00	25.40	28.42	1.77	0.00	PEAK	100	256	HORIZONTAL

An item 3 and 4 are Fundamental Emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss Factor	Preamplifier Loss Factor	Remark	Ant Pos	Table Pos	Pol/Phase	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		
1 @	2458.200	100.26			70.18	28.33	1.76	0.00	AVERAGE	100	0	VERTICAL
2 over	2458.400	108.60			78.51	28.33	1.76	0.00	PEAK	100	0	VERTICAL
3 !	2483.500	53.14	-0.86	54.00	22.99	28.37	1.77	0.00	AVERAGE	100	0	VERTICAL
4 !	2483.900	73.24	-0.76	74.00	43.09	28.37	1.77	0.00	PEAK	100	0	VERTICAL
1 over	2455.000	101.97			71.88	28.33	1.76	0.00	PEAK	107	184	HORIZONTAL
2 @	2457.600	92.73			62.64	28.33	1.76	0.00	AVERAGE	107	184	HORIZONTAL
3 !	2483.500	48.28	-5.72	54.00	18.13	28.38	1.77	0.00	AVERAGE	107	184	HORIZONTAL
4	2483.900	66.92	-7.08	74.00	36.77	28.38	1.77	0.00	PEAK	107	184	HORIZONTAL

An item 1 and 2 are Fundamental Emissions.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 8.JUL.2008 20:14:40

High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 8.JUL.2008 20:31:52

Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 9.JUL.2008 10:33:16

High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 9.JUL.2008 11:04:55

3.7 Antenna Requirements

3.7.1 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

3.7.2 Antenna Connector Construction

Please refer to section 2.3 in this test report; antenna connector complied with the requirements.

4 LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Mar. 03, 2008	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2008	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2008	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2008	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz – 30MHz	Mar. 27, 2008	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2008	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 14, 2008	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02364	1 GHz - 26.5 GHz	Apr. 24, 2008	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004	9 kHz - 40 GHz	Sep. 27, 2007	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 12, 2008	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 04, 2008	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.18, 2008	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 10, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 11, 2008	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2008	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2007	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2007	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2007	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 14, 2007	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 10, 2008	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Loop Antenna	TESEQ	HLA6120	24155	9KHz ~ 30MHz	Jan. 18, 2007*	Radiation (03CH03-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 30, 2008*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

5 TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6 TAF CERTIFICATE OF ACCREDITATION


Certificate No. : L1190-070110

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory


Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 10, 2007

PI, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.