

FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : 300N Wireless LAN Concurrent
Dual Band Gigabit Router
Model No. : BR-6475ND, GR-475ND, EW-7475PDD
Brand Name : EDIMAX
Filing Type : New Application
Applicant : EDIMAX TECHNOLOGY CO., LTD.
Manufacturer : No.3, Wu Chuan 3rd Road, Wu-Ku
Industrial Park. Taipei Hsien, Taiwan
FCC ID : NDD9564751027
Received Date : Jan. 13, 2011
Final Test Date : Mar. 22, 2011
Multiple Listing : Please refer to section 2.2

Statement

Test result included is only for the 802.11a/b/g (5725~5850 MHz / 2400~2483.5MHz) part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

Table of Contents

1 SUMMARY OF THE TEST RESULT	2
2 GENERAL INFORMATION.....	3
2.1 Product Details	3
2.2 Table for Multiple Listing	3
2.3 Accessories	3
2.4 Table for Filed Antenna.....	3
2.5 Table for Carrier Frequencies	4
2.6 Table for Test Modes	4
2.7 Table for Testing Locations.....	4
2.8 Table for Supporting Units	5
2.9 Table for Parameters of Test Software Setting.....	5
2.10 EUT Operation during Test	5
2.11 Test Configuration.....	6
3 TEST RESULT	9
3.1 AC Power Line Conducted Emissions Measurement	9
3.2 Peak Output Power Measurement	15
3.3 Power Spectral Density Measurement	17
3.4 6dB Spectrum Bandwidth Measurement	25
3.5 Radiated Emissions Measurement.....	33
3.6 Band Edge and Fundamental Emissions Measurement	59
3.7 Antenna Requirements	66
4 LIST OF MEASURING EQUIPMENTS.....	67
5 TEST LOCATION.....	69
6 TAF CERTIFICATE OF ACCREDITATION.....	70
APPENDIX A. MAXIMUM PERMISSIBLE EXPOSURE	A1 ~ A3
APPENDIX B. TEST PHOTOS	B1 ~ B9
APPENDIX C. PHOTOGRAPHS OF EUT	C1 ~ C14

History of This Test Report

Original Issue Date: Apr. 14, 2011

Report No.: FR0D2828AC

Attachment No.	Issue Date	Description


CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : 300N Wireless LAN Concurrent
Dual Band Gigabit Router
Model No. : BR-6475ND, GR-475ND, EW-7475PDD
Brand Name : EDIMAX
Applicant : EDIMAX TECHNOLOGY CO., LTD.
No.3, Wu Chuan 3rd Road, Wu-Ku Industrial
Park. Taipei Hsien, Taiwan

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jan. 13, 2011 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.


Wayne Hsu / Vice Manager

SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

1 SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	1.95 dB
3.2	15.247(b)(3)	Maximum Peak Output Power	Complies	9.84 dB
3.3	15.247(e)	Power Spectral Density	Complies	17.43 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	1.18 dB
3.6	15.247(d)	Band Edge and Fundamental Emissions	Complies	1.11 dB
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7℃	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2 GENERAL INFORMATION

2.1 Product Details

The differences between EUTs are the appearance and the connector of antennas. Both of EUTs can be supplied the electricity (power) by adapter or POE. Only the radio detail of IEEE 802.11a/b/g is shown in this report. For more detailed features description, please refer to the specifications or user's manual.

Items	Description
Power Type	Power from adaptert
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (DBPSK / DQPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11a: 5 ; 11b/g: 11
Channel Band Width (99%)	5G-11a: 16.41 MHz 2.4G-11b: 14.55 MHz ; 11g: 16.41 MHz
Conducted Output Power	5G-11a: 19.78 dBm 2.4G-11b: 17.45 dBm ; 11g: 20.16 dBm

2.2 Table for Multiple Listing

Brand and models that are exactly the same EUT, products with different models only because of market segmentation.

No.	Brand Name	Model Name
1	Edimax	BR-6475ND, GR-475ND, EW-7475PDD
2	Intellient	525039
3	SMC	SMCE21011 V2

2.3 Accessories

Power	Brand	Model	Rating
Switching Adapter	DVE	DSA-12GX-12 FUS 120120	INPUT : 100-240V ~ 50/60Hz 0.3A OUTPUT : +12V 1A

2.4 Table for Filed Antenna

Antenna Type 1

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
A	Dipole Antenna (white)	Reversed-SMA	3.00	TX / RX
B	Dipole Antenna (white)	Reversed-SMA	3.00	TX / RX

Antenna Type 2

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
A	Dipole Antenna (black)	Fixed on Board	3.00	TX / RX
B	Dipole Antenna (black)	Fixed on Board	3.00	TX / RX

Note: The 2.4G and 5G transmitters cannot be simultaneously transmitted.

2.5 Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency
5725~5850 MHz	149	5745 MHz
	153	5765 MHz
	157	5785 MHz
	161	5805 MHz
	165	5825 MHz

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

2.6 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on the entire possible configuration for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Adapter Mode /	Auto	-	-
Radiated Emissions Below 1GHz	POE Mode			
Maximum Peak Output Power Power Spectral Density 6dB Spectrum Bandwidth	11a/BPSK	6 Mbps	149/157/165	A
	11b/CCK	11 Mbps	1/6/11	A
	11g/BPSK	54 Mbps	1/6/11	A
Radiated Emissions Above 1GHz	11a/BPSK	6 Mbps	149/157/165	A
	11b/CCK	11 Mbps	1/6/11	A
	11g/BPSK	54 Mbps	1/6/11	A
Band Edge Emissions	11a/BPSK	6 Mbps	149/165	A
	11b/CCK	11 Mbps	1/11	A
	11g/BPSK	54 Mbps	1/11	A

2.7 Table for Testing Locations

Test Site No.	Site Category	Location
CO01-HY	Conduction	Hwa Ya
TH01-HY	OVEN Room	Hwa Ya
03CH02-HY	SAC	Hwa Ya

Semi Anechoic Chamber (SAC).

2.8 Table for Supporting Units

Support Unit	Brand	Model	FCC ID
(USB) Mouse	Microsoft	1004	DoC
Modem	ACEEX	DM-1414	IFAXDM1414
Notebook	DELL	D505	DoC
iPod nano	Apple	A1199	N/A
POE	D-Link	DWL-P200	N/A
Notebook (Remote workstation)	DELL	E5500	DoC

2.9 Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11a

Test Software Version	RT3x9x QA		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	0	0	0

Power Parameters of IEEE 802.11b/g

Test Software Version	RT3x9x QA		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	5	5	5
IEEE 802.11g	0	0	0

2.10 EUT Operation during Test

An executive program, "EMCTEST.EXE" under Win XP, which generates a complete line of continuously repeating "H" pattern was used as the test software.

The program was executed as follows :

- Turn on the power of all equipment.
- The NB sends "H" messages to the panel and displays "H" patterns on the screen.
- The NB sends messages to the modem.
- Repeat the step b to c.


At the same time, the following programs were executed:

- Executed "WiFi" to link with the remote workstation to receive and transmit data.
- Executed "Ping" to link with the remote workstation to receive and transmit data via RJ45 cable.
- Executed "RT3x9x QA" to keep transmitting signals at fixed frequency. (Only for radio tested.)


2.11 Test Configuration

2.11.1 Radiation Emissions Test Configuration


For radiated emissions 9kHz~1GHz
Adapter Mode



POE Mode



For radiated emissions above 1GHz



3 TEST RESULT

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Class B

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


3.1.3 Test Procedures

1. The EUT warm up about 15 minutes then start test.
2. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
5. The frequency range from 150 KHz to 30 MHz was searched.
6. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. The measurement has to be done between each power line and ground at the power terminal.

3.1.7 Results of AC Power Line Conducted Emissions Measurement


Final Test Date	Mar. 22, 2011	Test Site No.	CO01-HY
Temperature	20.8°C	Humidity	51.3%
Test Engineer	David	Configuration	Adapter Mode

Line



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.291	39.79	-20.71	60.50	39.10	0.09	0.60	QP
2	0.291	35.35	-15.15	50.50	34.66	0.09	0.60	Average
3	0.388	35.28	-12.82	48.10	34.59	0.09	0.60	Average
4	0.388	37.27	-20.83	58.10	36.58	0.09	0.60	QP
5	0.779	36.06	-9.94	46.00	35.36	0.10	0.60	Average
6	0.779	39.79	-16.21	56.00	39.09	0.10	0.60	QP
7	1.560	32.46	-13.54	46.00	31.74	0.12	0.60	Average
8	1.560	37.56	-18.44	56.00	36.84	0.12	0.60	QP
9	2.336	34.31	-11.69	46.00	33.57	0.14	0.60	Average
10	2.336	36.84	-19.16	56.00	36.10	0.14	0.60	QP
11	3.118	38.15	-17.85	56.00	37.39	0.16	0.60	QP
12	3.118	36.64	-9.36	46.00	35.88	0.16	0.60	Average

Neutral




	Freq	Level	Over	Limit	Read	Probe	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.150	27.43	-28.57	56.00	26.79	0.08	0.56	Average
2	0.150	44.19	-21.81	66.00	43.55	0.08	0.56	QP
3	0.223	40.96	-21.75	62.71	40.28	0.08	0.60	QP
4	0.223	39.25	-13.46	52.71	38.57	0.08	0.60	Average
5	0.297	42.77	-17.56	60.33	42.08	0.09	0.60	QP
6	0.297	37.73	-12.60	50.33	37.04	0.09	0.60	Average
7	0.387	37.22	-20.91	58.13	36.53	0.09	0.60	QP
8	0.387	34.35	-13.78	48.13	33.66	0.09	0.60	Average
9	0.590	33.50	-12.50	46.00	32.80	0.10	0.60	Average
10	0.590	37.63	-18.37	56.00	36.93	0.10	0.60	QP
11	0.778	40.40	-15.60	56.00	39.70	0.10	0.60	QP
12	0.778	36.63	-9.37	46.00	35.93	0.10	0.60	Average

Note:

Level = Read Level + LISN Factor + Cable Loss.


Final Test Date	Mar. 22, 2011	Test Site No.	CO01-HY
Temperature	20.8°C	Humidity	51.3%
Test Engineer	David	Configuration	POE Mode

Line



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.442	39.89	-17.13	57.02	39.20	0.09	0.60	QP
2	0.442	39.54	-7.48	47.02	38.85	0.09	0.60	Average
3	0.822	39.63	-6.37	46.00	38.92	0.11	0.60	Average
4	0.822	39.93	-16.07	56.00	39.22	0.11	0.60	QP
5	1.136	40.64	-5.36	46.00	39.93	0.11	0.60	Average
6	1.136	41.08	-14.92	56.00	40.37	0.11	0.60	QP
7	1.703	42.16	-3.84	46.00	41.43	0.13	0.60	Average
8	1.703	43.22	-12.78	56.00	42.49	0.13	0.60	QP
9	2.017	41.56	-14.44	56.00	40.83	0.13	0.60	QP
10	2.017	40.90	-5.10	46.00	40.17	0.13	0.60	Average
11	3.340	38.25	-7.75	46.00	37.49	0.16	0.60	Average
12	3.343	41.65	-14.35	56.00	40.89	0.16	0.60	QP

Neutral



	Freq	Level	Over	Limit	Read	Probe	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.442	41.87	-5.15	47.02	41.20	0.07	0.60	Average
2	0.442	42.09	-14.93	57.02	41.42	0.07	0.60	QP
3	0.822	42.21	-3.79	46.00	41.52	0.09	0.60	Average
4	0.822	42.42	-13.58	56.00	41.73	0.09	0.60	QP
5	1.075	43.71	-12.29	56.00	43.02	0.09	0.60	QP
6	1.075	43.23	-2.77	46.00	42.54	0.09	0.60	Average
7	1.390	44.97	-11.03	56.00	44.27	0.10	0.60	QP
8	1.390	44.05	-1.95	46.00	43.35	0.10	0.60	Average
9	1.710	41.92	-4.08	46.00	41.21	0.11	0.60	Average
10	1.710	43.13	-12.87	56.00	42.42	0.11	0.60	QP
11	3.350	41.58	-4.42	46.00	40.85	0.13	0.60	Average
12	3.351	43.42	-12.58	56.00	42.69	0.13	0.60	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

3.2 Peak Output Power Measurement

3.2.1 Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-multipoint antenna reduction operation, the limit has to be reduced by 1dB for every dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

3.2.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	MA2411B

3.2.3 Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

3.2.4 Test Setup Layout



3.2.5 Test Deviation

There is no deviation with the original standard.

3.2.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.2.7 Test Result of Peak Output Power

Final Test Date	Jan. 28, 2011	Test Site No.	TH01-HY
Temperature	20°C	Humidity	60%
Test Engineer	Ian	Configurations	802.11a/b/g

Configuration IEEE 802.11a

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	19.78	30.00	Complies
157	5785 MHz	19.26	30.00	Complies
165	5825 MHz	18.47	30.00	Complies

Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.45	30.00	Complies
6	2437 MHz	17.26	30.00	Complies
11	2462 MHz	17.44	30.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	19.91	30.00	Complies
6	2437 MHz	20.12	30.00	Complies
11	2462 MHz	20.16	30.00	Complies

3.3 Power Spectral Density Measurement

3.3.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.3.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

3.3.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3 kHz and VBW to 30 kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

3.3.4 Test Setup Layout



3.3.5 Test Deviation

There is no deviation with the original standard.

3.3.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.3.7 Test Result of Power Spectral Density

Final Test Date	Jan. 28, 2011	Test Site No.	TH01-HY
Temperature	20°C	Humidity	60%
Test Engineer	Ian	Configurations	802.11a/b/g

Configuration IEEE 802.11a

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	-19.00	8.00	Complies
157	5785 MHz	-20.12	8.00	Complies
165	5825 MHz	-21.25	8.00	Complies


Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-9.95	8.00	Complies
6	2437 MHz	-9.46	8.00	Complies
11	2462 MHz	-9.43	8.00	Complies

Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-18.19	8.00	Complies
6	2437 MHz	-18.00	8.00	Complies
11	2462 MHz	-18.55	8.00	Complies

Power Density Plot on Configuration IEEE 802.11a / 5745 MHz




Date: 28.JAN.2011 20:10:22

Power Density Plot on Configuration IEEE 802.11a / 5785 MHz




Date: 28.JAN.2011 20:12:22

Power Density Plot on Configuration IEEE 802.11a / 5825 MHz




Date: 28.JAN.2011 20:15:02

Power Density Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 28.JAN.2011 17:14:15

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 28.JAN.2011 17:18:07

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 28.JAN.2011 17:23:54

Power Density Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 28.JAN.2011 17:49:58

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 28.JAN.2011 17:52:10

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 28.JAN.2011 17:55:09

3.4 6dB Spectrum Bandwidth Measurement

3.4.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

3.4.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.4.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

3.4.4 Test Setup Layout



3.4.5 Test Deviation

There is no deviation with the original standard.

3.4.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.4.7 Test Result of 6dB Spectrum Bandwidth

Final Test Date	Jan. 28, 2011	Test Site No.	TH01-HY
Temperature	20°C	Humidity	60%
Test Engineer	Ian	Configurations	802.11a/b/g

Configuration IEEE 802.11a

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.57	16.41	500	Complies
157	5785 MHz	16.51	16.41	500	Complies
165	5825 MHz	16.57	16.41	500	Complies

Configuration IEEE 802.11b

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	11.51	14.55	500	Complies
6	2437 MHz	11.73	14.55	500	Complies
11	2462 MHz	11.73	14.55	500	Complies


Configuration IEEE 802.11g

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.51	16.41	500	Complies
6	2437 MHz	16.54	16.41	500	Complies
11	2462 MHz	16.51	16.41	500	Complies




FCC ID : NDD9564751027

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5825 MHz




Date: 28.JAN.2011 20:13:29

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz



Date: 28.JAN.2011 17:12:31


6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz



Date: 28.JAN.2011 17:16:52




6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 28.JAN.2011 17:48:28

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 28.JAN.2011 17:51:21



3.5 Radiated Emissions Measurement

3.5.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.5.3 Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.5.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.5.5 Test Deviation

There is no deviation with the original standard.

3.5.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.5.7 Results of Radiated Emissions (9kHz~30MHz)

Final Test Date	Jan. 20, 2011	Test Site No.	03CH02-HY
Temperature	21.5℃	Humidity	55%
Test Engineer	Daniel		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.5.8 Results of Radiated Emissions (30MHz~1GHz)


Final Test Date	Jan. 20, 2011	Test Site No.	03CH02-HY
Temperature	21.5℃	Humidity	55%
Test Engineer	Daniel	Configurations	Adapter Mode

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	125.060	28.27	-15.23	43.50	40.36	13.18	2.26	27.53	Peak
2	249.220	40.04	-5.96	46.00	49.84	12.97	4.05	26.82	Peak
3	288.020	39.59	-6.41	46.00	48.41	13.54	4.44	26.80	Peak
4	374.350	42.52	-3.48	46.00	50.30	14.86	4.77	27.41	Peak
5	498.510	44.10	-1.90	46.00	48.87	17.26	6.15	28.18	Peak
6	625.580	38.22	-7.78	46.00	39.23	19.84	7.28	28.13	Peak
7	749.740	37.82	-8.18	46.00	38.39	19.55	7.76	27.88	Peak
8	874.870	39.46	-6.54	46.00	37.73	20.09	9.08	27.44	Peak

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	56.190	36.40	-3.60	40.00	54.76	8.05	1.34	27.75	Peak
2	125.060	36.24	-7.26	43.50	48.33	13.18	2.26	27.53	Peak
3	249.220	37.18	-8.82	46.00	46.98	12.97	4.05	26.82	Peak
4	498.510	42.28	-3.72	46.00	47.05	17.26	6.15	28.18	Peak
5	625.580	41.85	-4.15	46.00	42.86	19.84	7.28	28.13	Peak
6	749.740	39.61	-6.39	46.00	40.18	19.55	7.76	27.88	Peak


Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	Feb. 08, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configurations	POE Mode

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	48.430	30.19	-9.81	40.00	46.57	10.34	1.07	27.79	Peak
2	249.220	37.19	-8.81	46.00	46.99	12.97	4.05	26.82	Peak
3	374.350	39.07	-6.93	46.00	46.85	14.86	4.77	27.41	Peak
4	498.510	42.05	-3.95	46.00	46.82	17.26	6.15	28.18	QP
5	625.580	37.03	-8.97	46.00	38.04	19.84	7.28	28.13	Peak
6	749.740	38.51	-7.49	46.00	39.08	19.55	7.76	27.88	Peak
7	874.870	39.45	-6.55	46.00	37.72	20.09	9.08	27.44	Peak

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	32.910	37.51	-2.49	40.00	49.55	15.11	0.71	27.86	QP
2	48.430	33.55	-6.45	40.00	49.93	10.34	1.07	27.79	QP
3	67.830	35.08	-4.92	40.00	53.67	6.81	2.30	27.70	QP
4	498.510	39.77	-6.23	46.00	44.54	17.26	6.15	28.18	Peak
5	625.580	43.45	-2.55	46.00	44.46	19.84	7.28	28.13	Peak
6	749.740	42.49	-3.51	46.00	43.06	19.55	7.76	27.88	Peak

Note:


The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.5.9 Results for Radiated Emissions (1GHz~10th Harmonic)


Final Test Date	Jan. 13, 2011	Test Site No.	03CH02-HY
Temperature	21.5℃	Humidity	55%
Test Engineer	Daniel	Configuration	802.11a Ch. 149

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8564.000	59.22			49.08	38.45	5.97	34.28	Peak
2	11490.000	59.59	-3.95	63.54	46.01	40.59	6.63	33.64	PK
3	17235.000	77.87			57.99	43.56	8.55	32.23	Peak

Note: The items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Preamp Loss Factor	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	7116.000	59.94			50.79	37.82	5.61	34.28 Peak
2	11490.000	45.77	-17.77	63.54	32.19	40.59	6.63	33.64 Average
3	11490.000	60.09	-23.45	83.54	46.51	40.59	6.63	33.64 Peak
4	17235.000	81.60			61.72	43.56	8.55	32.23 Peak

Note: The items 1 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Jan. 14, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configuration	802.11a Ch. 157

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8564.000	59.28			49.14	38.45	5.97	34.28	Peak
2	11570.000	60.78	-22.76	83.54	47.15	40.63	6.63	33.63	Peak
3	11570.000	46.33	-17.21	63.54	32.70	40.63	6.63	33.63	Average
4	@17355.000	78.36			58.57	43.49	8.50	32.20	Peak

Note: The items 1 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8564.000	64.11			53.97	38.45	5.97	34.28	Peak
2	11570.000	64.45	-19.09	83.54	50.82	40.63	6.63	33.63	Peak
3	11570.000	50.07	-13.47	63.54	36.44	40.63	6.63	33.63	Average
4	@17355.000	82.03			62.24	43.49	8.50	32.20	Peak

Note: The items 1 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Jan. 14, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configuration	802.11a Ch. 165

Horizontal

	Freq	Level	Over Limit	Limit Line	Read Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8560.000	59.35			49.19	38.45	5.97	34.26	Peak
2	11620.000	66.10	-17.44	83.54	52.44	40.65	6.63	33.62	Peak
3	11620.000	50.26	-13.28	63.54	36.60	40.65	6.63	33.62	Average
4	@17475.000	74.85			55.15	43.42	8.44	32.16	Peak

Note: The items 1 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8564.000	62.14			52.00	38.45	5.97	34.28	Peak
2	11650.000	69.78	-13.76	83.54	56.08	40.66	6.64	33.60	Peak
3	11650.000	53.69	-9.85	63.54	39.99	40.66	6.64	33.60	Average
4	17475.000	81.69			61.99	43.42	8.44	32.16	Peak

Note: The items 1 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Jan. 13, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configuration	802.11b Ch. 1

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4824.000	39.23	-14.77	54.00	33.40	35.76	4.58	34.51	Average
2	4824.000	52.67	-21.33	74.00	46.84	35.76	4.58	34.51	Peak
3	7236.000	67.14			57.95	37.85	5.63	34.29	Peak
4	9648.000	56.72			45.62	39.39	6.34	34.63	Peak

Note: The items 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4824.000	42.55	-11.45	54.00	37.35	35.13	4.58	34.51	Average
2	4824.000	55.78	-18.22	74.00	50.58	35.13	4.58	34.51	Peak
3	7236.000	70.85			62.61	36.90	5.63	34.29	Peak
4	9648.000	57.18			46.88	38.59	6.34	34.63	Peak

Note: The items 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Jan. 13, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configuration	802.11b Ch. 6

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4874.000	39.47	-14.53	54.00	33.48	35.83	4.61	34.45	Average
2	4874.000	52.73	-21.27	74.00	46.74	35.83	4.61	34.45	Peak
3	7311.000	52.82	-1.18	54.00	43.61	37.86	5.64	34.29	Average
4	7311.000	63.82	-10.18	74.00	54.61	37.86	5.64	34.29	Peak
5	9748.000	55.41			44.12	39.51	6.36	34.58	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4874.000	40.99	-13.01	54.00	35.65	35.18	4.61	34.45 Average
2	4874.000	54.94	-19.06	74.00	49.60	35.18	4.61	34.45 Peak
3	7311.000	50.20	-3.80	54.00	41.93	36.92	5.64	34.29 Average
4	7311.000	61.64	-12.36	74.00	53.37	36.92	5.64	34.29 Peak
5	9748.000	53.99			43.50	38.71	6.36	34.58 Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Jan. 13, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configuration	802.11b Ch. 11

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4924.000	38.78	-15.22	54.00	32.58	35.90	4.68	34.38	Average
2	4924.000	52.80	-21.20	74.00	46.60	35.90	4.68	34.38	Peak
3	7386.000	49.14	-4.86	54.00	39.90	37.88	5.65	34.29	Average
4	7386.000	60.38	-13.62	74.00	51.14	37.88	5.65	34.29	Peak
5	9848.000	56.06			44.61	39.61	6.38	34.54	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4924.000	39.53	-14.47	54.00	34.00	35.23	4.68	34.38	Average
2	4924.000	53.18	-20.82	74.00	47.65	35.23	4.68	34.38	Peak
3	7386.000	50.44	-3.56	54.00	42.12	36.96	5.65	34.29	Average
4	7386.000	61.71	-12.29	74.00	53.39	36.96	5.65	34.29	Peak
5	9848.000	56.75			46.10	38.81	6.38	34.54	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Jan. 13, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configuration	802.11g Ch. 1

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4824.000	37.05	-16.95	54.00	31.22	35.76	4.58	34.51	Average
2	4824.000	51.07	-22.93	74.00	45.24	35.76	4.58	34.51	Peak
3	7236.000	65.78			56.59	37.85	5.63	34.29	Peak
4	9648.000	54.92			43.82	39.39	6.34	34.63	Peak

Note: The items 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4824.000	38.67	-15.33	54.00	33.47	35.13	4.58	34.51	Average
2	4824.000	52.73	-21.27	74.00	47.53	35.13	4.58	34.51	Peak
3	7236.000	67.77			59.53	36.90	5.63	34.29	Peak
4	9648.000	55.04			44.74	38.59	6.34	34.63	Peak

Note: The items 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Jan. 13, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configuration	802.11g Ch. 6

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4874.000	36.78	-17.22	54.00	30.79	35.83	4.61	34.45	Average
2	4874.000	51.14	-22.86	74.00	45.15	35.83	4.61	34.45	Peak
3	7311.000	52.38	-1.62	54.00	43.17	37.86	5.64	34.29	Average
4	7311.000	67.83	-6.17	74.00	58.62	37.86	5.64	34.29	Peak
5	9748.000	54.97			43.68	39.51	6.36	34.58	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Preamp Loss Factor	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4874.000	38.14	-15.86	54.00	32.80	35.18	4.61	34.45 Average
2	4874.000	51.59	-22.41	74.00	46.25	35.18	4.61	34.45 Peak
3	7311.000	52.27	-1.73	54.00	44.00	36.92	5.64	34.29 Average
4	7311.000	68.22	-5.78	74.00	59.95	36.92	5.64	34.29 Peak
5	9748.000	55.15			44.66	38.71	6.36	34.58 Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Jan. 13, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configuration	802.11g Ch. 11


Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4924.000	50.32	-3.68	54.00	44.12	35.90	4.68	34.38	PK
2	7386.000	43.28	-10.72	54.00	34.04	37.88	5.65	34.29	Average
3	7386.000	59.43	-14.57	74.00	50.19	37.88	5.65	34.29	Peak
4	9848.000	55.97			44.52	39.61	6.38	34.54	Peak

Note: The item 4 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4924.000	50.36	-3.64	54.00	44.83	35.23	4.68	34.38	PK
2	7386.000	44.30	-9.70	54.00	35.98	36.96	5.65	34.29	Average
3	7386.000	61.02	-12.98	74.00	52.70	36.96	5.65	34.29	Peak
4	9848.000	55.89			45.24	38.81	6.38	34.54	Peak

Note: The item 4 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.6 Band Edge and Fundamental Emissions Measurement

3.6.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.6.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak

3.6.3 Test Procedures

1. The test procedure is the same as section 3.5.3; only the frequency range investigated is limited to 100MHz around band edges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

3.6.4 Test Setup Layout

This test setup layout is the same as that shown in section 3.5.4.

3.6.5 Test Deviation

There is no deviation with the original standard.

3.6.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.6.7 Test Result of Band Edge and Fundamental Emissions

Final Test Date	Jan. 14, 2011	Test Site No.	03CH02-HY
Temperature	21.5℃	Humidity	55%
Test Engineer	Daniel	Configuration	802.11a Ch. 149, 157, 165

Channel 149

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	5725.000	74.22			32.21	36.97	5.04	0.00	Average
2 @	5740.020	113.97			71.91	36.99	5.07	0.00	Average
1 @	5725.000	91.84			49.83	36.97	5.04	0.00	Peak
2 @	5738.900	124.29			82.23	36.99	5.07	0.00	Peak

The item 2 is fundamental emissions and the item 1 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Channel 157

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	5717.340	63.56			21.57	36.95	5.04	0.00	Average
2 @	5780.070	116.70			74.58	37.03	5.09	0.00	Average
3 @	5852.150	61.32			19.10	37.11	5.11	0.00	Average
1 @	5701.190	76.90			34.91	36.95	5.04	0.00	Peak
2 @	5780.750	127.19			85.07	37.03	5.09	0.00	Peak
3 @	5850.790	74.43			32.21	37.11	5.11	0.00	Peak

The item 2 is fundamental emissions and the items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Channel 165

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	5823.750	115.81			73.61	37.09	5.11	0.00	Average
2 @	5850.000	69.04			26.82	37.11	5.11	0.00	Average
1 @	5822.150	126.38			84.18	37.09	5.11	0.00	Peak
2 @	5850.150	86.92			44.70	37.11	5.11	0.00	Peak

The item 1 is fundamental emissions and the item 2 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	Jan. 13, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configuration	802.11b Ch. 1, 6, 11

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	2390.000	52.87	-1.13	54.00	17.82	32.03	3.02	0.00	Average
2 @	2413.930	110.18			75.07	32.09	3.02	0.00	Average
1 @	2388.850	65.31	-8.69	74.00	30.26	32.03	3.02	0.00	Peak
2 @	2412.980	118.45			83.34	32.09	3.02	0.00	Peak

The item 2 is fundamental emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	2439.010	108.31			73.05	32.21	3.05	0.00	Average
1 @	2438.060	116.54			81.28	32.21	3.05	0.00	Peak

The item 1 is fundamental emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	2464.090	108.87			73.51	32.28	3.08	0.00	Average
2 @	2483.500	52.39	-1.61	54.00	16.97	32.34	3.08	0.00	Average
1 @	2463.140	116.97			81.61	32.28	3.08	0.00	Peak
2 @	2483.500	64.65	-9.35	74.00	29.23	32.34	3.08	0.00	Peak

The item 1 is fundamental emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	Jan. 13, 2011	Test Site No.	03CH02-HY
Temperature	21.5°C	Humidity	55%
Test Engineer	Daniel	Configuration	802.11g Ch. 1, 6, 11

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	2359.780	52.12	-1.88	54.00	17.23	31.90	2.99	0.00	Average
2 @	2415.260	103.65			68.54	32.09	3.02	0.00	Average
1 @	2390.000	67.91	-6.09	74.00	32.86	32.03	3.02	0.00	Peak
2 @	2413.740	114.46			79.35	32.09	3.02	0.00	Peak

The item 2 is fundamental emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	2439.580	106.26			71.00	32.21	3.05	0.00	Average
1 @	2439.010	116.60			81.34	32.21	3.05	0.00	Peak

The item 1 is fundamental emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 @	2465.420	102.48			67.12	32.28	3.08	0.00	Average
2 @	2483.500	52.89	-1.11	54.00	17.47	32.34	3.08	0.00	Average
1 @	2463.900	113.30			77.94	32.28	3.08	0.00	Peak
2 @	2483.500	68.96	-5.04	74.00	33.54	32.34	3.08	0.00	Peak

The item 1 is fundamental emissions.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


Final Test Date	Jan. 28, 2011	Test Site No.	TH01-HY
Temperature	20°C	Humidity	60%
Test Engineer	Ian	Configurations	802.11a/b/g

Low Band Edge Plot on Configuration IEEE 802.11a / 5745 MHz




Date: 28.JAN.2011 20:08:25

High Band Edge Plot on Configuration IEEE 802.11a / 5825 MHz




Date: 28.JAN.2011 20:14:11

Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 28.JAN.2011 17:13:29

High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 28.JAN.2011 17:23:08

Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 28.JAN.2011 17:49:09

High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 28.JAN.2011 17:54:16

3.7 Antenna Requirements

3.7.1 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

3.7.2 Antenna Connector Construction

Please refer to section 2.4 in this test report; antenna connector complied with the requirements.

4 LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100132	9kHz – 2.75GHz	Sep. 14, 2010	Conduction (CO01-HY)
LISN	MessTec	NNB-2/16Z	2001/004	9kHz – 30MHz	Jan. 31, 2011	Conduction (CO01-HY)
LISN (Support Unit)	MessTec	NNB-2/16Z	2001/009	9kHz – 30MHz	Mar. 01, 2011	Conduction (CO01-HY)
EMI Filter	LINDGREN	LRE-2060	1004	< 450Hz	N/A	Conduction (CO01-HY)
EMI Filter	LINDGREN	N6006	201052	0 – 60Hz	N/A	Conduction (CO01-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832010001	9kHz – 30MHz	Mar. 02, 2011	Conduction (CO01-HY)
Isolation Transformer	Erika Fiedler OHG	D-65396 Walluf	58	45MHz-2.15GHz	N/A	Conduction (CO01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSU26.5	100015	20Hz ~ 26.5GHz	Nov. 19, 2010	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Oct. 22, 2010	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 02, 2010	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 02, 2010	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 30, 2010	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	0917017	300MHz~40GHz	Dec. 03, 2010	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	0949003	300MHz~40GHz	Dec. 03, 2010	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jul. 26, 2010*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100004	9 kHz - 40 GHz	Nov. 17, 2010	Radiation (03CH02-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30 MHz - 1 GHz 3m	May 01, 2010	Radiation (03CH02-HY)
Amplifier	Agilent	8447D	2944A11146	100 kHz – 1.3 GHz	Jul. 23, 2010	Radiation (03CH02-HY)
Amplifier	Agilent	8449B	3008A02373	1GHz – 26.5 GHz	Jul. 23, 2010	Radiation (03CH02-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1GHz~18GHz	Nov. 11, 2010	Radiation (03CH02-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz ~ 1GHz	Feb. 26, 2010	Radiation (03CH02-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX106	03CH02-HY	1GHz~40GHz	Feb. 26, 2010	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30 MHz - 2 GHz	Oct. 16, 2010	Radiation (03CH02-HY)
Turn Table	HD	DS 420	420/649/00	0 - 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	HD	MA 240	240/559/00	1 m - 4 m	N/A	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 29, 2010*	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is two year.

5 TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6 TAF CERTIFICATE OF ACCREDITATION


財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate No. : L1190-110111

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities


Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 11, 2011

P1, total 24 pages