

1 Human Exposure Assessment

1.1 Maximum Permissible Exposure

1.1.1 Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30
Note 1: f = frequency in MHz ; *Plane-wave equivalent power density				
Note 2: For the applicable limit, see FCC 1.1310				

RF Field Strength Limits for Controlled Use Devices (Controlled Environment)				
Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Averaging Time (minutes)
0.003-1	600	4.9	-	6
1-10	600/ <i>f</i>	4.9/ <i>f</i>	-	6
10-30	60	4.9/ <i>f</i>	-	6
30-300	60	0.163	10*	6
300-1500	3.54 <i>f</i> 0.5	0.0094 <i>f</i> 0.5	<i>f</i> /30	6
1500-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ <i>f</i> 1.2
150000-300000	0.354 <i>f</i> 0.5	9.4 x 10 ⁻⁴ <i>f</i> 0.5	3.33 x 10 ⁻⁴ <i>f</i>	616000/ <i>f</i> 1.2
RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Averaging Time (minutes)
0.003-1	280	2.19	-	6
1-10	280/ <i>f</i>	2.19/ <i>f</i>	-	6
10-30	28	2.19/ <i>f</i>	-	6
30-300	28	0.073	2*	6
300-1500	1.585 <i>f</i> ^{0.5}	0.0042 <i>f</i> ^{0.5}	<i>f</i> /150	6
1500-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> ^{1.2}
150000-300000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616000/ <i>f</i> ^{1.2}
Note 1: <i>f</i> is frequency in MHz.				
Note 2: For the applicable limit, see IC RSS-102				

1.1.2 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

E = Electric field (V/m)

G = EUT Antenna numeric gain (numeric)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

P = RF output power (W)

d = Separation distance between radiator and human body (m)



1.1.3 Result of Maximum Permissible Exposure (2.4G)

Transmitter Chains & Receiver Chains Information					
IEEE Std. 802.11 Protocol	Number of Transmit Chains (N _{TX})	Number of Receive Chains (N _{RX})	Correlation Signals with Multiple N _{TX}	RF Output Power (dBm)	Co-location
b	1	1	Correlated	25.38	Yes
g	1	1	Correlated	24.90	Yes
n (HT20)	2	1	Uncorrelated	25.57	Yes
n (HT40)	2	1	Uncorrelated	23.95	Yes

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.

Worst Maximum RF Output Power Result							
Exposure Environment		General Population / Uncontrolled Exposure					
Separation Distance (cm)		20					
Power Level	1	RF Output Power (dBm)					
Modulation Mode	N _{TX}	Chain-Port 1	Chain-Port 2	Sum Chain	Gain (dBi)	EIRP Power	PD (S) (mW/cm ²)
b	1	25.38	-	25.38	2.82	28.20	0.13144
g	1	24.90	-	24.90	2.82	27.72	0.11769
n (HT20)	2	23.94	20.54	25.57	2.64	28.22	0.13200
n (HT40)	2	22.68	18.00	23.95	2.64	26.60	0.09085
Maximum Permissible Exposure Limit (mW/cm ²)							1

Note 1: N_{TX} = Number of Transmit Chains



1.1.4 Result of Maximum Permissible Exposure (5.8G)

Transmitter Chains & Receiver Chains Information					
IEEE Std. 802.11 Protocol	Number of Transmit Chains (N _{TX})	Number of Receive Chains (N _{RX})	Correlation Signals with Multiple N _{TX}	RF Output Power (dBm)	Co-location
a	1	1	Correlated	22.35	Yes
n(HT20)	2	1	Uncorrelated	26.45	Yes
n(HT40)	2	1	Uncorrelated	24.86	Yes
ac(VHT20)	2	1	Uncorrelated	25.05	Yes
ac(VHT40)	2	1	Uncorrelated	25.01	Yes
ac(VHT80)	2	1	Uncorrelated	22.55	Yes
Note 1: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other. (i.e., EUT has simultaneously co-transmitting that operating 2.4GHz and 5GHz.) Note 2: RF output power specifies that Maximum Conducted (Average) Output Power.					

Worst Maximum RF Output Power Result						
Exposure Environment		General Population / Uncontrolled Exposure				
Separation Distance (cm)		20				
Power Level	1	RF Output Power (dBm)				
Modulation Mode	N _{TX}	Chain-Port 1	Chain-Port 2	Sum Chain	Gain (dBi)	PD (S) (mW/cm ²)
a	1	22.35	-	22.35	4.00	0.08585
n(HT20)	2	22.17	24.42	26.45	3.73	0.20751
n(HT40)	2	22.82	20.61	24.86	3.73	0.14406
ac(VHT20)	2	22.83	21.08	25.05	3.73	0.15045
ac(VHT40)	2	22.79	21.04	25.01	3.73	0.14907
ac(VHT80)	2	20.51	18.29	22.55	3.73	0.08456
Maximum Permissible Exposure Limit (mW/cm ²)						1
Note 1: N _{TX} = Number of Transmit Chains						

1.1.5 Result of Maximum Permissible Exposure(5.2G)

Transmitter Chains & Receiver Chains Information					
IEEE Std. 802.11 Protocol	Number of Transmit Chains (N _{TX})	Number of Receive Chains (N _{RX})	Correlation Signals with Multiple N _{TX}	RF Output Power (dBm)	Co-location
a	1	1	Correlated	19.95	Yes
n(HT20)	2	1	Uncorrelated	21.71	Yes
n(HT40)	2	1	Uncorrelated	21.30	Yes
ac(VHT20)	2	1	Uncorrelated	20.52	Yes
ac(VHT40)	2	1	Uncorrelated	20.69	Yes
ac(VHT80)	2	1	Uncorrelated	19.89	Yes
Note 1: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other. (i.e., EUT has simultaneously co-transmitting that operating 2.4GHz and 5GHz.) Note 2: RF output power specifies that Maximum Conducted (Average) Output Power.					

Worst Maximum RF Output Power Result							
Exposure Environment		General Population / Uncontrolled Exposure					
Separation Distance (cm)		20					
Power Level	1	RF Output Power (dBm)					
Modulation Mode	N _{TX}	Chain-Port 1	Chain-Port 2	Sum Chain	Gain (dBi)	EIRP Power	PD (S) (mW/cm ²)
a	1	19.95	-	19.95	4.00	23.95	0.08585
n(HT20)	2	17.44	19.68	21.71	3.73	25.45	0.20751
n(HT40)	2	19.12	17.28	21.30	3.73	25.03	0.15045
ac(VHT20)	2	18.37	16.52	20.52	3.73	24.26	0.14406
ac(VHT40)	2	18.29	16.97	20.69	3.73	24.42	0.14907
ac(VHT80)	2	17.81	15.68	19.89	3.73	23.63	0.08456
Maximum Permissible Exposure Limit (mW/cm ²)							1
Note 1: N _{TX} = Number of Transmit Chains							



Worst Maximum RF Output Power Result							
Exposure Environment		General Population / Uncontrolled Exposure					
Separation Distance (cm)		20					
Condition		RF Output Power (dBm)					
Modulation Mode	N _{TX}	Chain-Port 1	Chain-Port 2	Sum Chain	DG (dBi)	EIRP Power	PD (S) (mW/cm ²)
2.4 GHz	2	23.94	20.54	25.57	2.64	28.22	0.13200
5 GHz	2	22.17	24.42	26.45	3.73	30.18	0.20751
Co-location Total							0.33951
Maximum Permissible Exposure Limit (mW/cm ²)							1
Note 1: N _{TX} = Number of Transmit Chains							