

1.2. Operational Description

The EUT is a Wireless LAN USB Module with 11 channels. This device provided four kinds of transmitting speed 1, 2, 5.5 and 11Mbps and the device of RF carrier is DBPSK, DQPSK and CCK (IEEE 802.11b). The device provided of eight kinds of transmitting speed 6, 9, 12, 18, 24, 36, 48 and 54Mbps the device of RF carrier is BPSK, QPSK, 16QAM and 64QAM (IEEE 802.11g).

The device provided of eight kinds of transmitting speed 14.4、28.8、43.4、57.8、86.6、115.6、130 and 144.4Mbps in 802.11n(20M-BW) mode and 30、60、90、120、180、240、270 and 300 Mbps(40M-BW) the device of RF carrier is BPSK, QPSK, 16QAM and 64QAM (IEEE 802.11n), The IEEE 802.11n is Multiple In Multiple out (MIMO) Technology, and three antennas to support 2(Transmit) * 2(Receive) MIMO technology.

The device adapts direct sequence spread spectrum modulation. The antenna provides diversity function to improve the receiving function.

This Wireless LAN USB Module, compliant with IEEE 802.11b and IEEE 802.11g/n, is a high-efficiency Wireless LAN adapter. It allows your computer to connect to a wireless network and to share resources, such as files or printers without being bound to the network wires. Operation in 2.4GHz Direct Sequence Spread Spectrum (DSSS) and Orthogonal Frequency Division Multiplexing (OFDM) radio transmission, the Wireless LAN USB Module Wired Equivalent Protection (WEP) algorithm is used. In addition, its standard compliance ensures that it can communicate with any IEEE 802.11b and IEEE 802.11g/n network.