

FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment	: Wireless-N USB Adapter
Model No.	: EW-7718Un /GWA-H18n V1.0
Brand Name	: EDIMAX
Filing Type	: New Application
Applicant	: EDIMAX TECHNOLOGY CO., LTD. No.3, Wu Chuan 3rd Road, Wu-Ku Industrial Park, Taipei Hsien, Taiwan
FCC ID	: NDD9577180703
Manufacturer	: EDIMAX TECHNOLOGY CO., LTD. No.3, Wu Chuan 3rd Road, Wu-Ku Industrial Park, Taipei Hsien, Taiwan
Received Date	: Apr. 06, 2007
Test Date	: May 15, 2007
Multiple Listing	: Please refer to section 2.7

Statement

Test result included is only for the 802.11n part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Lab Code: 200079-0

SPORTON International Inc.

6F, No. 106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

Table of Contents

1. SUMMARY OF THE TEST RESULT	2
2. GENERAL INFORMATION.....	3
2.1. Product Details.....	3
2.2. Accessories.....	4
2.3. Table for Filed Antenna	5
2.4. Table for Carrier Frequencies.....	5
2.5. Table for Test Modes	6
2.6. Table for Testing Locations	6
2.7. Table for Multiple Listing	7
2.8. Table for Supporting Units.....	7
2.9. Table for Parameters of Test Software Setting	8
2.10. Test Configurations	9
3. TEST RESULT	11
3.1. AC Power Line Conducted Emissions Measurement.....	11
3.2. Maximum Peak Output Power Measurement	15
3.3. Power Spectral Density Measurement.....	17
3.4. 6dB Spectrum Bandwidth Measurement	22
3.5. Radiated Emissions Measurement	27
3.6. Band Edge Emissions Measurement.....	45
3.7. Antenna Requirements.....	50
4. LIST OF MEASURING EQUIPMENTS	51
5. TEST LOCATION.....	52
6. NVLAP CERTIFICATE OF ACCREDITATION	53
APPENDIX A. TEST PHOTOS	A1 ~ A6
APPENDIX B. PHOTOGRAPHS OF EUT	B1 ~ B7
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~ C3

History of This Test Report

Original Issue Date: May 16, 2007

Report No.: FR733004-n

☒ No additional attachment.

☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description


CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : Wireless-N USB Adapter
Model No. : EW-7718Un /GWA-H18n V1.0
Brand Name : EDIMAX
Applicant : **EDIMAX TECHNOLOGY CO., LTD.**
No.3, Wu Chuan 3rd Road, Wu-Ku Industrial Park, Taipei
Hsien, Taiwan

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Apr. 06, 2007 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.


Wayne Hsu

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

SPORTON International Inc.

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255

Page No. : 1 of 53

Issued Date : May 16, 2007

FCC ID : NDD9577180703

6F, No.106, Sec.1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C. TEL:886-2-26962468 FAX:886-2-26962255

1. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	18.70 dB
3.2	15.247(b)(3)	Maximum Peak Conducted Output Power	Complies	14.15 dB
3.3	15.247(e)	Power Spectral Density	Complies	27.33 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	3.68 dB
3.6	15.247(d)	Band Edge Emissions	Complies	1.67 dB
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2. GENERAL INFORMATION

2.1. Product Details

Items	Description
Power Type	Power from host
Modulation	DSSS for IEEE 802.11b ; OFDM for draft 802.11g see the below table for draft 802.11n
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	IEEE 802.11b (1/ 2/ 5.5/11) IEEE 802.11g (6/9/12/18/24/36/48/54) see the below table for draft 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Bandwidth (99%)	MCS15 (20MHz) : 17.60 MHz MCS15 (40MHz) : 36.20 MHz
Conducted Output Power	MCS15: 13.82 dBm (20MHz); MCS15: 15.85 dBm (40MHz)

Antenna & Bandwidth

Antenna	Single(Tx)		Two(Tx)		Two (RX Only)	
Bandwidth Mode	20 MHz	40 MHz	20 MHz	40 MHz	20 MHz	40 MHz
802.11b	V	X	X	X	X	X
802.11g	V	X	X	X	V	V
802.11n	X	X	V	V	V	V

IEEE 802.11n spec

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Datarate(Mbps)			
									800nsGI		400nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

2.2. Accessories

N/A

2.3. Table for Filed Antenna

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
1	Chip Antenna	NA	2.13	Internal
2	Chip Antenna	NA	2.13	Internal

2.4. Table for Carrier Frequencies

There are two bandwidth systems for draft 802.11n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

For draft 802.11n, the two TX Ant. 1 & Ant. 2 could transmit simultaneously.

2.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Channel	Antenna
AC Power Line Conducted Emissions	Normal Mode	-	1+2
Maximum Peak Conducted Output Power	MCS15/20MHz	1/6/11	1+2
Power Spectral Density	MCS15/40MHz	3/6/9	1+2
6dB Spectrum Bandwidth			
Radiated Emissions 9kHz~1GHz	MCS15/40MHz	6	1+2
Radiated Emissions 1GHz~10 th Harmonic	MCS15/20MHz	1/6/11	1+2
	MCS15/40MHz	3/6/9	1+2
Band Edge Emissions	MCS15/20MHz	1/6/11	1+2
	MCS15/40MHz	3/6/9	1+2

2.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

2.7. Table for Multiple Listing

The brand/model names in the following table are all refer to the identical product.

NO.	Brand Name	Model Name
1	Edimax	EW-7718Un, GWU-H18n
2	PCI	GW-US300MiniW
3	Air Live	MU5000USB
4	Sitecom	WL-182v1
5	MINITAR	MWNU
6	Topcom	Skyr@cer USB 4201n
7	JAHT	WN-7300NU
8	Planet	WNL-U552
9	MSI	US70SE

2.8. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D505	DoC
Printer	EPSON	C680	DoC
Modem	ACEEX	DM1414	IFAXDM1414

2.9. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2

Test Software Version	Ralink QA For 2870		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n	07 02	0A 05	09 05

Power Parameters of IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2

Test Software Version	Ralink QA For 2870		
Frequency	2422 MHz	2437 MHz	2452 MHz
IEEE 802.11n	06 01	0A 05	06 03

The NB sends “ H “ messages to the panel, and the panel displays “ H “ patterns on the screen.


The NB sends “ H “ messages to the printer, then the printer prints them on the paper.

The NB sends “ H “ messages to the modem.


2.10. Test Configurations

2.10.1. Radiation Emissions Test Configuration

Below 1GHz



Above 1GHz



3. TEST RESULT

3.1. AC Power Line Conducted Emissions Measurement

3.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

3.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

3.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5. Test Deviation


There is no deviation with the original standard.

3.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


3.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	28	Humidity	35%
Test Engineer	Ted	Phase	Line
Configuration	Normal Mode		



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.1936010	41.45	-22.43	63.88	41.21	0.10	0.14	QP
2	0.1936010	18.04	-35.84	53.88	17.80	0.10	0.14	Average
3	0.2139240	41.25	-21.80	63.05	40.95	0.10	0.20	QP
4	0.2139240	21.80	-31.25	53.05	21.50	0.10	0.20	Average
5	0.2758730	30.18	-30.76	60.94	29.67	0.10	0.41	QP
6	0.2758730	10.72	-40.22	50.94	10.21	0.10	0.41	Average
7	1.735	31.08	-24.92	56.00	30.55	0.10	0.43	QP
8	1.735	19.83	-26.17	46.00	19.30	0.10	0.43	Average
9	2.080	31.45	-24.55	56.00	30.93	0.10	0.42	QP
10	2.080	20.63	-25.37	46.00	20.11	0.10	0.42	Average
11	10.130	29.85	-30.15	60.00	29.42	0.21	0.22	QP
12	10.130	24.11	-25.89	50.00	23.68	0.21	0.22	Average

Temperature	28	Humidity	35%
Test Engineer	Ted	Phase	Neutral
Configuration	Normal Mode		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1840720	19.91	-34.39	54.30	19.67	0.10	0.14	Average
2	0.1840720	44.31	-19.99	64.30	44.07	0.10	0.14	QP
3	0.2234870	26.02	-26.67	52.69	25.68	0.10	0.24	Average
4	0.2234870	43.99	-18.70	62.69	43.65	0.10	0.24	QP
5	0.2758730	29.92	-31.02	60.94	29.41	0.10	0.41	QP
6	0.2758730	11.51	-39.43	50.94	11.00	0.10	0.41	Average
7	0.3334210	31.91	-27.46	59.37	31.24	0.10	0.57	QP
8	0.3334210	21.81	-27.56	49.37	21.14	0.10	0.57	Average
9	1.690	31.41	-24.59	56.00	30.88	0.10	0.43	QP
10	1.690	18.85	-27.15	46.00	18.32	0.10	0.43	Average
11	10.070	25.17	-24.83	50.00	24.65	0.30	0.22	Average
12	10.070	30.79	-29.21	60.00	30.27	0.30	0.22	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

3.2. Maximum Peak Output Power Measurement

3.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	NRV-Z32 (model 04)

3.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

3.2.4. Test Setup Layout



3.2.5. Test Deviation

There is no deviation with the original standard.

3.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.2.7. Test Result of Maximum Peak Output Power Measurement

Temperature	28	Humidity	58%
Test Engineer	Murphy	Configurations	802.11n

Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	12.25	30.00	Complies
6	2437 MHz	13.75	30.00	Complies
11	2462 MHz	13.82	30.00	Complies

Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	13.75	30.00	Complies
6	2437 MHz	15.85	30.00	Complies
9	2452 MHz	13.78	30.00	Complies

3.3. Power Spectral Density Measurement

3.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.3.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

3.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

3.3.4. Test Setup Layout



3.3.5. Test Deviation

There is no deviation with the original standard.

3.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.3.7. Test Result of Power Spectral Density Measurement

Temperature	28	Humidity	58%
Test Engineer	Murphy	Configurations	802.11n


Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-21.34	8.00	Complies
6	2437 MHz	-19.33	8.00	Complies
11	2462 MHz	-19.78	8.00	Complies

Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-20.00	8.00	Complies
6	2437 MHz	-21.55	8.00	Complies
9	2452 MHz	-23.31	8.00	Complies

Power Density Plot on Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2 / 2412 MHz




Date: 15.MAY.2007 10:00:45

Power Density Plot on Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2 / 2437 MHz




Date: 15.MAY.2007 10:08:48

Power Density Plot on Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2 / 2462 MHz




Date: 15.MAY.2007 10:21:10

Power Density Plot on Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2 / 2422 MHz




Date: 15.MAY.2007 09:12:31

Power Density Plot on Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2 / 2437 MHz



Date: 15.MAY.2007 09:21:18

Power Density Plot on Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2 / 2452 MHz



Date: 15.MAY.2007 09:25:24

3.4. 6dB Spectrum Bandwidth Measurement

3.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

3.4.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

3.4.4. Test Setup Layout



3.4.5. Test Deviation

There is no deviation with the original standard.

3.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.4.7. Test Result of 6dB Spectrum Bandwidth Measurement

Temperature	28	Humidity	58%
Test Engineer	Murphy	Configurations	802.11n


Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.04	17.60	500	Complies
6	2437 MHz	17.28	17.60	500	Complies
11	2462 MHz	17.32	17.60	500	Complies

Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	35.40	36.10	500	Complies
6	2437 MHz	34.00	36.20	500	Complies
9	2452 MHz	34.00	36.20	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2 / 2412 MHz




Date: 15.MAY.2007 09:56:01

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2 / 2437 MHz




Date: 15.MAY.2007 10:12:35

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2 / 2462 MHz




Date: 15.MAY.2007 10:17:07

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2 / 2422 MHz




Date: 15.MAY.2007 09:06:36

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2 / 2437 MHz



Date: 15.MAY.2007 09:18:44

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2 / 2452 MHz



Date: 15.MAY.2007 09:28:22

3.5. Radiated Emissions Measurement

3.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1000KHz / 1000KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.5.5. Test Deviation

There is no deviation with the original standard.

3.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	25	Humidity	50%
Test Engineer	Vic		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15/40MHz Ch 6 (Ant.1 +Ant.2)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	36.790	32.84	-7.16	40.00	43.64	14.35	2.56	27.71	Peak	---	---
2	109.540	37.06	-6.44	43.50	49.74	12.40	2.72	27.80	Peak	---	---
3	215.270	35.27	-8.23	43.50	50.78	9.27	3.43	28.21	QP	---	---
4 @	272.500	42.32	-3.68	46.00	53.40	13.40	3.83	28.31	QP	---	---
5	397.630	40.91	-5.09	46.00	49.28	16.38	4.29	29.04	Peak	---	---
6	532.460	37.64	-8.36	46.00	43.64	18.88	4.52	29.40	Peak	---	---

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	55.220	30.44	-9.56	40.00	49.26	7.19	1.74	27.75	Peak	---	---
2	109.540	30.56	-12.94	43.50	43.24	12.40	2.72	27.80	Peak	---	---
3	198.780	28.36	-15.14	43.50	43.31	9.61	3.54	28.09	Peak	---	---
4	454.860	36.02	-9.98	46.00	43.81	17.20	4.40	29.39	Peak	---	---
5	498.510	34.38	-11.62	46.00	40.96	18.09	4.43	29.10	Peak	---	---
6	665.350	41.54	-4.46	46.00	46.33	19.73	5.28	29.80	Peak	---	---

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Pol. : V is Vertical Polarization ; H is Horizontal Polarization.

3.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 20MHz Ch 1 Ant. 1 + Ant. 2

Horizontal




	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp			Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	46.78	-27.22	74.00	41.87	32.89	4.35	32.32	PEAK	---	---
2	7236.000	50.35			41.96	35.78	5.18	32.57	PEAK	---	---
3	9648.000	54.21			42.61	37.92	6.48	32.80	PEAK	---	---

Note:

Items 2 and 3 are on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 20MHz Ch 1 Ant. 1 + Ant. 2

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	49.16	-24.84	74.00	44.24	32.89	4.35	32.32	PEAK	---	---
2	7236.000	50.71			42.31	35.78	5.18	32.57	PEAK	---	---
3	9648.000	53.80			42.20	37.92	6.48	32.80	PEAK	---	---

Note:

Items 2 and 3 are on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 20MHz Ch 6 Ant. 1 + Ant. 2


Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4876.000	49.78	-24.22	74.00	44.73	32.98	4.36	32.30	PEAK	---	---
2	7303.000	52.00	-22.00	74.00	43.35	35.94	5.30	32.59	PEAK	---	---
3 @	7303.000	41.89	-12.11	54.00	33.24	35.94	5.30	32.59	Average	---	---
4	9752.000	53.38			41.59	38.01	6.58	32.80	PEAK	---	---

Note:

Item 4 is on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 20MHz Ch 6 Ant. 1 + Ant. 2


Vertical

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp			Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4876.000	54.12	-19.88	74.00	49.08	32.98	4.36	32.30	PEAK	---	---
2	4876.000	42.08	-11.92	54.00	37.03	32.98	4.36	32.30	Average	---	---
3	7308.000	54.21	-19.79	74.00	45.56	35.94	5.30	32.59	PEAK	---	---
4	7308.000	41.53	-12.47	54.00	32.88	35.94	5.30	32.59	Average	---	---
5	9752.000	53.65			41.86	38.01	6.58	32.80	PEAK	---	---

Note:

Item 5 is on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 20MHz Ch 11 Ant. 1 + Ant. 2


Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4932.000	56.42	-17.58	74.00	51.22	33.08	4.40	32.28	PEAK	---	---
2	4932.000	43.57	-10.43	54.00	38.37	33.08	4.40	32.28	Average	---	---
3	7384.000	58.49	-15.51	74.00	49.56	36.15	5.41	32.63	PEAK	---	---
4	7384.000	45.42	-8.58	54.00	36.49	36.15	5.41	32.63	Average	---	---
5	9848.000	53.75			41.73	38.08	6.74	32.79	PEAK	---	---

Note:

Item 5 is on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 20MHz Ch 11 Ant. 1 + Ant. 2


Vertical

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4936.000	62.00	-12.00	74.00	56.78	33.11	4.40	32.28	PEAK	---	---
2	4936.000	48.68	-5.32	54.00	43.45	33.11	4.40	32.28	Average	---	---
3	7380.000	57.78	-16.22	74.00	48.89	36.11	5.41	32.63	PEAK	---	---
4	7380.000	44.65	-9.35	54.00	35.76	36.11	5.41	32.63	Average	---	---
5	9848.000	53.66			41.63	38.08	6.74	32.79	PEAK	---	---

Note:

Item 5 is on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 40MHz Ch 3 Ant. 1 + Ant. 2

Horizontal


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4840.000	46.72	-27.28	74.00	41.77	32.92	4.35	32.31	PEAK	---	---
2	7270.000	50.38	-23.62	74.00	41.85	35.86	5.24	32.58	PEAK	---	---
3	9688.000	54.03			42.34	37.95	6.53	32.80	PEAK	---	---

Note:

Item 3 is on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 40MHz Ch 3 Ant. 1 + Ant. 2

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4848.000	49.62	-24.38	74.00	44.65	32.92	4.36	32.31	PEAK	---
2	7262.000	50.37	-23.63	74.00	41.89	35.82	5.24	32.58	PEAK	---
3	9688.000	53.99			42.31	37.95	6.53	32.80	PEAK	---

Note:

Item 3 is on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 40MHz Ch 6 Ant. 1 + Ant. 2


Horizontal

	Freq	Level	Over Limit	Limit	ReadAntenna	Cable	Preamp		Ant	Table
	MHz	dBuV/m	dB	dBuV/m	Level	Loss	Factor	Remark	Pos	Pos
					dBuV	dB/m	dB	dB	cm	deg
1	4880.000	49.27	-24.73	74.00	44.22	32.98	4.36	32.30 PEAK	---	---
2	7307.000	50.40	-23.60	74.00	41.75	35.94	5.30	32.59 PEAK	---	---
3	9752.000	53.52			41.73	38.01	6.58	32.80 PEAK	---	---

Note:

Item 3 is on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 40MHz Ch 6 Ant. 1 + Ant. 2


Vertical

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp			Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4880.000	52.52	-21.48	74.00	47.48	32.98	4.36	32.30	PEAK	---	---
2	4880.000	41.69	-32.31	74.00	36.64	32.98	4.36	32.30	PEAK	---	---
3	7312.000	52.97	-21.03	74.00	44.34	35.94	5.30	32.61	PEAK	---	---
4	7312.000	40.87	-13.13	54.00	32.23	35.94	5.30	32.61	Average	---	---
5	9748.000	53.71	---	---	41.91	38.01	6.58	32.80	PEAK	---	---

Note:

Item 5 is on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 40MHz Ch 9 Ant. 1 + Ant. 2


Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4908.000	49.22	-24.78	74.00	44.08	33.04	4.38	32.29	PEAK	---	---
2	7360.000	50.39	-23.61	74.00	41.58	36.07	5.36	32.62	PEAK	---	---
3	9808.000	53.45			41.51	38.05	6.69	32.79	PEAK	---	---

Note:

Item 3 is on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 40MHz Ch 9 Ant. 1 + Ant. 2

Vertical

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4908.000	53.49	-20.51	74.00	48.35	33.04	4.38	32.29	PEAK	---	---
2	4908.000	41.81	-12.19	54.00	36.67	33.04	4.38	32.29	Average	---	---
3	7356.000	50.57	-23.43	74.00	41.76	36.07	5.36	32.62	PEAK	---	---
4	9812.000	53.83			41.89	38.05	6.69	32.79	PEAK	---	---

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Item 4 is on un-restricted band, so the limit is -20dBc for the field strength of the fundamental emissions (see section 3.6.7.)

3.6. Band Edge Emissions Measurement

3.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.6.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

3.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

3.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

3.6.5. Test Deviation

There is no deviation with the original standard.

3.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 20MHz Ch 1 /Ch6 /Ch11 Ant. 1 + Ant. 2

Channel 1 is fundamental frequency at 2412 MHz.

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2390.000	67.95	-6.05	74.00	37.05	28.07	2.82	0.00	Peak	---	---
2 @	2404.810	109.69			78.76	28.11	2.82	0.00	Peak	---	---
1 @	2390.000	51.94	-2.06	54.00	21.04	28.07	2.82	0.00	Average	---	---
2 @	2404.620	100.33			69.40	28.11	2.82	0.00	Average	---	---

Channel 6 is fundamental frequency at 2437 MHz.

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2429.890	109.91			78.92	28.15	2.85	0.00	Peak	---	---
1 @	2429.890	100.51			69.52	28.15	2.85	0.00	Average	---	---

Channel 11 is fundamental frequency at 2462 MHz.

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2454.210	109.39			78.32	28.22	2.85	0.00	Peak	---	---
2	2483.850	69.65	-4.35	74.00	38.51	28.26	2.87	0.00	Peak	---	---
1 @	2454.780	100.13			69.06	28.22	2.85	0.00	Average	---	---
2 @	2483.500	52.33	-1.67	54.00	21.19	28.26	2.87	0.00	Average	---	---

Temperature	25	Humidity	50%
Test Engineer	Vic	Configurations	MCS15 40MHz Ch 3 / Ch6 / Ch9 Ant. 1 + Ant. 2

Channel 3 is fundamental frequency at 2422 MHz.

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2390.000	70.21	-3.79	74.00	39.31	28.07	2.82	0.00	Peak	---	---
2 @	2432.930	103.68			72.68	28.15	2.85	0.00	Peak	---	---
1 @	2390.000	51.98	-2.02	54.00	21.08	28.07	2.82	0.00	Average	---	---
2 @	2432.930	93.69			62.69	28.15	2.85	0.00	Average	---	---

Channel 6 is fundamental frequency at 2437 MHz.

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2448.130	106.53			75.50	28.19	2.85	0.00	Peak	---	---
1 @	2448.700	97.08			66.05	28.19	2.85	0.00	Average	---	---

Channel 9 is fundamental frequency at 2452 MHz.

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2443.380	105.06			74.03	28.19	2.85	0.00	Peak	---	---
2 @	2484.610	71.04	-2.96	74.00	39.90	28.26	2.87	0.00	Peak	---	---
1 @	2444.140	91.91			60.88	28.19	2.85	0.00	Average	---	---
2 @	2483.500	51.46	-2.54	54.00	20.32	28.26	2.87	0.00	Average	---	---


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2 / 2412 MHz



Date: 15.MAY.2007 09:58:00


High Band Edge Plot on Configuration IEEE 802.11n MCS15 20MHz Ant. 1 + Ant. 2 / 2462 MHz



Date: 15.MAY.2007 10:18:51


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2 / 2422 MHz



Date: 15.MAY.2007 09:09:01

High Band Edge Plot on Configuration IEEE 802.11n MCS15 40MHz Ant. 1 + Ant. 2 / 2452 MHz



Date: 15.MAY.2007 09:30:51

3.7. Antenna Requirements

3.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

3.7.2. Antenna Connector Construction

Please refer to section 2.3 in this test report, antenna connector complied with the requirements.

4. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100359	9kHz – 2.75GHz	Mar. 01, 2007	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2007	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2007	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2007	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
Isolation Transformer	Erika Fiedler OHG	D-65396 Walluf	58	45MHz-2.15GHz	N/A	Conduction (CO04-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Dec. 17, 2006	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100764	DC ~ 40GHz	Jul. 20, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100666	DC ~ 40GHz	Jul. 20, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 10, 2006	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 03, 2007	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 02, 2006	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2006	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2006	Conducted (TH01-HY)
Oscilloscope	Tektronix	TDS1012	CO38515	100MHz / 1GS/s	Jun. 20, 2006	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 07, 2007	Conducted (TH01-HY)
Data Generator	Tektronix	DG2030	063-2920-50	0.1Hz~400MHz	Jun. 16, 2006	Conducted (TH01-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 15, 2006	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	CPA9231A	1886	9 kHz - 2 GHz	Jan. 22, 2007	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	May 29, 2006	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004/040	9 kHz - 40 GHz	Sep. 21, 2006	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 24, 2006	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6903	1GHz ~ 18GHz	Apr. 17, 2007	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	NCR	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 02, 2006	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 02, 2006	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year. NCR: Non-Calibration required.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May. 4, 2007*	Conducted (TH01-HY)
Amplifier	MITEQ	AMF-6F-260400	923364	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is two year..

5. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 728, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6. NVLAP CERTIFICATE OF ACCREDITATION

United States Department of Commerce
National Institute of Standards and Technology

NVLAP[®]

Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 200079-0

Sporton International, Inc. Hwa Ya EMC Laboratory
Tao Yuan Hsien 333
TAIWAN

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communiqué dated 18 June 2005).*

2007-01-01 through 2007-12-31
Effective dates



Jolly S. Bruce
For the National Institute of Standards and Technology

NVLAP-01C (REV. 2006-09-13)