



FCC TEST REPORT

CATEGORY: Portable End Product

PRODUCT NAME: Bluetooth headset

FCC ID.: NDPBH-1000

FILING TYPE: Certification

MODEL NAME: BH-1000

APPLICANT: Partner Tech Corp.

10F, NO. 233-2, PAO CHIAO ROAD, SHIN TIEN, TAIPEI,
R.O.C.

MANUFACTURER: The same as Applicant.

ISSUED BY: SPORTON INTERNATIONAL INC.

6F, No. 106, Sec. 1, Hsin Tai Wu Rd., His Chih, Taipei Hsien,
Taiwan, R.O.C.

Statements:

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

Certificate or Test Report could not be used by the applicant to claim the product endorsement by CNLA, NVLAP or any agency of U.S. government.

The test equipment used to perform the test are calibrated and traceable to NML/ROC or NIST/USA.


Dr. Alan Lane
Vice General Manager
Sporton International Inc.


NVLAP®

Lab Code: 200079-0

Table of Contents

History of this test report	ii
1. General Description of Equipment under Test.....	1
1.1. Applicant.....	1
1.2. Manufacturer	1
1.3. Basic Description of Equipment under Test	1
1.4. Features of Equipment under Test.....	1
1.5. Table for Carrier Frequencies	2
2. Test Configuration of the Equipment under Test.....	3
2.1. Description of the Test	3
2.2. Frequency Range Investigated	3
2.3. Details of the Supporting Units.....	4
2.4. Connection Diagram of Test System	5
2.5. Test Software	6
3. Test Location and Standards	7
3.1. Test Location.....	7
3.2. Test Conditions	7
3.3. Test Standards	7
3.4. DoC Statement.....	7
4. Test Result and Details	8
4.1. Summary of the Test Results	8
5. Test Result	9
5.1. Test of Hopping Channel Bandwidth.....	9
5.2. Test of Number of Hopping Frequency	12
5.3. Test of Hopping Channel Separation	14
5.4. Test of Dwell Time of Each Frequency	17
5.5. Test of Maximum Peak Output Power	20
5.6. Test of Band Edges of the Operation Frequency.....	21
5.7. Test of AC Power Line Conducted Emission	24
5.8. Test of Spurious Radiated Emission	34
5.9. Antenna Requirements	49
5.10. RF Exposure.....	50
6. List of Measuring Equipments Used	52
Appendix A. Photographs of EUT	A1 ~ A21



History of this test report

No additional attachment.
 Additional attachment were issued as following record:



SPORTON LAB.

FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

1. General Description of Equipment under Test

1.1. Applicant

Partner Tech Corp.

10F, NO. 233-2, PAO CHIAO ROAD, SHIN TIEN, TAIPEI, R.O.C.

1.2. Manufacturer

The same as Applicant.

1.3. Basic Description of Equipment under Test

This product is a Bluetooth headset with a voice transmitter attached. The technical data has been listed on section " Features of Equipment under Test ". This equipment is able to be communicated with audio device with bleutooth interface. This equipment can be charged by power adapter. And there are 3 types of adapter filed in this project. See section 2.1 for test details.

1.4. Features of Equipment under Test

ITEMS	DESCRIPTION
Type of Modulation	GFSK
Number of Channels	79
Frequency Band	2400MHz ~ 2483.5MHz
Carrier Frequency of Each Channel	Please reference table below.
Channel Bandwidth	1MHz
Output Power	2.24dBm (peak)
Antenna Type / Gain	Integral Antenna / -3dBi
Function Type	Transceiver
Power Rating (DC/AC, Voltage)	5 VDC from power adapter
Duty Cycle	25 %
Humidity	10 ~ 90 %
Temperature Range (Operating)	-20 ~ 70 °C



1.5. Table for Carrier Frequencies

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	27	2429 MHz	54	2456 MHz
01	2403 MHz	28	2430 MHz	55	2457 MHz
02	2404 MHz	29	2431 MHz	56	2458 MHz
03	2405 MHz	30	2432 MHz	57	2459 MHz
04	2406 MHz	31	2433 MHz	58	2460 MHz
05	2407 MHz	32	2434 MHz	59	2461 MHz
06	2408 MHz	33	2435 MHz	60	2462 MHz
07	2409 MHz	34	2436 MHz	61	2463 MHz
08	2410 MHz	35	2437 MHz	62	2464 MHz
09	2411 MHz	36	2438 MHz	63	2465 MHz
10	2412 MHz	37	2439 MHz	64	2466 MHz
11	2413 MHz	38	2440 MHz	65	2467 MHz
12	2414 MHz	39	2441 MHz	66	2468 MHz
13	2415 MHz	40	2442 MHz	67	2469 MHz
14	2416 MHz	41	2443 MHz	68	2470 MHz
15	2417 MHz	42	2444 MHz	69	2471 MHz
16	2418 MHz	43	2445 MHz	70	2472 MHz
17	2419 MHz	44	2446 MHz	71	2473 MHz
18	2420 MHz	45	2447 MHz	72	2474 MHz
19	2421 MHz	46	2448 MHz	73	2475 MHz
20	2422 MHz	47	2449 MHz	74	2476 MHz
21	2423 MHz	48	2450 MHz	75	2477 MHz
22	2424 MHz	49	2451 MHz	76	2478 MHz
23	2425 MHz	50	2452 MHz	77	2479 MHz
24	2426 MHz	51	2453 MHz	78	2480 MHz
25	2427 MHz	52	2454 MHz		
26	2428 MHz	53	2455 MHz		



2. Test Configuration of the Equipment under Test

2.1. Description of the Test

- a) This test report is only for the BlueTooth part of the product. It has been verified that the emission of the BlueTooth module is independent of the status of the headset.
- b) The used peripherals as well as the configuration fulfill the requirements of ANSI C63.4:2001. The configuration is operated in a manner which tends to maximize its emission characteristics in a typical application.
- c) The following modes were tested:
 - Mode 1: X axis
 - Mode 2: Y axis
 - Mode 3: Z axis
 - Mode 4: EUT powered by adapter (35-5-200)
 - Mode 5: EUT powered by switching adapter (DSA-0051-03 FUS 50050F)
 - Mode 6: EUT powered by adapter (WP3501050D)
- d) 3 meters measurement distance of OATS was used in this test.
- e) Spurious emission below 1GHz is independent of channel selection, so only channel 78 was tested in this report.
- f) Radiation testing was performed on Mode 1~3. There are 3 adapters shown in the status below 1GHz. Among them, the testing result of switching adapter is the worst case, so only this data has been shown.
- g) Conduction testing was performed on Mode 4~6.

2.2. Frequency Range Investigated

- a) Conducted power line test: from 150 kHz to 30 MHz
- b) Radiated emission test: from 30 MHz to 25000 MHz



2.3. Details of the Supporting Units

Support Unit 1. -- Printer (EPSON)

FCC ID	: N/A
Model No.	: STYLUS COLOR 680
Power Supply Type	: Linear
Power Cord	: Non-Shielded
Serial No.	: SP0048
Data Cable	: Shielded, 1.35m
Remark	: This support device was tested to comply with FCC standards and authorized under a declaration of conformity.


Support Unit 2. – Notebook (DELL)

FCC ID	: N/A
Model No.	: PP01L
Serial No.	: SP0005
Remark	: This support device was tested to comply with FCC standards and authorized under Declaration of Conformity.

Support Unit 3. – Power Supply (EPE)

FCC ID	: N/A
Model No.	: EP-3000
Remark	: This support device was tested to comply with FCC standards and authorized under Declaration of Conformity.

2.4. Connection Diagram of Test System





2.5. Test Software

There are 2 softwares may be used in the testing.

- A) Channel & Power Controlling Software: This was provided by the manufacturer and is able to let the test engineer select the operating channel as well as the RF output power. The parameters for channel selection is trying to offer the test engineer the ability to fix the operating channel for testing, both normal data and continuously transmitting modes are allowed, and that for RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.
- B) "H" Pattern Generator: Except Access Point, the supporting equipment such as monitor or printer is always available. Under testing, these supporting equipment has to also under working condition. "H" Pattern Generator is able to continuously transmitting "H" character to those supporting equipments.



3. Test Location and Standards

3.1. Test Location

Test Location : Sporton Hwa Ya Testing Building
Address : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Tel: +886 3 327 3456 Fax: +886 3 318 0055
Test Site No. : CO04-HY , 03CH03-HY

3.2. Test Conditions

Normal Voltage : 120V/60Hz (power adapter)
Extreme Voltage : 138V and 102V (power adapter)
Normal Temperature : 20 °C
Extreme Temperature : -20 °C and 70 °C

3.3. Test Standards

Here is the list of the standards followed in this test report.

ANSI C63.4-2001

47 CFR Part 15 Subpart C (Section 15.247)

3.4. DoC Statement

This EUT is also classified as a device of computer peripheral Class B which DoC has to be followed. It has been verified according to the rule of 47 CFR part 15 Subpart B, and found that all the requirements has been fulfilled.



4. Test Result and Details

4.1. Summary of the Test Results

Applied Standard: 47 CFR Part 15 and Part 2			
Paragraph	FCC Rule	Description of Test	Result
5.1	15.247(a)(1)	Hopping Channel Bandwidth	Pass
5.2	15.247(a)(iii)	Number of Hopping Frequency Used	Pass
5.3	15.247(a)(1)	Hopping Channel Separation	Pass
5.4	15.247(a)(iii)	Dwell Time of Each Frequency	Pass
5.5	15.247 (b)(1)	Maximum Peak Output Power	Pass
5.6	15.247(c)	Band Edges of the Operation Frequency	Pass
5.7	15.247(d)	Power Spectral Density	Pass
5.8	15.107/15.207	AC Power Line Conducted Emission	Pass
5.9	15.209/15.247(c)	Spurious Radiated Emission	Pass
5.10	15.203	Antenna Requirement	Pass
5.11	2.1091/2.1093	Maximum Permissible Exposure for the EUT	Pass

5. Test Result

5.1. Test of Hopping Channel Bandwidth


5.1.1. Measuring Instruments

Item 9 of the table on section 6.

5.1.2. Test Procedures

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set RBW of spectrum analyzer to 30KHz and VBW to 300KHz.
3. The Hopping Channel bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.

5.1.3. Test Setup Layout



5.1.4. Test Result : See spectrum analyzer plots below

- Operating Mode: Continuously Transmitting
- Temperature: 25°C
- Relative Humidity: 60 %
- Duty Cycle of the Equipment During the Test: 100%
- Test Engineer: Sam Lee


Channel	Frequency (MHz)	Hopping Channel Bandwidth (KHz)
00	2402	822.000
39	2441	810.000
78	2480	816.000



FCC ID:NDPBH-1000
Issued on Sep. 10, 2004


Report No.: F472803

(Channel 00) :



Date: 10.AUG.2004 12:18:17

(Channel 39) :



Date: 10.AUG.2004 12:19:45

SPORTON International Inc.

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255


Page No. : 10 of 53
Issued Date : Sep. 10, 2004



FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

(Channel 78) :



Date: 10.AUG.2004 12:21:08

5.2. Test of Number of Hopping Frequency


5.2.1. Measuring Instruments

Item 9 of the table on section 6.

5.2.2. Test Procedures

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set RBW of spectrum analyzer to 100KHz and VBW to 100KHz.
3. The number of hopping frequency used is defined total number of the channels available on the spectrum.

5.2.3. Test Setup Layout



5.2.4. Test Result : See spectrum analyzer plots below


- Operating Mode: Normal Hopping
- Temperature: 25°C
- Relative Humidity: 60 %
- Duty Cycle of the Equipment During the Test: 100%
- Test Engineer: Sam Lee

Number of Hopping Frequency	Min. Limit
79	75



FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803



Date: 10.AUG.2004 13:03:03

5.3. Test of Hopping Channel Separation


5.3.1. Measuring Instruments

Item 9 of the table on section 6.

5.3.2. Test Procedures

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set RBW of spectrum analyzer to 30KHz and VBW to 100KHz.
3. The Hopping Channel Separation is defined as the separation between 2 neighboring hopping frequencies.

5.3.3. Test Setup Layout



5.3.4. Test Result : The spectrum analyzer plots are attached as below

- Operating Mode: Normal Hopping
- Temperature: 25°C
- Relative Humidity: 60 %
- Duty Cycle of the Equipment During the Test: 100%
- Test Engineer: Sam Lee

Channel	Frequency (MHz)	Hopping Channel Separation (KHz)	Limits (KHz)
00	2402	1000.0000	822.000
39	2441	1000.0000	810.000
78	2480	1000.0000	816.000


Note: The limit is 25KHz or 20dB bandwidth , which is greater.



FCC ID:NDPBH-1000
Issued on Sep. 10, 2004


Report No.: F472803

(Channel 00) :



Date: 10.AUG.2004 12:26:26

(Channel 39) :




Date: 10.AUG.2004 12:25:25



FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

(Channel 78) :



Date: 10.AUG.2004 12:23:30

5.4. Test of Dwell Time of Each Frequency


5.4.1. Measuring Instruments

Item 9 of the table on section 6.

5.4.2. Test Procedures

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set RBW of spectrum analyzer to 100kHz and VBW to 100kHz.
3. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
4. Set the EUT for DH5 packet transmitting.
5. Measure the maximum time duration, t , of one single pulse.
6. DH5 Packet permit maximum 320 hops per second in 79 channels. So, the dwell time is the time duration of the pulse times 128 within 31.6 seconds.

5.4.3. Test Setup Layout




5.4.4. Test Result : See spectrum analyzer plots below

- Operating Mode: Normal Hopping
- Temperature: 25°C
- Relative Humidity: 60 %
- Duty Cycle of the Equipment During the Test : 100%
- Test Engineer: Sam Lee

Channel	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
00	2402	3.08	0.39424	0.4
39	2441	3.08	0.39424	0.4
78	2480	3.08	0.39424	0.4




(Channel 00) :



Date: 10.AUG.2004 12:30:05

(Channel 39) :




Date: 10.AUG.2004 12:30:51



FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

(Channel 78) :



Date: 10.AUG.2004 12:31:59

5.5. Test of Maximum Peak Output Power


5.5.1. Measuring Instruments

Item 9 of the table on section 6.

5.5.2. Test Procedures

1. The transmitter output was connected to the vertical channel of the oscilloscope through a detector.
2. Record peak value from the meter.
3. Repeated the 1~2 for the middle and highest channel of the EUT.

5.5.3. Test Setup Layout



5.5.4. Test Result : See spectrum analyzer plots below

- Operating Mode: Normal Hopping
- Temperature: 25°C
- Relative humidity: 60 %
- Duty cycle of the equipment during the test : 100%
- Test Engineer: Sam Lee

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (mWatt)	Limits (dBm)
00	2402	2.12	1.62929	30 dBm
39	2441	2.10	1.62181	30 dBm
78	2480	2.24	1.67494	30 dBm



5.6. Test of Band Edges of the Operation Frequency

5.6.1. Measuring Instruments

Item 9 of the table on section 6.

5.6.2. Test Procedures

1. The transmitter output was connected to the spectrum analyzer via a low loss cable.
2. Set both RBW and VBW of spectrum analyzer to 100KHz with convenient frequency span including 100 KHz bandwidth from band edge.
3. The band edges emission was measured and recorded.

5.6.3.

Test Result in lower band (Channel 00) :	PASS
Test Result in higher band(Channel 78) :	PASS

5.6.4. Note on Band edge Emission

(A) Left Edge

The band edge emission plot shows 56.26dB delta between carrier maximum power and local maximum emission in the restricted band.

CH 00 Carrier power strength (dB μ V/m)	Delta (dB)	The maximum field strength in restrict band (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
70.67	56.26	25.92	54.00	-28.08

(B) Right Edge

The band edge emission plot shows 31.72dB delta between carrier maximum power and local maximum emission in the restricted band.

CH 78 Carrier power strength (dB μ V/m)	Delta (dB)	The maximum field strength in restrict band (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
65.84	31.72	34.12	54.00	-19.88


* The maximum field strength in restricted band is the emission of carrier power strength subtract to the delta between carrier maximum power and local maximum emission in the restricted band.



FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803


(Channel 00) :



Date: 10.AUG.2004 12:41:25



(Channel 78) :



Date: 10.AUG.2004 12:45:02

Observation : All emissions in the 100kHz band edge are all lower than carrier by more than 20dB.



5.7. Test of AC Power Line Conducted Emission

5.7.1. Measuring Instruments

Please reference item 1~7 in chapter 6 for the instruments used for testing.

5.7.2. Test Procedures

1. Configure the EUT according to ANSI C63.4.
2. The EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connected to the other LISNs. The LISN should provides 50uH/50ohms coupling impedance.
5. The frequency range from 150 KHz to 30 MHz was searched.
6. Use the Channel & Power Controlling software to make the EUT working on selected channel and expected output power, then use the "H" Patter Generator software to make the supporting equipments stay on working condition.
7. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
8. The measurement has to be done between each power line and ground at the power terminal for each RF channel. Only one RF channel has to be investigated since this test is independent with the RF channel selection.



5.7.3. Test Result of Conducted Emission

Test Mode	RF LINK (Mode 4)	Tested By	Wayne Hsu
Temperature / Humidity	27deg. C / 51%		

Line to Ground

Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		Line	dBuV	Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 0.1641380	13.68	-51.57	65.25	13.57	0.10	0.01	QP
2 0.1641380	6.28	-48.97	55.25	6.17	0.10	0.01	Average
3 0.1786590	13.28	-51.27	64.55	13.17	0.10	0.01	QP
4 0.1786590	5.06	-49.49	54.55	4.95	0.10	0.01	Average
5 0.2908840	7.83	-52.67	60.50	7.71	0.10	0.02	QP
6 0.2908840	3.49	-47.01	50.50	3.37	0.10	0.02	Average
7 0.3913610	5.67	-42.36	48.03	5.55	0.10	0.02	Average
8 0.3913610	12.21	-45.82	58.03	12.09	0.10	0.02	QP
9 0.5464400	3.61	-42.39	46.00	3.48	0.10	0.03	Average
10 0.5464400	9.57	-46.43	56.00	9.44	0.10	0.03	QP
11 0.8991650	6.71	-49.29	56.00	6.57	0.10	0.04	QP
12 0.8991650	2.58	-43.42	46.00	2.44	0.10	0.04	Average

Neutral to Ground

Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		Line	dBuV	Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 0.1844300	14.15	-50.13	64.28	14.04	0.10	0.01	QP
2 0.1844300	8.66	-45.62	54.28	8.55	0.10	0.01	Average
3 0.2340870	3.30	-49.00	52.30	3.19	0.10	0.01	Average
4 0.2340870	8.68	-53.62	62.30	8.57	0.10	0.01	QP
5 0.3428090	4.49	-44.64	49.13	4.37	0.10	0.02	Average
6 0.3428090	9.94	-49.19	59.13	9.82	0.10	0.02	QP
7 0.3751190	10.39	-48.00	58.39	10.27	0.10	0.02	QP
8 0.3751190	5.41	-42.98	48.39	5.29	0.10	0.02	Average
9 0.5464400	8.78	-47.22	56.00	8.65	0.10	0.03	QP
10 0.5464400	3.66	-42.34	46.00	3.53	0.10	0.03	Average
11 0.9581900	2.52	-43.48	46.00	2.38	0.10	0.04	Average
12 0.9581900	6.36	-49.64	56.00	6.22	0.10	0.04	QP



Test Mode	RF LINK (Mode 5)	Tested By	Wayne Hsu
Temperature / Humidity	27deg. C / 51%		

Line to Ground

Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		Limit	Line	Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1715050	41.91	-22.98	64.89	41.80	0.10	0.01 QP
2	0.1715050	30.92	-23.97	54.89	30.81	0.10	0.01 Average
3	0.3446320	36.96	-22.13	59.09	36.84	0.10	0.02 QP
4	0.3446320	30.31	-18.78	49.09	30.19	0.10	0.02 Average
5	0.6900770	34.06	-21.94	56.00	33.93	0.10	0.03 QP
6	0.6900770	26.36	-19.64	46.00	26.23	0.10	0.03 Average
7	0.8660670	37.12	-18.88	56.00	36.98	0.10	0.04 QP
8	0.8660670	26.47	-19.53	46.00	26.33	0.10	0.04 Average
9	1.044	35.86	-20.14	56.00	35.72	0.10	0.04 QP
10	1.044	18.91	-27.09	46.00	18.77	0.10	0.04 Average
11	1.384	33.17	-22.83	56.00	33.04	0.10	0.03 QP
12	1.384	20.95	-25.05	46.00	20.82	0.10	0.03 Average

Neutral to Ground

Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		Limit	Line	Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1720790	42.89	-21.97	64.86	42.78	0.10	0.01 QP
2	0.1720790	30.60	-24.26	54.86	30.49	0.10	0.01 Average
3	0.3440700	39.05	-20.05	59.10	38.93	0.10	0.02 QP
4	0.3440700	31.53	-17.57	49.10	31.41	0.10	0.02 Average
5	0.5173150	32.23	-23.77	56.00	32.10	0.10	0.03 QP
6	0.5173150	24.88	-21.12	46.00	24.75	0.10	0.03 Average
7	0.8585550	35.81	-20.19	56.00	35.67	0.10	0.04 QP
8	0.8585550	28.72	-17.28	46.00	28.58	0.10	0.04 Average
9	1.370	31.56	-24.44	56.00	31.43	0.10	0.03 QP
10	1.370	21.72	-24.28	46.00	21.59	0.10	0.03 Average
11	1.880	22.73	-33.27	56.00	22.61	0.10	0.02 QP
12	1.880	13.21	-32.79	46.00	13.09	0.10	0.02 Average



Test Mode	RF LINK (Mode 6)	Tested By	Wayne Hsu
Temperature / Humidity	27deg. C / 51%		

Line to Ground

Freq	Level	Over Limit		Read Line	LISN Level	Cable Factor		Remark
		MHz	dBuV	dB	dBuV	dB	dB	
1	0.1556680	12.36	-53.33	65.69	12.25	0.10	0.01	QP
2	0.1556680	8.28	-47.41	55.69	8.17	0.10	0.01	Average
3	0.1903870	12.26	-51.76	64.02	12.15	0.10	0.01	QP
4	0.1903870	9.38	-44.64	54.02	9.27	0.10	0.01	Average
5	0.2672410	9.23	-51.97	61.20	9.12	0.10	0.01	QP
6	0.2672410	6.05	-45.15	51.20	5.94	0.10	0.01	Average
7	0.3751190	9.32	-49.07	58.39	9.20	0.10	0.02	QP
8	0.3751190	4.84	-43.55	48.39	4.72	0.10	0.02	Average
9	2.920	6.13	-49.87	56.00	5.93	0.15	0.05	QP
10	2.920	2.38	-43.62	46.00	2.18	0.15	0.05	Average
11	7.370	8.82	-51.18	60.00	8.52	0.20	0.10	QP
12	7.370	5.81	-44.19	50.00	5.51	0.20	0.10	Average

Neutral to Ground

Freq	Level	Over Limit		Read Line	LISN Level	Cable Factor		Remark
		MHz	dBuV	dB	dBuV	dB	dB	
1	0.1524030	11.30	-44.57	55.87	11.19	0.10	0.01	Average
2	0.1524030	14.23	-51.64	65.87	14.12	0.10	0.01	QP
3	0.1903870	11.90	-52.12	64.02	11.79	0.10	0.01	QP
4	0.1903870	8.71	-45.31	54.02	8.60	0.10	0.01	Average
5	0.2847840	10.48	-50.20	60.68	10.36	0.10	0.02	QP
6	0.2847840	6.42	-44.26	50.68	6.30	0.10	0.02	Average
7	0.5406800	7.41	-48.59	56.00	7.28	0.10	0.03	QP
8	0.5406800	3.70	-42.30	46.00	3.57	0.10	0.03	Average
9	1.980	5.64	-50.36	56.00	5.52	0.10	0.02	QP
10	1.980	2.51	-43.49	46.00	2.39	0.10	0.02	Average
11	3.290	6.54	-49.46	56.00	6.38	0.10	0.06	QP
12	3.290	3.15	-42.85	46.00	2.99	0.10	0.06	Average

5.7.4. Photographs of Conducted Emission Test Configuration

- The photographs show the configuration that generates the maximum emission.

Mode 4

FRONT VIEW



REAR VIEW






FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

SIDE VIEW





FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

Mode 5

FRONT VIEW



REAR VIEW






FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

SIDE VIEW



SPORTON International Inc.

TEL : 886-2-2696-2468
FAX : 886-2-2696-2255

Page No. : 31 of 53
Issued Date : Sep. 10, 2004

Mode 6

FRONT VIEW



REAR VIEW





FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

SIDE VIEW





5.8. Test of Spurious Radiated Emission


5.8.1. Measuring Instruments

Please reference item 8~19 in chapter 6 for the instruments used for testing.

5.8.2. Test Procedures

1. Configure the EUT according to ANSI C63.4.
2. The EUT was placed on the top of the turn table 0.8 meter above ground.
3. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turn table.
4. Power on the EUT and all the supporting units.
5. The turn table was rotated by 360 degrees to determine the position of the highest radiation.
6. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.
7. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turn table was rotated (from 0 degree to 360 degrees) to find the maximum reading.
8. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
9. For emission above 1GHz, use 1MHz VBW & RBW for peak reading and 1MHz RBW & 300Hz VBW for average reading in spectrum analyzer.
10. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
11. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB higher than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported. (For peak measurement, RB=VB=1MHz, for average measurement, RB=1MHz, VB=10Hz)

5.8.3. Test Setup Layout





5.8.4. Test Results and Limit

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level

Test Mode	Mode 1(CH 78)	Temperature	24 deg. C	Tested By	Steve Chen
Freq. Range	30MHz~1GHz	Humidity	63%		

(A) Polarization: Horizontal

Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Ant Pos	Table Pos
		Line	Limit	Level	Factor	Loss	Factor		
1	129.110	30.93	-12.57	43.50	44.37	12.31	2.09	27.84 Peak	---
2	173.140	39.58	-3.92	43.50	50.94	14.01	2.38	27.75 Peak	162 184
3	181.470	35.99	-7.51	43.50	46.98	14.31	2.44	27.74 Peak	---
1	265.600	37.41	-8.59	46.00	49.15	12.77	2.93	27.44 Peak	---
2	666.400	34.17	-11.83	46.00	37.65	20.60	4.65	28.73 Peak	---
3	998.400	39.29	-14.71	54.00	37.94	23.86	5.69	28.20 Peak	---

(B) Polarization: Vertical

Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Ant Pos	Table Pos
		Line	Limit	Level	Factor	Loss	Factor		
1	80.660	26.33	-13.67	40.00	43.29	9.43	1.55	27.94 Peak	---
2	129.790	27.63	-15.87	43.50	41.03	12.33	2.11	27.84 Peak	---
3	161.070	24.84	-18.66	43.50	37.58	12.73	2.31	27.78 Peak	---
1	531.200	28.73	-17.27	46.00	36.02	17.37	4.07	28.73 Peak	---
2	666.400	34.48	-11.52	46.00	37.96	20.60	4.65	28.73 Peak	---
3	832.000	39.01	-6.99	46.00	40.59	21.84	5.22	28.64 Peak	---
4	998.400	35.74	-18.26	54.00	34.39	23.86	5.69	28.20 Peak	---



Test Mode	Mode 2(CH 78)	Temperature	24 deg. C	Tested By	Steve Chen
Freq. Range	30MHz~1GHz	Humidity	63%		

(A) Polarization: Horizontal

Freq	Level	Over Limit	Limit Line	Read Probe			Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
				dBuV/m	dB	dBuV/m	dBuV	dB	dB		
1	179.260	26.36	-17.14	43.50	37.47	14.20	2.43	27.74	Peak	---	---
2	186.740	26.69	-16.81	43.50	37.23	14.73	2.46	27.73	Peak	---	---
3	198.470	30.50	-13.00	43.50	39.97	15.67	2.56	27.70	Peak	---	---
1	265.600	35.58	-10.42	46.00	47.32	12.77	2.93	27.44	Peak	---	---
2	288.800	37.34	-8.66	46.00	48.16	13.48	3.05	27.35	Peak	---	---
3	998.400	36.38	-17.62	54.00	35.03	23.86	5.69	28.20	Peak	---	---

(B) Polarization: Vertical

Freq	Level	Over Limit	Limit Line	Read Probe			Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
				dBuV/m	dB	dBuV/m	dBuV	dB	dB		
1	101.060	28.86	-14.64	43.50	45.82	9.15	1.79	27.90	Peak	---	---
2	143.900	26.11	-17.39	43.50	39.47	12.33	2.12	27.81	Peak	---	---
3	166.340	25.38	-18.12	43.50	37.53	13.29	2.33	27.77	Peak	---	---
1	665.600	30.78	-15.22	46.00	34.26	20.60	4.65	28.73	Peak	---	---
2	832.000	40.84	-5.16	46.00	42.42	21.84	5.22	28.64	Peak	123	214
3	998.400	31.61	-22.39	54.00	30.26	23.86	5.69	28.20	Peak	---	---



Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level

Test Mode	Mode 3(CH 78)	Temperature	24 deg. C	Tested By	Steve Chen
Freq. Range	30MHz~1GHz	Humidity	63%		

(A) Polarization: Horizontal

Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant	Table
									Pos	Pos
									cm	deg
1	187.420	28.39	-15.11	43.50	38.86	14.79	2.46	27.72 Peak	---	---
2	190.820	28.12	-15.38	43.50	38.29	15.07	2.48	27.72 Peak	---	---
3	198.980	28.34	-15.16	43.50	37.75	15.72	2.57	27.70 Peak	---	---
1	265.600	35.79	-10.21	46.00	47.53	12.77	2.93	27.44 Peak	---	---
2	912.800	38.77	-7.23	46.00	39.68	21.99	5.39	28.29 Peak	---	---
3	1000.000	36.22	-17.78	54.00	34.83	23.90	5.69	28.20 Peak	---	---

(B) Polarization: Vertical

Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant	Table
									Pos	Pos
									cm	deg
1	30.340	27.46	-12.54	40.00	41.64	12.92	0.95	28.05 Peak	---	---
2	101.230	27.33	-16.17	43.50	44.25	9.18	1.80	27.90 Peak	---	---
3	129.110	25.56	-17.94	43.50	39.00	12.31	2.09	27.84 Peak	---	---
1	832.800	31.93	-14.07	46.00	33.50	21.83	5.23	28.63 Peak	---	---
2	912.800	38.85	-7.15	46.00	39.76	21.99	5.39	28.29 Peak	115	145
3	1000.000	34.40	-19.60	54.00	33.01	23.90	5.69	28.20 Peak	---	---



Test Mode	Mode 1 (2402MHz)	Temperature	26 deg. C	Tested By	Steve Chen
Freq. Range	1GHz~25GHz	Humidity	65%		

(A) Polarization: Horizontal

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Preamp		Remark	Ant Pos	Table Pos
		MHz	dBuV/m	dB	dBuV/m	dB	dB			
1	1000.000	43.96	-10.04	54.00	61.45	23.80	1.11	42.40 Average	---	---
2	1332.000	42.06	-11.94	54.00	58.47	24.77	1.35	42.53 Average	---	---
3	1582.000	46.30	-7.70	54.00	61.86	25.56	1.50	42.62 Average	---	---
1	4804.000	56.48	-17.52	74.00	65.24	33.19	2.40	44.35 Peak	---	---
2	4804.000	43.87	-10.13	54.00	52.63	33.19	2.40	44.35 Average	---	---

(B) Polarization: Vertical

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Preamp		Remark	Ant Pos	Table Pos
		MHz	dBuV/m	dB	dBuV/m	dB	dB			
1	1000.000	47.41	-6.59	54.00	64.90	23.80	1.11	42.40 Average	128	213
2	1362.000	46.47	-7.53	54.00	62.83	24.85	1.34	42.55 Average	---	---
3	1990.000	43.35	-10.65	54.00	57.45	27.08	1.52	42.70 Average	---	---
1	3332.000	42.72	-11.28	54.00	52.73	30.94	2.16	43.11 Average	---	---
2	4804.000	56.93	-17.07	74.00	65.69	33.19	2.40	44.35 Peak	---	---
3	4804.000	43.60	-10.40	54.00	52.36	33.19	2.40	44.35 Average	---	---



Test Mode	Mode 2 (2402MHz)	Temperature	26 deg. C	Tested By	Steve Chen
Freq. Range	1GHz~25GHz	Humidity	65%		

(A) Polarization: Horizontal

Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Ant Pos	Table Pos
		Line	Level	Factor	Loss	Factor	Remark		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	cm	deg
1	1000.000	45.29	-8.71	54.00	62.78	23.80	1.11	42.40	Average
2	1326.000	40.84	-13.16	54.00	57.27	24.75	1.35	42.53	Average
3	1662.000	40.28	-13.72	54.00	55.51	25.86	1.54	42.63	Average
1	4804.000	53.36	-20.64	74.00	62.12	33.19	2.40	44.35	Peak
2	4804.000	40.76	-13.24	54.00	49.52	33.19	2.40	44.35	Average

(B) Polarization: Vertical

Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Ant Pos	Table Pos
		Line	Level	Factor	Loss	Factor	Remark		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	cm	deg
1	1000.000	46.67	-7.33	54.00	64.16	23.80	1.11	42.40	Average
2	1996.000	43.00	-11.00	54.00	57.09	27.10	1.51	42.70	Average
3	2334.000	43.33	-10.67	54.00	56.27	27.99	1.70	42.63	Average
1	4804.000	62.25	-11.75	74.00	71.01	33.19	2.40	44.35	Peak
2	4804.000	45.16	-8.84	54.00	53.92	33.19	2.40	44.35	Average



Test Mode	Mode 3 (2402MHz)	Temperature	26 deg. C	Tested By	Steve Chen
Freq. Range	1GHz~25GHz	Humidity	65%		

(A) Polarization: Horizontal

Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Preamp			Ant Pos	Table Pos
						dB	dBuV/m	dB		
1	1000.000	49.03	-4.97	54.00	66.52	23.80	1.11	42.40	Average	132
2	1332.000	42.45	-11.55	54.00	58.86	24.77	1.35	42.53	Average	---
3	1660.000	41.26	-12.74	54.00	56.50	25.85	1.54	42.63	Average	---
1	4804.000	59.33	-14.67	74.00	68.09	33.19	2.40	44.35	Peak	---
2	4804.000	45.39	-8.61	54.00	54.15	33.19	2.40	44.35	Average	---

(B) Polarization: Vertical

Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Preamp			Ant Pos	Table Pos
						dB	dBuV/m	dB		
1	1662.000	42.37	-11.63	54.00	57.60	25.86	1.54	42.63	Average	---
2	1998.000	44.69	-9.31	54.00	58.76	27.11	1.52	42.70	Average	---
3	2332.000	42.81	-11.19	54.00	55.74	27.99	1.71	42.63	Average	---
1	3590.000	41.71	-12.29	54.00	51.33	31.58	2.12	43.32	Average	---
2	4804.000	62.97	-11.03	74.00	71.73	33.19	2.40	44.35	Peak	---
3	4804.000	47.28	-6.72	54.00	56.04	33.19	2.40	44.35	Average	---



Test Mode	Mode 1 (2441MHz)	Temperature	24 deg. C	Tested By	Steve Chen
Freq. Range	1GHz~25GHz	Humidity	63%		

(A) Polarization: Horizontal

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Preamp		Remark	Ant Pos	Table Pos
		Limit	Line			dB	dBuV/m			
1	1000.000	43.08	-10.92	54.00	60.57	23.80	1.11	42.40	Average	---
2	1332.000	40.27	-13.73	54.00	56.68	24.77	1.35	42.53	Average	---
3	1814.000	38.74	-15.26	54.00	53.38	26.42	1.61	42.67	Average	---
1	4884.000	53.56	-0.44	54.00	62.10	33.37	2.51	44.42	Average	131 201

(B) Polarization: Vertical

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Preamp		Remark	Ant Pos	Table Pos
		Limit	Line			dB	dBuV/m			
1	1000.000	45.46	-8.54	54.00	62.95	23.80	1.11	42.40	Average	---
2	1996.000	43.67	-10.33	54.00	57.76	27.10	1.51	42.70	Average	---
3	2334.000	43.09	-10.91	54.00	56.03	27.99	1.70	42.63	Average	---
1	3334.000	41.73	-12.27	54.00	51.73	30.95	2.16	43.11	Average	---
2	4884.000	54.90	-19.10	74.00	63.44	33.37	2.51	44.42	Peak	---
3	4884.000	44.97	-9.03	54.00	53.51	33.37	2.51	44.42	Average	---



Test Mode	Mode 2 (2441MHz)	Temperature	24 deg. C	Tested By	Steve Chen
Freq. Range	1GHz~25GHz	Humidity	63%		

(A) Polarization: Horizontal

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Loss		Preamp Factor	Remark	Ant Pos	Table Pos
		MHz	dBuV/m	dB	dBuV/m	dB	dB				
1	1000.000	45.42	-8.58	54.00	62.91	23.80	1.11	42.40	Average	101	189
2	1662.000	41.14	-12.86	54.00	56.37	25.86	1.54	42.63	Average	---	---
3	2438.000	44.55	-9.45	54.00	57.13	28.27	1.76	42.61	Average	---	---
1	4884.000	49.20	-24.80	74.00	57.74	33.37	2.51	44.42	Peak	---	---
2	4884.000	40.44	-13.56	54.00	48.98	33.37	2.51	44.42	Average	---	---

(B) Polarization: Vertical

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Loss		Preamp Factor	Remark	Ant Pos	Table Pos
		MHz	dBuV/m	dB	dBuV/m	dB	dB				
1	1000.000	44.20	-9.80	54.00	61.69	23.80	1.11	42.40	Average	---	---
2	1660.000	42.37	-11.63	54.00	57.61	25.85	1.54	42.63	Average	---	---
3	2334.000	43.15	-10.85	54.00	56.09	27.99	1.70	42.63	Average	---	---
1	4884.000	56.80	-17.20	74.00	65.34	33.37	2.51	44.42	Peak	---	---
2	4884.000	43.87	-10.13	54.00	52.41	33.37	2.51	44.42	Average	---	---



Test Mode	Mode 3 (2441MHz)	Temperature	24 deg. C	Tested By	Steve Chen
Freq. Range	1GHz~25GHz	Humidity	63%		

(A) Polarization: Horizontal

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Preamp		Remark	Ant Pos	Table Pos
		MHz	dBuV/m	dB	dBuV/m	dB	dB			
1	1000.000	42.18	-11.82	54.00	59.67	23.80	1.11	42.40 Average	---	---
2	1334.000	44.32	-9.68	54.00	60.74	24.77	1.35	42.54 Average	---	---
3	1662.000	40.74	-13.26	54.00	55.97	25.86	1.54	42.63 Average	---	---
1	4884.000	56.29	-17.71	74.00	64.83	33.37	2.51	44.42 Peak	---	---
2	4884.000	44.82	-9.18	54.00	53.36	33.37	2.51	44.42 Average	145	168

(B) Polarization: Vertical

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Preamp		Remark	Ant Pos	Table Pos
		MHz	dBuV/m	dB	dBuV/m	dB	dB			
1	1000.000	42.17	-11.83	54.00	59.66	23.80	1.11	42.40 Average	---	---
2	1996.000	44.19	-9.81	54.00	58.28	27.10	1.51	42.70 Average	---	---
3	2326.000	43.87	-10.13	54.00	56.81	27.97	1.72	42.63 Average	---	---
1	3000.000	41.95	-12.05	54.00	52.37	30.20	2.28	42.90 Average	---	---
2	3334.000	41.95	-12.05	54.00	51.95	30.95	2.16	43.11 Average	---	---
3	4884.000	59.42	-14.58	74.00	67.96	33.37	2.51	44.42 Peak	---	---
4	4884.000	46.01	-7.99	54.00	54.55	33.37	2.51	44.42 Average	---	---



Test Mode	Mode 1 (2480MHz)	Temperature	24 deg. C	Tested By	Steve Chen
Freq. Range	1GHz~25GHz	Humidity	63%		

(A) Polarization: Horizontal

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Preamp		Remark	Ant Pos	Table Pos
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB			
1	1000.000	47.00	-7.00	54.00	64.49	23.80	1.11	42.40 Average	---	---
2	1326.000	39.80	-14.20	54.00	56.23	24.75	1.35	42.53 Average	---	---
3	1596.000	40.06	-13.94	54.00	55.56	25.61	1.51	42.62 Average	---	---
1	4958.000	50.59	-3.41	54.00	59.09	33.53	2.44	44.47 Average	121	154

(B) Polarization: Vertical

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Preamp		Remark	Ant Pos	Table Pos
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB			
1	1000.000	49.41	-4.59	54.00	66.90	23.80	1.11	42.40 Average	---	---
2	1662.000	43.78	-10.22	54.00	59.01	25.86	1.54	42.63 Average	---	---
3	2916.000	44.30	-9.70	54.00	55.31	29.91	1.94	42.86 Average	---	---
1	3172.000	42.34	-11.66	54.00	52.58	30.59	2.18	43.01 Average	---	---
2	4964.000	54.27	-19.73	74.00	62.74	33.55	2.46	44.48 Peak	---	---
3	4964.000	39.32	-14.68	54.00	47.79	33.55	2.46	44.48 Average	---	---



Test Mode	Mode 2 (2480MHz)	Temperature	24 deg. C	Tested By	Steve Chen
Freq. Range	1GHz~25GHz	Humidity	63%		

(A) Polarization: Horizontal

Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Ant Pos	Table Pos
		Limit	Line	Level	Factor	Loss	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	cm	deg
1	1000.000	48.39	-5.61	54.00	65.88	23.80	1.11	42.40	Average
2	1332.000	41.35	-12.65	54.00	57.76	24.77	1.35	42.53	Average
3	1662.000	41.28	-12.72	54.00	56.51	25.86	1.54	42.63	Average
1	4804.000	53.87	-20.13	74.00	62.63	33.19	2.40	44.35	Peak
2	4804.000	40.50	-13.50	54.00	49.26	33.19	2.40	44.35	Average

(B) Polarization: Vertical

Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Ant Pos	Table Pos
		Limit	Line	Level	Factor	Loss	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	cm	deg
1	1662.000	42.71	-11.29	54.00	57.94	25.86	1.54	42.63	Average
2	1996.000	43.27	-10.73	54.00	57.36	27.10	1.51	42.70	Average
3	2334.000	46.96	-7.04	54.00	59.90	27.99	1.70	42.63	Average
1	4804.000	59.79	-14.21	74.00	68.55	33.19	2.40	44.35	Peak
2	4804.000	45.12	-8.88	54.00	53.88	33.19	2.40	44.35	Average



Test Mode	Mode 3 (2480MHz)	Temperature	24 deg. C	Tested By	Steve Chen
Freq. Range	1GHz~25GHz	Humidity	63%		

(A) Polarization: Horizontal

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Preamp		Ant Remark	Table Pos	Table Pos
		MHz	dBuV/m	dB	dBuV/m	dB	dB			
1	1000.000	44.26	-9.74	54.00	61.75	23.80	1.11	42.40 Average	110	230
2	1326.000	41.11	-12.89	54.00	57.54	24.75	1.35	42.53 Average	---	---
3	1662.000	40.23	-13.77	54.00	55.46	25.86	1.54	42.63 Average	---	---
1	4958.000	56.87	-17.13	74.00	65.37	33.53	2.44	44.47 Peak	---	---
2	4958.000	41.72	-12.28	54.00	50.22	33.53	2.44	44.47 Average	---	---

(B) Polarization: Vertical

Freq	Level	Over Limit		Read Line	Probe Factor	Cable Preamp		Ant Remark	Table Pos	Table Pos
		MHz	dBuV/m	dB	dBuV/m	dB	dB			
1	1596.000	42.33	-11.67	54.00	57.83	25.61	1.51	42.62 Average	---	---
2	1662.000	41.52	-12.48	54.00	56.75	25.86	1.54	42.63 Average	---	---
3	1996.000	43.29	-10.71	54.00	57.38	27.10	1.51	42.70 Average	---	---
1	3596.000	42.55	-11.45	54.00	52.17	31.60	2.11	43.33 Average	---	---
2	4958.000	57.38	-16.62	74.00	65.88	33.53	2.44	44.47 Peak	---	---
3	4958.000	42.66	-11.34	54.00	51.16	33.53	2.44	44.47 Average	---	---

Remark: The emission except listed above is too low to be measured.


5.8.5. Photographs of Radiated Emission Test Configuration

- The photographs show the configuration that generates the maximum emission.

FRONT VIEW



REAR VIEW





SPORTON LAB.

FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

5.9. Antenna Requirements

5.9.1. Standard Applicable

47 CFR Part15 Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

47 CFR Part15 Section 15.247 (b):

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

If the intentional radiator is used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

5.9.2. Antenna Connector Used in this Product

The maximum Gain antenna used in this product is inverted -F antenna without antenna connector.



SPORTON LAB.

FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

5.10. RF Exposure

5.10.1. Limit For Maximum Permissible Exposure (MPE)

This product can be classified as mobile device, so the 2.5cm separation distance warning is required.

In this section, the power density at 2.5cm location is calculated to examine if it is lower than the limit.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

F = frequency in MHz

*Plane-wave equivalent power density



5.10.2.MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (mW/cm}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=2.5cm, as well as the gain of the used antenna, the RF power density can be obtained.

5.10.3.Calculated Result and Limit

Channel No.	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)
Channel 00	-3	0.50	2.12	1.6293	0.0104	1
Channel 39	-3	0.50	2.1	1.6218	0.0104	1
Channel 78	-3	0.50	2.24	1.6749	0.0107	1

From the calculated result shown in above table, the power density is lower than limit at location 2.5cm far away.



6. List of Measuring Equipments Used

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9 KHz – 2.75 GHz	Feb. 16, 2004	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	2001/004	9 KHz – 30 MHz	Jun. 09, 2004	Conduction (CO04-HY)
LISN (Support Unit)	MessTec	NNB-2/16Z	99041	9 KHz – 30 MHz	Apr. 27, 2004	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB044	9KHz~30MHz	Apr. 21, 2004	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz~1GHz 3m	Jun. 21, 2004	Radiation (03CH03-HY)
Spectrum analyzer	R&S	FSP40	100004	9KHZ~40GHz	Aug. 23, 2003	Radiation (03CH03-HY)
Amplifier	HP	8447D	2944A09072	100KHz – 1.3GHz	Nov. 05, 2003	Radiation (03CH03-HY)
Biconical Antenna	SCHWARZBECK	VHBB 9124	301	30MHz –200MHz	Jul. 23, 2004	Radiation (03CH03-HY)
Log Antenna	SCHWARZBECK	VUSLP 9111	221	200MHz -1GHz	Jul. 23, 2004	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz~1GHz	Dec. 03, 2003	Radiation (03CH03-HY)
Amplifier	MITEQ	AFS44	849984	100MHz~26.5GHz	Mar. 26, 2004	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6821	1GHz – 18GHz	Sep. 12, 2003	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 ~ 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Horn Antenna	Schwarzbeck	BBHA9170	154	15GHz~40GHz	Jun. 09, 2004	Radiation (03CH03-HY)
RF Cable-HIGH	Jye Bao	RG142	CB030-HIGH	1GHz~29.5GHz	Dec. 05, 2003	Radiation (03CH03-HY)

※ Calibration Interval of instruments listed above is one year.



FCC ID:NDPBH-1000
Issued on Sep. 10, 2004

Report No.: F472803

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum analyzer	R&S	FSP7	838858/014	9KHZ~7GHZ	Sep. 03, 2003	Conducted (TH01-HY)
Power meter	R&S	NRVS	100967	DC~40GHz	Mar. 02, 2004	Conducted (TH01-HY)
Power sensor	R&S	NRV-Z51	100666	DC~40GHz	Mar 18, 2004	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	836953/060	30MHz-6GHz	Mar. 11, 2004	Conducted (TH01-HY)
AC power source	G.W.	GPC-6030D	C671845	DC 1V~60V	Nov. 06, 2003	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2003	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz~7GHz	Jan. 01, 2004	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz~1GHz	Jan. 01, 2004	Conducted (TH01-HY)

※ Calibration Interval of instruments listed above is one year.

APPENDIX A. Photographs of EUT








REPORT NO. : F472803


472803















REPORT NO. : F472803





SPORTON LAB.

REPORT NO. : F472803

472803



SPORTON International Inc.

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255

PAGE NUMBER : A9 OF A21

ISSUED DATE : Sep. 06, 2004



SPORTON LAB.

REPORT NO. : F472803



472803

SPORTON International Inc.

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255

PAGE NUMBER : A10 OF A21

ISSUED DATE : Sep. 06, 2004



SPORTON LAB.

REPORT NO. : F472803

472803



SPORTON International Inc.

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255

PAGE NUMBER : A11 OF A21

ISSUED DATE : Sep. 06, 2004



SPORTON LAB.

REPORT NO. : F472803

472803





SPORTON LAB.

REPORT NO. : F472803

472803



472803





SPORTON LAB.

REPORT NO. : F472803

472803





SPORTON LAB.

REPORT NO. : F472803

472803



SPORTON International Inc.

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255

PAGE NUMBER : A16 OF A21

ISSUED DATE : Sep. 06, 2004



SPORTON LAB.

REPORT NO. : F472803

472803



SPORTON International Inc.

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255

PAGE NUMBER : A17 OF A21

ISSUED DATE : Sep. 06, 2004



SPURON LAB.

REPORT NO. : F472803

472803





SPORTON LAB.

REPORT NO. : F472803

472803







SPORTON LAB.

REPORT NO. : F472803

