



# FCC RF EXPOSURE REPORT

Applicant	:	Partner Tech Corporation
Address	:	2F., No. 206, Jian 8th Rd., Zhonghe Dist., New Taipei City , Taiwan
Manufacturer	:	Partner Tech Corporation
Address	:	2F., No. 206, Jian 8th Rd., Zhonghe Dist., New Taipei City , Taiwan
Factory	:	Guangzhou ZhiHua Electronic Technology Co., Ltd
Address	:	9F, No.40 Jinxiu Road, Economic Technology and Development District, Guangzhou
Equipment	:	POS Monitor
Model No.	:	COCO
Trade Name	:	PARTNER
Date of Sample Receipt	:	Oct. 16, 2024
Date(s) of Test	:	Oct. 28, 2024~Oct. 30, 2024
FCC ID.	:	NDPCOCO

## I HEREBY CERTIFY THAT:

The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Leevin Li / Supervisor



## Contents

<b>1. Test Configuration of Equipment under Test.....</b>	<b>4</b>
1.1 Feature of Equipment .....	4
1.2 General Information of Test.....	5
<b>2. Radio Frequency Exposure .....</b>	<b>6</b>
2.1 Reference.....	6
2.2 RF Exposure Limit.....	6
2.3 RF Exposure Evaluation Results .....	6



### **History of this test report**

<b>Version No.</b>	<b>Report No</b>	<b>Date</b>	<b>Description</b>
Rev.01	24100151-DRFCC02	Nov. 04, 2024	Initial Issue



## 1. Test Configuration of Equipment under Test

### 1.1 Feature of Equipment

Product	POS Monitor
Model Name	COCO
Model Discrepancy	N/A
Frequency Range	13.56MHz
Modulation Type	ASK
Antenna Type	PCB Antenna
EUT Power Rating	5V-1A
Temperature	Operating Temp: 0°C ~+40°C Storage Temp: -20°C ~+60°C

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.]



## 1.2 General Information of Test

Test Site	<b>Cerpass Technology Corporation(Cerpass Laboratory)</b> Address: Room 102, No. 5, Xing'an Road, Chang'an Town, Dongguan City, Guangdong Province Tel: +86-769-8547-1212 Fax: +86-769-8547-1912
FCC Designation No.:	CN1288
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 40,000MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.



## 2. Radio Frequency Exposure

### 2.1 Reference

According to §1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

### 2.2 RF Exposure Limit

1 mW

### 2.3 RF Exposure Evaluation Results

#### NFC

Operation Mode	Frequency (MHz)	Fundamental Emission (dBuV/m)	E.I.R.P (dBm)	E.I.R.P (mW)	Limit (mW)
NFC	13.56	64.74	-30.49	0.001	1

Note: dBm=dBuV/m-95.23

#### Conclusion

Pass.

-----THE END OF REPORT-----