

**Environmental evaluation and exposure limit according to FCC CFR 47part 1,
§1.1307, §1.1310**

The booster may be installed indoors or outdoors as stated in the User's manual page V, the calculation was done to confirm a safe distance.

Limit for power density for general population/uncontrolled exposure is $f/1500$ mW/cm² for 300 – 1500 MHz frequency range:

$$P = 806/1500 = 0.53 \text{ mW/cm}^2$$

The power density P (mW/cm²) = $P_T / 4\pi r^2$, where

P_T is the transmitted power, which is equal to the peak transmitter output power plus maximum antenna gain.

Indoor antenna installation

The maximum equivalent isotropically radiated power EIRP is

$$P_T = 36.98 \text{ dBm} + 0.2 \text{ dBi} = 37.18 \text{ dBm} = 5224 \text{ mW}, \text{ where}$$

36.98 dBm is the EUT maximum output power for CMRS application;
0.2 dBi – antenna assembly gain.

The minimum safe distance "r", where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{5224 / (0.53 \times 12.56)} = 28 \text{ cm}.$$

Outdoor antenna installation

The maximum equivalent isotropically radiated power EIRP is

$$P_T = 36.98 \text{ dBm} + 7 \text{ dBi} = 43.69 \text{ dBm} = 25003 \text{ mW}, \text{ where}$$

36.98 dBm is the EUT maximum output power for CMRS application;
7 dBi – antenna assembly gain (please refer to page 7 of User_manual_28127).

The minimum safe distance "r", where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{25003 / (0.53 \times 12.56)} = 61.3 \text{ cm}.$$

A warning about a safe distance is contained in the user manual.