

**Environmental evaluation and exposure limit according to FCC CFR 47part 1,
§1.1307, §1.1310**

The booster may be installed indoors or outdoors as stated in the User's manual page V, the calculation was done to confirm a safe distance.

Limit for power density for general population/uncontrolled exposure is $f/1500$ mW/cm² for 300 – 1500 MHz frequency range:

$$P = 806/1500 = 0.53 \text{ mW/cm}^2$$

The power density P (mW/cm²) = $P_T / 4\pi r^2$, where

P_T is the transmitted power, which is equal to the peak transmitter output power plus maximum antenna gain.

Indoor antenna installation

The maximum equivalent isotropically radiated power EIRP is

$$P_T = 36.69 \text{ dBm} + 0.2 \text{ dBi} = 36.89 \text{ dBm} = 4887 \text{ mW, where}$$

36.69 dBm is the EUT maximum output power at analog FM modulation in 851-862 MHz band; 0.2 dBi – antenna assembly gain.

The minimum safe distance “r”, where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{4887 / (0.53 \times 12.56)} = 28 \text{ cm.}$$

Outdoor antenna installation

The maximum equivalent isotropically radiated power EIRP is

$$P_T = 36.69 \text{ dBm} + 7 \text{ dBi} = 43.69 \text{ dBm} = 23388 \text{ mW, where}$$

36.69 dBm is the EUT maximum output power at analog FM modulation in 851-862 MHz band; 7 dBi – antenna assembly gain (please refer to page 7 of User_manual_28127_rev1).

According to manufacturer statement provided in user manual the maximum manufacturer rated power is 40 dBm. In a DAS system they suppose a loss about 9 dB due to cable insertion, splitter, etc.

The maximum equivalent isotropically radiated power EIRP shall be

$$P_T = 40 \text{ dBm} + 7 \text{ dBi} - 9 \text{ dB} = 38 \text{ dBm} = 6309 \text{ mW and}$$

$$\text{ERP} = 38 \text{ dBm} - 2.15 \text{ dB} = 35.85 \text{ dBm} = 3846 \text{ mW} \approx 3.85 \text{ W} < 5 \text{ W.}$$

The minimum safe distance “r”, where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{23388 / (0.53 \times 12.56)} = 60 \text{ cm.}$$

A warning about a min safe distance is contained in the user manual common for some boosters.