

1. TEST REPORT CERTIFICATION

APPLICANT : CRE TECHNOLOGY CO., LTD.

ADDRESS : 5F, NO. 46, SEC. 2,  
KAI-FENG ST., TAIPEI,  
TAIWAN, R.O.C.

EUT DESCRIPTION : MOUSE

(A) POWER SUPPLY : 115/230V

(B) MODEL : CREUBV

(C) FCC ID : NHM-CREUBV

FINAL TEST DATE : 11/06/1998

MEASUREMENT PROCEDURE USED :

PART 15 SUB PART B OF FCC RULES AND  
REGULATIONS ( 47 CFR PART 15 )  
FCC / ANSI C63.4 - 1992

WE HEREBY SHOW THAT:

THE MEASUREMENTS SHOWN IN THE ATTACHMENT WERE  
MADE IN ACCORDANCE WITH THE PROCEDURES INDICATED,  
AND THE ENERGY EMITTED BY THE EQUIPMENT WAS  
FOUND TO BE WITHIN THE LIMITS APPLICABLE.

TESTING ENGINEER : Leo Huang DATE 11/6  
Leo Huang

SUPERVISOR : Jesse Ho DATE 11/6/98  
Jesse Ho

APPROVED BY : Johnson Ho DATE 11/6/98  
Johnson Ho

2. TEST STATEMENT

2.1 TEST STATEMENT

TO whom it may concern,

This letter is to explain the test condition of this project.  
The EUT be tested as the following status.

CPU: PENTIUM    - 166 MHz

CPU Clock Signal: 66 MHz

The data was shown in this report reflects the worst-case  
data for the condition as listed above.

2. TEST STATEMENT

2.2 DEPARTURE FROM DOCUMENT POLICIES, PROCEDURE OR SPECIFICATIONS

DID HAVE

ANY DEPARTURE FROM DOCUMENT POLICIES  
& PROCEDURES OR FROM SPECIFICATIONS.

YES \_\_\_\_\_ , NO N/A .

IF YES, THE DESCRIPTION AS BELOW.

2.3 TEST STATEMENT

1. THE CERTIFICATE OR REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL, WITHOUT THE WRITTEN APPROVAL OF THE LABORATORY.
2. THE REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT ENDORSEMENT BY NVLAP OR ANY AGENCY OF THE U.S. GOVERNMENT.

3. EUT MODIFICATIONS

THE FOLLOWING ACCESSORIES WERE ADDED TO THE EUT  
DURING TESTING:

NO MODIFICATION BY SRT LAB.

4. MODIFICATION LETTER

THIS SECTION CONTAINS THE FOLLOWING DOCUMENTS:

A. LETTER OF MODIFICATIONS

## 5. CONDUCTED POWER LINE TEST

## 5.1 TEST EQUIPMENT

THE FOLLOWING TEST EQUIPMENT WAS USED DURING THE  
CONDUCTED POWER LINE TEST :

| EQUIPMENT/<br>FACILITIES | SPECIFICAT<br>- IONS           | MANUFACTURER         | MODEL#/<br>SERIAL#             | DATE OF CAL.<br>& CAL.CENTER | DUE<br>DATE |
|--------------------------|--------------------------------|----------------------|--------------------------------|------------------------------|-------------|
| SPECTRUM<br>ANALZER      | 9 KHz TO<br>1 GHz              | HP                   | 8590L/<br>3624A1317            | AUGUST, 1998<br>ETC          | 1Y          |
| EMI TEST<br>RECEIVER     | 9 KHz TO<br>30 MHz             | ROHDE &<br>SCHWARZ   | ESHS30/<br>826003/008          | AUGUST, 1998<br>ETC          | 1Y          |
| LISN                     | 50 uH, 50<br>ohm               | SOLAR<br>ELECTRONICS | 9252-50-<br>R24-BNC/<br>951315 | AUGUST, 1998<br>ETC          | 1Y          |
| LISN                     | 50 uH, 50<br>ohm               | SOLAR<br>ELECTRONICS | 9252-50-<br>R24-BNC/<br>951318 | AUGUST, 1998<br>ETC          | 1Y          |
| SIGNAL<br>GENERATOR      | 9 KHz TO<br>1080 MHz           | ROHDE &<br>SCHWARZ   | SMY01/<br>841104/019           | APRIL, 1998<br>ITRI          | 1Y          |
| POWER<br>CONVERTER       | 0 TO 300<br>VAC 47 -<br>500 Hz | AFC                  | AFC-1KW/<br>850510             | APRIL, 1998<br>SRT           | 1Y          |

## 5.2 CONFIGURATION OF THE EUT

THE EUT WAS CONFIGURED ACCORDING TO ANSI C63.4 - 1992.  
ALL INTERFACE PORTS WERE CONNECTED TO THE APPROPRIATE  
PERIPHERALS.      ALL PERIPHERALS AND CABLES ARE LISTED  
BELOW.

### -EUT

| DEVICE | MANUFACTURER                | MODEL # | FCCID      |
|--------|-----------------------------|---------|------------|
| MOUSE  | CRE TECHNOLOGY<br>CO., LTD. | CREUBV  | NHM-CREUBV |

### -REMARK

### -INTERNAL DEVICES

| <u>DEVICE</u> | <u>MANUFACTURER</u> | <u>MODEL #</u> | <u>DoC/FCCID</u> |
|---------------|---------------------|----------------|------------------|
|---------------|---------------------|----------------|------------------|

-PERIPHERALS

| DEVICE   | MANUFAC-<br>TURER | MODEL# /<br>SERIAL# | FCCID        | CABLE               |
|----------|-------------------|---------------------|--------------|---------------------|
| MONITOR  | OPTIQUEST         | 4500DC              | GWGMULTI82   | POWER-UNS<br>DATA-S |
| PRINTER  | HP                | 2225C               | BS46XU2225C  | POWER-UNS<br>DATA-S |
| MODEM    | SMARTEAM          | 1200AT              | EF56A51200AT | POWER-UNS<br>DATA-S |
| KEYBOARD | HP                | SK-2502             | GYUR41SK     | DATA-UNS            |
| PC       | COMPAQ            | SERIES 3431         | EUN3431      | POWER-UNS           |
|          |                   |                     |              |                     |
|          |                   |                     |              |                     |
|          |                   |                     |              |                     |

-REMARK

- (1) . CABLE - UNS : UNSHIELDED CABLE  
              S     : SHIELDED CABLE
- (2) . CABLES - ALL 1m OR GREATER IN LENGTH-  
              BUNDLED ACCORDING TO ANSI C63.4 - 1992.

5.3 EUT OPERATING CONDITION



OPERATING CONDITION IS ACCORDING TO ANSI C63.4 - 1992.

1. EUT POWER ON.
2. "H" PATTERN SENT TO THE FOLLOWING PERIPHERALS:
  - PRINTER
  - MONITOR
  - MODEM
3. CPU : PENTIUM - 166MHz  
CLOCK CHIP : 66MHz

## 5.4 TEST PROCEDURE

THE EUT WAS TESTED ACCORDING TO ANSI C63.4 - 1992. THE CONDUCTED TEST WAS PERFORMED IN AN ANECHOIC CHAMBER. THE FREQUENCY SPECTRUM FROM 0.45 MHz TO 30 MHz WAS INVESTIGATED. THE LISN USED WAS 50 ohm / 50 uHenry AS SPECIFIED BY SECTION 5.1 OF ANSI C63.4 - 1992. CABLES AND PERIPHERALS WERE MOVED TO FIND THE MAXIMUM EMISSION LEVELS FOR EACH FREQUENCY.

## 5.5 TEST SETUP



5.6 CONDUCTED POWER LINE EMISSION LIMIT

| FREQUENCY RANGE (MHz) | CLASS A | CLASS B |
|-----------------------|---------|---------|
| 0.045 - 1.705         | 1000 uV | 250 uV  |
| 1.705 - 30            | 3000 uV | 250 uV  |

NOTE : IN THE ABOVE TABLE, THE TIGHTER LIMIT  
APPLIES AT THE BAND EDGES.

## 5.7 CONDUCTED POWER LINE TEST RESULT

THE FREQUENCY SPECTRUM FROM 0.45 MHz TO 30 MHz WAS INVESTIGATED. ALL READINGS ARE QUASI-PEAK VALUES WITH A RESOLUTION BANDWIDTH OF 9 KHz.

TEMPERATURE : 28 CHUMIDITY : 78 %RH

| FREQUENCY(MHz) | LINE 1 (uv) | LINE 2 (uv) | LIMIT (uv) |
|----------------|-------------|-------------|------------|
| 0.62           | 28.84       | *           | 250        |
| 0.76           | *           | 41.21       | 250        |
| 0.90           | 35.48       | 46.77       | 250        |
| 3.66           | 1109        | 136.5       | 250        |
| 3.87           | 120.2       | 139.6       | 250        |
| 20.0           | 109.6       | 101.2       | 250        |
|                |             |             |            |
|                |             |             |            |
|                |             |             |            |
|                |             |             |            |

- REMARKS : (1) . \* = MEMENT DOES NOT APPLY FOR THIS FREQUENCY
- (2) . UNCERTAINTY IN CONDUCTED EMISSION MEASURED IS <+/-2dB
- (3) . CPU: PENTIUM - 166MHz CLOCK CHIP : 66MHz
- (4) . TEST CONFIGURATION PLEASE SEE 4.2
- (5) . TEST EQUIPMENT PLEASE SEE 4.1
- (6) . ANY DEPARTURE FROM SPECIFICATION : N/A

SIGNED BY TESTING ENGINEER : 

## 6. RADIATED EMISSION TEST

## 6.1 TEST EQUIPMENT

THE FOLLOWING TEST EQUIPMENT WAS USED DURING THE  
RADIATED EMISSION TEST :

| EQUIPMENT /<br>FACILITIES | SPECIFICAT<br>-IONS    | MANUFACTUR<br>-ER  | MODEL#/<br>SERIAL#     | DATE OF CAL.<br>& CAL. CENTER | DUE<br>DATE |
|---------------------------|------------------------|--------------------|------------------------|-------------------------------|-------------|
| RECEIVER                  | 20 MHz TO<br>1000 MHz  | R & S              | ESVS 30/<br>841977/003 | APRIL, 1998<br>ITRI           | 1Y          |
| SPECTRUM<br>ANALYZER      | 100 Hz TO<br>1500 MHz  | HP                 | 8568B/<br>3019A05294   | OCT , 1997<br>ETC             | 1Y          |
| SPECTRUM<br>ANALYZER      | 9 KHz TO<br>22 GHz     | HP                 | 8593E/<br>3322A00670   | APRIL, 1998<br>ITRI           | 1Y          |
| SPECTRUM<br>ANALYZER      | 100 Hz TO<br>1000 MHz  | IFR                | A-7550/<br>2684/1248   | JULY, 1998<br>ETC             | 1Y          |
| SIGNAL<br>GENERATOR       | 9 KHz TO<br>1080 MHz   | ROHDE &<br>SCHWARZ | SMY01/<br>841104/019   | APRIL, 1998<br>ITRI           | 1Y          |
| DIPOLE<br>ANTENNA         | 28 MHz TO<br>1000 MHz  | EMCO               | 3121C/<br>9003-535     | DEC, 1997<br>SRT              | 1Y          |
| DIPOLE<br>ANTENNA         | 28 MHz TO<br>1000 MHz  | EMCO               | 3121C/<br>9611-1239    | DEC, 1997<br>SRT              | 1Y          |
| BI-LOG<br>ANTENNA         | 26 MHz TO<br>2000 MHz  | EMCO               | 3142/<br>96081-1073    | DEC, 1997<br>SRT              | 1Y          |
| BI-LOG<br>ANTENNA         | 26 MHz TO<br>1100 MHz  | EMCO               | 3143/<br>9509-1152     | DEC, 1997<br>SRT              | 1Y          |
| PRE-AMPLIFIER             | 0.1 MHz TO<br>1300 MHz | HP                 | 8447D/<br>2944A08402   | APRIL, 1998<br>ITRI           | 1Y          |
| PRE-AMPLIFIER             | 0.1 MHz TO<br>1300 MHz | HP                 | 8447D/<br>2944A06412   | AUGUST, 1998<br>ETC           | 1Y          |
| HORN ANTENNA              | 1 GHz TO<br>18 GHz     | EMCO               | 3115/<br>9012-3619     | DEC, 1997<br>SRT              | 1Y          |

## 6.2 CONFIGURATION OF THE EUT

SAME AS SECTION 5.4 OF THIS REPORT.

## 6.3 EUT OPERATING CONDITION

SAME AS SECTION 5.3 OF THIS REPORT.

## 6.4 TEST PROCEDURE


THE EUT WAS TESTED ACCORDING TO ANSI C63.4 - 1992. THE RADIATED TEST WAS PERFORMED AT SRT LAB'S OPEN SITE. THIS SITE IS ON FILE WITH THE FCC LABORATORY DIVISION, REFERENCE 31040/SIT.

THE FREQUENCY SPECTRUM FROM 30 MHz TO 1 GHz WAS INVESTIGATED. MEASUREMENTS WERE MADE AT THREE METERS WITH AN ADJUSTABLE DIPOLE ANTENNA. PERIPHERALS, CABLES, EUT ORIENTATION, AND ANTENNA HEIGHT WERE VARIED TO FIND THE MAXIMUM EMISSION FOR EACH FREQUENCY.

THE FREQUENCY SPECTRUM FROM 30 MHz TO 2 GHz WAS INVESTIGATED. THE MEASUREMENTS UNDER 1 GHz WITH RESOLUTION BANDWIDTH OF 120 KHz ARE QUASI-PEAK READING MADE AT THREE METERS USING AN ADJUSTABLE DIPOLE ANTENNA. PERIPHERALS, CABLES, EUT ORIENTATION, AND ANTENNA HEIGHT WERE VARIED TO FIND THE MAXIMUM EMISSION FOR EACH FREQUENCY.


THE MEASUREMENTS ABOVE 1 GHz WITH A RESOLUTION BANDWIDTH OF 1 MHz ARE PEAK READING AT A DISTANCE OF THREE METERS WITH A HORN ANTENNA.

6.5 RADIATED TEST SETUP



## 6.5 RADIATED TEST SETUP

ELECTRICAL AND ELECTRONIC EQUIPMENT IN THE RANGE OF 9 kHz TO 40 GHz

ANSI  
C63.4-1992LEGEND

- 1 Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth forming a bundle 30 to 40 cm long, hanging approximately in the middle between ground plane and table.
- 2 I/O cables that are connected to a peripheral shall be bundled in center. The end of the cable may be terminated if required using correct terminating impedance. The total length shall not exceed 1 m.
- 3 If LISNs are kept in the test setup for radiated emissions, it is preferred that they be installed under the ground plane with the receptacle flush with the ground plane.
- 4 Cables of hand-operated devices, such as keyboards, mice, etc., have to be placed as close as possible to the controller.
- 5 Non-EUT components of EUT system being tested.
- 6 The rear of all components of the system under test shall be located flush with the rear of the table.
- 7 No vertical conducting wall used.
- 8 Power cords drape to the floor and are routed over to receptacle.

## 6.6 RADIATED EMISSION LIMIT

ALL EMISSION FROM A DIGITAL DEVICE, INCLUDING ANY NETWORK OF CONDUCTORS AND APPARATUS CONNECTED THERETO, SHALL NOT EXCEED THE LEVEL OF FIELD STRENGTH SPECIFIED BELOW :

## CLASS B

| FREQUENCY<br>(MHz) | DISTANCE<br>(m) | FIELD STRENGTH<br>(uV/m) |
|--------------------|-----------------|--------------------------|
| 30 - 88            | 3               | 100                      |
| 88 - 216           | 3               | 150                      |
| 216 - 960          | 3               | 200                      |
| ABOVE 960          | 3               | 500                      |

## CLASS B ( OPEN CASE )

| FREQUENCY<br>(MHz) | DISTANCE<br>(m) | FIELD STRENGTH<br>(uV/m) |
|--------------------|-----------------|--------------------------|
| 30 - 88            | 3               | 199.5                    |
| 88 - 216           | 3               | 298.5                    |
| 216 - 960          | 3               | 398.1                    |

## CLASS A

| FREQUENCY<br>(MHz) | DISTANCE<br>(m) | FIELD STRENGTH<br>(uV/m) |
|--------------------|-----------------|--------------------------|
| 30 - 88            | 3               | 316.3                    |
| 88 - 216           | 3               | 473.2                    |
| 216 - 960          | 3               | 613.0                    |
| ABOVE 960          | 3               | 1000.0                   |

- NOTE : 1. IN THE EMISSION TABLES ABOVE, THE TIGHTER LIMIT APPLIES AT THE BAND EDGES.
2. DISTANCE REFERS TO THE DISTANCE BETWEEN MEASURING INSTRUMENT, ANTENNA, AND THE CLOSEST POINT OF ANY PART OF THE DEVICE OR SYSTEM.

## 6.7 RADIATED EMISSION TEST RESULT

THE FREQUENCY SPECTRUM FROM 30 MHz TO 1 GHz WAS INVESTIGATED. ALL READINGS UNDER 1 GHz ARE QUASI-PEAK VALUES WITH A RESOLUTION BANDWIDTH OF 120 KHz. MEASUREMENTS WERE MADE AT 3 METERS.

THE MEASUREMENTS ABOVE 1 GHz WITH A RESOLUTION BANDWIDTH OF 1 MHz ARE PEAK READING AT A DISTANCE OF 3 METERS.

TEMPERATURE : 28 C

HUMIDITY : 78 %RH

| FREQ.<br>(MHz) | CABLE<br>LOSS<br>(dB) | ANT.<br>FACTOR<br>(dB) | READING (dBuV) |       | EMISSION (uV) |       | LMTS<br>(uV) |
|----------------|-----------------------|------------------------|----------------|-------|---------------|-------|--------------|
|                |                       |                        | HORIZ          | VERT  | HORIZ         | VERT  |              |
| 99.82          | 0.6                   | 11.9                   | 24.37          | *     | 69.74         | *     | 150          |
| 331.7          | 1.6                   | 15.3                   | 16.37          | 15.30 | 63.61         | 91.94 | 200          |
| 371.4          | 1.9                   | 17.4                   | *              | 20.56 | *             | 98.40 | 200          |
| 455.8          | 2.2                   | 19.1                   | *              | 14.99 | *             | 65.24 | 200          |
| 576.1          | 2.4                   | 20.8                   | 13.19          | *     | 65.99         | *     | 200          |
| 847.7          | 2.7                   | 22.7                   | 11.67          | 15.64 | 71.37         | 112.7 | 200          |
|                |                       |                        |                |       |               |       |              |
|                |                       |                        |                |       |               |       |              |

REMARKS : (1). MEASUREMENT DOES NOT APPLY FOR THIS FREQUENCY.

(2). THE MAXIMUM CONDITION WAS WITH THE MONITOR POWER CORD CONNECTED TO THE PERSONAL COMPUTER.

(3). CPU : PENTIUM - 166MHz CLOCK CHIP : 66MHz

(4). SAMPLE CALCULATION  
 $20 \text{ LOG(EMISSION) uV/m} = \text{CABLE LOSS (dB)} + \text{FACTOR (dB)} + \text{READING (dBuV/m)}$

(5). TEST CONFIGURATION PLEASE SEE 5.4

(6). TEST EQUIPMENT PLEASE SEE 5.1

(7). UNCERTAINTY IN RADIATED EMISSION MEASURED IS  $\pm 4\text{dB}$

(8). ANY DEPARTURE FROM SPECIFICATION : N/A

SIGNED BY TESTING ENGINEER :

