



RF EXPOSURE REPORT

REPORT NO.: SA980225L04

MODEL NO.: WLN-2210, TEW-652BRP, ENHWI-N4,
A02-RB-W300N

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: CAMEO COMMUNICATIONS, INC.

ADDRESS: 5F, No. 42, Sec. 6, Mincyuan E. Rd., Neihu
District, Taipei City 114, Taiwan

ISSUED BY: Bureau Veritas Consumer Product Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau T-suen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



RF EXPOSURE MEASUREMENT (MOBILE DEVICE)

1. INTRODUCTION

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF EXPOSURE LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
(A) LIMITS FOR OCCUPATIONAL / CONTROL EXPOSURES				
300-1500	F/300	6
1500-100,000	5	6
(B) LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz



3. FRIIS FORMULA

Friis transmission formula : $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance r .

Ref.: David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,

Page 640, Eq. (11-133).

4. EUT OPERATING CONDITION

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**.



A D T

6. TEST RESULTS

6.1 ANTENNA GAIN

The maximum Gain measured in Fully Anechoic Chamber is 2dBi or 1.584893 (numeric).

6.2 OUTPUT POWER INTO ANTENNA & RF EXPOSURE VALUE AT DISTANCE 20cm:

802.11b DSSS MODULATION: 1TX

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/CM ₂)	LIMIT OF POWER DENSITY (mW/CM ₂)
1	2412	79.799	19.02	0.025	1.000
6	2437	71.450	18.54	0.023	1.000
11	2462	80.538	19.06	0.025	1.000

802.11g OFDM MODULATION: 1TX

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/CM ₂)	LIMIT OF POWER DENSITY (mW/CM ₂)
1 2412		252.930	24.03	0.080	1.000
6 2437		256.448	24.09	0.081	1.000
11 2462		199.986	23.01	0.063	1.000

DRAFT 802.11n (20MHz) OFDM MODULATION: 1TX

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (mw)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/CM ₂)	LIMIT OF POWER DENSITY (mW/CM ₂)
1	2412	252.348	24.02	0.080	1.000
6	2437	254.683	24.06	0.080	1.000
11	2462	254.097	24.05	0.080	1.000

DRAFT 802.11n (20MHz) OFDM MODULATION: 2TX

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ₂)	LIMIT OF POWER DENSITY (mW/CM ₂)
		CHAIN 0	CHAIN 1				
1	2412	18.02	18.03	126.920	21.04	0.040	1.000
6	2437	19.01	19.06	160.154	22.05	0.050	1.000
11	2462	19.03	19.07	160.707	22.06	0.051	1.000



A D T

DRAFT 802.11n (40MHz) OFDM MODULATION: 1TX

CHAN.	CHAN. FREQ. (MH z)	PEAK POWER OUTPUT (mw)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/CM ₂)	LIMIT OF POWER DENSITY (mW/CM ₂)
1	2422	200.447	23.02	0.063	1.000
4	2437	203.236	23.08	0.064	1.000
7	2452	159.956	22.04	0.050	1.000

DRAFT 802.11n (40MHz) OFDM MODULATION: 2TX

CHAN.	CHAN. FREQ. (MH z)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ₂)	LIMIT OF POWER DENSITY (mW/CM ₂)
		CHAIN 0	CHAIN 1				
1	2422	18.02	18.09	127.804	21.07	0.040	1.000
4	2437	17.58	18.57	129.225	21.11	0.041	1.000
7	2452	17.53	18.12	121.487	20.85	0.038	1.000